

No. 640-1111
U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration
In Dept. _____
per Dwg. _____
ion Name: _____

MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing,
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I

MANUFACTURER'S NAME	Durez Division, Hooker Chemicals & Plastics Corporation	EMERGENCY TELEPHONE NO.	(716) 696-6000
ADDRESS (Number, Street, City, State, and ZIP Code) Walck Road, North Tonawanda, New York 14120			
CHEMICAL NAME AND SYNONYMS	N/A	TRADE NAME AND SYNONYMS	Durez 1308 Black
CHEMICAL FAMILY	N/A	FORMULA	N/A

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES	%	TLV (Units)
	%	TLV (Units)
Phenol	<5%	Skin - 5PPM or 19mg/M ³
Asbestos	35%	2 fibers/ml >5µ in length

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)	N/A	SPECIFIC GRAVITY (H ₂ O=1)	1.53-1.55
VAPOR PRESSURE (mm Hg.)	N/A	PERCENT. VOLATILE BY VOLUME (%)	N/A
VAPOR DENSITY (AIR=1)	N/A	EVAPORATION RATE (=1)	N/A
SOLUBILITY IN WATER	Negligible		
APPEARANCE AND ODOR	Black granular material with slight odor of phenol		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	N/A	FLAMMABLE LIMITS	N/A	Lel	Uel
EXTINGUISHING MEDIA	Water, chemical foams or CO ₂ with water the preferred media.				
SPECIAL FIRE-FIGHTING PROCEDURES	Use normal equipment and procedures.				
CALLER 367/399					
12/1/2006					
UNUSUAL FIRE AND EXPLOSION HAZARDS	Organic dusts and mixtures can be explosive				