	Gals.	Qts.	Pts.	½ Pts.
***AD-EL-ITE PAINT AND VARNISH REMOVER Y-70** A top-quality remover. Contains no alkalies, acids, oils, or water. Does not raise the grain or discolor the wood. Evaporates very slowly. Very effective in removing old paint, enamel, lacquer and baked japan	3.96	1.35	.86	.66
***ALKALI-RESISTING PRIMER Y-5041** An easy to apply masonry primer-sealer for interior newly plastered or damp walls, and exterior masonry, brick, stucco and concrete blocks, which are to be painted with synthetic rubber-base or oil base paints. Penetrates deeply into the pores and adheres firmly to the surface to create perfect bond for finish coat. Resists moisture and alkali. Seals in active lime. Prevents fresh plaster from burning through and discoloring the finish coat APPLICATION—Brush, Spray THINNER—Turpentine DRYING TIME—16 hours Covers 350-400 Sq. Ft. per gal. **(Also See SPRED Primer-Sealer Alkali-Resisting Primer)**	8.96	2.70	—	—
ALKYD ENAMELS See: Brush-Day-Lite Alkyd Flat and Tint White; Japalac; Florenamel; Rustmaster; Ripolin; Spred Lustre.				
***ALUMINUM ASPHALT ROOF PAINT Y-605** Recommended for tar paper, composition and asphalt roofs. Will rejuvenate weathered roofs and insulate with a silvery sheet of aluminum in one coat. Made with selected asphalts, finest grade aluminum flakes and solvents APPLICATION—Brush, Spray THINNER—Mineral Spirits or Turp. DRYING TIME—10 hours Covers 275-400 Sq. Ft. per gal., depending on surface.	6.13	—	—	—
ALUMINUM PAINTS See: Metallite; Japalac Spray Enamel **ASBESTOS SHINGLE PAINT** See: SPRED House Paint; SPRED Glide-On				
BARN PAINT See: Endurance Barn Paint **BASECOATS (Primers)** For Exteriors—See SPRED House Paint Primecoat #1; Rustmaster Metal Primer; Rustmaster Galvanized Primer, Endurance House Paint For Interiors—See: Gliddencoat; Speed-Wall Interior Basecoat; SPRED Primer-Sealer; Ripolin Undercoat, Alkali-Resisting Primer. **BASEMENT PAINTS** For Floors—See: Florenamel For Walls—See: SPRED SATIN; SPRED Glide-On				
***BLACK ASPHALTUM Y-67** A weather resisting, quick drying, gloss black asphaltum base paint. Recommended for exterior iron work, fences, metal sash and other exterior metal surfaces where an economical finish is desired APPLICATION—Brush, Spray DRYING TIME—2 to 3 hours THINNER—Mineral Spirits or Turp. Covers 400-500 Sq. Ft. per gal.	4.26	1.46	.93	.63

*AVAILABLE IN 5-GAL. CANS AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

	Gals.	Qts.	Pts.	½ Pts.
BLACKBOARD FINISHES See: Vismatic Green Chalkboard Coating				
BLENDING COLORS See: SPRED Dramatone Tinting Colors; Colors-In-Oil				
BRICK PAINTS See: SPRED House Paint; SPRED Glide-On				
BRUSH-DAY-LITE ALKYD FLAT ENAMEL Y-5700 line Beautiful, completely washable, flat alkyd enamel for interior wall surfaces, including plaster, wood, concrete, wallboard and metal. Can be applied quickly with a wide brush or roller. Flows out smoothly. One coat is usually sufficient. Colors match SPRED SATIN.				
White and Colors	7.71	2.35	—	—
APPLICATION—Brush, Roller, Spray DRYING TIME—4 hrs; overnight for recoating THINNER—Mineral Spirits or Turpentine COVERAGE—Up to 550 sq. ft. per gal.				
BRUSH-DAY-LITE ALKYD FLAT EN. INT. TINT BASE Y5787	7.66	2.22	—	—
BRUSH-DAY-LITE ALKYD FLAT ENAMEL TINT WHITE Y5780 For tinting Brush-Day-Lite Alkyd Flat Enamel Colors	7.41	2.18	—	—
BRUSHING LACQUER See: Glid-Tone Crystalacq				
CANVAS PRESERVATIVE See: Neva-Rot				
CEMENT AND STUCCO PAINT See: SPRED House Paint; SPRED Glide-On				
COLORS-IN-OIL Y-1700 line Unexcelled for tinting flat wall paints, Semi-Gloss and Gloss enamels, glazing liquids, white lead and white paste paint. Ground extremely fine in special pale linseed oil for quick and positive dispersion. The finest pigments are used to develop perfect tone and strength of color. Not to be used in latex, emulsion paints, or lacquer.	Gals.	Qts.	½ Pts.	1" x 5" Tubes
Raw Umber, Burnt Umber, Y1708, Y1703	9.41	2.70	.96	.62
Raw Sienna, Burnt Sienna, Y1719, Y1702	9.51	2.73	.98	.62
Ivory Drop Black, Y1709	—	2.78	.97	.62
Lamp Black, Y1720	7.96	2.18	.90	.62
Prussian Blue, Y1711	—	2.93	.97	.62
Chrome Green, Light; Chrome Green, Medium, Y1706, Y1705	13.51	3.63	1.25	.62
Perma-Green, Y1745	—	5.83	1.74	.62
Chrome Yellow, Light and Medium, Y1716, Y1707	—	5.33	1.51	.62
Chrome Yellow, Dark, Y1742	—	5.68	1.69	.62
Yellow Ochre, Y1701	10.16	2.93	.98	.62
Venetian Red, Y1718	8.11	2.28	.93	.62
American Vermilion (Interior Use Only) Y1717	—	5.33	1.51	.62
Perma Blue, Y1746	—	5.28	1.57	.62
CONCRETE PAINT See: SPRED House Paint; SPRED Glide-On				
CRACK AND CREVICE FILLER See: SPRED Patch				
CREOSOTE PAINT See: Stock Farm Paint				

	Gals.	Qts.	Pts.	½ Pts.
***CRAFTSMAN LATEX PAINT Y-3050 line** A specially formulated ready-to-use interior latex paint for application by brush or roller for plaster, wallboard, acoustical tile, masonry and wallpaper.	(NOT AVAILABLE PACIFIC REGION)			
***CRAFTSMAN MILDEW RISISTANT WHITE HOUSE PAINT Y-2217** A house point with unusual brushing qualities and elasticity making it ideal for all exterior painting on wood, asbestos siding and metal. New self-cleaning properties make its brightness last. Helps protect surface from mildew.	(NOT AVAILABLE PACIFIC REGION)			
***CRAFTSMAN HOUSE PAINT WHITE Y-2218** An oil base exterior paint with easy brushing qualities making it perform well on wood, brick, stucco, concrete and metal.	(NOT AVAILABLE PACIFIC REGION)			
DECK PAINT See: Florenamel **DEEP COLORS** See: SPRED SATIN; SPRED SATIN Dramatone Tint Base; SPRED LUSTRE Dramatone Tint Base See: INT. TINT BASE LUSTRE, SATIN, BDL ALKYD FLAT **DRAMATONE MULTI-PURPOSE TINTING COLORS** See: SPRED Products Section				
***DRIWAL (Silicone) Y-534** A transparent, water-repellent finish for exterior, above-ground brick, stone and masonry. Does the job in ONE COAT. Keeps rain water from penetrating the pores. Resists efflorescence and staining. Masonry surfaces show no visible change in color or texture when treated with this material. Recommended for use on brick and mortar, concrete, cement-base paints, asbestos-cement combinations, sandstone, stucco and stones other than limestone. Not to be used on cinder block or other light weight aggregate concrete blocks with extremely porous surfaces. This invisible water-repellent coating contains silicone to combat masonry deterioration. Not recommended for limestone surfaces APPLICATION—Brush, Spray DRYING TIME—2 hours THINNER—None required COVERAGE—125 to 275 Sq. Ft. per gallon depending on porosity of surface	5.26	—	—	—
ENAMELS See: Japalac; Ripolin; Brush-Day-Lite Alkyd Flat; Florenamel; SPRED Lustre; Rustmaster **ENAMEL UNDERCOATER** See: Gliddencoat; Ripolin Undercoat; Interior Basecoat				
***ENDURANCE BARN PAINT — Red Y-500** A new, highest quality paint with excellent hiding power. It dries to a tough glossy film that withstands the rigors of the roughest weather. Provides long-lasting protection for borns, sheds, granaries, silos, water tank exteriors, storehouses, fences, etc. Use it on exterior wood and metal APPLICATION—Brush, Spray DRYING TIME—Overnight; 36 hours for recoating THINNER—Mineral Spirits or Turpentine COVERAGE—500 Sq. Ft. per gallon	5.86	1.80	—	—

*AVAILABLE IN 5-GAL. CANS AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

	Gals.	Qts.	Pts.	½ Pts.
***ENDURANCE EXTERIOR BASECOAT Y-1851**				
Exterior primer for new wood and previously painted wood that is badly weathered or chalked. Use it to spot-prime bare spots resulting from peeling and flaking. Made from specially prepared oils to produce the elasticity, adhesion and control penetration necessary for finest exterior paint jobs	—	—	—	—
APPLICATION—Brush, Spray DRYING TIME—48 hours for recoating THINNER—Mineral Spirits or Turpentine COVERAGE—450 to 500 Sq. Ft. per gallon				
***ENDURANCE HOUSE PAINT Y-1800 LINE**				
For Siding, Trim and Shutters				
Contains more heavy-bodied, pure linseed oil per gallon for longer life; pure white lead for added strength, water-resistance and extra durability; titanium for whiteness and hiding; zinc oxide to combat mildew, magnesium silicate for protection against cracking and checking. The exclusive Glidden formula makes this the finest, longest-lasting, self-cleaning exterior house paint manufactured. May be tinted with DRAMATONE Tinting Colors.				
Outside White, Y1800	—	—	—	—
Regular Colors and Black, Y1800 Line	—	—	—	—
Non-Chalking Trim White, Y1892	—	—	—	—
Crylite Green, Y1828	—	—	—	—
Deep Turquoise, Y1870	13.40	3.85	2.10	—
Shutter Green, Y1861	9.40	2.81	1.60	—
Dark Walnut; Dark Blue, Y1872, Y1871	8.10	2.46	1.46	—
APPLICATION—Brush, Spray, Roller DRYING TIME—16 hours; recoat in 72 hours THINNER—Mineral Spirits or Turpentine COVERAGE—550 Sq. Ft. per gallon				
***ENDURANCE HOUSE PAINT Y-1850**				
Mildew and Fume-Resistant				
A deluxe, Super White House Paint — ideal for the finest homes. Excellent for exterior wood, masonry and metal in any climate. A Non-staining House Paint that stays white and bright for years. Especially suited for industrial areas, where homes are subjected to chemical fumes, heavy smog and smoke. Its formulation makes it ideal for farm buildings and fences. Combats mold, mildew and the roughest year-round weather	—	—	—	—
APPLICATION—Brush, Spray THINNER—Mineral Spirits or Turpentine DRYING TIME—16 hours; 72 hours for recoating COVERAGE—Up to 550 Sq. Ft. per gallon				
ENDURANCE HOUSE PAINT, PASTEL COLORS Y-1800 line				
Pastel colors are easily obtained by tinting existing colors of ENDURANCE HOUSE PAINT or NON-CHALKING TRIM WHITE Y1892 with DRAMATONE Tinting Colors. See ENDURANCE HOUSE PAINT Color Card.	—	—	—	—

*AVAILABLE IN 5-GAL. CANS
AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

GLD027043

	Gals.	Qts.	Pts.	½ Pts.
***ENDURANCE IMPERIAL ONE-COAT Y-1867** **White House Paint (Alkyd Fortified)** Premium quality self-cleaning white exterior paint. Gives extra hiding and coverage with its built-in second coat. Has depth and richness of enamel. Easy brushing. Once over is enough with this amazing one-coat paint! Fortified with alkyds to give extra durability and lasting beauty ..... APPLICATION—Brush, Spray THINNER—Mineral Spirits or Turpentine DRYING TIME—48 hours COVERAGE—550 Sq. Ft. per gallon	9.50	2.81	—	—
***ENDURANCE VELVET (Flat Exterior Finish) Y-2700 line** FOR WOOD SHINGLES, SHAKES, WOOD SIDING AND TRIM. May be used also on metal surfaces. It brushes easily and will produce a beautiful flat finish in one coat over most previously painted surfaces if the color contrast is not great. Dries dust free in one hour. It provides a "breather type" film which aids the elimination of internal moisture. White and Colors ..... APPLICATION—Brush, Spray DRYING TIME—Dust-free 1 hr.; 48 hours for recoating THINNER—Mineral Spirits or Turpentine COVERAGE—Up to 550 Sq. Ft. per gallon	7.26	2.26	—	—
***EVERON HOUSE PAINT (White) Y-2200** An excellent paint that stays clean and bright because of its special formula which provides controlled chalking. A superior finish for all wood surfaces exposed to weather and changing climatic conditions. Resists fumes in industrial areas! EVERON HOUSE PAINT brushes easily, penetrates deeply when used as a primer, adheres tenaciously as a finish coat, dries with an elastic, high gloss finish that remains firm and durable. EVERON is truly the economical HOUSE PAINT ..... APPLICATION—Brush, Roller, Spray DRYING TIME—16 hours; recoat in 48 hours THINNER—Mineral Spirits or Turpentine COVERAGE—550 Sq. Ft. per gallon	—	—	—	—

FARM BUILDING PAINTS

For Exteriors—See: Endurance Paints; Metallite; SPRED House Paint; SPRED Glide-On; Stock Farm White

For Interiors—See: SPRED Products

FENCE PAINTS

See: Stock Farm White; Metallite; Rustmaster; Black Asphaltum

FILLER, WOOD

See: Glid-Tone Wood Filler

FLOOR FINISHES

See: Florenamel; Glid-Tone Gloss Varnish; Xpert Clear Gloss

*AVAILABLE IN 5-GAL. CANS AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

	Gals.	Qts.	Pts.	½ Pts.
***FLORENAMEL (Alkyd) Y-850 line** An alkyd enamel with extra durability, for use on porches, floors of wood and concrete, canvas decks, railings — inside and outside. Will not waterspot; standing pools of water do not affect it. FLORENAMEL gives concrete basement floors and walls a mirror-like enamel finish. It's scrubbable. FLORENAMEL is made to take the roughest wear and weather. May be tinted with DRAMATONE Tinting Colors. All colors APPLICATION—Brush, Spray DRYING TIME—12 hours THINNER—Turpentine or Mineral Spirits COVERAGE—500 to 600 Sq. Ft. per gallon	8.01	2.51	—	—
***GLIDDENCOAT (White Enamel Undercoat) Y-555** A perfect enamel undercoat for woodwork. Produces a firm opaque film to hold out succeeding coats of finishing enamel, making it possible to secure full luster and depth of gloss. Works easily, flows evenly without showing brush marks and requires only light sanding. Can be tinted with Colors-In-Oil or DRAMATONE Tinting Colors APPLICATION—Brush, Spray DRYING TIME—Overnight for sanding and recoating THINNER—Mineral Spirits or Turpentine COVERAGE—500 Sq. Ft. per gallon	6.86	2.16	1.28	.87
GLIDE-ON, SPRED See: SPRED Products Section				
GLID STRIP (Non-Flammable) Y-74 **Wash Away Paint and Varnish Remover** A non-flammable, water-flush paint and varnish remover that stays wet longer and permits working on larger areas. Has less tendency to run and sag on upright surfaces due to its heavy body. Easy to use. Just brush it on, wait a few minutes, then wash it off with water. GLID STRIP also acts as a cleaner for old, hardened nylon and pure bristle paint and varnish brushes. Will soften latex paints for easy removal	7.71	2.53	1.35	.88
GLID-TONE CRYSTALACQ (Brushing Lacquer) Y-2840 A crystal clear, quick-drying, water and wear-resistant lacquer finish for brush application. Easy to use. Excellent for floors, woodwork, furniture, linoleum, etc. APPLICATION—Brush DRYING TIME—1 to 6 hours, depending on surface THINNER—Glid-Tone Crystalacq Reducer COVERAGE—300 Sq. Ft. per gallon	8.06	2.45	1.43	—
GLID-TONE CRYSTALACQ REDUCER, Y2822 Special Thinner for Crystalacq	—	—	1.16	—

*AVAILABLE IN 5-GAL. CANS
AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

	Gals.	Qts.	Pts.	½ Pts.
GLID-TONE GLOSS VARNISH Y-1 A deluxe, general-purpose interior varnish. Epoxy resins give it extreme abrasion resistance, durability, and lasting beauty. Excellent on all interior wood surfaces, bar and tabletops, woodwork, furniture and floors. Especially suitable over newly stained woodwork where Glid-Tone Stains have been applied. May be rubbed ..... APPLICATION—Brush DRYING TIME—6 to 8 hours THINNER—Mineral Spirits or Turpentine COVERAGE—650 Sq. Ft. per gallon	9.26	2.75	1.56	.98
***GLID-TONE REDWOOD STAIN Y-31** A penetrating flat Redwood Stain and Sealer designed especially to protect and beautify natural exterior wood such as siding, shingles, shakes, panels, doors, fences, picnic tables and yard furniture. If gloss finish is desired use Clear Redwood Finish Y30 ..... APPLICATION—Brush, Spray DRYING TIME—Overnight THINNER—Mineral Spirits, Turpentine, VM & P Naphtha COVERAGE—First Coat on rough, new wood: 200-300 Sq. Ft. per gallon. Finished Wood: 300-400 Sq. Ft. per gallon, first coat. 2nd Coat: Up to 600 Sq. Ft. per gallon. 3rd Coat: Up to 800 Sq. Ft. per gallon.	5.86	1.85	—	—
***GLID-TONE REDWOOD FINISH Clear Polyurethane Y-30** A brilliant gloss finish for redwood, red cedar, pine and other exterior wood surfaces. Mildew and fume resistant. Provides a tough, erosion resistant film that maintains flexibility and resists checking, cracking, hardening ..... APPLICATION—Brush, Spray DRYING TIME—Overnight THINNER—Mineral Spirits, Turpentine, VM & P Naphtha COVERAGE—First coat on rough new wood; 200 to 300 Sq. Ft. per gallon. Finished wood; 300 to 400 Sq. Ft. Second coat; 500 to 600 Sq. Ft. Third coat; 600 to 800.	8.61	2.51	—	—
GLID-TONE RE-GRAIN GROUND COAT Y-260 An enamel undercoater that produces o firm, opaque film, renews worn out finishes as described in "Step 1" in the Glid-Tone Re-Grain Process folder. For more detailed information see Glid-Tone Regrain Process Folder	—	2.16	1.28	.87
GLID-TONE SATIN-SHEEN VARNISH Y-47 A new satin sheen varnish that dries free from all cloudiness and preserves the natural beauty of the wood. Excellent for use over GLID-TONE stains and for all interior work where a dull finish or rubbed effect is desired. Sufficiently pale for use over light modern stains. DO NOT USE ON FLOORS ..... APPLICATION—Brush DRYING TIME—2 hours THINNER—Mineral Spirits or Turpentine COVERAGE—650 Sq. Ft. per gallon	8.46	2.48	1.44	.92

***AVAILABLE IN 5-GAL. CANS AT 15c PER GALLON LESS THAN 1-GAL. PRICES.**

GLD027046

	Gals.	Qts.	Pts.	½ Pts.
GLID-TONE SPAR VARNISH Y-48				
Extra durable spar varnish for exterior surfaces exposed to weather. Recommended as the finest varnish available for exterior use — spars, hulls, decks, house sidings, paneling, porch ceilings, outdoor furniture, etc. Makes perfect finish over Glid-Tone Stain on exterior surfaces	9.91	2.86	1.63	1.05
APPLICATION—Brush DRYING TIME—8 hours; 48 hours for recoating THINNER—Mineral Spirits or Turpentine COVERAGE—650 Sq. Ft. per gallon				
GLID-TONE VARNISH STAIN Y-1201-02-03				
Stains and varnishes in one operation. Dries quickly, to a high lustre. For use on furniture, woodwork and floors. Unusually waterproof	7.81	2.41	1.38	.92
APPLICATION—Brush, Spray DRYING TIME—4 to 6 hours; 24 hours for recoating THINNER—Mineral Spirits or Turpentine COVERAGE—600 Sq. Ft. per gallon				
GLID-TONE WOOD STAIN Y-242 line				
An all-purpose, pigmented wiping stain for all types of wood, plywood and veneer, exterior and interior surfaces. Especially suitable for knotty pine wood paneling in recreation rooms. Excellent for use on new or old furniture, woodwork, cabinets, wall paneling and floors. GLID-TONE Stain heightens the beauty of the wood grain. Holds color evenly. May be coated with varnish, shellac or lacquer. May be tinted with DRAMATONE Tinting Colors to produce additional beautiful colors.				
APPLICATION—Wiping Cloth, Brush DRYING TIME—12 hours Stains, All Colors	6.46	2.00	1.22	.82
THINNER—Glid-Tone Stain Reducer				
GLID-TONE STAIN REDUCER Y-251	3.96	1.41	.91	.70

EFFECTIVE MAY 15, 1963
SUBJECT TO CHANGE WITHOUT NOTICE

SPRED SATIN

AND SPRED RELATED PRODUCTS

Glidden QUALITY PRODUCTS

	Gals.	Qts.	Pts.	½ Pts.
SPRED SATIN Y-3400 line (100% Latex Interior Paint)				
Original 100% latex base paint for interior walls, ceilings, woodwork. Excellent for masonry, interior plaster, porous wallboards, acoustical tile, wallpaper. The ideal latex paint for schools, hospitals, residences, offices, motels, hotels, apartments, housing projects, etc. Extremely fast, easy application; self priming, cuts painting time in half. No disagreeable odor. Guaranteed washable. May be tinted with DRAMATONE Tinting Colors.				
3418 Decorator White	6.79	2.18	1.22	.81
3470 Ceiling Flat White and Standard Colors	6.79	2.18	—	—
3480 Dramatone Tint Base	6.10	1.93	—	—
3487 Int. Tint Base	6.15	1.95	—	—
DEEP COLORS				
3434 Charcoal Black	6.79	2.18	1.22	.81
APPLICATION—Brush, Roller, Spray				
DRYING TIME—20 minutes; may be recoated in 4 hours				
THINNER—Water				
COVERAGE—Up to 500 Sq. Ft. per gallon over most surfaces				
***SPRED LUSTRE SEMI-GLOSS ENAMEL Y-4600 line** (Interior-Exterior Washable Alkyd Enamel)				
Ready to use. Covers most surfaces in One Coat. Requires no other primer on new plaster or new wood. Ideal for kitchens, bathrooms, hallways — walls, furniture, plaster, woodwork and metal. Washes like tile. Colors match SPRED SATIN. May be tinted with DRAMATONE Tinting Colors.				
4600 White and Colors; 4618 SPRED Lustre Pastel Tinting White	8.86	2.66	1.53	—
4680 SPRED Lustre Dramatone Tint Base	7.96	2.31	—	—
4687 Int. Tint Base	8.26	2.44	—	—
APPLICATION—Brush, Roller, Spray				
DRYING TIME—Dust free 3 to 4 hours; recoat overnight				
THINNER—Mineral Spirits or Turpentine				
COVERAGE—Approx. 550 Sq. Ft. per gallon				
DRAMATONE MULTI-PURPOSE TINTING COLORS Y-1781 line (For Tinting Latex, Alkyd and Other Paints)				
Tinting colors for use with SPRED SATIN Latex Paint, Alkyd Semi-Gloss Enamel, Alkyd Flat Enamel and Other Paints. See Dramatone displays for wide range of colors.	2 Oz. Paks	1 Oz. Paks	¼ Oz. Paks	1/16 Oz. Paks
1781 Blue; 1782 Lamp Black; 1783 Umber Brown; 1784 Green; 1786 Red Oxide; 1787 Ruby Red; 1788 Ferrite Yellow	Per Pak. .62	Per Pak. .52	Per Pak. .42	Per Pak. .40
1791 Hansa Yellow; 1792 Light Green; ‡1793 Bright Orange	.72	.60	.49	.47

*AVAILABLE IN 5-GAL. CANS AT 15c PER GALLON LESS THAN 1-GAL. PRICES.
‡FOR INTERIOR USE ONLY.

GLD027048

	Gals.	Qts.	Pts.	½ Pts.
***SPRED HOUSE PAINT Y-3600 line** **(100% Latex Exterior Paint)** A new blister-resistant house paint for exterior wood and masonry. May be applied without primer over sound previously painted surfaces which are in good condition. Has a remarkable fast drying time of thirty minutes, which practically eliminates damage from bugs, rain and dust. May be applied over damp surfaces. Has long lasting velvet-like sheen. Once the Spred House Paint system is used on a house, future paintings will require only one coat. White and Colors	8.30	2.55	—	—
APPLICATION—Brush, Roller, Spray Gun DRYING TIME—4 hours for recoating THINNER—Water COVERAGE—Approx. 450 Sq. Ft. per gal. on smooth surface				
***SPRED HOUSE PAINT WHITE TINT BASE—Y3625**	8.30	2.55	—	—
***SPRED PRIMECOAT =1 Y-3651** **(Thin With Mineral Spirits)** Spred Primecoat =1 provides a firm foundation on new or unpainted exterior surfaces. The ideal undercoat that creates the finest possible two coat paint job when used under Spred House Paint. Excellent also for recoating badly weathered or porous surfaces that have been previously painted. This primecoat has been especially formulated for Spred House Paint	8.30	2.55	—	—
APPLICATION—Brush, Roller, Spray Gun DRYING TIME—48 Hours THINNER—Turpentine or Mineral Spirits COVERAGE—450-550 Sq. Ft. per gallon				
***SPRED GLIDE-ON Y-3500 line** **(Vinyl-Latex Exterior Masonry Paint)** An exterior vinyl-latex masonry paint, unaffected by the alkalinity found in all masonry surfaces. Designed for use on stucco, concrete, brick, concrete block, cinder block, asbestos shingle and panel siding, unglazed tile and primed metal. Keeps out moisture yet the surface "breathes" to let vapor escape from inside. A tough vinyl film that resists driving rains, hottest sunshine, mildew, snow and ice, sea air and salt water spray, strongest smog, dust and chemical fumes. Resists cracking, peeling, fading, blistering, acid and alkali action. White and Colors	7.41	2.26	—	—
APPLICATION—Brush, Roller, Spray DRYING TIME—Overnight for recoating THINNER—Water COVERAGE—Up to 400 Sq. Ft. per gallon				

*AVAILABLE IN 5-GAL. CANS
AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

	Gals.	Qts.	Pts.	½ Pts.
***SPRED PRIMER-SEALER Y-3416** **(A Latex Vapor-Barrier)** An excellent latex primer for porous surfaces of dry-wall construction, plaster, masonry and asbestos covered pipes. Seals high-suction plaster, most water stains, "hot spots" and discolored surfaces. Assures positive sealing and holdout for succeeding finishing coats of either latex or oil base paints. May be intermixed with latex paints for color, or tinted with DRAMATONE Tinting Colors. An approved vapor barrier which helps to prevent outside paint failures ..... APPLICATION—Brush, Roller, Spray THINNER—Water DRYING TIME—20 minutes; may be recoated in 4 hours COVERAGE—Up to 400 Sq. Ft. per gallon on plaster; 100 Sq. Ft. per gallon on porous wallboard	6.36	2.01	—	—
***SURFACE BOND Y-55** **(Seals Powdery Masonry Surfaces)** A high quality, clear finish bonding coat. Designed to penetrate deeply into chalky surfaces left by previous coats of cement bondings or powder type paints on masonry surfaces. Dries hard to help prevent further chalking. Anchors old surface to make a perfect bond for SPRED GLIDE-ON, as well as other exterior and interior masonry paints ..... APPLICATION—Brush, Spray DRYING TIME—1 to 4 days depending upon drying conditions THINNER—Turpentine or Mineral Spirits COVERAGE—300 to 400 Sq. Ft. per gallon	6.61	2.08	—	—
***SPRED STIPPLE-TEXTURE AND BLOCK FILLER Y-3090** **(Silicated Latex For Masonry and Dry-Wall Construction)** Ready to use on new or old surfaces. Gives all the advantages of texture and all the beauty of paint in one application. Hides irregular surfaces on plaster, wallboard, masonry blocks and wallpaper, seals spackled nail heads and tape joints. Easily applied with brush or roller. May be stippled or lightly textured in a variety of patterns and techniques. Especially made for texturing and stippling and for filling masonry blocks, pores and voids, to eliminate "pinholing" in finish coat, to assure better water repellency and to develop excellent appearance on interior and exterior masonry. May be tinted with DRAMATONE Tinting Colors. White ..... APPLICATION—Brush for texturing, followed by stipple brush, sponge, trowel, whisk broom, comb, etc., as desired. Use roller for stipple effect. Brush, roll or spray when used as a block filler. DRYING TIME—Overnight THINNER—Water COVERAGE—Texturing and filling blocks—75 to 100 Sq. Ft. per gallon. Stippling: 175 to 200 Sq. Ft. per gallon	6.16	1.88	—	—
SPRED SURFACENE Y-66 **(Liquid Surface Conditioner and Brush Cleaner)** A clear liquid that can be applied to old enameled, painted or varnished surfaces to clean the surface, dull the gloss and insure good adhesion for a new finish coat. Eliminates the work and dust of sanding and prepares surfaces for refinishing in one easy operation. SURFACENE may also be used as a brush cleaner ..... APPLICATION—Cloth or Brush	5.41	1.76	1.10	—

*AVAILABLE IN 5-GAL. CANS AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

GLD027050

	Gals.	Qts.	Pts.	½ Pts.
SPRED PATCH Y-3475 **(100% Latex Spackling Compound)** A ready-to-use spackling compound. Will not bleed through paint, or flash. Does not shrink. Dries to a "puff" which may be easily sanded. Does not clog sandpaper. Excellent adhesion APPLICATION—Putty Knife DRYING TIME—30 minutes THINNER—Water	5.11	1.89	4 oz. Tube .51	.74
SPRED FLAT Y-3000 **(Oil-Emulsion Interior Paint)** One gallon makes six quarts of paint when mixed with two quarts of water. Easy to apply over wallpaper, new or old plaster, wallboard, painted surfaces, cement and rough tile walls. Has limited washability. White APPLICATION—Brush, Roller, Spray DRYING TIME—30 minutes; recoat 4 to 12 hours, depending upon surface THINNER—Water COVERAGE—Up to 650 Sq. Ft. per gallon	6.21	1.93	—	—

GLD027051

	Gals.	Qts.	Pts.	½ Pts.	
GLID-TONE WOOD FILLER Y-700 For use on all open-grained wood such as oak, chestnut, walnut and mahogany. Has pure silex base and will not shrink or break away from the pores of the wood when dry. Furnished in paste form. Must be reduced with naphtha or turpentine .... APPLICATION—Brush, Cloth THINNER—Turpentine, Naphtha	6.39	1.98	—	.76	
GLOSS FINISHES See: Japalac; Ripolin; Florenamel; Rustmaster					
HEAT RESISTING ALUMINUM See: Metallite **HOUSE PAINT** See: SPRED House Paint; Endurance Paints; SPRED Glide-On; Everon **IRON PRIMER** See: Liquid Red Lead; Rustmaster Metal Primers **IMPERIAL ONE-COAT WHITE HOUSE PAINT** See: Endurance Imperial **INTERIOR ALUMINUM** See: Metallite All-Purpose Aluminum					
JAPALAC SCREEN AND IRON ENAMEL Y-1222 Gloss black, solid-covering enamel for exterior screens, wood and metal sash, wrought iron, decorative lamps, etc. Also ideal for interior ironwork, pipes, grills, furnaces, stoves, heaters, andirons, etc. Will not clog screen mesh. Resists weather and protects metal from rusting ..... APPLICATION—Brush, Spray or Special Applicator DRYING TIME—6 to 8 hours THINNER—Mineral Spirits or Turpentine COVERAGE—600 Sq. Ft. per gallon	5.51	1.79	1.10	.75	
JAPALAC ENAMEL Y-1200 line **Quick-Drying, Alkyd Gloss** An extra-durable, alkyd enamel in brilliant colors that cover in ONE COAT. Bright hues and muted tones give new life and sparkle to old surfaces — walls, ceilings, woodwork and furniture. JAPALAC Quick-Drying Alkyd Enamel is formulated for the finest enameling inside and outdoors. It looks, wears and washes like baked enamel. Colors may be tinted with DRAMATONE Tinting Colors. Ultra White, Brilliant Black, Flat Black and Colors ..... APPLICATION—Brush, Roller, Spray DRYING TIME—4 to 6 hours; 24 hours for recoating THINNER—Mineral Spirits or Turpentine COVERAGE—Approx. 500 Sq. Ft. per gallon	10.30	3.01	1.71	½ Pts. 1.07	¼ Pts. .71

	Gals.	Qts.	Pts.	½ Pts.
JAPALAC SPRAY ENAMEL Y-4000 line In Ready-To-Spray Cans All-purpose, interior-exterior enamel in pressurized, aerosol cans ready for immediate spraying. Extra-durable, quick-drying enamel of brilliant beauty. Gives professional appearance to porch and lawn furniture, bicycles, toys, tables, chairs, etc. Ideal for wickerwork. Colors match regular JAPALAC Alkyd Enamel colors. In addition, JAPALAC SPRAY ENAMEL is available in ready-to-spray interior-exterior Aluminum, rich Gold, and a clear finish. White, All Colors, and Clear ..... APPLICATION—Spray DRYING TIME—Ten minutes	—	16 Av. Oz. Can 1.59	—	—
LACQUER See: Glid-Tone Crystalacq (Brushing Lacquer) **LATEX PAINTS** See: SPRED Products Section **LINOLEUM COATING** See: Glid-Tone Crystalacq				
***LIQUID RED LEAD (Modified) Y-506** Recommended whenever a shop coat of red lead is specified. Comes ready to apply, is extremely elastic and is an excellent rust preventative ..... APPLICATION—Brush, Spray DRYING TIME—16 hours; 48 hours for recoating THINNER—Mineral Spirits or Turpentine COVERAGE—500 to 600 Sq. Ft. per gallon	9.31	2.79	1.63	1.05
MACHINERY ENAMEL See: Rustmaster Enamel; Japalac **MASONRY FINISHES** See: SPRED House Paint; Silicone Driwall; SPRED Glide-On				
***METALLITE ALL PURPOSE ALUMINUM Y-592** An extremely smooth, chrome-like aluminum finish for use on radiators, furnace jackets, airducts, hot water tanks and heaters, pipes and other interior surfaces. Will not tarnish under ordinary conditions. It maintains its brilliance. Makes an excellent sealer over asphalt. Retards corrosion caused by fumes and moisture. Withstands heat up to 500°F. Hides with one coat. Easily cleaned. Reflects light .... APPLICATION—Brush, Roller, Spray DRYING TIME—2 to 4 hours: 24 hours for recoating THINNER—Mineral Spirits or Turpentine COVERAGE—650 Sq. Ft. per gallon	7.40	2.28	1.36	.88

*AVAILABLE IN 5-GAL. CANS AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

	Gals.	Qts.	Pts.	½ Pts.
METAL PRIMER See: Liquid Red Lead; Rustmaster Metal Primer				
MILDEW-RESISTING PAINTS See: SPRED Glide-On; Endurance Mildew and Fume-Resistant Paint				
METAL PROTECTIVE PAINTS See: Rustmaster; Metallite; Liquid Red Lead				
***NEVA-ROT Y-1502** **(Wood and Canvas Preservative)** A preservative that combats mold, fungus, mildew, termites, ants, beetles, bacteria, rot and decay. Equally effective on wood, canvas and rope. Highly recommended for new or old lumber, handrails, porches, columns, stairways, fence posts, cribs, barns, foundation timbers, ropes, lines, canvas awnings — wherever non-metal surfaces require protection from insects and bacterial damage. NEVA-ROT has been tested and approved by the U. S. Navy as a preservative. It is odorless and non-toxic to humans, will not irritate eyes or skin. Neva-Rot Green Y-1502 APPLICATION—Brush, Spray, Dip, Swab DRYING TIME—Overnight THINNER—None Required COVERAGE—200 Sq. Ft. per gallon	5.56	1.87	—	—
ONE-COAT HOUSE PAINT See: Endurance Imperial				
OIL COLORS IN TUBES See: Colors-In-Oil				
PAINT AND VARNISH REMOVER See: Glid-Strip; Ad-El-Ite				
PATCHING PLASTER See: SPRED Patch				
PORCH AND DECK ENAMEL See: Florenamel				
PRIMERS AND SEALERS See: Alkali-Resisting Primer Y5042; Endurance Exterior Basecoat; Speed-Wall Interior Basecoat; SPRED Primer-Sealer; Glidden-coat Enamel Undercoat; Ripolin Undercoat; Surface Bond				
RED LEAD (Liquid) See: Liquid Red Lead				
RIPOLIN ENAMEL (Quick-Drying White) Y-2900, Y-2950 One of the oldest and finest enamels with world-wide acceptance. Architects and painters recognize RIPOLIN as the finest enamel for interior and exterior decorating. May be tinted with Colors-In-Oil or DRAMATONE Tinting Colors. Gloss, Semi-Gloss (White Only) APPLICATION—Brush, Roller, Spray DRYING TIME—6 to 8 hours; 24 hours for recoating THINNER—Mineral Spirits or Turpentine COVERAGE—600 Sq. Ft. per gallon	10.61	3.26	1.86	1.09

*AVAILABLE IN 5-GAL. CANS AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

GLD027054

	Gals.	Qts.	Pts.	½ Pts.
RIPOLIN UNDERCOAT Y-2555 A perfect first coater for new wood or previously painted surfaces. Dries to a firm opaque film. Especially designed for use with Ripolin Semi-Gloss and Gloss Enamels. Completely hides and seals a surface so that finishing coats of Ripolin Enamel produce full luster and depth of gloss. Requires only light sanding. May be tinted with Colors-In-Oil or DRAMATONE Tinting Colors ..... APPLICATION—Brush, Spray DRYING TIME—Overnight for sanding and recoating THINNER—Mineral Spirits or Turpentine COVERAGE—500 Sq. Ft. per gallon	7.76	2.41	1.43	—
RIPOLIN YACHTING FINISHES		(PRICES UPON REQUEST)		
***ROCKSPAR VARNISH Y-50** Heavy bodied varnish for all interior surfaces. One coat equivalent to two coats of ordinary varnish. No shrinkage on drying. Dries with deep high gloss ..... APPLICATION—Brush DRYING TIME—Overnight; 24 hours for recoating THINNER—Mineral Spirits or Turpentine COVERAGE—Up to 700 Sq. Ft. per gallon	8.46	2.56	1.50	.96
RUSTMASTER GLOSS ENAMEL Y-470 line *A high quality versatile enamel of excellent quality. It has exceptional ease of application and may be applied by brushing, or spraying as a finish coat over metal with Y470 or Y471 Rustmaster Primer. Rustmaster Gloss Enomel guards against rusting of machinery and equipment in the factory and on the farm as well as metal surfaces around the home and schools such as metal window frames and casings, iron fences, railings, bicycles, lawn mowers, playground equipment, etc.* Royal Blue, Greenfield, Slate, Gloss Black, Flat Black, Aluminum..... *Suntone, Flare Red* ..... White ..... APPLICATION—Brush or Spray DRYING TIME—Overnight THINNER—Turpentine or Mineral Spirits for Brushing; VM & P Naphtha for Spraying COVERAGE—Up to 500 Sq. Ft. per gallon	9.21 9.21 9.21	2.76 2.76 2.76	1.60 1.60 1.60	1.02 1.02 1.02
RUSTMASTER METAL PRIMER Y-470 A new, unexcelled, fast drying corrosion resistant exterior and interior metal primer containing revolutionary Phenolic Resin Penetrating Liquid (U.S. Patent No. 2978424) that cuts through rust and seals metal pores, locking out air and corrosive moisture. A finish coat of Rustmaster Enamel will provide an exceptionally durable coating .... APPLICATION—Brush or Spray DRYING TIME—Overnight THINNER—Turpentine or Mineral Spirits for brushing; VM & P Naphtha for spraying COVERAGE—Up to 500 Sq. Ft. per gallon	9.21	2.76	1.60	1.02

*AVAILABLE IN 5-GAL. CANS AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

	Gals.	Qts.	Pts.	½ Pts.
RUSTMASTER PRIMER Y-4030 (Spray Can) Same quality as Rustmaster Metal Primer Y470, packed in handy spray can for easy, instant use. Ideal for hard-to-reach areas APPLICATION—Spray DRYING TIME—Overnight for recoating	16 Oz. Can 1.89	—	—	—
RUSTMASTER GALVANIZED PRIMER Y-471 Provides longer-lasting protection for galvanized metal and aluminum. Use on new galvanized steel without chemical treatment. This prime coat may be used as a finish coat or recoated with Rustmaster Enamel, Endurance House Paint or Japalac.... APPLICATION—Brush, Roller, Spray DRYING TIME—48 hours THINNER—Turpentine, Mineral Spirits COVERAGE—Approx. 350 Sq. Ft. per gallon	Gals. 9.21	2.76	1.60	1.02
ROOF PAINTS See: Aluminum Asphalt Roof Paint; Metallite All-Purpose Aluminum **SCREEN ENAMELS** See: Japalac Screen and Iron Enamel **SEMI-GLOSS ENAMELS** See: Ripolin; SPRED Lustre				
SILICONE SLICK SPRAY Y-58 **(Miracle Lubricant With 1001 Uses)** A new, spray lubricant that protects and preserves while it lubricates. An excellent ice and water repellent. Push button spray lubricates hard-to-reach parts and areas. Makes windows, drawers, doors and other sticking items slide freely. Stops squeaks	6 Oz. Can 1.59	16 Oz. Can 2.95	—	—
SPACKLING COMPOUND See: SPRED Patch **SPAR VARNISH** See: Glid-Tone Spar Varnish				
***SPEED-WALL ALKYD INTERIOR BASECOAT Y-4516** A ready-to-use, low odor, alkyd-type primer sealer for new and old interior wall surfaces of plaster, masonry or wallboard. Also for previously painted walls in poor condition and patched areas. Its remarkable ease of brushing and exceptional filling, sealing, hiding, and alkali-resisting properties are gained through the use of special resins, pigments, and oils APPLICATION—Brush, Roller, Spray DRYING TIME—Overnight for recoating THINNER—Mineral Spirits or Turpentine COVERAGE—Up to 450 Sq. Ft. per gallon	Gals. 6.31	Qts. 1.98	—	—
SPRED PRODUCTS See: SPRED Products Section **STAINS** See: Glid-Tone Stain				

*AVAILABLE IN 5-GAL. CANS AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

	Gals.	Qts.	Pts.	½ Pts.
***STOCK FARM WHITE PAINT Y-596** An excellent low cost exterior paint for use on wood surfaces such as fences, barns, outbuildings, sheds, etc. This material, produced for use in stock farms, is formulated without lead pigments, and contains wood preservatives. The creosote-like odor tends to repel livestock APPLICATION—Brush, Spray DRYING TIME—Overnight; 24 hours for recoating THINNER—Mineral Spirits or Turpentine COVERAGE—Up to 450 Sq. Ft. per gallon depending upon surface condition	6.51	—	—	—
STOVE AND IRON ENAMEL See: Japalac Screen and Iron Enamel **SURFACE CONDITIONER** See: SPRED Surfacene; Surface Bond **TILE ROOF PAINT** See: SPRED Glide-On				
TINTING COLORS See: Dramatone Multi-Purpose Tinting Colors; Colors-In-Oil **TRIM AND SHUTTER COLORS** See: Endurance House Paint **TUBE COLORS** See: Dramatone Multi-Purpose Tinting Colors; Colors-In-Oil **UNDERCOATERS** See: Gliddencoat; Ripolin Undercoat; Surface Bond; Speed-Wall Interior Basecoat; SPRED Primer-Sealer; Endurance Exterior Basecoat; Rustmaster Metal Primer 470; Rustmaster Galvanized Primer 471. **VAPOR BARRIER** See: SPRED Primer-Sealer **VARNISHES** See: Glid-Tone Spar; Glid-Tone Satin Sheen; Glid-Tone Gloss; Rockspar, Xpert **VARNISH REMOVER** See: Ad-El-Ite; Glid-Strip **VINYL-LATEX PAINT** See: SPRED Glide-On				
VISMATIC GREEN CHALKBOARD COATING Y-594 A lusterless matte finish, green in color. Extremely popular in a large number of America's finest school, college and university classrooms. It is used to paint black chalkboards in a new light-reflecting color that is easy on the eyes. This green finish achieves maximum visibility and minimum light wave vibration of chalk lines and letters. Easy to apply APPLICATION—Brush, Spray DRYING TIME—Overnight for recoating THINNER—Mineral Spirits COVERAGE—Up to 500 Sq. Ft. per gallon	9.56	2.77	1.62	—

*AVAILABLE IN 5-GAL. CANS AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

	Gals.	Qts.	Pts.	½ Pts.
WOOD FILLER See: Glid-Tone Wood Filler **WOOD FINISHES** See: Glid-Tone Products, Xpert **WOOD PRESERVATIVE** See: Neva-Rot **WOOD STAIN** See: Glid-Tone Stain				
YACHT AND BOAT FINISHES (Ripolin)		(PRICES UPON REQUEST)		
Xpert Polyurethane Liquid Plastic Satin Sheen Y-37 Clear plastic satin-sheen finish for interior-exterior use. Outwears conventional interior finishes two to one. Provides 25% more durability for exteriors. For use on floors, furniture, paneling or exterior redwood, doors, shutters, etc. Not recommended over shellac, lacquer sanding sealers, lacquer or for large areas of exterior siding.	11.51	3.33	1.88	—
Xpert Polyurethane Liquid Plastic Clear Gloss Y-51 Clear, high gloss plastic finish that will outwear conventional lacquers and varnishes two to one for interior use. Gives up to 25% greater durability for exteriors. May be used on floors, furniture, paneling or exterior redwood, cedar doors, etc. Not recommended over shellac, lacquer sanding sealers, lacquer or for large areas of exterior siding.	9.56	2.85	1.65	—
Xpert Wood Finish Clear Y-2842 A water white lacquer; provides a clear, satin sheen finish for interior wood floors, paneling, trim, cabinets and fine furniture. Dries in thirty minutes and may be recoated in two hours. It is non-yellowing and has good resistance to water, alcohol and chemicals.	8.11	2.48	1.46	—

NOTE: Although the formulations and recommendations contained in this price list have been established through careful evaluation, users of Glidden paints are urged to obtain specific information concerning their painting requirements. Seller's liability shall in no event exceed value of this material, which is warranted only to conform to formula or sample. Seller hereby expressly excludes all other express or implied warranties whatsoever.

Gals.	Qts.	Pts.	½ Pts.

GL D027059

	Gals.	Qts.	Pts.	½ Pts.

GLD027060

CODE NUMBER AND DESCRIPTION

Y-1 ..... Glid-Tone Gloss Varnish
Y-30 .. Glid-Tone Redwood Clear Finish
Y-31 ..... Glid-Tone Redwood Stain
Y-37 ..... Xpert Satin Sheen
Y-47 ... Glid-Tone Satin Sheen Varnish
Y-48 ..... Glid-Tone Spar Varnish
Y-50 ..... Rockspar Varnish
Y-51 ..... Xpert Clear Gloss
Y-55 ..... Surface Bond
Y-58 ..... Silicone Slick Spray
Y-66 ..... Spred Surfacene
Y-67 ..... Black Asphaltum
Y-70 Adelite Paint & Varnish Remover
Y-74 .. Glid-Strip Paint & Var. Remover
Y-242 .. Glid-Tone Stain—Honey Maple
Y-243 .. Glid-Tone Stain—Fr. Provincial
Y-244 Glid-Tone Stain—Mod. Red Mah.
Y-245 ..... Glid-Tone Stain—Walnut
Y-246 ..... Glid-Tone Stain—Wheat
Y-247 ..... Glid-Tone Stain—Blonde
Y-248 .. Glid-Tone Stain—Brown Mah.
Y-249 ..... Glid-Tone Stain—Platinum
Y-250 ..... Glid-Tone Stain—Suntan
Y-251 ..... Glid-Tone Stain Reducer
Y-252 ..... Glid-Tone Stain—Maple
Y-254 ..... Glid-Tone Stain—Cherry
Y-255 ..... Glid-Tone Stain—Ebony
Y-257 .... Glid-Tone Stain—Driftwood
Y-258 .... Glid-Tone Stain—Fruitwood
Y-259 .... Glid-Tone Stain—Butternut
Y-260 Glid-Tone Regrain Ground Coat
Y-470 ..... Rustmaster Primer
Y-471 . Rustmaster Galvanized Primer
Y-472 ..... Rustmaster Aluminum
Y-475 ..... Rustmaster White
Y-476 ..... Rustmaster Black
Y-477 ..... Rustmaster Flat Black
Y-478 ..... Rustmaster Suntone
Y-479 ..... Rustmaster Royal Blue
Y-480 ..... Rustmaster Greenfield
Y-481 ..... Rustmaster Flare Red
Y-482 ..... Rustmaster Slate
Y-500 Endurance House Paint Barn Red
Y-506 ..... Ready Mixed Red Lead
Y-534 ..... Silicone Driwal Clear
Y-555 Gliddencoat Enamel Und. White
Y-592 All-Purpose Metallite Alum. Paint
Y-594 Vismatic Green Chalkbd. Coating
Y-596 ..... Stock Farm Paint White
Y-605 .. Aluminum Asphalt Roof Paint
Y-700 ..Glid-Tone Natural Wood Filler
Y-854 ..... Florenamel Tile Red
Y-871 ..... Florenamel Tile Green
Y-874 ..... Florenamel Harbor Gray
Y-875 ..... Florenamel Chateau Gray
Y-876 ..... Florenamel Spice Wood
Y-1201 Glid-Tone Var. Stain, Dark Oak
Y-1202 Glid-Tone Varnish Stain Walnut
Y-1203 Glid-Tone Varnish, Stain Mah.
Y-1207 ..... Japalac Brilliant Black
Y-1208 ..... Japalac Flat Black
Y-1212 ..... Japalac Bud Green
Y-1217 ..... Japalac Ultra White
Y-1219 ..... Japalac Dawn Gray
Y-1222 ..... Japalac Screen Black
Y-1246 ..... Japalac Rich Blue
Y-1250 ..... Japalac Delphinium
Y-1255 ..... Japalac Light Ivory
Y-1256 ..... Japalac Vermilion
Y-1260 ..... Japalac Rose Pink
Y-1263 ..... Japalac Botany Brown
Y-1267 ..... Japalac Ribbon Blue
Y-1269 ..... Japalac Blue Turquoise
Y-1270 ..... Japalac Lemon Yellow
Y-1271 ..... Japalac Greenbrier
Y-1502 ..... Neva-Rot Green
Y-1701 .... Colors in Oil Yellow Ochre
Y-1702 .... Colors in Oil Burnt Sienna
Y-1703 .... Colors in Oil Burnt Umber
Y-1705 Colors in Oil Med. Chrome Green
Y-1706 Colors in Oil Lt. Chrome Yellow
Y-1707 Colors in Oil Med. Chrome Yel.
Y-1708 ..... Colors in Oil Raw Umber
Y-1709 ..... Colors in Oil Ivory Black
Y-1711 ... Colors in Oil Prussian Blue
Y-1716 Colors in Oil Lt. Chrome Yellow
Y-1717 .. Colors in Oil Amer. Vermilion
Y-1718 .... Colors in Oil Venetian Red
Y-1719 ..... Colors in Oil Raw Sienna
Y-1720 ..... Colors in Oil Lampblack
Y-1742 Colors in Oil Dark Chrome Yel.
Y-1745 .... Colors in Oil Perma Green
Y-1746 ..... Colors in Oil Perma Blue
Y-1781 ..... Dramatone Blue
Y-1782 ..... Dramatone Lampblack
Y-1783 ..... Dramatone Umber Brown
Y-1784 ..... Dramatone Green
Y-1786 ..... Dramatone Red Oxide
Y-1787 ..... Dramatone Ruby Red
Y-1788 .... Dramatone Ferrite Yellow
Y-1791 .... Dramatone Hansa Yellow
Y-1792 ..... Dramatone Light Green
Y-1793 .... Dramatone Bright Orange
Y-1800 Endurance House Paint White
Y-1802 Endurance House Paint Black
Y-1813 .... End. H.P. Tobacco Brown
Y-1828 ..... End. H.P. Crylite Green
Y-1850 ..... End. H.P. Mildew & Fume Res. White
Y-1851 .... End. Basecoat Mildew & Fume Res.
Y-1855 ..... End. H.P. Castle Red
Y-1856 ..... End. H.P. Ivory
Y-1857 ..... End. H.P. Cream
Y-1859 ..... End. H.P. Light Gray
Y-1860 ..... End H.P. Medium Gray
Y-1861 ..... End. H.P. Shutter Green
Y-1867 .... End. H.P. Imperial White
Y-1870 .... End. H.P. Deep Turquoise
Y-1871 ..... End. H.P. Dark Blue
Y-1872 ..... End. H.P. Dark Walnut
Y-1886 ..... End. H.P. Light Canary
Y-1887 ..... End. H.P. Pastel Green
Y-1892 End. H.P. Non-Chalking White
Y-2200 ... Everon House Paint White
Y-2218 Craftsman House Paint White
Y-2555 ..... Ripolin Undercoat White
Y-2750 ..... End. Velvet H.P. White
Y-2751 End. Velvet H.P. Mayflower Yel.
Y-2752 End. Velvet H.P. Sterling Gray
Y-2754 .. End. Velvet H.P. Gunmetal
Y-2756 End. Velvet H.P. Cottage Ivory
Y-2758 End. Velvet H.P. Granada Red
Y-2759 End. Velvet H.P. Shrub Green
Y-2761 End. Velvet H.P. Brown Antique
Y-2764 ... End. Velvet Shadow Green
Y-2822 . Glid-Tone Crystalacq Reducer
Y-2840 ..... Glid-Tone Crystalacq
Y-2842 ..... Xpert Clear Wood Finish
Y-2900 ..... Ripolin Ultra White
Y-2950 Ripolin Semi-Gloss Enamel White
Y-3000 ..... Spred Flat White
Y-3050 ..... Craftsman Latex Pt. Alaska White
Y-3051 Craftsman Latex Pt. Tusk Ivory
Y-3052 Craftsman Latex Pt. Spearmint
Y-3053 .. Craftsman Latex Pt. Azalea
Y-3054 Craftsman Latex Pt. Pewter Gray
Y-3055 .... Craftsman Latex Pt. Aqua
Y-3056 ... Craftsman Latex Pt. Hemp
Y-3057 Craftsman Latex Pt. Brook Blue
Y-3058 . Craftsman Latex Pt. Maytime
Y-3059 Craftsman Latex Pt. Bone White
Y-3090 Spred Stipple Text. Bone White
Y-3401 ..... Spred Satin Pale Ivory
Y-3405 . Spred Satin Confetti Yellow
Y-3406 ... Spred Satin Light Apricot
Y-3407 .. Spred Satin Pinefrost Green
Y-3409 ... Spred Satin Tropic Green
Y-3410 ..... Spred Satin Spray Blue
Y-3412 ..... Spred Satin Blue Azure
Y-3413 .... Spred Satin Bone White
Y-3414 ..... Spred Satin Moonmist
Y-3415 .... Spred Satin Blossom Pink
Y-3416 ..... Spred Primer Sealer
Y-3418 . Spred Satin Decorator White
Y-3434 .. Spred Satin Charcoal Black
Y-3441 ..... Spred Satin Cheer
Y-3443 ... Spred Satin Cotton Candy
Y-3447 .... Spred Satin Sandy Beige
Y-3448 . Spred Satin Silver Turquoise
Y-3449 .... Spred Satin Oyster White
Y-3467 ... Spred Satin Pebble Beach
Y-3470 Spred Satin Ceiling Flat White
Y-3472 .. Spred Satin Medallion Gold
Y-3475 ..... Spred Patch
Y-3477 ... Spred Satin Biscayne Blue
Y-3478 ..... Spred Satin Aquaglow
Y-3479 . Spred Satin Sherwood Green
Y-3480 ..... Spred Satin Dramatone Tint. Base
Y-3487 Spred Satin Int. Tinting Base
Y-3501 ..... Spred Glide-On Bamboo
Y-3504 .. Spred Glide-On Silver Smoke
Y-3506 .... Spred Glide-On Tang Red
Y-3507 .... Spred Glide-On Sunflower
Y-3510 .. Spred Glide-On Jewel Green
Y-3513 .. Spred Glide-On Gray Velvet
Y-3515 . Spred Glide-On Lt. Tangerine
Y-3516 ... Spred Glide-On Mist Brown
Y-3519 ..... Spred Glide-On Cascade
Y-3525 . Spred Glide-On Tinting White
Y-3600 ..... Spred Latex H.P. White
Y-3602 Spred Latex H.P. Sunbeam Yel.
Y-3603 ..... Spred Latex H.P. Taffy
Y-3606 . Spred Latex H.P. Dover Gray
Y-3607 .... Spred Latex H.P. Bayberry
Y-3608 ..... Spred Latex H.P. Bark
Y-3612 .. Spred Latex H.P. Evergreen
Y-3613 ..... Spred Latex H.P. Onyx
Y-3615 ..... Spred Latex H.P. Fiesta
Y-3616 ... Spred Latex H.P. Polo Tan
Y-3620 Spred Latex H.P. Cape Cod Red
Y-3625.....Spred H.P. Tinting White
Y-3651 ..... Spred Prime Coat No. 1
Y-4000....Japalac Spray Enamel White
Y-4001 Japalac Spray Enamel Flat Black
Y-4002 Japalac Spray Enamel Gloss Blk.
Y-4003 ..... Japalac Spray Enamel Delphinium
Y-4004 Japalac Spray Enamel Dawn Gray
Y-4005 Japalac Spray Enamel Bud Green
Y-4006 Japalac Spray Enamel Vermilion
Y-4008 ..... Japalac Spray Aluminum
Y-4009 ..... Japalac Spray Gold
Y-4010 ... Japalac Spray Clear Plastic
Y-4011 .... Japalac Spray Copper Tone
Y-4013 Japalac Spray Enamel Rose Pink
Y-4015 Japalac Spray Enamel Lemon Yel.
Y-4016 Japalac Spray Enamel Greenbrier
Y-4017 .... Japalac Spray Flat White
Y-4018 . Japalac Spray Blue Turquoise
Y-4019 ..... Japalac Spray Tan Bark
Y-4030 ..... Rustmaster Primer
Y-4516 ..... Interior Base Coat
Y-4550 ..... Speedenamel White
Y-4551 ..... Speedenamel Black
Y-4552 ..... Speedenamel Orange
Y-4553 ..... Speedenamel Deep Green
Y-4554 ..... Speedenamel Med. Green
Y-4556 ..... Speedenamel Fire Red
Y-4560 .... Speedenamel Med. Yellow
Y-4561 ..... Speedenamel Light Gray
Y-4562 ... Speedenamel Machine Gray
Y-4564 ... Speedenamel Imperial Blue
Y-4565 ..... Speedenamel Bright Red
Y-4569 ..... Speedenamel Hydro Blue
Y-4570 ..... Speedenamel Red Oxide Metal Primer
Y-4571 ... Speedenamel Spring Green
Y-4572 .... Speedenamel Neutral Gray
Y-4573 .... Speedenamel EZC Green
Y-4574..Speedenamel School Bus. Yel.
Y-4575 ..... Speedenamel Tint White
Y-4576 ... Speedenamel Deep Orange
Y-4577 .... Speedenamel Mah. Brown
Y-4600 ..... Spred Lustre White
Y-4605 .... Spred Lustre Peach Glow
Y-4618 .. Spred Lustre Tinting White
Y-4641 .. Spred Lustre Crocus Yellow
Y-4643 .. Spred Lustre Cotton Candy
Y-4647 ..... Spred Lustre Sahara
Y-4648 ..... Spred Lustre Caribbean
Y-4649 ... Spred Lustre Oyster White
Y-4651 .... Spred Lustre Congo Ivory
Y-4655 ..... Spred Lustre Springtime
Y-4657 ..... Spred Lustre Woodland
Y-4659 .. Spred Lustre Meadow Green
Y-4660 ..... Spred Lustre Zircon
Y-4662 ..... Spred Lustre Blue Ice
Y-4663 ... Spred Lustre Smoky White
Y-4664 ..... Spred Lustre Plaza Gray
Y-4665 ..... Spred Lustre Pink Haze
Y-4667 .. Spred Lustre Pebble Beach
Y-4672 .. Spred Lustre Medallion Gold
Y-4677 .. Spred Lustre Biscayne Blue
Y-4678 ..... Spred Lustre Aquaglow
Y-4679 . Spred Lustre Sherwood Green
Y-4680 ..... Spred Lustre Dramatone Tinting Base
Y-4687 Spred Lustre Int. Tinting Base
Y-5701 ..... Brush-Day-Lite A. Flat Dutch Ivory
Y-5705 Brush-Day-Lite A. Flat Jonquil
Y-5707 Brush-Day-Lite A. Flat Mint Green
Y-5710 ..... Brush-Day-Lite A. Flat Ocean Spray
Y-5712 ..... Brush-Day-Lite A. Flat Chelsea Blue
Y-5713 Brush-Day-Lite A. Flat Buhrstone
Y-5714 Brush-Day-Lite A. Flat Smoketone
Y-5718 ..... Brush-Day-Lite A. Flat Tinting White
Y-5743 .. Brush-Day Lite A. Cloud Pink
Y-5747 . Brush-Day-Lite A. Flat Taupe
Y-5767 . Brush-Day-Lite A. Flat Beige
Y-5778 Brush-Day-Lite A. Flat Aqua Surf
Y-5780 ..... Brush-Day-Lite A. Flat Dramatone Tinting Base
Y-5787 ..... Brush-Day-Lite A. Intermediate Tinting Base

THE GLIDDEN COMPANY
National Headquarters
900 Union Commerce Building
Cleveland 14, Ohio

SALES OFFICES AND FACTORIES: New York • San Francisco • Los Angeles
Minneapolis • Dallas • Chicago • St. Louis • New Orleans • Cleveland
Atlanta • Portland • Reading • Canada: Toronto and Montreal
Branches in principal cities throughout the United States and Canada.

FORM No. 765

Printed in U.S.A.

GLD027061