

Endurance Mint Base

Liquid

CONSISTENCY

FOR USE ON

CUSTOMER

LABORATORY NO.

COST CLASS

DATE

9/4/6

STRAINER

PEBBLE OR

WT. OR BE 13.6

NUMBER

CODE

ONE GALLON BATCH

LARGE BATCH

IS AGITATION REQUIRED

HY-R

85-90 KU

TEMP.

VISC. RED.

VISCOSIMETER

Stormer

COLOR

SHEEN

FLASH PT.

NON VOL.

MATCH FOR

REDUCER

S-43

Standard Formula

Not to be used

BAKE

TEMP.

DRIP TIME

TUMBLING

SPRINKLING

AMT. FOR BRUSHING as needed

REMARKS:

AIR DRIES IN

O.N.

A. D. TO RECOAT IN

72 hrs.

22 Loz.

35 Loz.

1/2 Loz.

5/16 Loz.

1 Loz.

2 Loz.

1-1/8

4-1/2

13

40

2-1/4

13

1-1/2

0-286

0-62

0-1

S-43

S-148

VM-432

VM-523

VM-433

S-72

APA Advance Puffing

Agent if needed.

YIELD

1.42

100

FORMULATOR

J. E. Southwick

28-8-8

GLD058972

N12029

676890079

COST	DATE	ANALYSIS
		PICANT VEHICLE PIGMENT 41 100
		"Y" Trade Sales Unit 9-10-68 <i>K.H.L. Law per L.N.</i> Endurance Tint Base 9/14/56
		Titanium Calcium 43% Zinc Oxide 32 Calcium Carbonate 25 100%
		PICANT VEHICLE RAW LINSEED OIL 55% BODIED LINSEED OIL 22 MINERAL SPIRITS & Driers 23 100%
		Y-1804-U CUSTOMERS