

NEG. NO. AI-10

## TRADEMARK FILE INFORMATION

Trademark: Polar Patch  
Trademark Owner: The Monroe Company, Inc.  
Last Assignee: Monroe, Incorporated  
Date of First Use  
in Commerce: October 30, 1975  
Registration No.: 1,074,557  
Date Trademark  
Registered: October 4, 1977  
Size of Label in  
Trademark File: 17.1875 x 7 inches



Receipt of Pictured Label by Patent Office:

### DIRECTIONS

POLAR-PATCH is a Cold Temperature Roof Cement of heavy paste consistency which contains a blend of imported and domestic quick-setting asphalt and pure oil, plus a generous quantity of pure Canadian asbestos fiber. It is especially reinforced for extra long service by the addition of special Fine Oil. Apply by trowel.

**CLEAN THE SURFACE THOROUGHLY.** If it is dusty or sandy, sweep with a stiff brush or broom -- if it is covered with treated rust or a previous coating that is scaling, scrape or wire brush until a hard foundation is attained. Nail down all edges of loosened joints and cracks.

Apply POLAR-PATCH with a trowel's broad 1/8" to 1/4" in thickness, smoothing down the edges. Where there is a large hole in the roof, fasten a piece of Ro-ROF Fiberglas Membrane 2" larger than the hole. Apply POLAR-PATCH thickly around the hole. Lay patch on the hole and press down. Then apply more POLAR-PATCH over the entire patch, especially over the edges. If the hole is extra large, nail the patch down.

Leave patches and joints, eaves, valleys, skylights, chimneys and flashings dry for 24 hours before POLAR-PATCH will set. Ro-ROF Fiberglas Membrane over these areas. During extremely cold weather store in a warm room to prevent cracking and insure proper application.

**CAUTION: HARMFUL OR FATAL IF SWALLOWED.**

| COVERAGE                            |                                |
|-------------------------------------|--------------------------------|
| TYPE OF APPLICATION                 | POLAR-PATCH Requirement        |
| Flashing - smooth roofs 100 sq. ft. | 10 gal. (8" wide x 1/2" thick) |
| Flashing - gravel roofs 100 sq. ft. | 15 gal. (8" wide x 1/2" thick) |
| Roof rest repairs - 100 sq. ft.     | 15 gal. (12" thick)            |

NET CONTENTS 5 GALLONS

## MONROE

QUALITY PRODUCTS

---

## POLAR-PATCH

THE COLD TEMPERATURE ROOF CEMENT



THE MONROE COMPANY, INC.