

AMERICAN

FIXTURE WIRE ASBESTOS

PLAINTIFF'S
EXHIBIT
E-329

TABLE NO. 5030

Type AF

150°C 300 VOLTS

CONSTRUCTION: Stranded copper conductor, tape, felted asbestos insulation, flame, heat and moisture resistant impregnation.

USES: Approved for all types of interior illumination, particularly fluorescent lighting fixtures, therapeutic devices, and all high wattage units, especially where socket temperatures exceed 90°C (194°F). NEMA colors available.

Size AWG	Number of Strands	Minimum Insulation Thickness in MILS	Approx. Outside Diameter in Inches	Current Carrying Capacity Amperes	Approx. Lbs. Per 1000 Ft.	Standard Length Per Spool	Feet Per Standard Package
18	16	30	.11	6	10	500' Spool	4000
16	26	30	.12	8	14	500' Spool	2000
14	41	30	.14	17	20	500' Spool	2000
12	65	45	.19	23	30	500' Spool	2000
10	104	45	.21	28	44	500' Spool	500

TABLE NO. 5035

Type AF

18	1	30	.10	6	10	500' Spool	4000
16	1	30	.11	8	13	500' Spool	2000
14	1	30	.12	17	19	500' Spool	2000
12	1	45	.17	23	27	500' Spool	2000
10	1	45	.19	28	41	500' Spool	500

TABLE NO. 5040

Type AF — Braided

18	16	30	.14	6	15	500' Spool	4000
16	26	30	.15	8	19	500' Spool	2000
14	41	30	.17	17	23	500' Spool	2000
12	65	45	.22	23	32	500' Spool	2000
10	104	45	.24	28	46	500' Spool	500

TABLE NO. 5045

Type AF — Braided

18	1	30	.13	6	15	500' Spool	4000
16	1	30	.14	8	18	500' Spool	2000
14	1	30	.15	17	22	500' Spool	2000
12	1	45	.20	23	29	500' Spool	2000
10	1	45	.22	28	43	500' Spool	500

LISTED BY UNDERWRITERS' LABORATORIES, INC. FILE NO. E-7363