

1949 ed

Industrial Toxicology

over activated charcoal and is shipped in steel

that of a combat agent was in 1915. It enters to produce acid chloride for direct chlorination. with acid chlorides and acetates or carbonates.

effect but owing to the warning symptom for the same. Furthermore, it is about 80 per cent of the same (2). The physiological local hydrolysis of phosgene are but slightly efficient carbonyl chloride and corrosion, particularly water content. The effects of carbonyl chloride. Box and Cullum (3). They found that concentrations of phosgene of inhaled substances means of measurement. cited by the American in 1949 for phosgene is

contaminant with the strips of paper which dimethylaminobenzene in the air. In orange and will detect

Industrial Toxicology

[255]

CHLORINATED DIPHENYL

one part of phosgene per million of air. Phosgene is said to be detectable in the field by its so-called tobacco reaction (2). Smokers notice a peculiar flat metallic taste while smoking when phosgene is present in the atmosphere even in very low concentrations. Feigl (6) refers to the detection of phosgene by its conversion to diphenyl carbohydrazine which in turn gives a violet color with copper salts. This test is said to be especially useful for the determination of carbonyl chloride in commercial chloroform and carbon tetrachloride.

REFERENCES

1. Vetter, E. B.: *The Medical Aspects of Chemical Warfare*. Williams & Wilkins Co., Baltimore, 1936, p. 89.
2. Prentiss, A. M.: *Chemicals in War*. McGraw-Hill Book Co., Inc., New York, 1937, p. 164.
3. Box, G. E. P., and Cullumbe, H.: The relationship between survival time and dosage with certain toxic agents. *Brit. J. Pharmacol. Chemotherapy* 2: 27 (March 1947).
4. Box, G. E. P., and Cullumbe, H.: The effect of exposure to sublethal doses of phosgene on the subsequent L(Ct) 50 for rats and mice. *Brit. J. Pharmacol. Chemotherapy* 2: 28 (March 1947).
5. Weston, R. E., and Karel, L.: The biological assay of inhaled substances by the dosimetric method. *J. Pharmacol. Exptl. Therap.* 58: 195 (1946); *J. Ind. Hyg. Toxicol.* 28: 23 (1947); An adaptation of the dosimetric method for use in smaller animals. *Ibid.* 28: 92 (1947).
6. Feigl, F.: *Qualitative Analysis by Spot Tests*. Nordemann Publ. Co., Inc., New York, 1939, p. 248.

CHLORINATED DIPHENYL AND THE CHLORONAPHTHALENES

Characteristics

Chlorinated diphenyl is prepared by the direct replacement of one or more of the hydrogen atoms of diphenyl, $C_6H_5-C_6H_5$, by chlorine. Chlorination may proceed until all the hydrogen atoms have been replaced. The greater the amount of chlorine introduced, the higher the melting point, and the more the substance becomes resinous or waxy in nature. The chlorinated naphthalenes vary in physical state from a thin fluid, mobile liquid to a crystalline or amorphous wax and vary in properties according to the degree of chlorination. The above chlorinated waxes are free from moisture, do not absorb water, are neutral and noncorrosive to metals, do not support combustion, are high in dielectric strength, and have an extraordinary specific inductive capacity. They are marketed under such trade names as "Arochlor", "Halowax", and "Seekay." The melting points of

the chlorinated naphthalenes vary from 87° to 130°, and the boiling points from 288° to 371° C. The specific gravity ranges from 1.4 to 1.7. They are soluble in many organic solvents and oils, especially when heated together.

Industrial Uses

These substances have wide application in industry, chiefly owing to their special insulating and water resistant properties, their chemical stability, and their flame resistance. They are especially used in condensers and in the insulation of wires and cables used in war ships. To a certain extent they are used as solvents for rubber or aniline, as well as for varnish, gums, and resins when mixed in the molten state.

Toxicity

Poisoning by the chlorinated naphthalenes may take the form of acne, particularly of the face, or of toxic jaundice produced by necrosis of the liver. As early as 1918, an acne-form eruption of the skin noted among workers handling chloronaphthalene was ascribed to this substance. Jones has pointed out that in the absence of cleanliness, chloronaphthalene irritated the sebaceous glands causing an excess of cell growth and secretion followed by plugging of the gland and possible secondary infection (1). Schwartz in 1936, discussed dermatitis of workers in the chloronaphthalene and chlorodiphenyl industry. He reported a further outbreak of "Halo-wax acne" or "cable rash" among electricians installing heat and flame-proof cables on ships in 1943 (2, 3).

Systemic poisoning from these chlorinated substances usually follows the inhalation of fume rather than from the handling of the dry hydrocarbon waxes. Damage is severe and occasionally fatal. Acute yellow atrophy of the liver is generally associated with serious exposure to the chlorinated naphthalenes and diphenyl fumes. Three fatalities were reported in 1930-1937 (4, 5). In 1939, three additional cases were reported by Greenburg, Mayers, and Smith (6) and a further case by Collier in 1943 (7). While acne may be taken as a warning sign in workers handling this material it is not invariably present and systemic poisoning may occur in the absence of this sign. Hunter recommends the medical supervision of all such workers with special care regarding the hygienic conditions of employment and with adequate ventilation (8). Precautionary measures were suggested for workers handling chlorinated naphthalenes and diphenyl compounds in 1943 by Greenburg (9). The maximum allowable concentration value for chlorinated diphenyl accepted by the American Conference of Governmental Industrial Hygienists for 1949 was one milligram per cubic meter.

Industrial Toxicology

Analysis

The fume content of the or chlorinated naphthalene position of this material for chloride formed. In such the composition of the chloride more of a whole series of chloride be present. In the present method can only be taken present.

1. Jones, A. T.: The etiology of origin. *J. Ind. Hyg. Toxicol.*
2. Schwartz, L.: *Dermatitis by* 586 (1936).
3. Schwartz, L.: An outbreak. *J. Am. Med. Assoc.* 122: 15
4. Flinn, F. B., and Jurvik, W. liver. *Proc. Soc. Exptl. Biol.*
5. Drinker, C. K., Warren, M. toxic effects from certain 282 (1937).
6. Greenburg, L., Mayers, M. I from exposure to certain 20 (1939).
7. Collier, E.: Poisoning by oil
8. Hunter, D.: *Industrial Toxicol.*
9. Greenburg, L.: Chlorinated (1943). Safety measures for industry. *Ind. Bull.*, Div.

THE CHLORINATED

Characteristics

The four chloronitroparaffins are listed together with their

Industrial Uses

The four chloronitroparaffins than the straight nitroparaffins many synthetic rubbers, and

130°, and the boiling points range from 1.4 to 1.7. They are, especially when heated

in industry, chiefly owing to properties, their chemical stability especially used in condensers in war ships. To a certain extent, as well as for varnish, etc.

may take the form of acne, produced by necrosis of the skin of the skin noted among workers exposed to this substance. Acne, chloronaphthalene, is of cell growth and secretion and secondary infection (1). Cases in the chloronaphthalene further outbreak of "Halos" installing heat and flame-

A substance usually follows handling of the dry hydrocarbonally fatal. Acute yellow with serious exposure to the skin. Three fatalities were reported in other cases by Collier in 1943 sign in workers handling this acute poisoning may occur in the medical supervision of the hygienic conditions of employment. Precautionary measures of naphthalenes and diphenyl maximum allowable concentration by the American Conference 1949 was one milligram

Analysis

The fume content of the air following the heating of chlorinated diphenyl or chlorinated naphthalenes may be determined by the catalytic decomposition of this material followed by suitable determination of the inorganic chloride formed. In such cases, however, the chlorine content and hence the composition of the chloro derivative in use must be known since one or more of a whole series of chloro compounds of varying chlorine content may be present. In the presence of more than one chloro-derivative, this method can only be taken as a rough index of the amount of contaminant present.

References

1. Jones, A. T.: The etiology of acne with special reference to acne of occupational origin. *J. Ind. Hyg. Toxicol.* 23: 290 (1941).
2. Schwartz, L.: Dermatitis from synthetic resins and waxes. *Am. J. Pub. Health* 86: 686 (1936).
3. Schwartz, L.: An outbreak of Halowax acne, "cable rash", among electricians. *J. Am. Med. Assoc.* 122: 158 (1943).
4. Flinn, F. B., and Jarvik, N. E.: Action of certain chlorinated naphthalenes on the liver. *Proc. Soc. Exptl. Biol. Med.* 35: 116 (1936).
5. Drinker, C. K., Warren, M. F., and Bennett, G. A.: The problem of possible systemic effects from certain chlorinated hydrocarbons. *J. Ind. Hyg. Toxicol.* 19: 283 (1937).
6. Greenberg, L., Mayers, M. R., and Smith, A. R.: The systemic effects resulting from exposure to certain chlorinated hydrocarbons. *J. Ind. Hyg. Toxicol.* 21: 29 (1939).
7. Collier, E.: Poisoning by chlorinated naphthalene. *Lancet* 244: 72 (1943).
8. Hunter, D.: *Industrial Toxicology*. Clarendon Press, Oxford, 1944, p. 69.
9. Greenberg, L.: Chlorinated naphthalenes and diphenyls. *Ind. Med.* 12: 520 (1943). Safety measures for use of chlorinated naphthalenes and diphenyls in industry. *Ind. Bull., Div. Ind. Hyg., N. Y. Dept. Labor* 28: 10, 404 (1942).

THE CHLORINATED MONONITROPARAFFINS

Characteristics

The four chloronitroparaffins which are of some industrial importance are listed together with their physical properties in Table 3.

Industrial Uses

The four chloronitroparaffins listed above are more active as solvents than the straight nitroparaffins. 1-Chloro-1-nitropropane will dissolve many synthetic rubbers, including Buna N, Chemigum, Hycar O. R., and