


No. 82 G

EFFECTIVE SEPTEMBER 29, 1966
SUBJECT TO CHANGE WITHOUT NOTICE



-ER

Glidden Paints
SPRED PRODUCTS



THE GLIDDEN COMPANY, NATIONAL HEADQUARTERS, CLEVELAND 2, OHIO

N13685

[illegible]

GLD026102



*AD-EL-ITE PAINT AND VARNISH REMOVER

A top-quality remover. Contains no alkalis, acids, oils or water. Does not raise the grain or discolor the wood. Evaporates very slowly. Very effective in removing old paint, enamel, lacquer and baked Japan.

APPLICATION—Brush

Gals.	Qts.	Pts.	½ Pts.
-------	------	------	--------

2.05 (4 Per Case)	.76	.51	.37
----------------------	-----	-----	-----

*ALKALI-RESISTING PRIMER No. 6419

An easy to apply masonry primer-sealer for interior newly plastered or damp walls, and exterior masonry, brick, stucco and concrete blocks, which are to be painted with synthetic rubber-base or oil base paints. Penetrates deeply into the pores and adheres firmly to the surface, to create perfect bond for finish coat. Resists moisture and alkali. Seals in active lime. Prevents fresh plaster from burning through and discoloring the finish coat.

APPLICATION—Brush, Spray THINNER—Turpentine
DRYING TIME—16 hours Covers 350-400 Sq. Ft. per gal.

(Also See SPRED Primer-Sealer Alkali-Resisting Primer)

5.10	1.51	—	—
------	------	---	---

ALKYD ENAMELS

See: Speed-Wall Alkyd Flat and Semi-Gloss and Gloss White; Japalac; Florenamel; Nev-A-Rust; Ripolin; Speed-Wall Interior Basecoat; SPRED Lustre

*ALUMINUM ASPHALT ROOF PAINT

Recommended for tar paper, composition and asphalt roofs. Will rejuvenate weathered roofs and insulate with a silvery sheet of aluminum, in one coat. Made with selected asphalt, finest grade aluminum flakes and solvents.

APPLICATION—Brush, Spray THINNER—Mineral Spirits or Turp.
DRYING TIME—10 hours Covers 275-400 Sq. Ft. per gal., depending on surface.

3.45	—	—	—
------	---	---	---

ALUMINUM PAINTS

See: Metallite; Japalac Spray Enamel, Aluminum

ASBESTOS SHINGLE PAINT

See: SPRED Glide-On

ASPHALT ROOF COATINGS (Plain, Fibrated, Plastic)

(PRICES UPON REQUEST)

ASPHALT ROOF PAINT

See: SPRED Glide-On.

BARN PAINT

See: Endurance Barn Paint

BASECOATS (Primers)

For Exteriors—See: Endurance Exterior Basecoat; Surface Bond
For Interiors—See: Gliddencoat; Speed-Wall Interior Basecoat;
SPRED Primer-Sealer; Ripolin Undercoat

BASEMENT PAINTS

For Floors —See: Pli-Namel; Florenamel
For Walls —See: SPRED SATIN; SPRED Glide-On

*BLACK ASPHALTUM

A weather-resisting, quick-drying, gloss black asphaltum base paint. Recommended for exterior iron work, fences, metal sash and other exterior metal surfaces where an economical finish is desired.

APPLICATION—Brush, Spray DRYING TIME—2 to 3 hours
THINNER—Mineral Spirits or Turp. Covers 400-500 Sq. Ft. per gal.

1.90	.69	.49	.36
------	-----	-----	-----

* AVAILABLE IN 5-GAL. CANS
AT 15¢ PER GALLON LESS THAN 1-GAL. PRICES.

GLD026103



BLACKBOARD FINISHES

See: Vismatic Green Chalkboard Coating

BLEACH

See: Glid-Tone Wood Bleach

BLENDING COLORS

See: SPRED Dramatone Tinting Colors; Colors-In-Oil

BRICK PAINTS

See: SPRED Glide-On.

BRUSHES, ALL TYPES

(PRICES UPON REQUEST)

BRUSHING LACQUER

See: Glid-Tone Crystalacq

BRUSH RESTORER

See: Glid-Strip

CANVAS PRESERVATIVE

See: Neva-Rot

CAULKING COMPOUND

(PRICES UPON REQUEST)

CEMENT AND STUCCO PAINT

See: SPRED Glide-On.

CLEANER, LIQUID

See: Glid-N Liquid Cleaner

COLORS-IN-OIL

Unexcelled for tinting flat wall paints, Semi-Gloss and Gloss enamels, glazing liquids, white lead and white paste paint. Ground extremely fine in special pale linseed oil for quick and positive dispersion. The finest pigments are used to develop perfect tone and strength of color. Not to be used in latex, emulsion paints or lacquer.

Raw Umber, Burnt Umber	5.08	1.50	.55	.24
Raw Sienna, Burnt Sienna	5.98	1.73	.61	.25
Ivory Drop Black	—	1.58	.57	.24
Lamp Black	4.40	1.34	.52	.24
Prussian Blue	—	1.86	.64	.27
Ultramarine Blue (Interior Use Only)	—	—	.70	.27
Chrome Green, Light; Chrome Green, Medium	7.80	2.19	.73	.28
Perma-Green	—	3.56	1.07	.33
Chrome Yellow, Light and Medium	—	2.86	.89	.30
Chrome Yellow, Dark	—	3.51	1.06	.32
Yellow Ochre	5.20	1.54	.56	.25
Venetian Red	4.68	1.40	.53	.25
Rose Lake (Interior Use Only)	—	—	.91	.31
American Vermilion (Interior Use Only)	—	2.91	.91	.31
Perma Blue	—	3.11	.96	.32

CONCRETE PAINT

See: SPRED Glide-On; Pli-Namel.

CRACK AND CREVICE FILLER

See: SPRED Patch; SPRED Stipple Texture

CREOSOTE PAINT

See: Stock Farm Paint

† SUPPLIED IN FULL CASES OR BOXES ONLY.
NOT SUBJECT TO FULL CASE ALLOWANCE.



DECK PAINT

See: Florenamel

DEEP COLORS

See: SPRED SATIN

DETERGENTS

See: Glid-N Liquid Cleaner

DRAMATONE MULTI-PURPOSE TINTING COLORS

See: SPRED Products Section

DRIER

See: Japan Drier

*DRIWAL (Clear)

A damp-resisting, stain-resisting material designed for application on limestone, stucco, sandstone, concrete and other porous surfaces of masonry. It penetrates pores of surface and coats them with an insoluble substance which makes them fully water-repellent. Does not change texture nor discolor surface. Contains no paraffine.

APPLICATION—Brush, Spray

DRYING TIME—2 hours

THINNER—None Required

COVERAGE—125 to 275 Sq. Ft. per gallon depending on porosity of surface

2.55

*DRIWAL (Silicone)

A transparent, water-repellent finish for exterior, above-ground brick, stone and masonry. Does the job in ONE COAT. Repels rain water from penetrating the pores. Resists efflorescence and staining. Masonry surfaces show no visible change in color or texture when treated with this material. Recommended for use on brick and mortar, concrete, cement-base paints, asbestos-cement combinations, sandstone, stucco and stones other than limestone. Not to be used on chder block or other light weight aggregate concrete blocks with extremely porous surfaces. This invisible water-repellent coating contains silicone to combat masonry deterioration.

APPLICATION—Brush, Spray

DRYING TIME—2 hours

THINNER—None Required

COVERAGE—125 to 275 Sq. Ft. per gallon depending on porosity of surface

3.15

ENAMELS

See: Jopalac; Ripolin; Speed-Wall Alkyd Flat; Speed-Wall Alkyd Semi-Gloss; Truck, Tractor and Machinery; Florenamel; Pli-Namel; SPRED Lustre

ENAMEL UNDERCOATER

See: Gliddencoat; Ripolin Undercoat

*ENDURANCE BARN PAINT — No. 500 RED

A new, highest quality paint with excellent hiding power. It dries to a tough glossy film that withstands the rigors of the roughest weather. Provides long-lasting protection for barns, sheds, granaries, silos, water tank exteriors, storehouses, fences, etc. Use it on exterior wood and metal.

APPLICATION—Brush, Spray

DRYING TIME—Overnight; 36 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—550 Sq. Ft. per gallon

3.05

1.00

* AVAILABLE IN 5-GAL CANS

AT 15¢ PER GALLON LESS THAN 1-GAL. PRICES.



*ENDURANCE EXTERIOR BASECOAT

Exterior primer for new wood and previously painted wood that is badly weathered or chalked. Use it to spot-prime bare spots resulting from peeling and flaking. Made from specially prepared oils to produce the elasticity, adhesion and control penetration necessary for finest exterior paint jobs. Can be tinted with Colors-In-Oil or DRAMATONE Tinting Colors.

APPLICATION—Brush, Spray
DRYING TIME—48 hours for recoating
THINNER—Mineral Spirits or Turpentine
COVERAGE—450 to 500 Sq. Ft. per gallon

Gals.

Qts.

Pts.

½ Pts.

5.20

1.54

—

—

*ENDURANCE HOUSE PAINT

Contains more heavy-bodied, pure linseed oil per gallon for longer life; pure white lead for added strength, water-resistance and extra durability; titanium for whiteness and hiding; zinc oxide to combat mildew; magnesium silicate for protection against cracking and checking. The exclusive Glidden formula makes this the finest, longest-lasting, self-cleaning exterior house paint manufactured. May be tinted with DRAMATONE Tinting Colors.

Outside White No. 1800

Tinting White No. 1804, Regular Colors and Black

Crylight Green No. 1828

APPLICATION—Brush, Spray, Roller
DRYING TIME—16 hours; recoat in 72 hours
THINNER—Mineral Spirits or Turpentine
COVERAGE—550 Sq. Ft. per gallon

5.20

1.54

.90

—

5.20

1.54

—

—

5.70

1.66

—

—

*ENDURANCE HOUSE PAINT

MILDEW & FUME-RESISTANT

A deluxe, lead-free Super White House Paint—ideal for the finest homes. Excellent for exterior wood, masonry and metal in any climate. A Non-Staining House Paint that stays white and bright for years. Especially suited for industrial areas, where homes are subjected to chemical fumes, heavy smog and smoke. Its lead-free formulation makes it ideal for farm buildings and fences. Combats mold, mildew and the roughest year-round weather.

APPLICATION—Brush, Spray
DRYING TIME—16 hours; 72 hours for recoating
THINNER—Mineral Spirits or Turpentine
COVERAGE—Up to 550 Sq. Ft. per gallon

5.20

1.54

—

—

ENDURANCE HOUSE PAINT, PASTEL COLORS

Pastel colors are easily obtained by tinting existing colors of ENDURANCE HOUSE PAINT or ENDURANCE TINTING BASE WHITE No. 1804, with DRAMATONE Tinting Colors. See ENDURANCE HOUSE PAINT Color Card

*ENDURANCE IMPERIAL ONE-COAT

WHITE HOUSE PAINT (Alkyd Fortified)

Premium quality white exterior paint. Gives extra hiding and coverage with its built-in second coat. Has depth and richness of enamel. Easy brushing. Once over is enough with this amazing one-coat paint! Fortified with alkyds to give extra durability and lasting beauty.

APPLICATION—Brush, Spray
DRYING TIME—48 hours
THINNER—Mineral Spirits or Turpentine
COVERAGE—550 Sq. Ft. per gallon

5.95

1.73

—

—

* AVAILABLE IN 5-GAL. CANS

AT 15¢ PER GALLON LESS THAN 1-GAL. PRICES.

GLD026106



ENDURANCE SHINGLE AND SHAKE STAIN

ENDURANCE SHINGLE AND SHAKE STAIN colors are made by mixing two parts ENDURANCE HOUSE PAINT with one part BLENDING LIQUID. This combination makes an ideal finish for use on grained cedar shakes, wood shingles, rough surfaced cedar, redwood and fir—on porous, rough or hand-split siding, fences, barns, and rough structures that have weathered a long time. ENDURANCE SHINGLE AND SHAKE STAIN embodies the finest quality paint pigments dispersed and blended in a strong wood preservative liquid that holds color after long exposure. It also acts as a protective finish against dry rot, decay, moisture and insects. ENDURANCE SHINGLE AND SHAKE STAIN penetrates deeply into the wood to retard warping, curling and splitting. It combats the roughest weather for many years. For combination prices, SEE ENDURANCE HOUSE PAINT AND BLENDING LIQUID.

APPLICATION—Brush, Dip, Spray

DRYING TIME—16 hours; 48 hours for recoating

COVERAGE—Approx. 300 Sq. Ft. per gallon depending on type of surface

*BLENDING LIQUID

BLENDING LIQUID is a combination of treated oils and solvents specially formulated to be mixed with ENDURANCE HOUSE PAINT and TRIM AND SHUTTER COLORS. This combination produces ENDURANCE SHINGLE AND SHAKE STAIN, a quality preservative finish available in many modern colors.

Gals.	Qts.	Pts.	1/2 Pts.
2.20 (6 Per Case)	.79	—	—

ENDURANCE TRIM AND SHUTTER COLORS

Beautiful, deep, rich colors, designed to harmonize with ENDURANCE HOUSE PAINT colors. These colors hold their brilliance and weather-resisting luster on wood, metal, brick and concrete. Excellent also for use on store fronts, ornamental grill work, trellises, porch and lawn furniture, etc.

†Shutter Red No. 108. Deep Turquoise No. 150

†Light Yellow No. 37

Shutter Green No. 71

Chestnut Brown No. 92; Dark Blue No. 158

Trim White No. 82

†To be discontinued when stocks are exhausted.

APPLICATION—Brush, Spray

DRYING TIME—24 hours; 48 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—Approx. 550 Sq. Ft. per gallon

8.65

2.40

1.33

—

6.85

1.95

1.11

—

4.00

1.74

1.00

—

5.15

1.53

.90

—

5.50

1.61

.94

—

EUSTON WHITE LEAD

(PRICES UPON REQUEST)

*EVERON HOUSE PAINT (White)

An excellent paint that stays clean and bright because of its special formula which provides controlled chalking. A superior finish for all wood surfaces exposed to weather and changing climatic conditions. Resists fumes in industrial areas! EVERON HOUSE PAINT brushes easily, penetrates deeply when used as a primer, adheres tenaciously as a finish coat, dries with an elastic, high gloss finish that remains firm and durable. EVERON is truly the economical HOUSE PAINT.

APPLICATION—Brush, Roller, Spray

DRYING TIME—16 hours; recoat in 48 hours

THINNER—Mineral Spirits or Turpentine

COVERAGE—550 Sq. Ft. per gallon

4.25

1.30

—

—

* AVAILABLE IN 5-GAL. CANS

AT 15c PER GALLON LESS THAN 1-GAL. PRICES.



FARM BUILDING PAINTS

For Exteriors—See: Endurance Paints, Metallite, SPRED
Glide On, Nev-A-Rust, Stock Farm White
For Interiors—See: SPRED Products, Maintenance Finishes Section

FENCE PAINTS

See: Stock Farm White, Metallite, Nev-A-Rust

FILLER, WOOD

See: Glid-Tone Wood Filler

FLOOR FINISHES

See: Pli-Namel, Florenamel, Penetrex, Glid-Tone Gloss Varnish

FLOOR WAX

See: Glidden Paste Wax, Glid-N Floor Wax

*FLORENAMEL (Alkyd)

An alkyd enamel with extra durability, for use on porches, floors of wood and concrete, canvas decks, railings—inside and outside. Will not waterspot; standing pools of water do not affect it. FLORENAMEL gives concrete basement floors and walls a mirror-like enamel finish. It's scrubbable. FLORENAMEL is made to take the roughest wear and weather. May be tinted with DRAMATONE Tinting Colors. All colors.

APPLICATION—Brush, Spray
DRYING TIME—12 hours
THINNER—Turpentine or Mineral Spirits
COVERAGE—500 to 600 Sq. Ft. per gallon

4.60

1.39

—

—

*GLIDDENCOAT (White Enamel Undercoat)

A perfect enamel undercoat for woodwork. Produces a firm opaque film to hold out succeeding coats of finishing enamel, making it possible to secure full luster and depth of gloss. Works easily, flows evenly without showing brush marks and requires only light sanding. Can be tinted with colors in oil or DRAMATONE Tinting Colors.

APPLICATION—Brush, Spray
DRYING TIME—Overnight for sanding and recoating
THINNER—Mineral Spirits or Turpentine
COVERAGE—500 Sq. Ft. per gallon

4.20

1.29

.78

.50

GLIDDEN PASTE WAX

For furniture, floors and automobiles; in fact, any surface where a wax finish is desired. It polishes quicker and easier than other similar products and will retain its gloss and finish over a period of several months. It dries hard and imparts longer protection to floor surfaces even when subjected to extreme hard usage.

APPLICATION—Cloth or Applicator

4 lbs.
†2.06

1 lb.
†.60

—

—

GLIDDENS PAR VARNISH

The finest interior-exterior spar varnish. Has extreme resistance to exposure, water and acids. Recommended for exterior surfaces such as doors, porch ceilings and those places inside the home which are subjected to water and exposure, such as window sills.

APPLICATION—Brush
DRYING TIME—8 hours, 48 hours for recoating
THINNER—Mineral Spirits or Turpentine
COVERAGE—650 Sq. Ft. per gallon

5.40

1.59

.93

.57

GLIDE-ON, SPRED

See: SPRED Products Section

* AVAILABLE IN 5-GAL CANS
AT 15¢ PER GALLON LESS THAN 1-GAL PRICES.

† SUPPLIED IN FULL CASES OR BOXES ONLY.
NOT SUBJECT TO FULL CASE ALLOWANCE.



GLID-N FLOOR WAX (Liquid)

For use on all types of floors. Dries to a gloss finish without polishing. The hard wax film resists wear, keeps dirt on surface where it can be removed easily with a stiff brush or damp mop. Resists water. Scrubbable.....

GLID-N LIQUID CLEANER (Detergent)

An excellent degreaser as well as cleaner. Does a remarkably easy job on walls, woodwork, floors, linoleum, tile, windows, dishes, mirrors and automobiles. Dries free from streaks. Harmless to the skin. Requires only two to three teaspoonsful to a gallon of water.....

GLID STRIP (Non-Flammable)

Wash Away Paint and Varnish Remover

A non-flammable, water-fresh paint and varnish remover that stays wet longer and permits working on larger areas. Has less tendency to run and sag on upright surfaces due to its heavy body. Easy to use. Just brush it on, wait a few minutes, then wash it off with water. GLID STRIP also acts as a cleaner for old, hardened nylon and pure bristle paint and varnish brushes. Will soften latex paints for easy removal.....

*GLID-TITE GALVANIZED IRON PRIMER

A primer for all galvanized metal, plymetal, galvaneal, or treated metal surfaces. The metal requires no previous etching with acids. Excellent for use on new eave troughs and gutters. Finish coat adhesion is better if application is thin rather than heavy.....

APPLICATION—Brush

DRYING TIME—Overnight; 72 hours for recoating

THINNER—Turpentine or Mineral Spirits

COVERAGE—Up to 600 Sq. Ft. per gallon

GLID-TONE CRYSTALACQ (Brushing Lacquer)

A crystal clear, quick-drying, water- and wear-resistant lacquer finish for brush application. Easy to use. Excellent for floors, woodwork, furniture, linoleum, etc.....

APPLICATION—Brush

DRYING TIME—1 to 6 hours, depending on surface

THINNER—Glid-Tone Crystalacq Reducer

COVERAGE—300 Sq. Ft. per gallon

GLID-TONE CRYSTALACQ REDUCER

Special Thinner for Crystalacq.....

* AVAILABLE IN 5-GAL CANS
AT 15¢ PER GALLON LESS THAN 1-GAL PRICES.



GLID-TONE GLOSS VARNISH

A deluxe, general-purpose interior varnish. Phenolic ether resins give it extreme abrasion resistance, durability, and lasting beauty. Excellent on all interior wood surfaces, bar and tabletops, woodwork, furniture and floors. Especially suitable over newly stained woodwork where Glid-Tone Stains have been applied. May be rubbed.

APPLICATION—Brush

DRYING TIME—6 to 8 hours

THINNER—Mineral Spirits or Turpentine

COVERAGE—650 Sq. Ft. per gallon

GLID-TONE SATIN-SHEEN VARNISH

A new satin sheen varnish that dries free from all cloudiness and preserves the natural beauty of the wood. Excellent for use over GLID-TONE stains and for all interior work where a dull finish or rubbed effect is desired. Sufficiently pale for use over light modern stains. DO NOT USE ON FLOORS.

APPLICATION—Brush

DRYING TIME—2 hours

THINNER—Mineral Spirits or Turpentine

COVERAGE—650 Sq. Ft. per gallon

GLID-TONE SPAR VARNISH

Extra durable spar varnish for exterior surfaces exposed to weather. Recommended as the finest varnish available for exterior use — spars, hulls, decks, house siding, paneling, porch ceilings, outdoor furniture, etc. Makes perfect finish over Glid-Tone Stain on exterior surfaces.

APPLICATION—Brush

DRYING TIME—8 hours; 48 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—650 Sq. Ft. per gallon

GLID-TONE WOOD STAIN

An all-purpose, pigmented wiping stain for all types of wood, plywood and veneer, exterior and interior surfaces. Especially suitable for knotty pine wood paneling in recreation rooms. Excellent for use on new or old furniture, woodwork, cabinets, wall paneling and floors. GLID-TONE Stain heightens the beauty of the wood grain. Holds color evenly. May be coated with varnish, shellac or lacquer. May be tinted with DRAMATONE Tinting Colors to produce additional beautiful colors.

APPLICATIONS—Wiping Cloth, Brush

DRYING TIME—12 hours Stains, All Colors

THINNER—Glid-Tone Stain Reducer Glid-Tone Stain Reducer

GLID-TONE WOOD BLEACH

Has the amazing properties of bleaching practically any type of wood from its original color to an almost natural white and without any deposit of a salt of any kind in the pores of the wood, necessary to the production of the blond effects so popular and modern at present.

Available in two size units. Large unit consists of 1 gallon of No. 1 Solution and 1 quart of No. 2 Solution. Small unit consists of 1 quart of No. 1 Solution and 1/2 pint of No. 2 Solution.

APPLICATION—Mop, Cloth, Waste

DRYING TIME—12 hours or more

† SUPPLIED IN FULL CASES OR BOXES ONLY.
NOT SUBJECT TO FULL CASE ALLOWANCE.

Gals.	Qts.	Pts.	1/2 Pts.
5.25	1.55	.91	.57
4.60	1.39	.84	.53
5.70	1.66	.96	.59
3.25	1.03	.67	.44
†2.05 †6 Per Case	.76	.51	.37
Large Unit †4.80	Small Unit †2.55	—	—



JAPALAC SPRAY ENAMEL

In Ready-To-Spray Cans

All-purpose, interior-exterior enamel in pressurized, aerosol cans ready for immediate spraying. Extra-durable, quick-drying enamel of brilliant beauty. Gives professional appearance to porch and lawn furniture, bicycles, toys, tables, chairs, etc. Ideal for wickerwork. Colors match regular JAPALAC Alkyd Enamel colors. In addition, JAPALAC SPRAY ENAMEL is available in ready-to-spray interior-exterior Aluminum, rich Gold, and a clear finish.

White, Colors, and Clear

APPLICATION—Spray

DRYING TIME—Ten minutes

JAPALAC VARNISH STAIN

Stains and varnishes in one operation. Dries quickly, to a high lustre. For use on furniture, woodwork and floors. Unusually waterproof.

APPLICATION—Brush, Spray

DRYING TIME—4 to 6 hours; 24 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—600 Sq. Ft. per gallon

*JAPAN DRIER

A top quality drier for use in drying oil and linseed oil paints. It is made from hard gums. Very popular with professional painters. Two and one-half gallons are enough for fifty gallons of oil.

LACQUER

See: Glid-Tone Crystalacq (Brushing Lacquer)

LATEX PAINTS

See: SPRED Products Section

LINOLEUM COATING

See: Glid-Tone Crystalacq

LINSEED OIL

(PRICES UPON REQUEST)

LIQUID CLEANER

See: Glid-N Liquid Cleaner

*LIQUID RED LEAD (Modified)

Recommended whenever a shop coat of red lead is specified. Comes ready to apply, is extremely elastic and is an excellent rust preventative.

APPLICATION—Brush, Spray

DRYING TIME—16 hours; 48 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—500 to 600 Sq. Ft. per gallon

LIQUID WAX

See: Glid-N Floor Wax

MACHINERY ENAMEL

See: Truck, Tractor and Machinery Enamel; Japalac

MASONRY FINISHES

See: Clear Driwall; Silicone Driwall; SPRED Glide-On

* AVAILABLE IN 5-GAL CANS

AT 15¢ PER GALLON LESS THAN 1-GAL. PRICES.

GLD026112