

TABLE 6. TYPICAL GAS ANALYSES
Constituents of Gas—Percent by Volume

No. Type	Source	CO ₂	O ₂	N ₂	CO	H ₂	CH ₄	C ₂ H ₆	C ₃ H ₈	C ₄ H ₁₀	C ₅ H ₁₂	Sp. Calorific Value, Btu per Cu Ft. ^a	Btu per Cu Ft. ^a	
													Gross	Net
1 Natural gas	Typical	..	..	0.8	..	..	83.4	15.8	..	..	..	0.61	1123	1021
2 Propane	Commercial (natural gas)	..	..	..	..	..	2.2	97.3	..	..	..	1.55	2558	2358
3 Propane	Commercial (refinery gas)	..	..	..	..	..	2.0	72.9	..	..	..	1.77	2504	2316
4 Butane	Commercial (natural gas)	..	..	..	..	..	..	6.0	94.0	..	..	2.04	3210	2961
5 Butane	Commercial (refinery gas)	..	..	..	..	..	..	5.0	86.7	..	..	2.00	3184	2935
6 Butane-air	..	..	..	..	..	..	..	..	17.2	..	..	1.16	550	516
(Illuminants)														
7 Reformed natural	Straight shot generator	2.1	0.3	1.5	13.6	48.3	33.0	..	1.2	..	..	0.41	559	497
8 Refinery oil	Vapor phase crack	0.2	0.2	0.5	1.2	13.1	23.3	21.9	39.6	..	..	0.89	1475	1351
9 Oil gas	Portland, Ore.	1.2	0.5	2.4	7.7	54.2	30.1	..	3.9	..	..	0.37	570	510
10 Coal gas	Cont'n. Vert.	3.0	0.2	4.4	10.9	54.5	24.2	..	2.8	..	..	0.42	532	477
11 Coke oven gas	By-product	2.0	0.3	4.8	5.5	51.9	32.3	..	3.2	..	..	0.40	569	509
12 Producer gas	Bituminous	11.5	..	60.0	27.5	1.0	..	..	..	..	..	0.86	163	153
13 Blast furnace gas	..	4.5	0.6	50.9	27.0	14.0	3.0	..	..	..	..	1.02	92	92
14 Blue gas	Bituminous	5.5	0.9	27.6	28.2	5.4	6.6	..	0.7	..	..	0.70	260	239
15 Carburetted water gas	Heavy oil with blow run	6.0	0.9	12.4	26.8	32.2	13.5	..	8.2	..	..	0.66	530	451
16 Carburetted water gas	High Btu	0.7	0.3	5.8	11.7	28.0	36.1	..	17.4	..	..	0.63	840	770
17 Mixed Gas	Natural, Blue, Producer, Reformed Natural	3.9	0.1	15.5	10.3	17.8	46.9	5.4	0.1	..	..	0.63	650	586
18 Mixed Gas	Coal, Natural	1.1	0.4	6.6	4.0	35.8	45.7	4.6	III.	..	..	0.46	700	627
19 Mixed Gas	Natural, Coke Oven	1.0	0.2	5.5	2.0	20.9	66.6	2.6	III.	1.8	..	0.52	802	721
20 Sewage Gas	Decatur, Ill.	22.0	..	6.0	..	2.0	68.0	..	1.2	..	..	0.79	690	621

^a This table abstracted from *Gaseous Fuels*, American Gas Association, and from A.G.A. Laboratories Data.
^b At 60°F and 30 in. mercury, absolute pressure.

reaction, or by combinations of these processes. Liquefied petroleum gases (propane and butane) are higher hydrocarbon gases normally obtained as a by-product of oil refineries or by stripping natural gas. These two compounds are generally gaseous under usual atmospheric conditions although they can be liquefied by the application of moderate pressures at normal temperatures.

The demand for gaseous fuels has increased so tremendously during the past 25 years that few cities now can be said to depend solely on one source of supply. During peak load periods, heating demands on natural gas distribution systems may necessitate augmenting the base supply with supplemental fuels such as high Btu oil gas or liquefied petroleum gas-air mixtures. The supply of manufactured gases may be similarly increased by adding natural gas, reformed refinery gases, or relatively low heating value mixtures of liquefied petroleum gas and air.

In American gas practice the heating value of a gas and appliance efficiencies are based on the gross heating value. This value is the number of Btu liberated by complete combustion, at constant pressure, of one cubic foot of gas saturated with water vapor and measured at 60°F and 30 in. of mercury, with air at the same temperature and pressure. Products of combustion are cooled to the initial temperature of the gas and air and the water formed by combustion of free and combined hydrogen is condensed to the liquid state.

Classification of Gases

Representative properties of gaseous fuels commonly employed for domestic heating processes are shown in Table 6.^{15, 16, 17, 18}

Natural gas contains from 55 to 98 percent methane with various percentages of higher hydrocarbons, chiefly ethane. In addition to these components, small quantities of non-combustible gases such as carbon dioxide, nitrogen, and helium are sometimes present. Percentages of the different components vary with the area from which natural gas is withdrawn. They may even vary slightly from any given well during its lifetime but these variations are inconsequential insofar as the utilization of the gas is concerned. Heating values of natural gases vary from 900 to 1400 Btu per cu ft but the usual range for use is from 1000 to 1050 Btu (gross) per cu ft. A typical analysis is given in Table 6.

Manufactured gases commonly produced are listed in Table 6. Gross, or higher, calorific values of typical send-out gases made from these manufactured gases generally range from 500 to 600 Btu per cu ft. Due largely to the greatly increased demand for city gases the tendency during recent years has been to increase rather than to decrease heat content of manufactured gases, thus making it possible to serve more customers through the existing distribution system.

Mixed gases are a result of increased distribution of natural gas, through transcontinental transmission lines, into areas having existing manufactured gas facilities. In such instances some gas companies supply a 600 to 800 Btu mixture (See Table 6). In some territories these mixtures are distributed as an intermediate step in changing over from manufactured gas to natural gas. Although the burden of adjusting installed heating and air conditioning equipment and supplying new orifices and burner equipment is generally assumed by the gas companies when the gas is changed, it is advisable to consult the local gas company to insure that equipment is provided with proper orifices and burners when installed.

Most states enforce legislation through their public service commissions