

OCT 17 1972

PLAINTIFF'S
EXHIBIT

CAP-35

Cement Asbestos Products Company

Ragland, Alabama

FROM: W. H. Beasley

October 14, 1972

TO: S. D. Weaver

SUBJECT: Asbestos Sampling

Attached is a copy of our latest report of asbestos dust sampling. I have inserted the last test results as a comparison. You will notice one or two areas where work is needed, but the average is well below the five fiber standard in effect now and within the two fiber level required in 1976.

Storace

cc: W. R. Bond
Stanley Mooney
Burl McGarrahan

HER 0008190



AMERICAN SMELTING AND REFINING COMPANY

DEPARTMENT OF ENVIRONMENTAL SCIENCES

3422 SOUTH - 700 WEST, SALT LAKE CITY, UTAH 84119

October 11, 1972

K. W. NELSON
DIRECTOR

Mr. W. Horace Beasley
Cement Asbestos Products Company
P. O. Box 119
Ragland, Alabama 35131

The table below gives the asbestos fiber count for each of the filter samples you recently sent to us:

Filter No.	Volume	Time	9-22-72	3-6-72
			Fibers/ml >5.0 μ	
Filter Changer - 1	60	30	1.2	3.6
Resin - 2	60	30	0.2	2.6
BATCH OPER - 3	60	30	3.4	1.0
CALENDER - 4	60	30	0	0.8
Coupling AREA - 5	94	47	0.6	1.2
MOA LATHES - 6	94	47	0.2	1.2
TRAY Loader - 7	54	27	0	0.0
Tap Cpl. Col. - 8	60	30	0	0.7
Pipe Ladle AREA - 9	60	30	0	1.7
SHOP AREA - 10	60	30	0	0.0
OFFICE DOOR - 11	60	30	0.2	1.4
CUTOFF SAW - 12	100	50	0.1	0.2
AVERAGE			0.5	1.2

These samples were counted by phase-contrast microscopy at 450X magnification.

Although no fibers were counted in several of these samples, this does not mean that there were no fibers present. They simply lay outside of the counting area.

Michael O. Varner
Supervisor of Field Services

MOV/bbc

HER 0008191