



1932

TRANSACTIONS

National Safety Council

Incorporated

TWENTY-FIRST ANNUAL
SAFETY CONGRESS



Washington, D. C.

October 3 to October 7, 1932

The Wardman Park and
Shoreham Hotels

Copyright, 1933, National Safety Council, Inc.

CONTENTS

Council Officers and Directors.....	PAGE 3
Council Purposes and Policies.....	7
General Sessions—	
Annual Meeting of Members.....	9
Annual Banquet.....	21
Advanced Safety Engineering.....	23
General Round Table.....	33
Fire Prevention.....	39
Industrial Health Section.....	45
Industrial Nursing Section.....	79
Safety in Foremanship by the Conference Method.....	83
Accident Prevention Equipment Manufacturers' Section.....	107
Aeronautical Section.....	111
A. S. S. E.—Engineering Section.....	119
Automotive and Machine Shop Section.....	131
Cement Section.....	141
Chemical Section.....	157
Construction Section.....	177
Delivery, Taxicab and Bus Section.....	191
Electric Railway Section.....	201
Food Section.....	217
Marine Section.....	233
Meat Packing, Tanning and Leather Industries Section.....	251
Metals Section.....	263
Mining Section.....	277
Paper and Pulp Section.....	309
Petroleum Section.....	327
Power Press Section.....	347
Public Utilities Section.....	357
Quarry Section.....	379
Refrigeration Section.....	387
Rubber Section.....	395
Safety Section, ARA—Steam Railroad Section, NSC.....	405
Textile Section.....	435
Woodworking and Lumber Manufacturing Section.....	447
Index.....	455

★ ★
Although the National Safety Council endeavors to eliminate from discussion at its conventions matters which are not pertinent to its purposes or which are contrary to its policies, the Council accepts no responsibility for the views expressed either in the papers presented or in the discussions thereon.

★ ★
NOTE: The sessions of the Street and Highway Traffic Section, the Child Education Section, and the Home Safety session are published in a separate small volume of these Transactions, available on request.

National Safety Council

Incorporated

20 North Wacker Drive, Chicago

HONORARY MEMBERS

ASSOCIATION OF IRON AND STEEL ELECTRICAL ENGINEERS
ROBERT W. CAMPBELL
ARTHUR WILLIAMS

OFFICERS (1932-1933)

J. I. BANASH, President.
ROBERT I. CATLIN, Vice-President for Public Safety.
J. E. CULLINEY, Vice-President for Engineering.
HOWARD B. FONDA, Vice-President for Membership.
G. T. HELLMUTH, Vice-President for Business Administration.
J. E. LONG, Vice-President for the Division of Safety Councils.
GEORGE H. WAREFL, Vice-President for Industrial Safety.
DR. C. H. WATSON, Vice-President for Health.
A. W. WHITNEY, Vice-President for Education.
WILL COOPER, Treasurer.
W. H. CAMERON, Managing Director and Secretary.

EXECUTIVE COMMITTEE (1932-1933)

Wm. F. ANDERSON, Safety Division, Milwaukee Association of Commerce.
C. R. AUEL, Past President.
J. I. BANASH, Consulting Engineer.
ERNEST W. BICK, United States Rubber Company.
C. W. BERGQUIST, Past President.
C. B. BOULET, Public Utilities Section.
W. H. CAMERON, National Safety Council.
ROBERT W. CAMPBELL, Past President.
ROBERT I. CATLIN, Actua Life Insurance Company.
FRANK H. COGAN, Marine Section.
WILL COOPER, Stevens Hotel.
J. E. CULLINEY, Bethlehem Steel Company.
EDWARD DANA, Boston Elevated Railway.
LEWIS A. DEBLOIS, Past President.
MARCUS A. DOW, Past President.
HOWARD B. FONDA, Burroughs Wellcome & Co. (U. S. A.) Inc.
P. H. GLATFELTER, York County Safety Council.
DR. THOMAS W. GOSTLING, Superintendent of Alton Schools.
HARRY GUILBERT, The Pullman Company.
G. T. HELLMUTH, Chicago, North Shore & Milwaukee R. R. Co.
WALTER G. KING, Past President.
FRANKLIN M. KREML, Evanston Safety Council.
FRANK J. LARAHAN, Fort Pitt Malleable Iron Company.
THOMAS E. LIGHTFOOT, Mining Section.
JOHN E. LONG, The Delaware & Hudson Railroad Corporation.

H. W. LORIMER, Cleveland Safety Council.
 W. W. MACK, Delaware Safety Council.
 ARTHUR T. MONEY, Past President.
 LEW R. PALMER, Past President.
 C. E. PETTINGER, Past President.
 J. J. PLAZAK, Paper & Pulp Section.
 Lt. Col. HENRY A. REYNOLDS, Past President.
 C. E. SASTON, General Electric Company.
 CHARLES R. SCOTT, Past President.
 ERNEST L. SIMONS, New Haven Safety Council.
 C. W. SMITH, Standard Oil Company (Indiana).
 H. S. SMITH, ASSE—Engineering Section.
 R. T. SOLENSKY, Accident Prevention Equipment Manufacturers' Section.
 JOHN H. TAYLOR, Birmingham Safety Council.
 ARTHUR M. TONE, Consulting Marine Engineer.
 C. P. TOLMAN, Past President.
 GEORGE H. WARREN, Union Pacific Railroad Company.
 Dr. CASSIUS H. WATSON, American Telephone & Telegraph Company.
 W. L. WHITE, Jr., Cement Section.
 A. W. WHITNEY, National Bureau of Casualty & Surety Underwriters.
 Dr. C.-E. A. WINSLOW, Yale Medical School.
 ARTHUR H. YOUNG, Past President.

DIRECTORS (1932-1933)

AUGUSTUS L. ABBOTT, St. Louis Safety Council.
 M. S. ACKERMAN, Jr., Lehigh Valley Safety Council.
 WM. F. ADERS, Safety Division, Milwaukee Association of Commerce.
 J. I. BANASH, Consulting Engineer.
 JOHN BANKS, Madison County Safety Council.
 JOHN W. BARTON, Safety Department, Nashville Chamber of Commerce.
 ERNEST W. BECK, United States Rubber Company.
 W. A. BENNETT, Worcester Safety Council.
 L. G. BESTLEY, Richmond Safety Council.
 C. W. BERGQUIST, Western Electric Company.
 DAVIS S. BEYER, Liberty Mutual Insurance Company.
 E. F. BLANK, Jones & Laughlin Steel Corporation.
 C. B. BOULET, Public Utilities Section.
 W. R. BOYD, Jr., American Petroleum Institute.
 THOMAS W. BREWER, Hazelton Safety Council.
 R. A. BRYANT, Safety Division, Syracuse Chamber of Commerce.
 RALPH C. BUSH, Electric Railway Section.
 Geo. A. CALDWELL, Knoxville Safety Council.
 W. H. CAMERON, National Safety Council.
 ROBERT I. CANNON, Aetna Life Insurance Company.
 FRANK H. COGAN, Marine Section.
 WILL COOPER, Stevens Hotel.
 J. E. CULINEY, Bethlehem Steel Company.
 EDWARD DANA, Boston Elevated Railway.
 F. A. DAVISON, Consulting Engineer.
 CLIFFORD DAVIS, Street & Highway Traffic Section.
 L. W. DAVLEY, Refrigeration Section.
 CHARLES D. DAVSON, Grand Rapids Safety Council.
 Dr. A. DeBorja, Consulting Engineer.
 JAY E. DICKER, Mason City Safety Council.

JAMES B. DOUGLAS, The Philadelphia Gas Works Company.
 Dr. LOUIS J. DUBUIS, Metropolitan Life Insurance Company.
 Dr. CHARLES H. EAMES, Textile Section.
 FREDERIC W. EASTON, Blackstone Valley Safety Council.
 HARVEY ELLIOT, Armour & Company.
 DONALD A. FINKBINDER, Toledo Safety Council.
 RALPH T. FISHER, Eastday Safety Council.
 THOMAS FINEBERG, Western Pennsylvania Safety Council.
 HOWARD B. FORDY, Burroughs Wellcome & Co. (U. S. A.) Inc.
 P. H. GLAVIELLE, York County Safety Council.
 ERNEST P. GOUGH, Consulting Engineer.
 Dr. THOMAS W. GOSLING, Child Education Section.
 ORRIN M. GRAVES, Quarry Section.
 HARRY GILBERT, The Pullman Company.
 ISAAC HART, The Acheson, Topoka & Santa Fe Railway Co.
 D. T. HARRINGTON, U. S. Bureau of Mines.
 E. M. HENSTELMAN, Safety Bureau, Duluth Chamber of Commerce.
 G. T. HEDMUTH, Chicago, North Shore & Milwaukee R. R. Co.
 C. L. HERRMANN, Petroleum Section.
 CHAS. E. HILL, New York Central Lines.
 HARRY D. IMMER, Department of Labor & Industry, Pennsylvania.
 JOHN PRICE JACKSON, New York Edison Company.
 DANA E. JONES, Manufacturers' Association of Erie.
 ROLAND JONES, Woodworking and Lumber Manufacturing Section.
 IRA V. KERNER, Pennsylvania Salt Mfg. Co.
 FRANKLIN M. KREML, Evanson Safety Council.
 FRANK J. LANAHAN, Fort Pitt Malleable Iron Company.
 THOMAS E. LIGHTFOOT, Mining Section.
 R. M. LITTLE, New York Department of Education.
 J. E. LONG, The Delaware & Hudson Railroad Corporation.
 H. W. LUDLOW, Cleveland Safety Council.
 W. W. MACK, Delaware Safety Council.
 H. T. MARTIN, Fisk Rubber Company.
 E. W. MATSON, Minnesota Safety Council.
 PANTON MENDELSSOHN, Detroit.
 HENRY J. MINER, Food Section.
 W. S. MOELLER, Fort Wayne Safety Council.
 CURAN L. MOLER, Dayton Safety Council.
 R. B. MOREY, Industrial Accident Prevention Associations.
 VILHELM MCCURTACK, Harvard University.
 WM. G. MCCULLAM, Elizabeth Safety Council.
 T. H. MCKENNEY, Illinois Steel Company, South Works.
 A. D. McWHORTER, Safety Division, Memphis Chamber of Commerce.
 Col. BEN P. NICKLIN, Chattanooga Safety Council.
 JOHN A. OARTEL, Carnegie Steel Company.
 GEORGE C. A. OW, The Detroit Edison Company.
 THOS. E. OWEN, Employees' Publication Section.
 LEW R. PALMER, Equitable Life Assurance Society.
 JOHN C. PARKER, Brooklyn Safety Council.
 C. E. PETTINGER, American Mutual Liability Insurance Company.
 BEAUMOND PLATT, Louisville Safety Council.
 J. J. PLAZAK, Paper & Pulp Section.
 H. B. PORTER, Baltimore Safety Council.
 CHAS. E. REYNOLDS, Providence Safety Council.
 Lt. Col. HENRY A. REYNOLDS, Lehigh Portland Cement Company.

C. L. Rice, Chicago Safety Council.
 DR. A. D. RISTEEN, The Travelers Insurance Company.
 JOHN ROACH, Chemical Section.
 CHAS. J. ROIT, Newark Safety Council.
 THOMAS ROTIL, Rochester Safety Council.
 JOHN RUSSELL, Jr., Construction Section.
 G. E. SANFORD, General Electric Company.
 HENRY G. SCHAFFNER, Erie Safety Council.
 OTTO SCHENK, Wheeling Safety Council.
 ROBERT L. SCHMITT, Metals Section.
 CHARLES B. SCOTT, Bureau of Safety.
 GEN. JOHN H. SHERBURN, Massachusetts Safety Council.
 DR. L. A. SHODDY, Bethlehem Steel Company.
 ERNEST L. SIMONDS, New Haven Safety Council.
 GEORGE P. SINGER, Reading-Berks County Safety Council.
 OLIVER T. SNETT, Safety Division, St. Paul Association.
 CHARLES F. SMITH, Rubber Section.
 C. W. SMITH, Standard Oil Company (Indiana).
 E. J. SMITH, Power Press Section.
 H. S. SMITH, ASSE—Engineering Section.
 R. T. SOLENSTEN, Accident Prevention Equipment Manufacturers' Section.
 E. C. SPRING, Lansdale, Montgomery Co., Pa.
 GEORGE R. STEPHENS, The Safety Bureau, Buffalo Chamber of Commerce.
 ETHELBERG STEWART, Washington, D. C.
 CARL STORCK, Automotive & Machine Shop Section.
 LUCIUS S. STORRS, United Railways & Electric Co.
 ALFRED H. SWAYNE, General Motors Corporation.
 JOHN H. TAYLOR, Birmingham Safety Council.
 HENRY D. TEFFT, Meat Packing, Tanning & Leather Industries Section.
 NORMAN F. TITUS, Hudson County Safety Council.
 ARTHUR M. TODE, Consulting Marine Engineer.
 W. D. TURBEVILLE, San Antonio Safety Council.
 WILLIAM F. VEECH, Railway Safety Council.
 VINCENT WAKEFIELD, Kansas City Safety Council.
 GEORGE H. WARFEL, Union Pacific Railroad Company.
 DR. CASSIUS H. WATSON, American Telephone & Telegraph Company.
 HARRY M. WEDGER, Illinois Bell Telephone Company.
 CARROLL V. WELLS, Delivery, Taxicab & Bus Section.
 ALBERT C. WHITE, JR., Springfield Safety Council.
 W. L. WHITE, JR., Cement Section.
 S. E. WHITING, Liberty Mutual Insurance Company.
 A. H. WHITNEY, National Bureau of Casualty & Surety Underwriters.
 W. H. WINANS, Union Carbide & Carbon Corporation.
 C. T. WINEGAR, Detroit Industrial Safety Council.
 DR. C.-E. A. WINSLOW, Yale Medical School.
 J. M. WOLTZ, Youngstown Sheet & Tube Company.

a proper staff, and not by some enthusiastic person who has not been trained for the work. Why not use more registered nurses in the smaller plants? The registered nurse is much better qualified to interpret a physician's plan of medical service than any lay attendant.

Much depends upon the physical condition of the employees. I am of the opinion that the physician, by reason of his professional attainments, is best qualified to handle some of the problem cases among employees. Mental symptoms, brought about by worry over home affairs, quite often produce accidents. In many cases the fear and worry of sickness in the family can be greatly allayed by a talk with the doctor or the nurse. Many of these cases have come under my personal observation.

It should also be absolutely the part of the physician to say when a man shall return to his regular employment after injury, and this decision should not be influenced in the slightest by its possible affect on any "no-lost time accident" contest or record. These contests are proper and have brought about outstanding results in the reduction of lost-time frequency figures. However, there have been cases of injured employees being urged unduly to return to some form of work merely to prevent the marking up of a lost-time accident. Nothing should be allowed to interfere with the employee's welfare. The physician has every motive to return the employee to his regular work as promptly as possible, but his higher duty is to conserve both the physical and economic welfare of the employee as well as the employer.

The safety director has need of the medical service, and the two should earnestly co-operate and seek to bring about a mutual feeling among the employees. Both departments are striving by all possible means to prevent economic waste chargeable to the disabilities and hazards of industry.

TUESDAY AFTERNOON SESSION

October 4, 1932

The delegates first attended an informal luncheon, and then gathered for the afternoon meeting in a Joint Session with the Metals Section. This session was devoted to a symposium on the dust problem in industry. Chairman Greenburg immediately introduced the first speaker.

The Effects of Inhaled Mineral Dusts

By LEROY U. GARDNER

Director, Saranac Laboratory for the Study of Tuberculosis, Saranac Lake, N. Y.

As long as men have worked in stone it has been appreciated that an unusually large proportion of them suffer from disease of the lungs. It was natural to assume that such disease would be caused by the dust generated, and this belief was strengthened by the discovery of black, grey or red pigments in the lungs, sometimes accompanied by the formation of scar tissue.

The term, pneumokoniosis was introduced to describe the lung pigmented in this manner. With further observation pathologists attempted to classify various forms of pneumokoniosis on a basis of the type of dust inhaled and such names as anthracosis, siderosis, chalciosis and even byssinosis and tobaccosis made their appearance. It was recognized that some forms of the disease were attended by severe symptoms and result in death but there was no correlation between the clinical and pathological pictures and the causative dust. Finally, statistical study demonstrated that of all kinds of industrial dusts silica generally produced a definite type of disease with a characteristic pathological lesion and complex of symptoms.

trained for
The registered
service than

of the opinion
lified to handle
ught about by
the fear and
the doctor or
ation.

n a man shall
uld not be in-
cident" contest
ing results in
been cases of
work merely to
owed to inter-
to return the
her duty is to
well as the

ould earnestly
employees. Both
ate chargeable

for the after-
in was devoted
ing immediately

12.6.33
S. S. T.

Mac Lake, N. Y.

at an unusually
lural to assume
was strength-
metimes accom-

emented in this
various forms
names as an-
le their appear-
ended by severe
the clinical and
ly demonstrated
type of disease

Today the clinical entity known as silicosis is one form of pneumonokoniosis which is quite clearly defined. Moreover, within the last three or four years asbestosis has also been shown to produce another specific type of reaction attended by symptoms differing in some respects from silicosis.

The other forms of pneumonokoniosis still lack complete definition. The widespread use of radiography has brought together a mass of descriptive data from individuals exposed to many kinds of occupational dusts but these findings have not yet been correlated with pathological anatomy, chemical studies of the tissues and detailed analyses of industrial atmospheres. There is a tendency to assume that many of these pulmonary changes are due to the action of silica perhaps modified by the chemical components of the dust. We shall only be in a position to speak with assurance about them when the pure types of dust and their various combinations have been studied in human beings or in experimental animals.

For the sake of clarity no mention has been made of the infections which so frequently complicate some forms of pneumonokoniosis. In the prebacteriological era of medicine the use of such terms as "grinders' consumption" and "miners' phthisis" reflects the popular association of pneumonokoniosis with tuberculosis. The names were justified both by clinical and pathological observation for it has been subsequently shown that, in silicosis at least, a super-imposed tuberculosis may cause death in perhaps 75 per cent of the cases. Some observers even go so far as to state that silicosis itself does not develop unless the lungs are previously damaged by a latent tuberculous infection. This is probably an exaggeration, for typical silicosis can be produced in the experimental animal by the inhalation of silica without infection.

The role of asbestos dust as an excitant of tuberculous infection is not as clear cut as that of pure silica. While there are numerous reports of death in asbestosis due to a terminal tuberculosis, nevertheless surveys of living workers have failed to demonstrate any excess of such infection. Simple anthracosis is said to prevent the progression of tuberculous infection. Statistics from coal mining districts do show a tuberculosis rate much lower than that "normal" for the age group. As yet corroborated experimental proof of protective action of coal against tuberculous infection is lacking.

Not only the tubercle bacillus but other bacteria seem to develop with special facility in the tissues previously damaged by silica. For example, the pneumonia rate among silicotic native laborers of South Africa is many times that in non-silicotic natives living under similar conditions. In coal miners, likewise, pneumonia is a common and often fatal complication.

What has been said of the effects of inhaled inorganic dusts would indicate that the reaction of the tissues is not merely a response to mechanical irritation by particulate matter. Today it is generally accepted that the injury is chemical in nature and that only certain of the common types of industrial dusts possess properties capable of exciting reaction. In the cases of silica and the silicate of magnesium or asbestos the slightly alkaline body fluids probably effect a slow solution of the dust particles liberating silica in colloidal form. This substance irritates the connective tissue cells which respond by multiplying. The result is an overgrowth of the supporting framework elements at the expense of the more delicate cells specialized for specific functions.

For these two types of dust the character and form of the pathological changes has been carefully worked out. In *silicosis* the essential tissue change consists of nodules of connective tissue which develop first in the lymphoid tissues situated in the drainage apparatus of the lungs. These nodules interfere with the physiological removal of foreign bodies and subsequently inhaled particles accumulate in the framework of the lung itself. Such reaction gradually decreases the normal elasticity of the organ and encroaches upon its functional elements. As a result the cardinal symptom of the disease, dyspnoea or shortness of breath develops. Because of the excessive amounts of scar tissue formed in the lungs the right side of the heart

encounters increasing difficulty in forcing blood into the organs. In an attempt to compensate the overworked heart muscle becomes thicker and heavier and unless infection intervenes the time eventually arrives when the heart fails and death occurs from this cause.

The reasons for the prevalence of infection in the silicotic lung are not altogether clear. It is obvious that when the drainage system is so obstructed by nodules of scar tissue that more dust particles can only be removed with difficulty, the same must be true of bacteria which may be inhaled. As a consequence they remain in the lung and set up progressive infections. But this is not the whole story. The silicotic tissue apparently offers a peculiarly favorable soil for the continued multiplication of tubercle bacilli and perhaps other bacteria. Experiment has shown that even attenuated organisms of this type will produce rapidly fatal tuberculosis in a silicotic guinea pig. Furthermore, inhaled silica dust will cause a pre-existing latent tuberculous focus, harboring a few attenuated bacilli, to become progressive and spread.

The cause of this effect upon tuberculous infection has not yet been ascertained but probably it is in some way associated with the death of tissue caused by the toxic silica. Associated with this factor is an increased activity of the phagocytes which are stimulated by the irritating silica so that these cells tend to migrate rapidly and carry tubercle bacilli into previously uninvolved portions of the lung.

Asbestos dust, perhaps because of its fibrous structure, is not transported very far within the lung. It tends to lodge along the walls of the finer tubes and little of it is removed by the lymphatic drainage system. Tissue reaction, probably initiated by the solution of the fibers, occurs in their immediate vicinity. As in the case of silica this reaction consists of an overgrowth of the connective tissues which is later transformed into leather-like scars.

Aluminum oxide will serve admirably as an example of a non-siliceous dust whose particles are as hard and sharp as those of crystalline silica. When a measured quantity of such particles, 1 to 3 micra in diameter, are injected into the ear vein of a rabbit the majority of them come to rest in its liver and spleen. There they remain, apparently harmless, collected in large phagocytic cells and producing no reaction of the connective tissues for at least two years. Injection of the same quantity of the same sized quartz particles excites the formation of so much scar tissue that the functional elements are almost completely destroyed and the organs are reduced to nodular masses of leather-like consistence.

Carborundum, the carbide of silicon, when inhaled by guinea pigs for periods as long as four years, likewise fails to excite significant overgrowth of the connective tissues. It produces only a low grade inflammatory change with no nodules.

Instances such as those cited constitute the basis for believing that the cellular response to dust particles is not due to their hardness and sharpness but to chemical substances liberated by the action of the tissues upon them. The case for solubility has not been proven directly, for the detection of soluble silica in the tissues offers technical difficulties which today are unsurmountable. Nevertheless this substance is known to be a cell poison and in weak concentrations it will provoke an overgrowth of the connective tissues.

Mention should be made of the effect of inhaled coal dust. Most city dwellers breathe in sufficient quantities of this material during an average life-time to pigment considerable areas of their lungs. Deposits of grey or black dust will be found along the course of the lymphatic drainage system but this pigmentation is associated with little or no new growth of connective tissue. The coal miner's lung is much blacker but in most instances it also develops no deforming scars. When such reaction does occur analysis usually reveals appreciable amounts of silica in the lungs. The presence of excessive quantities of carbon dust apparently influences the localization of moderate amounts of silica so that the latter is not deposited in nodules as in pure silicosis but in streaks along lymph vessels as pure coal would localize.

Coal miners' fibrosis, due to relatively small amounts of silica, is therefore dif-

ferent
excess
pure
variety
silicosis
Fina
slowly
to the
But it
at least
high co
develop
gestion
trations
This
attention
to an in
of that
in the
should b

The

Saniti

The
capacity
chemical
the dust

One
dust in
health
maining
example,
such as
with this
much less
true of
marble d
little lung
quartz c
readily.

So far
for any
parenchy
It is kno
by the h
size of t
With
apparent
greater q
of the atm

In an attempt to heavier and unless this and death occurs

are not altogether acted by nodules of dirty, the same must they remain in the story. The silicotic dust multiplication shown that even at silicosis in a silicotic existing latent tuberculous and spread.

been ascertained but caused by the toxic the phagocytes which migrate rapidly and lung.

transported very far and little of it is usually initiated by the the case of silica this is later transformed

siliceous dust whose

When a measured to the ear vein of a

There they remain, bring no reaction of one quantity of the scar tissue that the scars are reduced to

pigs for periods as of the connective no nodules.

ing that the cellular less but to chemical the case for solubility in the tissues offers less this substance is take an overgrowth

Most city dwellers

life-time to pigment will be found along

is associated with ing is much blacker

such reaction does lungs. The presence

localization of nodules as in pure silicosis

is therefore dif-

ferent from that of the pure quartz worker. When the amount of inhaled silica is excessive, the effect of the coal is negligible and the reaction approximates that in pure silicosis. There is said to be more reaction to hard coal than to the bituminous variety but there is evidence to suggest that this is due to the greater amount of siliceous rock which must be worked in mining anthracite coal.

Finally, consider the silicosis of granite cutters. This develops somewhat more slowly than that of the pure quartz miner and it has been maintained that this is due to the relatively small amount of uncombined silica in granite (25 to 40 per cent). But it is believed that other components of the glomerate granite may neutralize or at least inhibit the effects of the silica so that only after prolonged exposures to high concentrations does significant reaction occur. While typical silicotic nodules develop in guinea pigs inhaling pure quartz for a year, not even the earliest suggestion of nodules have appeared in the lungs of animals inhaling comparable concentrations of granite (40 per cent silica) for four years.

This brief discussion of some of the problems involved in pneumonokoniosis draws attention to the limitations of our present knowledge. It indicates that the reaction to an inhaled dust is determined by the chemical and probably physical composition of that dust. It emphasizes the need to further study of different types of dust both in the pure state and in measured combinations. The ultimate aim of such a study should be the neutralization of the toxic action of such dangerous substances as silica.

The Dust Content of the Atmosphere in Various Dusty Industries

By J. J. BLOOMFIELD

Sanitary Engineer, United States Public Health Service, Washington, D. C.

The speaker said in part: The properties of a given dust which determine its capacity to produce pulmonary pathology are, the nature of the dust, that is, its chemical and mineralogical composition, its particle size, and finally the quantity of the dust dispersed in the atmosphere.

One of the outstanding results of the last 20 years of research in the field of dust inhalation is the demonstration of the fact that, in general, the degree of health hazards associated with the inhalation of any dust, all other factors remaining constant, is dependent upon the mineralogical composition of the dust. For example, it is now well established that the inhalation of certain types of dust, such as granite dust, will in time produce fibrosis of the lungs, at times associated with tuberculosis. In other cases exposure to dust may result in the production of much less fibrosis without notable tendency toward subsequent tuberculosis; this is true of cement dust. And finally, there are certain types of dust, as typified by marble dust, which in the quantities and lengths of exposure so far observed produce little lung fibrosis. In general, it has been found that those dusts which are high in quartz content are the ones which produce a disabling fibrosis of the lungs most readily.

So far as the size of the dust particle is concerned, it is apparent that in order for any given dust to produce injury to the lungs, it must gain access to the parenchyma of the lung, the site where the harmful effects of the dust take place. It is known that not all of the particles of inhaled dust gain access or are retained by the human lung. In this connection it is of importance to have regard to the size of the dust particles present in the industrial atmosphere.

With reference to the quantity of dust present in the air of a workroom it is apparent that when the dust concentration is high the exposed person will inhale a greater quantity in a given period of time than he will when the dust concentration of the atmosphere is relatively low, and since the rate of production of the fibrosis

is partially dependent upon the rate in which the dust is inhaled, this latter item plays an important role in predicting the relative danger of different environments. Hence the need for the evaluation of the quantity of dust in the industrial atmosphere is obvious.

Research on the problem of industrial dust inhalation has indicated that so far as their fibrosis producing qualities are concerned, dusts may be divided into three groups: (1) those composed completely of combined silica, that is silicates, such as pure asbestos; (2) those containing free silica in the crystalline form known as quartz, (granite contains approximately 35 per cent of quartz); and (3) dust containing free silica in a non-crystalline form such as diatomaceous earth. In general, it has been found that the harmfulness of a quartz containing dust is in direct proportion to its quartz content. For this reason, in attempting to evaluate the harmfulness of a dust, it is of the utmost importance to ascertain its exact mineralogical composition.

It has been our experience that to determine accurately the exact mineralogical composition of a dust one should resort to a combined chemical and petrographic analysis. By no other method have we found it possible to determine the amount of quartz present in a given sample. In certain instances, such as when one is dealing with a mixture of quartz and pure potash feldspar, it is possible to determine the amount of quartz present in such dust merely by a chemical analysis. However, most dusts which come into question are mixtures of quartz and silicates. Take granite for example. The average granite is made up chiefly of three minerals in about the following proportions: feldspar 60 per cent, quartz 30 per cent, and mica 15 per cent. Chemical analysis shows that this average granite contains 70 per cent of silica. Of this 70 per cent, 30 per cent is present as quartz (free silica) and the other 40 per cent is present as combined silica, in chemical combination with the other minerals that make up granite; it is possible to determine these proportions only with the aid of the petrographic microscope.

We find in practice that samples of dust settled out of the atmosphere at the breathing level of the worker serve admirably for both chemical and mineralogical determinations. Table 1 presents the quartz content of dusts obtained in various industries which we have studied.

TABLE 1
Percentage of Quartz Present in Various Industrial Dusts

Kind of Dust	Percentage of Quartz
Rock drilling dust (bituminous coal mine).....	54.0
Granite cutting dust.....	35.2
Rock drilling dust (anthracite coal mine).....	31.0
Brass foundry dust.....	19.0
Dust from raw mills in cement plant.....	6.5
Slate mill dust (Vermont red slate).....	3.0
Silverware polishing dust.....	1.7
Anthracite coal dust.....	1.5
Bituminous coal dust.....	1.2
Cement dust.....	1.0
Slate mill dust (Vermont green slate).....	trace
Talc mill dust.....	none
Marble cutting dust.....	none

It is evident from this table that rock drilling occupations in the coal mining industry and certain occupations in the granite cutting industry and in brass foundries would be in the hazardous class as judged by the proportions of quartz in the atmospheric dust.

It has been found that the larger particles of dust are more easily removed from the lungs than the smaller particles, and that the smaller particles are more likely to be retained in the lungs.

In order to obtain access to the dust in the atmosphere, it may be obtained by means of an instrument which will slip may be used. In another method, the percentage of dust may be obtained by means of a measurement of the refractive index of the dust. This method is easy to use.

As pointed out, the atmosphere is the source of the injury.

From the quantitative point of view, the size range of dust requiring control will depend on the refractive index of the dust. In industrial hygiene, the dust content and certain characteristics of the dust are of importance. This difference in dust content is one-half and such normal variation in the atmosphere.

So far as the size range of dust is concerned, the size limit of dust which is most harmful to the lungs is about 36 microns. The median size of dust in the atmosphere is about 36 microns. In comparing the results of measurements made by Navrogorodskii and by Navrogorodskii, it is found that the median size of dust in the atmosphere is about 36 microns.

In connection with the importance of the dust in the atmosphere, it is of importance to know the direct or indirect effects of dust on the human body.

this latter item
ent environments.
Industrial atmos-

ed that so far as
divided into three
s silicates, such
form known as
and (3) dust con-
arth. In general,
dust is in direct
to evaluate the
in its exact min-

act mineralogical
and petrographic
amine the amount
as when one is
possible to deter-
chemical analysis.
artz and silicates.
fly of three min-
artz 30 per cent.
granite contains
as quartz (free
chemical com-
ble to determine

atmosphere at the
and mineralogical
ained in various

Dusts

Percentage of Quartz

54.0
35.2
31.0
19.0
6.5
3.0
1.7
1.5
1.2
1.0
trace
none
none

the coal mining
al in brass found-
ions of quartz in

It has been demonstrated that particles of dust of a size greater than 10 to 12 microns in longest dimension are very seldom found in the lungs. This absence of larger particles is partly due to the fact that the numbers of such particles greater than ten microns in size present in industrial air is, as compared with the lower sizes, comparatively small; furthermore, these larger particles do not penetrate to the terminal portions of the respiratory tract. Hence we need only concern ourselves with those dust particles that are less than ten microns in longest dimension.

In order to ascertain whether or not an industrial dust is capable of gaining access to the lungs, it is necessary to know something of the size of the particles in the dust under consideration. In practice the samples for particle size studies may be obtained by the use of the Owens jet dust counter. The advantage of this instrument over other devices is that the Owens apparatus projects the atmospheric dust in unaltered condition directly on a microscope cover-slip. This cover-slip may then be properly mounted and examined by any one of several methods. In another method a microphotograph of the dust is made at a high magnification; the particles revealed on an enlarged print or screen may be measured by means of a millimeter scale. No matter which method one uses for particle-size measurements the results may be treated in the customary manner. The particles may be grouped in classes according to size, from which a percentage distribution curve is easily obtained.

As pointed out earlier, a knowledge of the quantity of dust dispersed in the atmosphere is very important, since with any given dust the rate of production of the injury will be dependent upon the total quantity inhaled.

From the practical hygienic viewpoint, the particle count is at present the best quantitative index of the degree of atmospheric pollution. The decision as to the size range of the particles which should be included in the dust count is a question requiring careful consideration. Obviously the size of the smallest visible particle will depend on the magnification and type of illumination used in the microscope, the refractive properties of the dust and to some extent on the visual acuity of the observer. We must bear in mind that our chief interest in this problem is in the industrial hygienic aspect. Primarily we are interested in differentiating between the dust content in the ordinary normal atmospheres, not yet known to be harmful, and certain industrial dusts which are known to be associated with lung damage. This difference is sharply marked so far as the dust particles between approximately one-half and ten microns in diameter are concerned; but the difference between such normal and abnormal air is masked and lost when we include in our determination the particles of ultra-microscopic size which are present in vast numbers in all air.

So far as the upper limit of particle size is concerned it has been demonstrated by the South African studies that particles greater than ten microns in longest dimension are, as a rule, of negligible importance. The data concerning the lower size limit of potentially hazardous dust is not so conclusive. Moir of South Africa, who examined microscopically 120 dust particles obtained from two specimens of silicotic lung, found that only 13 per cent of the particles were less than 0.5 microns and about 36 per cent of the particles were less than one micron in diameter. The majority of the particles, 60 per cent, were between one and three microns in size. The median size of the dust was found to be 1.2 microns in diameter. Drinker, in comparing the size frequency of the particles measured by Moir with the particles measured by him of the dust found in the sputum of men employed in ore mills, found a close correspondence. These findings have also been corroborated by Navrogorodato.

In connection with the lower limit of particle size of dust of pathological significance the following pertinent question arises: Aside from the evidence direct or indirect of the non-retention of minute particles of dust by the lungs, what

TABLE 2
Average Dust Counts in Certain Dusty Trades

Industry and Occupation	Dust exposure in millions of particles per cubic foot	Average per cent of quartz in dust
Talc Mining and Milling:		None
Jack-hammer drillers	2,160	None
Packers	50	None
Muckers	45	None
Crushermen and cylindermen	14	None
Slate Finishing Mills:		3
Floormen	1,598	3
Loaders	1,276	3
Disc crusher operators	312	3
Quartz Grinding Plant:		99
Mill operators	173	99
Laborers	83	99
Packers	55	99
Granite Quarrying and Finishing:		35
Leyner drillers	144	35
Jack-hammer drillers	112	35
Hand pneumatic tool finishers	59	35
Machine pneumatic tool finishers	36	35
Plug drillers	37	35
Attendant labor (indoors)	17	35
Anthracite Coal Mining:		1.5
Miners and helpers	232	1.5
Attendant labor	31	1.5
Bituminous Coal Mining:		1.2
Coal cutters and loaders	112	1.2
Attendant labor	4	1.2
Marble Cutters	33	None
Cotton Cloth Manufacturing:		None
Carders	9	None
Weavers and spinners	5	None
Silverware Manufacturing:		1.7
Dusty trades	5	1.7
Non-dusty trades	2	1.7

evidence is there that appreciable percentages of ordinary industrial dusts ever fragment into those minute sizes less than 0.5 microns in diameter? The best answer to this question would be data of actual measurement of such dust. Unfortunately we have but scant published data on the particle size frequency of dusts in the air of industrial establishments. In 1929 Fehnel made some particle size measurements in connection with the dust study of hard rock drilling in New York City. He reported the findings on three samples, which showed the dust which was less than 1 micron in size to vary from 1 to 15 per cent. Most of the dust in these hard rock drilling operations was between 2 and 5 microns in size. Badham, in studying the dust hazard among sandstone workers in Sydney, Australia, measured some 16,000 particles of dust in the air of work places and found that 67 per cent of these particles were about 1 micron in size. In a particle size

sta-
ma-
spe-
On-
tha-
1-
con-
ber-
lim-
mer-
of-
hic-
find-
Hes-
bein-
Da-
haza-
sum-
indus-
mine-
indus-
grine-
tries-
most

It-
in the
more
ard.
lead-
their
know.

The
loss o
Johan
dollar
ization
Mir
compe
ing to
other
against
has gr
It is
pay me
Stran.

Sample	Average per cent of quartz in dust
1	None
2	None
3	None
4	None
5	None
6	3
7	3
8	3
9	3
10	99
11	99
12	99
13	99
14	35
15	35
16	35
17	35
18	35
19	35
20	1.5
21	1.5
22	1.5
23	1.2
24	1.2
25	1.2
26	None
27	None
28	None
29	None
30	1.7
31	1.7
32	1.7

all dusts ever
ter? The best
uch dust. Un-
quency of dusts
ne particle size
illing in New
owed the dust
Most of the
microns in size.
Sydney, Aus-
nces and found
a particle size

study of twenty-five samples of eleven different kinds of aerial industrial dusts made by the filar micrometer method at a magnification of 1,000 diameters, the speaker found that practically all of the dust was less than 5 microns in size. Only 2 per cent of the particles were less than 0.5 microns, 21 per cent were less than 1 micron, and the majority of the dust, 71 per cent, was found to be between 1 and 3 microns in diameter.

From all of the evidence therefore, and in the absence of conclusive proof to the contrary, it is apparent that we need only be concerned with those dust particles between one-half and 5 microns in size, and from a practical standpoint the lower limit of particle size to be counted may well be taken at about 1 micron. Many methods have been devised and used for the purpose of determining the quantity of dust in air. Suffice it to say that for the purpose of dust sampling in either high or low dust concentrations, the Greenburg-Smith impinger apparatus now finds universal favor. This instrument has been used by the United States Public Health Service in all of its dust studies during the past nine years and is also being used by other workers in this field in this country and abroad.

During the past nine years the writer has made numerous investigations of dust hazard in many industrial establishments throughout the country. In Table 2, a summary is presented of the average dust content of the air in a few of these dusty industries. This table clearly shows that the highest dust exposure was in the tale mines, slate finishing mills, quartz grinding plant, coal mining and granite cutting industries. Owing to the high percentage of quartz present in the dust of the quartz grinding and granite cutting plants, as compared with the dust in the other industries listed in Table 2, quartz grinding and granite cutting are revealed to be the most hazardous of the occupations we have studied.

Orig. papers - 33 Clinical and Statistical Aspects of Silicosis

By ALBERT E. RUSSELL, M. D., F. A. C. P.

Surgeon, U. S. Public Health Service; Surgeon, U. S. Bureau of Mines,
Washington, D. C.

It would be difficult to estimate with any degree of accuracy the number of people in the United States who are engaged in dusty trades. It is evident, however, that more people are exposed to dust, which constitutes the greatest single industrial hazard, than is generally supposed. Certain dusts contain poisonous elements, such as lead, arsenic, mercury, etc., which give rise to general conditions resulting from their absorption. This paper, however, will deal only with those dusts which are known to be direct factors in the production of pulmonary diseases.

Economic Aspects of Silicosis

The economic problem presented by silicosis is tremendous. The suffering and loss of life due to it cannot be adequately measured. In the gold mining area around Johannesburg, South Africa, during the period 1911 to 1929, more than 33 million dollars have been paid in compensation alone. The costs of medical care, hospitalization, and legal proceedings further augment this enormous figure.

Mines in Australia are reported to have been bankrupted by payment of silicosis compensation. I know of a company in our own country which has claims amounting to more than a million dollars for disability due to dust inhalation. There are other plants in the East which will be bankrupted if all the claims which are filed against them are allowed. In most of the industrial states the number of claims filed has greatly increased in recent years.

It is clear that dust-prevention work, like any health-promoting activity, would pay many times in money, good health, and efficient operation.

Strangely enough, only during the past 25 years has dust received much attention

as an etiological factor of disease. The rapid development of industrialization within that period partly explains the impetus toward the study of this source of industrial hazard. The advances which have been made in all branches of industrial medicine have helped to center attention on dust and its effect upon the health, inasmuch as the number of the workers in dusty trades is larger than that of any other group exposed to a single industrial hazard; and an additional reason for increased interest in this subject is gathered from the study of mortality statistics, which reveal the fact that workers in dusty trades have an excessive death rate from tuberculosis, as well as from other respiratory diseases.

The most notable studies of silicosis have been made in the gold mines of South Africa, where the disease, with its complications, has been most commonplace among the miners. It became necessary either to study the disease and devise methods for its control or else to abandon mining. Consequently, funds, personnel and clinical material were made available for the first time on a large scale. Investigators in South Africa have become foremost in this field of research; their scientific work is widely known and has served as a basis for legislation, compensation rates, and further study of the disease silicosis.

There are almost 300,000 workers in the South African mines. It was because of the excessive incidence of silicosis among the miners around Johannesburg that the International Labour Office of the League of Nations selected that city for the first International Silicosis Conference.

In the United States the first study of the effect of dust was made by Dr. A. J. Lanza, an officer of the Public Health Service serving with the Bureau of Mines. His observations, made on miners in the Joplin, Mo., district and published by the Bureau of Mines and Public Health Service, have been confirmed by subsequent studies. Agencies which have done and are now doing investigative work are the U. S. Public Health Service, the Bureau of Mines, and the Universities of Harvard, Yale, and Pennsylvania. Private persons have also contributed valuable information on silicosis.

The word "pneumoconiosis" is of Greek origin and means "dusty lungs." It is an inclusive term and is being used now more than previously with a designation as to the type of dust responsible for the pathology. There are few instances where a pure dust, i. e., one unmixed with other elements, occurs in industry.

The intelligent consideration of the relation of dust to the etiology of pulmonary disease must include the following: 1. Chemistry and petrography of dust, 2. Concentration, 3. Size of particles, 4. Condition of worker at beginning of exposure, 5. Length of exposure, and 6. Effects produced.

The dusts most frequently met with in the industries are inorganic—incidentally, more harmful. It has been shown conclusively that silica, one of the most common dusts encountered, alone produces more permanent pulmonary damage than all other causes combined.

Condition of Worker at Beginning of Exposure

Reference has been made to the manner in which a tuberculous infection is augmented by the presence of silica. It follows that a worker having a tuberculous infection, either latent or active, will suffer more from the effects of dust than a person who is not so infected. It is highly necessary for workers to be examined thoroughly before being permitted to engage in a dusty trade. Experience with miners in South Africa has shown that a worker having a latent tuberculosis, or a worker in whom such infection was not demonstrable, or if a worker was of the so-called "phthisic" type, he developed silicosis more rapidly and a tuberculous complication earlier than did the normal worker.

The length of exposure to dust is evidently a great factor in the production of disability. It has been found that the occurrence of silicosis is in direct relation to

Effects Produced

In order to determine the effects produced by dust inhalation, a number of studies were made. These observations included a study of the sickness of workers with special reference to respiratory diseases, physical examinations supplemented by x-ray and laboratory tests, and a study of the mortality records.

I am presenting here some of the recommendations of the International Silicosis Conference on diagnosis and classification. The disease can conveniently be divided into three stages, designated "first," "second," and "third" stages.

"In the diagnosis of every stage of silicosis a history must be established of exposure to inhalation of silica dust in a quantity commensurate with the clinical and radiological findings.

"In the first stage, symptoms referable to the respiratory system may be slight or even absent. Incapacity for work may be slightly impaired. There must be a departure from the normal in percussion and auscultatory signs, and the radiogram must show an increased density of linear shadows and the presence of nodular shadows.

"In the second stage there must be an increase of all the physical signs observable in the first stage, and the radiograph must show an increase in the number and size of the nodular shadows with a tendency to confluence. There must be some degree of definite impairment of working capacity.

"In the third stage all the above conditions are grossly accentuated, and there is total loss of working capacity.

"Tuberculosis may be present in any of the above described stages, altering the symptoms, physical signs, and radiographic appearance, and the degree of working incapacity. Its presence must therefore influence the stage classification."

"Patients with silicosis in uncomplicated form are usually well nourished and apparently healthy, except, of course, in the advanced stages.

"Limitation of chest expansion is a very consistent finding, and unless the patient has engaged in athletics, the extent of limitation is usually in proportion to the length of service. The restriction of the chest was found (each side was measured with obstetrical calipers) to be symmetrical, in contradistinction to the asymmetry occurring in pulmonary tuberculosis.

Symptoms

Dyspnea is usually the first symptom and most constant complaint in silicosis, and it increases with length of exposure and even after exposure ceases, if the disease has become well established. Dr. Lanza, the American pioneer in the study of silicosis, observed a very great amount of dyspnea among the miners with silicosis in the Joplin District, Missouri. I do not know of any clinician who has failed to mention this finding when describing the symptoms of silicosis.

It has also been my observation that pains in the chest were a common complaint. A cough, which was usually non-productive, and frequent colds were also in evidence.

Diagnosis of Silicosis

Most of the physicians with whom I have worked or have discussed silicosis are prone to rely solely on the x-ray findings for diagnosis. These men had not been doing tuberculosis work, however, and were not particularly adept in the usual procedures employed in making physical examinations of the chest. The x-ray does give more information than any one other means. However, much can be learned by physical examination, which can usually be confirmed by the x-ray.

The following are some of the principal points in diagnosis by physical examination:

Percussion usually reveals a general impairment of resonance, the intensity of

which aspect varies as a rule with length of service. This finding is consistent with the character of a generalized fibrosis, which is a common characteristic of silicosis. Tactile and vocal fremitus were not changed appreciably in the earlier stages, but as the generalized fibrosis of silicosis increased these were decreased in intensity. Fibrosis of tuberculosis causes an increase in both tactile and vocal fremitus. The condition is, however, localized, whereas the fibrosis of silicosis is general throughout the lungs.

In my cases of granite cutters there was no marked change to any particular variety of breath sounds in uncomplicated cases, but rather a softening (or "soft pedal" effect) on all the breath sounds, which naturally brought out the vesicular type of breathing.

Rales were absent in the uncomplicated cases. No toxemia was present, which is accounted for by the absence of infection.

Tuberculosis as a Complication of Silicosis

It is not surprising that workers who have latent tuberculosis infections become disabled earlier than the average individual. It was our experience that these cases, they were still young people and the disease ran a more prolonged course. This was not true of the cases which developed silicosis first. The South African investigators, too, have observed that the cases which they classify as "phthisoid" break down with tuberculosis early in their mining careers.

Physical examination of silicotic patients who are breaking down with a tuberculous complication provides information which is not always available with the x-ray. Dr. Pancost stated in a talk on pneumoconiosis at the local (Washington) medical society recently that during this transitional stage the differential diagnosis is often impossible. When the tuberculous complication has advanced, diagnosis is, of course, easy.

Inquiry into the patient's condition will usually reveal symptoms which are common to uncomplicated tuberculosis. It was our experience that early complaints were fatigue, night sweats, increase in dyspnea, pains in the chest, and an afternoon rise in temperature. There was frequently complaint of a cough, which was productive. Many patients had hemoptysis and later in the disease, frank hemorrhages from the lungs. Loss of weight did not seem to occur so early as in uncomplicated cases; but when this symptom became manifest, it was marked. Tubercle bacilli were usually found in the sputum early in the disease.

The later stages presented no great differences from those culminating types of uncomplicated tuberculosis.

The physical signs presented variations from those in uncomplicated cases, inasmuch as there existed already a general pulmonary fibrosis. The latent or post-complicated cases of tuberculosis.

The x-rays of cases in this stage usually revealed areas of conglomeration, or fusing, of fibrotic markings. They were less distinct in character than in uncomplicated silicosis. This fact will be demonstrated in the slides.

The diagnosis of silicosis is not an easy task. The patient's history, careful analysis of his occupational life, a study of his physical condition and reliable x-rays are necessary to determine the presence of silicosis and to attempt to evaluate the extent of disability present. It is obvious that it is difficult for physicians to do this and a greater task for a lay jury. It seems to me that it would be better to have the suspected case examined at a reliable clinic or general hospital by a group of unbiased physicians and to abide by their findings rather than to have these cases fought out in courts. In most every manufacturing city large general hospitals and tuberculosis clinics are available and the use of these institutions will, it seems, insure better decisions both to the patient and to the industry.

Cause of Silicosis Among Workers no Longer Exposed to Silica Dust

In the study of silicosis one of the most important questions which has arisen is the health history of those individuals who have worked in the granite industry for a number of years and then left to find occupations in other trades where there was no further dust exposure. It was possible during the course of the study at Barre to observe 24 such cases.

The latency of silicosis has been referred to by other investigators. The South African workers found that "a steady fall over a period of years in dust concentration is not associated with the corresponding fall in the silicosis incidence." Dr. Watkins-Pitchford also records cases of miners who had been exposed to dust for a long period of time, apparently sufficient to develop silicosis, but who went into the war apparently not silicotic. He asserted that such cases were liable to develop tuberculosis. Doctor Pancoast presents a case of advanced pneumoconiosis in a quartz miner who had been exposed to dust for eight years. He had been out of the mining industry for ten years, yet the x-ray showed extensive pneumoconiosis with irregularities of diaphragm, and by fluoroscope he found the diaphragm restricted on each side. There was, perhaps, a tuberculous infection intervening at the time.

Britton reports two cases of workers who had been exposed to dust between seven and eight years. They changed occupations and had been away from siliceous dust for eight and nine years. They developed pulmonary symptoms and were found to be suffering from silicosis and tuberculosis. Tattersall also observed cases of latent silicosis in his studies. "Some of the men (rock drillers), moreover, had changed their occupation for various reasons quite apart from health, but in due course the inevitable dyspnea came on. One man, for instance, worked eight years regularly with rock drills, from 1906 to 1914, then joined the Army, was passed as A-1; but in spite of his open-air life, dyspnea came on in 1918, and from then until his death six years later his illness was a typical case of silicosis."

The influence of dust in mortality from tuberculosis is clearly indicated in the following table. New methods of manufacturing stone which created excessive dust by the use of pneumatic tools, were introduced in the granite industry about the beginning of the present century, and the tuberculosis rate has increased rapidly with their use. The rate has risen in direct proportion to the length of time during which they have been employed as follows:

15 per 1000	1890-1894
108 per 1000	1910-1914
195 per 1000	1924-1926

(During period of our observations.)

A consideration of the mortality statistics of Barre, Vermont, shows that there has been an excessive death rate from pneumonia and other respiratory diseases (tuberculosis excluded) during this period.

Methods for the Control of Dust in Industry and for the Protection of the Worker

By THEODORE HATCH

Instructor in Industrial Sanitation, Harvard School of Public Health and
Harvard Engineering School

The speaker said in part: The health hazard associated with exposure to industrial dusts varies with the industry and depends upon a number of factors, chief of which are the physical characteristics of those exposed, the chemical and physical properties of the dust, and its concentration in the atmosphere of the work place.

The evaluation of the hazard in a given industrial plant must therefore be based upon a thorough investigation of the factory conditions and a careful interpretation of the results. The investigation should include physical examinations of the men and determinations of its physical properties such as particle size. The sources of dust and the concentrations produced by the dusty processes must be determined by a complete dust survey. This should be accompanied by an occupational analysis to determine the extent and frequency of exposure of the workers to the hazardous dust. A knowledge of the plant processes and the characteristics of operation of the dust producing machines is also necessary.

In the present state of our knowledge, the manner in which these factors combine to determine the dust hazard cannot be subjected to an exact analysis. The health lengthen the time of exposure necessary to produce the damage, and the object of any program of prevention, therefore, is so to control conditions that the limited time for safe exposure is extended beyond the ordinary span of exposure.

The most direct means of controlling the hazard is by reducing the dust concentration to which the workers are exposed. The efficiency of the required dust control depends upon the allowable concentration in the atmosphere which in turn is determined by the toxicity of the dust and the tolerance of those exposed. The standard of permissible dustiness may be increased by careful selection of the men, by means of physical examination, and limiting their exposure through a system of rotation of employment. It may be further increased by reducing the percentage of toxic material in the dust and otherwise controlling its chemical and physical characteristics.

Standards of permissible dustiness have been proposed for a few of the dusty trades. From a study of the sickness and death rates among the workers in relation to the dust concentrations to which they are exposed, safe concentrations have been determined for the cement and granite cutting industries in the United States, the gold mines in South Africa, and the sandstone industry in Australia. The permissible concentration of zinc oxide has been determined direct by studying its effect upon experimental subjects.

A standard for lead mining which has been proposed was based upon the conditions found in that industry. This list, while it is not complete, serves to indicate the limited nature of the data and emphasizes the importance of careful interpretation of factory conditions in the evaluation of the dust hazard. It often requires years to demonstrate the hazardous nature of certain dusts, and immediate results therefore may have little value. In the absence of definite knowledge, the safe course is to consider all dusts dangerous until proved innocent.

The dusty processes encountered in industry differ widely and exhibit a considerable variation in the restrictions placed upon the design and operation of devices for the control of the dust. No single method of control can be universally applied; on the contrary a number of methods have been developed to meet the needs of the dusty trades and the choice of methods must be based upon a thorough study of local conditions. The common methods may be listed as follows: (1) substitution of a non-hazardous process, (2) isolation of hazardous process, (3) general ventilation, (4) control of dust at point of origin.

The silicosis hazard has been reduced in a number of industries by substituting for the dusty process one which is dust-free or which produces a relatively harmless dust. In the granite industry the surfacing machine, a heavy dust producing tool, has been replaced to some extent by the gang saw and the artificial abrasive wheel. These are wet processes and have reduced the dust concentrations associated with the surfacing of the stone to a figure well below the hygienic safe limit. In grinding and polishing jobs, the sandstone wheels have been replaced by artificial abrasive wheels containing little or no free silica and though dust is still produced,

exposure to it does not lead to the high tuberculous rate formerly found among grinders and polishers. Another example of this method is the substitution of steel shot and other silica free abrasives for sand in the blasting of castings. To give satisfactory results, the foundry sand must be removed from the castings before blasting, otherwise it is broken up and scattered as silicious dust.

This method of control is decidedly limited in application since it usually involves fundamental changes in the manufacturing process. Moreover, great care must be taken in substituting the so-called harmless dust, to make sure that a new hazard is not replacing the old one.

It is possible to isolate the dusty process in many cases. This may consist merely in confining the hazardous stages of manufacture to a separate building or room, thereby reducing the number of men exposed to the dust (and these men may be protected by masks), or it may mean complete isolation for the workers in an enclosed space. Complete isolation of sandblasting operations within a cabinet is now common practice. Escape of dust is prevented by keeping the cabinet under a slight negative pressure, and by means of suitable controls and windows, the operations may be directed from the outside. For some processes automatic blasting, requiring no direct operation, may be employed, although the entrance and exit locks for the material must be carefully maintained in order to prevent the escape of dust at these points.

In a few instances of generalized dust production throughout the factory, the use of general ventilation may prove satisfactory as a means of dust control. Under such conditions, the introduction of large quantities of dust-free air serves to reduce the dust concentration by simple dilution. This method is used in certain mining operations, also for purposes of removing heat and toxic gases as well as dust. In general, it involves the installation of large fans and is expensive to operate. In cold climates it becomes prohibitive owing to the great increase in the cost of heating. General ventilation should be looked upon as an adjunct to other methods of control, rather than an independent method.

Effective control of the dust at the point of generation prevents it from reaching the breathing zone of the worker and hence offers a positive means of reducing the dust hazard. It may be effected by the use of water or other liquids for capturing the dust, or by means of local exhaust ventilation.

The use of water for laying dust is an old method of control. It has been used extensively in connection with grinding wheels and is commonly employed in mining and tunnel operations in the form of wet drilling and water sprays. In operation, some of the particles are carried off immediately by the stream of water whereas others are thrown into the air with the water spray. The latter, however, are suspended in water droplets and therefore settle out rapidly. This method of control undoubtedly reduces the dust concentration but investigations have shown that it does not always give the high degree of protection required. Its efficiency depends primarily upon the completeness with which the particles are wet. In some cases the fine particles are surrounded by envelopes of gas and may pass through the liquids without coming in contact with it. Others, escaping with the water spray, may remain suspended in the atmosphere after the water droplets have evaporated. The wetting efficiency has been increased in some cases through the use of oils and other liquids.

Local exhaust ventilation consists in removing the dust through a suction hood placed close to the point of generation. This method of control is widely used in industry and is most effective when applied to a stationary dust producing machine or when it is attached to a moving tool, thus keeping it at a fixed distance from the point of dust origin. Its general application has been recognized and most states have incorporated specifications for the design of local exhaust systems in their industrial codes. Surveys in certain industrial plants, however, have demonstrated that many systems do not have the required efficiency of dust removal. This

for a careful study of the characteristics of operations of the dusty process and the importance of the aerodynamic characteristics of an exhaust hood in determining its efficiency. They also suggest the impossibility of employing any single measure of operation as the basis of design.

State codes commonly specify exhaust hood requirements in terms of the negative static pressure at the hood throat. In some cases a single value has been adopted for all dusty processes and an examination of existing codes reveals a considerable variation in the suction requirements. In some cases the diameter of the throat is also specified.

The use of this index arises from the fact that it constitutes an approximate measure of the rate of air flow into the hood. This is true, however, only when the area of the throat and the shape and size of the hood are also specified.

The inclusion of these factors in the specifications, however, is not enough since the efficiency of an exhaust hood is not a function of the rate of air flow, but rather of the air velocity at the point of dust generation, and this in turn is determined by the nature of the process and the design and location of the hood. Furthermore, the rate of air flow necessary to develop the required air velocity also depends upon the shape and size of the hood and its distance from the dust source.

Thus the static suction at the throat bears little relation to the dust collecting efficiency of an exhaust hood and has no place in legal specifications. On the contrary, the only satisfactory index of operation is the efficiency of dust removal itself. Industrial codes should therefore be written in terms of permissible dust concentrations and approval must be based upon actual dust determinations in the factory. In this connection it must be emphasized that visual inspection is not enough since with the ordinary conditions of illumination, concentration below 50-60 million particles per cubic foot of air cannot be detected by the eye alone. In general, concentrations of this magnitude are well above the hygienic safe limit.

Satisfactory data upon the design of exhaust hoods can be secured only through experimental investigation and experience, combined with actual quantitative measurements of dust collecting efficiency and carefully executed investigations of this source must replace the present uncertain methods of design.

Methods of Protecting the Worker Against Dust Inhalation

By PHILIP DRINKER

Associate Professor, Industrial Hygiene, Harvard School of Public Health,
Boston, Mass.

The silicosis problem in this country is not a pleasant spectacle for those of us concerned with industrial hygiene and safety measures. Painful as the cure may be, it consists of two perfectly definite steps: (a) medical examinations of new employees and routine examinations of all persons exposed to dangerous dust concentrations; and (b) reduction of dust concentrations breathed by workers to what are considered to be safe limits.

If dustiness can be controlled by local exhaust fans and dust collecting equipment, protective devices such as respirators or positive pressure helmets have no place except as emergency equipment. However, many processes like abrasive (sand or steel) blasting, paint and enamel spraying, porcelain manufacture, stone cutting, and grinding, and the like, will not, in all probability, be made reasonably dust free for some years to come. In work of this type, respirators and other protective devices have an important place. The safety man should understand thoroughly what can be expected of protective devices, and above all, should be able to check and direct whether the workers are getting the protection they require.

One sees occasionally statements to the effect that respirators have no place in industry because they filter out only large particles and let pass the small ones which are always the more harmful. Against this is the indisputable fact that the dust catching efficiency of several makes of respirators exceeds 90 per cent on of dust particles entering and leaving respirators shows a slight but unimportant reduction in average size of the dust particles. But by far the most convincing proof that well built respirators remove dust is the microscopic examination of the nasal discharge and sputum of a man who wears a respirator in a dusty atmosphere, and of one who does not.

Requirements for Respirators. Up to the present time our only U. S. specifications for respirators have been formulated by the Bureau of Mines. Respirators which is the direct result of their pioneer war work in gas masks. The Bureau requires for approval that a gas mask canister (which includes respirators) have at least 50 per cent filtering efficiency against tobacco smoke, measured at 85 liters per minute, and a resistance at all times of less than four inches of water gauge, prohibitive. They require also a "man test" in which the respirator shall give adequate protection to men performing light work in an atmosphere containing an irrepirable suspension (not silica) of definite concentration.

A paper by Katz, Smith, and Meier of the Bureau of Mines, has made it clear that these specifications are inadequate for respirators in daily use in industry. A resistance of four inches at 85 liters per minute is too high for any but the trained subject such as the soldier in war time or the rescue squad of our mines and public utilities. Katz showed that respirators with high efficiency and low resistance were entirely practical to manufacture and to use.

The Bureau determines tobacco smoke efficiencies by estimating photometrically the smokiness of air entering and leaving the filter of the respirator. The actual density or concentration of the smoke particles in air is not estimated. By a similar photometric procedure, the filter can be tested for silica dust efficiency. The test is rapid and reasonably accurate—hence, its appeal to the laboratory worker. For tobacco smoke testing, the method works nicely but for dusts it is not, in the writer's opinion, satisfactory. A dust concentration far higher than that ordinarily met with in dusty industries is essential to the test, and unless special measures are used, the actual concentration is unknown.

For some time, there have been used in this laboratory the following test methods:
1. Definitely known concentrations of finely ground silica (less than 2 microns) within the concentration limits of approximately 50 to 200 million particles per cubic foot are drawn through the respirator at 28.3 liters per minute, the effluent air passed through a standard impinger, and the impinger sample compared against another sample, taken at the same time, of the unfiltered air. Comparisons of the two samples can be made by the standard dust counting method by turbidimetry or photometry. The last mentioned is much the quickest and is sufficiently accurate for all practical purposes. A test to twenty minute dusting should give an efficiency of at least 90 per cent.

2. Finely ground calcium carbonate (less than 2 microns) in the form of "whiting limestone" or of magnesium oxide smoke (less than 1 micron) from burned magnesium ribbon can be determined either chemically or photometrically, both procedures being quicker and more accurate than the counting method. A 90 per cent minimum efficiency is required, the test concentration varying from 25 to 150 mg. per cubic meter.

3. By burning yellow phosphorus, a wet white suspension of about the texture of tobacco smoke is obtained. A filter which shows 90 per cent efficiency against this substance usually exceeds 90 per cent against fine silica. Estimations can best

be made either by using two impingers in series or by electric precipitator and determining chemically the quantity of smoke collected.

4. Smoke made by burning various kinds of pipe tobacco are a little easier to catch than the smoke formed by burning the special mixture used by the Bureau. By drying thoroughly ordinary pipe tobacco and using chemically dried air, a smoke approximating that used by the Bureau is apparently obtained. A filter which shows 50 per cent efficiency against smoke from dried tobacco will generally exceed 90 per cent against all dusts.

5. Resistance to airflow, by the Bureau's set-up, should not exceed 0.5 inches before filter dusting (item 1) nor 0.4 inches after dusting, both resistance tests to be made at 85 liters per minute, using an inclined manometer and suitable flow-meter. (The Bureau now permits any resistance less than four inches.)

A more exacting resistance test is obtained by drawing through known amounts of magnesium oxide fume which has an extraordinary tendency to plug filters.

6. For the man test, a small hole is punched through the face piece of the respirator and a small bore, dust free tube is connected to a special type of impinger or to an electric precipitator. A man, wearing the respirator, performs moderate work in an atmosphere of known dustiness and air from within the face piece of the respirator is sampled for dustiness at a steady known rate of about 15 liters per minute or less. The dustiness of the sample thus collected should not exceed 2 million particles per cubic foot or have an efficiency of less than 90 per cent, whichever rating is the more exacting. The sampling rate, in this case, must be about 15 liters per minute, in order not to interfere with the natural respiratory efforts of the subject. If it is desired to sample by impinger, a tube with a nozzle diameter of about 16 millimeters (instead of the standard 24 millimeters) should be used, with which instruments a rate of 15 liters per minute is suggested.

Requirements for Sandblast Helmets. Winslow, Greenburg, and Reeves have shown that positive pressure sandblast helmets can be tested while actually in use by the sandblaster. An improvement of their technic has been made by Greenburg and Bloomfield, so that anyone familiar with the standard impinger outfit can perform the necessary tests. All admit that sandblast helmets should be tested under practical sandblast conditions and not in the laboratory.

A hole is made in the helmet, a suitable rubber tube connected, and the air within the helmet sampled by the standard impinger, at 1 cubic foot a minute, for a reasonable period—preferably at least twenty minutes. The subject should be sandblasting throughout the period of sampling. The dustiness thus found should be less than two million particles per cubic foot, regardless of the abrasive used or the condition of the objects being blasted. As a control, it is advisable to sample the compressed air supplied to the helmet in case the air supply is itself also dusty.

Requirements for Paint Spray Masks. As paint spraying is carried out only with a convenient source of compressed air at hand, it is natural that masks supplied with positive pressure should be used. Like the sandblaster, the painter moves about but little and is not greatly inconvenienced by a light air-line attached to his back or clothing. While spraying under practical conditions, air within his mask should be sampled and the protection afforded by the mask rated in terms of the concentration inside the face piece. The device should give the same measure of protection as afforded by the sandblast helmet.

The manufacturer of protective equipment should be allowed all possible license in modifications and improvements having to do with appearance, obstruction to vision, comfort, ruggedness and practicability of his equipment. If the manufacturer desired his product to be certified as to its performance under the conditions for which he designed and built it, the prospective purchaser and safety engineer is equally desirous of knowing the performance data.

In view of the past work of the Bureau of Mines, the unquestioned integrity of

place in
small cases
that the
cent on
the time
important
convincing
out of the
impinger.

specific
respirators
a schedule
the Bureau
and) have
85 liters
or gauge
resistance
shall give
aiming an

to it clear
easy. A
trained
times and
distance

metrically
the actual
1. By a
easy. The
7 worker
is not in
that ordi-
measures

method
microns)
files per
efficient
4 against
of the
bidimetry
accurate
efficiency

whiting
ed mag-
in proce-
per cent
50 mg

resistance
against
the test

its personnel and the uniform high caliber of its work. The Bureau's laboratories at Pittsburgh seem the logical place for such certification to be done. The manufacture of protective equipment welcomes definite specifications he can meet, no matter how rigorous, and expects to pay the testing bill whether his equipment is passed or rejected. No private testing laboratory would be expected to undertake this type of work without charging the manufacturer a fee adequate to give the laboratory a reasonable profit. The Bureau's fees in the past for this type of work have been modest, but the funds reverted to the U. S. Treasury, and not to the Bureau's laboratory. Unless an absurd and wholly unnecessary hardship is to be placed upon the Bureau, it should be permitted to do such work on a cost, or pay-as-you-go, basis.

General Discussion

Chairman Greenburg after delivery of the papers invited discussion, which was lengthy and spirited. This may be summarized as follows:

Dr. H. K. Fennell, Philadelphia, pointed out that while X-ray presents the best method of observing changes in the lungs and also for determination of their incapacity, most examinations are not thorough. This point is frequently overlooked. Expert evidence is very important in making a diagnosis and grading incapacity.

The point made by Dr. Russell, of the advisability of special boards to decide the physical status of employees exposed to silica hazards, was also emphasized by Dr. W. J. McConnell, Metropolitan Life Insurance Company, New York City. In this connection Commissioner R. C. Knutson, Wisconsin Industrial Commission, spoke of the difficulties experienced in handling compensation cases. He suggested amendments to the occupational disease laws in various states for the complete coverage of occupational diseases, so that claims can be decided by the commissions rather than by common law. The conflict of testimony by so-called experts appearing before the commissions is sometimes remarkable. In some cases a final decision has been necessarily withheld until after an autopsy. John Roach, Deputy Commissioner of Labor, New Jersey, advocated the appointment of a Medical Board to be paid by the State whose opinion in compensation cases should be final.

There is a great difference of opinion about these cases, said Chairman Greenburg. The compensation commissions differ, the doctors differ, and on the other hand, industrialists have not been alert to the situation, but they can do a great deal in their decisions. Some time ago I suggested in connection that the commission should be made up of a lawyer, a physician specialist, and an engineer, but this suggestion did not meet with very much favor.

Asked to outline how silicosis cases are handled in Canada, Dr. J. C. Cunningham, Toronto, Ontario, said: Our laws define the terms silicosis and tuberculosis, and they further define the industries and occupations affected, but they refer to mining especially. The cases come from the individual physicians and are referred to the silicosis board. When the claim is received, the board examines the records and the claimants, to see if the regulations of exposure have been complied with. If so the claimant is personally referred to the silicosis board; two or three of the members examine the case personally, and then each case is decided by all three members of the board. The claim is then referred back to the compensation board.

Two other points of interest occur to me, he said further: first, we have had a number of stone cutters with 15 years exposure to limestone, contracting tuberculosis; second, in an extensive examination of workers exposed to silica dust and alkaline powders, reports in the literature have shown the rapid development of silicosis, but in our experience in examination of two small groups with similar exposure has shown only a small amount of fibrosis. The importance of exposure to dust also has not yet been sufficiently realized.

Dr. J. J. point made pressure rise made as to not operate ventilation.

It is impossible to protect work. It is possible in the various and many workers will rather die and will not.

It has been have had all the present workers but due to prevalence of a in a real silico years old, reactions, transmissible.

Professor protection if in a high reduce the apparatus, man is not efficient pro

For the re

Chairman
Nominating
For Chair
Vice-Chair
Secretary
Chairman

Dr. J. P. Leland, U. S. Public Health Service, Washington, D. C., emphasized the point made by Professor Drinker concerning the use of masks, that the minimum pressure necessary to operate such a mask should be noted, that a decision should be made as to what this is, and that we should be sure that pulmonary excursion does not operate against appreciable pressure and against proper and continuous lung ventilation.

It is important to find some workable protective device, said Mr. Roach, that will protect workers in sixty or seventy different industries where the exposure exists. It is possible that in laboratories a well made apparatus will work fairly well, but in the various industries workers are found who have sharp and irregular features, and many times a mask or respirator will not work on these faces as on other workers with round, smooth features. The protective device thus becomes a menace rather than a help. We are also very much concerned whether the filter is satisfactory and will properly strain out the particles.

It has been mentioned, said Dr. Russell, that some limestone and sandstone workers have had silicosis. We must remember that granite workers and others have shown the presence of silicosis, although they have not been directly exposed, and other workers beside cutters have shown the presence of silicosis, all of these cases being due to previous occupational exposure involving silica hazards. Recently we had a case of a man with silicosis and tuberculosis, his job having been loading coal (not a real silicosis exposure), but previously he had been a gold miner. He is now 50 years old, has tuberculosis, and three of his five children also give positive tuberculin reactions, which is against the usual conception that tuberculosis from silicosis is transmissible.

Professor Drinker said: I have been asked whether I consider a respirator a good protection if no other apparatus is available. My answer is that it would not be. In a high concentration of dust, if the respirator is functioning properly, it should reduce the amount of dust breathed. But a respirator is not really an eight-hour day apparatus. In other processes, however, where the work is intermittent and a workman is not obliged to wear his respirator continuously, it should function as an efficient protective apparatus.

WEDNESDAY MORNING SESSION

October 5, 1932

For the record of this joint session of delegates of the Industrial Health Section with the Chemical Section, see page 166 of this volume.

WEDNESDAY AFTERNOON SESSION

October 5, 1932

Chairman Greenburg, on the opening of this session, called for the report of the Nominating Committee and officers were chosen as follows:

For Chairman, Dr. R. C. Leland, American Medical Association, Chicago.

Vice-Chairman, Dr. W. R. Riddan, American Red Cross, New York City.

Secretary, Dr. C. O. Sappington, Chicago.

Chairman Greenburg then introduced the first speaker.

TWENTY-FIRST ANNUAL SAFETY CONGRESS
NATIONAL SAFETY COUNCIL



Safety Section, A.R.A.--Steam
Railroad Section, N.S.C.

Section Officers 1931-32

Chairman—C. T. BAILEY, Chief Safety Agent, Oregon Short Line Railroad.
First Vice-Chairman—C. E. HILL, General Safety Agent, New York Central Lines.
Second Vice-Chairman—C. L. LAFONTAINE, General Safety Supervisor, Great Northern Railway.
Secretary—J. C. CAVISTON.

(NOTE: The following pages contain a condensed abstract of the records of the sessions of the Safety Section, A.R.A.—Steam Railroad Section, N.S.C., as published in full by the American Railway Association in a booklet entitled, "Proceedings of the 12th Annual Meeting of the Safety Section, Washington, D. C., October 4 to 6, 1932.")

TUESDAY MORNING SESSION

October 4, 1932

The sessions of the Safety Section, American Railway Association—Steam Railroad Section, National Safety Council, convened in the Hotel Washington with Chairman C. T. Bailey, Chief Safety Agent, Oregon Short Line Railroad, Salt Lake City, Utah, presiding. The invocation was given by L. G. Bentley, Chesapeake & Ohio Railway.

Report of Committee on Relations with National Safety
Council

By ROBERT SCOTT

Director, Insurance and Safety, Atlantic Coast Line Railroad

Mr. Scott said in part: Your committee finds pleasure in reporting that much satisfactory progress has been made in the direction of co-ordinating the work of both sections with the view of avoiding duplication of effort and expense and to the end that the cause of safety might be advanced.

The first annual meeting of the Steam Railroad Section, National Safety Council, was held in Philadelphia in October, 1915, while the Safety Section of the American Railway Association held its first special session in Boston in September, 1921. Both of these sections have been functioning properly and well ever since they came into existence, and have been a powerful force in the reduction of avoidable accidents.

On September 2, 1931, a meeting was held in Chicago at which there were present members of the committee on relations and officers of both sections. At this meeting

in the stress of economy it has been necessary drastically to restrict all expenditures, and dark because the economic depression kept our backs and shoulders bowed to the storm which has raged around us—but during all this stress, you gentlemen of the Safety Section have carried the banners of safety and safety first flying, and your shock troops have been supporting and defending them and there has been no let-up. While there have been let-ups in other directions, there has been no let-up in this safety movement, even with your depleted forces.

Now, as we approach the crest of the hill, the slogan "33 by '33" floats down to our ears from the throats of thousands whose lives have been spared by the drive for safety. I see the light growing clearer ahead and as we lift our heads and throw back our shoulders, I see a smoother, broader, lighter pathway with more moderate slope stretching away to the green meadows above. The storm clouds are breaking, the warm rays of the economic sun are gradually coming through; doubt and despair are nearing their end.

TUESDAY AFTERNOON SESSION

October 4, 1932

Report of Committee on Prevention of Highway Crossing Accidents

By H. A. ROWE

Manager, Claims Department, Delaware, Lackawanna & Western Railroad,
New York City

The speaker said in part: The Committee is again gratified to be able to announce a further reduction of grade crossing accidents, fatalities, and injuries in 1931 as compared with 1930. Thus we have had three consecutive years of progress in the curbing of crossing crashes, the records being as follows: 1931, total accidents 4,100, killed 1,811, injured 2,657; 1930, accidents 4,833, killed 2,920, injured 3,517; and in 1929 there was a slight reduction.

The year 1928 was the peak year in railroad crossing fatalities, since which time the reduction of such fatalities has been 757 per year, the 1931 record being but one more killed than in 1922, when the careful crossing campaign was inaugurated.

The outstanding accomplishment of crossing accident reduction can be better grasped when we note that motor vehicle fatalities on streets and highways in 1922 were 13,676 but in 1931 there was an increase of 18,913 deaths or 139 per cent. During this same 10-year period there was an increase of but one death at railroad crossings.

A very important feature of the committee work has been the careful crossing campaign which has continued to enlist the interest and cooperation of many organizations and the general public. This has been furthered by general publicity, the regular posters initiated for this special campaign and other literature.

During the past year the National Safety Council has been active in its educational campaign for the prevention of accidents, and in its May, 1932, issue of the *National Safety News* contributed a most useful and illuminating frontispiece. The crossing accident situation was stressed in the same issue of the *News*, and in many other respects the National Safety Council has shown deep interest in cooperating in the prevention of crossing accidents.

Opportunity is presented for a fuller enjoyment of the facilities offered by the 41 Community Safety Councils associated with the National Safety Council. Collectively, 30 Councils reach 808,000 school children through 3,141 meetings. Railroad safety representatives, cooperating with such local Councils, have an excellent opportunity of extending the gospel of careful crossing over railroads. These Councils hold vast numbers of other meetings and should be regarded as fertile soil.

WEDNESDAY MORNING SESSION

October 5, 1932

Report of Committee on Train Service Accidents

By D. G. PHILLIPS

Superintendent of Safety, The Wabash Railway

The speaker said in part: In the year 1931, out of 3,099 fatalities and 35,656 persons injured, according to reports to the Interstate Commerce Commission, 4,624 of these fatalities and 18,349 of the persons injured occurred in train service accidents. While it is true that a large proportion of these fatalities occurred in grade crossing accidents and to trespassers, it is also true that over half of the fatalities to employees on duty occurred in what is known as train service accidents and about one-third of the injuries to employees occurred in train service accidents.

We feel, therefore, that we are justified in saying that the prevention of train service accidents is probably the most important safety problem confronting us today, as far as accidents in and around railroads are concerned.

Under the heading "coupling or uncoupling cars or locomotives" in 1931 12 persons were killed and 394 persons injured. This may be compared for the year 1930, when 30 persons were killed and 604 injured. The year 1931, therefore, shows a decrease of 60 per cent in the number of fatalities and 35 per cent in the number of personal injuries; and these may be compared further with the record for 1920, when there were 151 fatalities and 2,450 injuries due to this cause.

The principal reason for personal injuries under this heading is due to employees stepping in between moving cars, usually at a time when coupling is about to be made, to determine if the knuckle has fully opened, to adjust location of couplers, or to adjust the coupling or uncoupling lever, with the result that they are caught between the couplers; or perhaps due to tripping or falling while performing this act, and are thus run over by the car. Our remedy for correcting this dangerous practice is for each and every railroad to make a positive and definite rule prohibiting employees from going between moving cars when nearing each other, to examine the employees to see that the rule is understood by them, and that supervisory officers see that the rule is enforced.

Under the heading "coupling or uncoupling air or steam hose," in 1931, 13 persons were killed and 175 persons injured, which may be compared with the record for 1930, when 7 persons were killed and 232 injured. The increase of 86 per cent in the number of fatalities is decidedly regrettable, although the record shows a decrease of 24 per cent in the number of injuries. The principal cause of employee injuries under this head is due to their failure to protect themselves by performing this work in accordance with the rules.

The remedy for this class of accidents where car men are employed rests in a full and complete enforcement of the blue signal rule which is quite uniform on all railroads. Railroad managements should improve this blue signal so as to make it as efficient as possible. The rule should also govern the placing of the blue signal so as to make sure that it is in a location where it will serve the best purpose as a signal to warn train, engine and yard men who might be guided by it. Where engine is coupled onto cars and trainmen are performing this work without blue signal protection, they should not permit themselves to get into a place where an unexpected movement of the cars might cause an accident, without first notifying the engine man and fireman so as to be fully protected.

Under the heading "operating hand brakes," in 1931 there were 18 fatalities and 324 persons injured, as compared with the record for 1930 when 26 persons were killed and 1,154 injured. The year 1931 shows a decrease of 31 per cent in

Ohio Railroad

years of railroad
ion to safety into
is inherently safe
is convinced him-
self does not need
emistic and who is

outine service are
ould say their home
work any mental
their duties, and
not become easily
to face any situa-
-1) per cent of the

thers but that they
problem we have,
anything occurring
king, employees of
sife and the things
on with all. Their
They seem to get
-pleless.

nt efforts of those
safety campaigner
work, to constantly
practices. These
the unsafe.

ind as the fatalists
blem all to itself,
ely, intensive and
elf that any large
ve censured myself
is type, because in
in the service, due
se about this type
d to the possibility

eristics. Generally
thoughts are along
ful individual, with
h his private habits

eady response from
elongs, his family,
reach him through
the success of these
he supervising officer
safety to his gang,
elf.

that in the yards
from \$1,500 to
ough our 38 main
thout one dollar's
a damage of only
to my mind, has

concerning railroads
of doubt—public
other industry can
movement has been
to invite lawyers,
of life to attend
have had those men
but were doing in
on generally in a

ureau of Safety,

Commission

accident investiga-
mission. How-
looked and which
not only to the
cause of an
him develop the
suddenly occurs, and
idea of impressing
occurrence of acci-

accidents, however
by competent in-
of a similar char-
for the principal
what disciplinary
There the matter
important side of
a view to profiting
the right direction.
rued is on the job
of. General officers.
Federal Commis-
ness of what has
are learned that
sequence so far as
is no commotion
although the small
an accident should
of so-called major

It may be argued that no one has time to dignify minor accidents by careful and painstaking investigation, but the answer to any such argument is that if they are investigated carefully and with sufficient thoroughness to bring out any underlying condition or situation which may exist, the time soon will come when there will not be very many to investigate, and we may rest assured that the occurrence of major accidents will decrease just as rapidly as do the minor accidents. Furthermore, all employees involved are available for questioning, whereas in the more disastrous accident important witnesses are often permanently silent.

Railroad casualties have been decreasing for years, although just what the immediate trend is I cannot pretend to say; you may rest assured, however, that they will continue to decrease, but only if all accidents are treated with the importance they deserve. As to the steps to be followed by the various railroads in this humanitarian work, these must be worked out for each individual organization. They all have the same object in view, the saving of life and limb, and I do not believe that anything can impress itself to any better advantage on the rank and file of railroad workers in the way of accident prevention than to have the investigation of the minor accident, regardless of its character, as thoroughly and painstakingly handled as the investigation of the major accident. The investigation of the major accident obviously would take more time because of more facts to be developed, and more evidence of one kind or another to be considered, but aside from the question of volume there would appear to be no difference in the investigation itself. The result to be accomplished is the same in each, and only by handling it in the same manner can those results be best attained.

WEDNESDAY AFTERNOON SESSION

October 5, 1932

Value of "Safe Practices" Committees

By F. HARTENSTIEN

Assistant to General Manager, Lehigh Valley Railroad

The speaker said in part: In our efforts to reduce the number of casualties on the railroads it becomes natural for us to analyze their causes and if possible adopt ways and means to prevent repetition. After a careful study of this subject, and considering that 75 per cent or more of the injuries that occur on the railroads are the result of unsafe practices, it appears to be in order to make a change in our safety organization that is adaptable or more in keeping with the causes which are responsible for producing unsatisfactory safety records. With the hope and expectation that a change in the name of safety committees to that of "safe practices committees" will be conducive of better results, it is recommended to the members of the Section that such a change be made.

The change is recommended for the purpose of inspiring careful employees who are dependable safety workers to caution their co-workers when they observe them doing anything that is liable to result in personal injury. Also, to more clearly instill in the minds of committees and other employees that the causes of the majority of personal injuries on the railroad are from unnecessarily taking chances and their discontinuance will be a large contribution to the goal that we are struggling to make by the end of the year 1933.

If it is decided to change the name of committees it should be understood that reporting any unsafe conditions observed on railroad property must not be discontinued, but a careful analysis of the records indicate that a very small percentage of our injuries occur from defects and unfavorable conditions, and the change suggested should direct the attention of officers and employees to the real reason for the majority of railroad accidents.

of train, a trainman may go over the running board if necessary to get on top of the train to extinguish fire or pass signals. If anything should develop on the engine requiring getting out on the running board to fix it, and such work cannot be deferred, the train must stop between stations to permit it to be done.

THURSDAY MORNING SESSION

October 6, 1932

Power Apparatus in Maintenance of Way Work

By LEM ADAMS

Engineer, Maintenance of Way, Union Pacific System

The speaker said in part: The maintenance of way employees on any railroad are constantly beset with hazards of accidents. When the motor car is set on the track for the day's work there is a potential hazard of being struck by a train, an automobile at a grade crossing, or another track car. Hence we surround them with innumerable rules and regulations to safeguard their movements.

Men in this branch of railroad service must constantly be on the alert to protect themselves. Their tools are watched closely for the smallest defect that might result in injury from particles of flying steel, and the very best steels and heat treating methods are used to provide tools that will be as nearly fool-proof as possible.

Yet with all these precautions, we still have accidents. Perhaps a rail is struck with a spike maul when a spike is not properly hit, or a sledge hammer falls when striking a track chisel in cutting a rail, and we have a cut or eye injury from flying steel, or an adze strikes a knot in a cross-tie when adzing for gauge and a foot is cut. Or perhaps a bar slips, or the trip gives way when operating a ratchet jack for spotting track, and we have a broken arm or other serious injury. These things are especially prevalent when large groups of men are working in a rail renewal or ballasting gang.

With such a picture before us, we maintenance of way men have for years been thinking in terms of machinery to do the more arduous and dangerous operations. Then, too, we were thinking in terms of efficiency, for safety and efficiency usually go hand in hand.

(The speaker then showed a score or more of lantern slides illustrating various types of power equipment employed in maintenance of way work.)

This set of equipment is one of our best safety agents. However, all power operated tools are unfortunately not the safest to use, although they are great labor savers. Some tools in this class are the power saw, the sandblast for cleaning surfaces preparatory to repainting, the power drill for either rail or bridge work, and many others—but efficiency and accuracy of work demand their use, and with proper care on the part of the operators they can be handled safely.

Planning for Safety in Track Construction

By FRANK R. BRADFORD

Director of Safety & Fire Prevention, Boston & Main Railroad

The speaker said in part: My object in being here is to show you a picture illustrating one of the modern methods of main line rail renewal. The operation, which is notable in many respects, is the outcome of the idea that the old established methods of rail renewal were no longer justified from the standpoint of economy, advantage of the operating department, or safety to the maintenance of men.

(10) Avoiding getting men excited by unnecessary hollering on the job, etc.

(11) Have all laborers examined as to physical condition before employment.

The report of the resolutions committee was then presented by J. A. Long of the Delaware & Hudson Railroad, Chairman, and two resolutions were formally presented and adopted by the Section delegates.

The first was a resolution of condolence upon the death of J. Flanagan, Manager, Safety Department, Chicago, Milwaukee, St. Paul & Pacific Railroad.

The second resolution acknowledged with thanks and appreciation efforts of all who had participated in making the Washington Congress Session successful.

Report of the Nominating Committee

The report of the tellers who canvassed the election of officers for the Section, was made by J. J. Heavey, The Erie Railroad, and announcement was made of the election as follows:

Chairman of the Section—Charles E. Hill, General Safety Agent, New York Central Lines.

First Vice-Chairman—C. L. LaFontaine, General Safety Supervisor, Great Northern Railway.

Second Vice-Chairman—H. A. Parish, Assistant to General Manager, Chicago & North Western Railway.

Members selected for the Committee of Directions for the Ensuing Year:

Eastern Territory—F. Hartenstein, Assistant to General Manager, Lehigh Valley Railroad; H. A. Rowe, Manager, Claims Department, Delaware, Lackawanna and Western Railroad.

New England Territory—C. N. Woodward, Assistant to General Manager, New York, New Haven & Hartford Railroad.

Southern Territory—Robert Scott, Director Insurance & Safety, Atlantic Coast Line Railroad.

Canadian Territory—A. O. Beck, Director, First Aid & Accident Prevention, Canadian National Railways.

Members of the *Committee on Nomination* for the ensuing year: F. W. Curtis, Supervisor, Safety & Fire Prevention, Denver & Rio Grande Western Railroad. Chairman: E. C. Evans, Superintendent of Safety, Louisville & Nashville Railroad; C. F. Larson, Superintendent of Safety, Missouri Pacific Railroad; F. M. Metcalfe, Superintendent of Safety, Northern Pacific Railway; J. C. Pratt, Supervisor of Safety, The Redding Company.

The closing minutes of the session were devoted to the introduction of the new chairman, Charles E. Hill, and to appreciative and eulogistic remarks concerning the services rendered by officers of the section during the past year.

ADJOURNMENT

General Ch.
Mass.

Vice-Chairman

Secretary :
Woolen

Chairman F
A. Hale

Chairman A.
Worcester

Chairman F
Conn.

Chairman S
R. I.

Chairman E
ford, Co

Members at
ARTHUR

RUSSELL
ton.

WALTER
Mas

JOHN H
PAUL W

The opening
with General
pany, Boston
officers and s