

Form Approved OMB
No. 44-R1387
Approval Expires:
July 30, 1972

U.S. DEPARTMENT OF LABOR

Form No. OSHA-20
May, 1971

82610-RM
(Same as 81106)

MATERIAL SAFETY DATA SHEET

SECTION I					
MANUFACTURER'S NAME MONSANTO COMPANY			EMERGENCY TELEPHONE NO. (314) 694-1000		
ADDRESS, including city, state, and ZIP Code 800 North Lindbergh Boulevard, St. Louis, Missouri 63166					
CHEMICAL NAME AND SYNONYMS			TRADE NAME AND SYNONYMS Capacitor 21		
CHEMICAL FAMILY Chlorinated Aromatic			FORMULA Mixture		
SECTION II HAZARD AND IDENTIFICATION					
PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES					% TLV (Units)
SECTION III PHYSICAL DATA					
BOILING POINT (°F)	760 mm	275-320	SPECIFIC GRAVITY (H ₂ O = 1) (25/15.5°C)	1.187	
VAPOR PRESSURE (mm Hg.)	at 100°C	> 0.05	PERCENT VOLATILE BY VOLUME (%)	N.A.	
VAPOR DENSITY (AIR = 1)	Not Avail.		EVAPORATION RATE (H ₂ O = 1)	< 1	
SOLUBILITY IN WATER	at 25°C negligible	< 0.01%			
APPEARANCE AND ODOR	colorless oil aromatic odor				
SECTION IV FIRE AND EXPLOSION HAZARD DATA					
FLASH POINT (ASTM D93)	Not Avail.		FLAMMABLE LIMITS (% L) (% U)	Not Avail.	
EXTINGUISHING MEDIA	Water, foam, CO ₂ , or dry chemical.				
SPECIAL FIRE FIGHTING PROCEDURES	Respiratory protection when fighting fires where exposure to vapors or gases is possible.				
HAZARDOUS REACTION (e.g., with water, acids, etc.)	Highly volatile (hydrochlorides and chlorine) can be evolved in fires of this product.				

DSW 009558

LEXOLDMON006351

Capacitor 21

SECTION V HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE

Not Available

EFFECTS OF OVEREXPOSURE

Skin irritation in the form of chloracne, systematic intoxication leads to nausea, vomiting, loss of weight, edema and abdominal pain.

EMERGENCY AND FIRST AID PROCEDURES

Remove from exposure. Remove contaminated clothing. Wash contacted area with large amounts of water and soap. Refer to physician.

SECTION VI REACTIVITY DATA

STABILITY

UNSTABLE

STABLE

X

CONDITIONS TO AVOID

INCOMPATIBILITY (Materials to avoid)

HAZARDOUS DECOMPOSITION PRODUCTS

CO, CO₂, smoke, soot, chlorides and chlorine

HAZARDOUS POLYMERIZATION

MAY OCCUR

WILL NOT OCCUR

CONDITIONS TO AVOID

X

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Absorb on clay, sawdust or other absorbant material. Place in drums. Bury in approved chemical landfill in accordance with local and state regulations.

WASTE DISPOSAL METHOD

Burn in an approved incinerator in accordance with local and state regulations.

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Special type)

Bureau of Mines approved respirator for organic

VENTILATION

LOCAL EXHAUST

Yes - for vapors

SPECIAL

Vapors.

MECHANICAL (General)

OTHER

PROTECTIVE GLOVES

rubber

EYE PROTECTION

chemical goggles

OTHER PROTECTIVE EQUIPMENT

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Avoid skin and eye contact.
Avoid inhalation of vapors.

OTHER PRECAUTIONS

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, MONSANTO COMPANY MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

JAG:HOH:JTG:WBP

4/14/72

DSG 009559

LEXOLDMON006352