

NEG. NO. K-9A

TRADEMARK FILE INFORMATION

Trademark:	Johns Manville JM
Trademark Owner:	Johns-Manville Corporation
Last Assignee:	None
Date of First Use	
in Commerce:	April 10, 1929
Registration No.:	566,486
Date Trademark	
Registered:	November 11, 1952
Size of Label in	
Trademark File:	N/A

Receipt of Pictured Label by Patent Office: N/A

Johns-Manville

ASBESTOS FIBROUS ROOF AND FOUNDATION COATING

Contents: Asphalt, Asbestos Fibre, Mineral Spirits and Slatedust

PRODUCTS  **OF QUALITY**
CAUTION—COMBUSTIBLE MIXTURE
N. Y. F. D.—C. of A. No. _____

- Keep away from heat, sparks and open flame.
- Keep container closed and away from heat.
- Use with adequate ventilation.

DIRECTIONS FOR APPLYING

ROOFING: Surface to be coated must be free from dirt, dust, and scale. Stir contents thoroughly immediately before using. Apply with 3-knot roofing brush or wide stiff paint brush in thick uniform coating, giving special attention to weathered areas, laps, and joints.

FOUNDATIONS: Surface to be coated should be thoroughly brushed to remove all loose sand and cement. Stir coating thoroughly immediately before using. Apply with 3-knot roofing brush in thick uniform coating direct to cement foundation surface. No primer necessary. **CAUTION:** This product is designed as a damp-proofing for exterior foundations and will not function as a waterproofing against actual ground water.

Contents: 5 GALLONS

Johns-Manville Asbestos Fibrous Roof and Foundation Coating is specifically designed for coating old roofs of all kinds and to provide a damp-proofing for the exterior foundations of homes, commercial and industrial buildings.

HANDLING INSTRUCTIONS

KEEP AWAY FROM
OPEN FIRES

- Nothing should be added to this product without consulting the manufacturer.
- As temperature falls this material tends to thicken.
- Restore proper consistency by placing in a warm room.

REPLACE COVER
TIGHTLY

**JOHNS-MANVILLE
SALES CORPORATION
NEW YORK, N. Y.**

L-1564-B

Printed in U.S.A.