

CROCKIT
CROCKIT
CROCKIT

1213-009 6-64

CAUTION!
COMBUSTIBLE!
CONTAINS LEAD
HARMFUL
IF SWALLOWED

Keep away from heat and open flame. Do not apply on walls, furniture, window sills or other interior surfaces of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use.

Use With Adequate Ventilation
KEEP OUT OF THE REACH OF CHILDREN.

14-42

FINEST Professional
No. 22 HOUSE
★ TRIM AND TINTING

QUALITY
Glidden
PRODUCT

GREAT WHITE PLEST

NO. 22 HOUSE PAINT TRIM & TINTING WHITE

No. 22 House Paint is non-chalking and has unusual whiteness and elasticity. It has been formulated for use as a brilliant, lasting trim white and will not chalk down on other colors or foundations. No. 22 House Paint may be tinted with Glidden Dramatone Multi-Purpose Tinting Colors or Colors-In-Oil to produce light tints. Its extra high hiding and exceptional ease of brushing make No. 22 House Paint especially suitable for professional painter use.

DIRECTIONS

SURFACE PREPARATION: NEW WOOD must be cured, dry and clean. Shellac all knots. Prime with No. 51 Professional Exterior House Paint Primer as directed for usage. Putty all cracks, nail holes and open joints. Caulk casings and chimneys where necessary.

PREVIOUSLY PAINTED WOOD surfaces in good repaint condition need only be clean. Painted surfaces that are badly worn, heavily chipped, cracked, blistered, flaking or peeling should be wire brushed, scraped or burned off to the bare wood. Prime these areas with No. 51 Professional Exterior House Paint Primer. **FINISH COATS:** Follow directions for new wood.

FINISH COATS: Apply finish coats of No. 22 House Paint unthinned. If two finish coats are to be applied, thin the first coat with 1/2 pint of turpentine or mineral spirits per gallon. Allow 48 hours drying time between coats.

MATERIAL PREPARATION: Mix thoroughly by boxing. No. 22 House Paint should be applied without thinning, although thinning with 1/2 pint of turpentine or mineral spirits per gallon is permissible when using over extremely hot or very cool surfaces. Always box after thinning. Do not add driers. May be tinted to light tints with Glidden Dramatone Multi-Purpose Tinting Colors or Colors-In-Oil.

MATERIAL APPLICATION: Paint only when weather conditions are favorable and temperature is above 50° F. Apply liberally, brushing until coating is smooth and free of segs. For best performance, do not cover more than 550 square feet of surface with each gallon of paint. To spray, reduce 10% — 15% with turpentine or mineral spirits and use 30 to 40 pounds of air pressure. LC6563

THE GLIDDEN COMPANY, CLEVELAND 2, OHIO
Factories and Branches in Principal Cities Throughout United States and Canada.

GLD011722

Made in U.S.A.

Pigment Vehicle	89.0%
Extender	10.0%
Calcium Hydroxide	41.4%
10% Lead	8.6
Oil Soluble	30.5
Carbonate	10.0
Mineral Oil	10.5
Vehicle	100.0%
Thinned	7.1%
Unthinned	92.9
Mineral Oil	85.4
Driers	100.0%
Y-5023	465