1) Maintain copies of any test required under Subsection (a)(6) for a period of 3 years;

2) Provide copies of these tests to the Agency upon request; and

3) Provide annual test result certification to bulk gasoline plants and terminals where the delivery vessel is loaded.

d) Any delivery vessel which has undergone and passed a test in another state which has a USEPA-approved leak testing and certification program will satisfy the requirements of Subsection (a). Delivery vessels must display a sticker, decal or stencil approved by the state where tested or comply with the requirements of Subsection (b). All such stickers, decals or stencils shall be displayed no later than December 31, 1987.

(Source: Added in R85-21(A) at 11 Ill. Reg. 11770, effective June 29, 1987)

SUBPART Z: DRY CLEANERS

Section 215.601 Perchloroethylene Dry Cleaners

The owner or operator of a dry cleaning facility which uses perchloroethylene shall:

a) Vent the entire dryer exhaust through a properly designed and functioning carbon adsorption system or equally effective control device; and

b) Emit no more than 100 ppmv of volatile organic material from the dryer control device before dilution, or achieve a 90 percent average reduction before dilution; and

c) Immediately repair all components found to be leaking liquid volatile organic material; and

d) Cook or treat all diatomaceous earth filters so that the residue contains 25 kg (55 lb) or less of volatile organic material per 100 kg (220 lb) of wet waste material; and

e) Reduce the volatile organic material from all solvent stills to 60 kg (132 lb) or less per 100 kg (220 lb) of wet waste material; and

f) Drain all filtration cartridges in the filter housing or other sealed container for at least 24 hours before discarding the cartridges; and

g) Dry all drained filtration cartridges in equipment connected to an emission reduction system or in a manner that will eliminate emission of volatile organic material to the atmosphere.

(Source: Adopted at 7 Ill. Reg. 1244, effective January 21, 1983)

Section 215.602 Exemptions

The provisions of Section 215.601 are not applicable to perchloroethylene dry cleaning operations which are coin-operated or to dry cleaning facilities consuming less than 10 gallons per month (360 gallons per year) of perchloroethylene.

(Source: Adopted at 7 Ill. Reg. 1244, effective January 21, 1983)

Section 215.603 Testing and Monitoring

a) Compliance with Section 215.601(a), (f) and (g) shall be determined by a visual inspection;

b) Compliance with Section 215.601(c) shall be determined by a visual inspection of the following: hose connections, unions, couplings and valves; machine door gaskets and seatings; filter head gasket and seating; pumps; base tanks and storage containers; water separators; filter sludge recovery; distillation unit; diverter valves; saturated lint from lint baskets; and cartridge filters; and

c) Compliance with Section 215.601(b), (d) and (e) shall be determined by methods or procedures approved by the Agency.

(Source: Adopted at 7 Ill. Reg. 1244, effective January 21, 1983)

Section 215.604 Compliance Dates and Geographical Areas

a) Except as otherwise stated in subsection (b), every owner or operator of an emission source subject to this Subpart shall comply with its standards and limitations in accordance with the following dates:

1) For Section 215.601(a) through (c), by December 31, 1983;

2) For Section 215.601(d) through (g), by May 1, 1983.

b) If an emission source is not located in one of the counties listed below and is also not located in any county contiguous thereto, the owner or operator of the emission source shall comply with the requirements of Sections 215.601 through 215.603 no later than December 31, 1987:

Cook	Macoupin
DuPage	Madison
Kane	Monroe
Lake	Saint Clair

(Board Note: These counties are proposed to be designated as nonattainment by the USEPA at 47 Fed. Reg. 31588, July 21, 1982.)

c) Notwithstanding subsection (b) above, if any county is designated as nonattainment by the