

AMERICAN ASBESTOS TEXTILE CORP.

MAIN OFFICE AND PLANT: 1032 STANBRIDGE ST., NORRISTOWN, PA. 19404

P.O. BOX 228 - PHONE 215-275-4602 - TWX 510-660-0184



MILLS AT:
NORRISTOWN, PA.
MILFORD SQUARE, PA.
MEREDITH, N. H.

Afilato
HILADOS Y TEJIDOS DE ASBESTO S. A.
TOLUCA, MEXICO

November 3, 1972.

Ford Motor Company
3001 Miller Road
Dearborn, Michigan 48121


Attention: Mr. Henry B. Lick
Industrial Hygienist
Industrial Hygiene Section

Gentlemen:

As requested, we are returning herewith your "Environmental Health Data Questionnaire".

Very truly yours,

AMERICAN ASBESTOS TEXTILE CORP.


W. Maaskant

wm:ewm
encl.

8005 0313

SCF-FORD-0907

PRODUCED BY FORD

Please mail completed form to:

Henry B. Lusk
Ford Motor Company
Central Medical Services Building
Industrial Hygiene
3001 Miller Road
Dearborn, Michigan 48121

MATERIAL Asbestos Tape 1/32" thick Underwriters' Grade
 Manufactured by American Asbestos Textile Corp. Questionnaire completed by G.A.
 , date: 11/2/72.

1. List the components by chemical names and the approximate percentage of each:

a) 81% Chrysotile Asbestos

d) _____

b) ~~_____~~

e)

c) 19% Cellulose fiber

1)

2. Toxicity (please list as none, slight, moderate, extreme, or unknown)

Ingestion None

Inhalation None

Absorption None

- A. Source of toxicity data: Not applicable

- B. Any other applicable information available such as standard toxicity forms. Not applicable

3. Irritation (please list as none, slight, moderate, extreme, or unknown)

Eyes	Unknown
------	---------

Skin None

Respiratory tract Moderate, only if airborne concentration is high.

4. Skin sensitizer: Yes ; No ☒ x

5. Estimated threshold limit value OSHA: 5 fibers longer than 5 microns/cc

6. Precautions for normal conditions of use or available standard precautionary forms.
None for normal use.

7. Recommended protective equipment Bureau of Mines approved respirator, such as MSA Dustfoe 66, only if concentration of airborne fibers exceeds 5/cc.

8. Warning properties (odor, irritation to eyes, nose or throat): None

9. First aid and medical procedure for excessive exposures:

External	Not applicable
----------	----------------

Internal	Not applicable
----------	----------------

- ## 10. Properties:

Is material flammable? NO ; explosive? NO

- | | | | |
|------------------|----------------|-------------------------------|---------------------|
| Flash point | Not applicable | Ignition temperature | Approximately 400°F |
| Explosive limits | N.A. | Specific gravity | 2.4 (approx.) |
| Boiling point | N.A. | Vapor pressure mm Hg at 25° C | N.A. |

8005 0314

PRODUCED BY FORD

10. (continued)

- . Vapor density Not applicable
- . pH (state % of solution measured) 9.2. to 9.8
- . If the flash point changes during evaporation, give data: Not applicable
- . Does the material decompose violently when exposed to air? water? heat?
strong oxidizers? No

11. Give procedure in case of breakage or leakage: Not applicable

12. Transportation and storage requirements: Closed containers with OSHA
Caution label.

All data requested on this form is for hazard evaluation purposes only and will be held in confidence as proprietary rights if requested.

FORD MOTOR COMPANY
Industrial Hygiene Unit
Environmental Health Section
Employee Health Services Department

8005 0315

PRODUCED BY FORD