ONE

GALLON

Poise

by O'BRIEN

"TOP QUALITY SINCE 1875"

EGGSHELL

HOUSE PAINT

WHITE

MADE BY THE O'BRIEN CORPORATION

SOUTH BEND, IND. • BALTIMORE, MD. • OKLAHOMA CITY, OKLA. • SAN FRANCISCO, CAL. • LOS ANGELES, CAL.

49 TOC 001669

POISE
EGGSHELL HOUSE PAINT

Poise Eggshell House Paint is a high quality, economy-priced outside paint with a pleasing low lustre. It is an all-purpose type finish for most surfaces—wood siding, wood and **unglazed** asbestos shingles, stucco, concrete, masonry (see ***CAUTION**), metal and trim. Available in White or Tinting White. Tinting White is a non-chalking finish for body or trim that may be tinted with Tone-All, with Oil Colors, or applied straight.

DIRECTIONS

Preparation—Surface must be clean and dry. Remove chalk and loose paint. Where moisture is present, ventilate behind siding. Repair flashings and structural defects.

Previously Painted Wood Shingles

Apply one coat of Poise Eggshell House Paint, thinned with one pint of linseed oil per gallon.

New Wood — Clapboard, Plywood, Masonite, Trim

Apply one coat of White Crest House Paint Primer White, thinned with two or three pints of linseed oil per gallon. Tint toward finish color. Finish with Poise Eggshell House Paint applied at package consistency.

Previously Painted Surfaces — Wood, Metal, Concrete, Masonry, Asbestos-Cement

Apply one coat of Poise Eggshell House Paint at package consistency. (Over badly weathered surfaces, prime first with White Crest House Paint Primer White at package consistency. Tint toward finish color.)

New Concrete, Masonry and Asbestos-Cement*

Apply one coat O'Brien A-R Primer. Tint toward finish color with Tone-All. Finish with Poise Eggshell House Paint applied at package consistency.

REGISTERED
REG. NO. 23736
DATE 4-9-63

New Metal

Apply one coat of Tame Rust Metal Primer. Etch galvanized metal, such as gutters and downspouts, before priming. Finish with Poise Eggshell House Paint applied at package consistency.

Application—Apply Poise Eggshell House Paint by brush or spray at temperature not less than 60° F. Allow 48 hours good drying weather between coats. When necessary, thin **sparingly** with mineral spirits. Stir well before and during use.

Tinting—Do not use more than 4 ounces of Tone-All Colorant per gallon.

***CAUTION:** New masonry should be thoroughly dry before painting. Do not paint glazed type asbestos shingles! Do not paint chronically damp masonry.

DO NOT TAKE INTERNALLY

CAUTION! COMBUSTIBLE! CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat and open flame. Do not apply on window sills, toys, furniture or interior surfaces of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. KEEP OUT OF THE REACH OF CHILDREN.

POISE EGGSHELL HOUSE PAINT WHITE

Titanium Dioxide	16.94%
18% Leaded Zinc Oxide	14.90%
Silicates	18.73%
Heat Treated Linseed Oil	15.35%
Raw Linseed Oil	6.52%
Aromatic Hydrocarbons	4.31%
Mineral Spirits and Driers	23.25%
	100.00%

49 TOC 001670