

BRAKE SHOE SPECIFICATIONS

APPLICATION SECTION 39
TRUCK

MODEL	LOC.	AXLE CAPACITY	BRAKE SIZE	AIR or HYD.	SHOE & LINING PART NUMBER	
					PRIMARY	SECONDARY
TRUCK						
1972 - continued						
L-LN SERIES						
L-LN600/800	F	6M, 6.5M, 6M	14" x 3 1/2"	H	C8TZ 2018-A	C8TZ 2018-A
L800/900, LN600/900	F	6M, 7M	15" x 3"	H	D1TZ 2018-A	D1TZ 2018-A
L800/900, LN600/900	F	9M, 12M	15" x 3"	H	C8TZ 2018-C	C8TZ 2018-C
L800/900, LN600/900	F	6M, 7M, 9M	15" x 3"	A	C5TZ 2018-E	C5TZ 2018-C
L800/900, LN700/900 (Bendix)	F	9M, (12M w/o C/P/B)	15" x 3 1/2"	A	C5TZ 2018-F	C5TZ 2018-D
L800/900, LN700/900-Rockwell (Timken)	F	12M with C/P/B	15" x 3 1/2"	A	C5TZ 2018-B	C5TZ 2018-B
L-LN600/900	F	6M, 7M	16" x 2 1/2"	A	C8TZ 2018-B	C6TZ 2018-B
L800/900, LN700/900	F	9M, (12M w/o C/P/B)	16 1/4" x 3 1/2"	A	C1TT 2018-E	C1TT 2018-E
L800/900, LN700/900	F	12M with C/P/B	16 1/4" x 3 1/2"	A	DOHZ 2018-A	DOHZ 2018-A
LN800 (Kelsey)	R	15M	15" x 6"	H	C8TZ 2218-C	C8TZ 2218-C
L800, LN600/800 (Kelsey)	R	17.5M	15" x 6"	H	C8TZ 2218-D	C8TZ 2218-D
L800, LN600/800 (Wagner)	R	15M, 17.5M	15" x 5"	H	C5TZ 2218-B	C5TZ 2218-B
L800, LN600/800	R	17.5M	15" x 6"	A	C5TZ 2218-F	C5TZ 2218-F
L800, LN600/800	R	17.5M	15" x 6"	H	C8TZ 2218-J	C8TZ 2218-J
L800/900, LN700/900	R	18.5M	15" x 6"	H	C8TZ 2218-G	C8TZ 2218-G
L-LN600/900	R	17.5M, 18.5M	15" x 6"	A	C5TZ 2218-G	C5TZ 2218-G
L800/900, LN700/900	R	18.5M	15" x 7"	H	C8TZ 2218-H	C8TZ 2218-H
L-LN700/900	R	18.5M	15" x 7"	A	C5TZ 2218-B	C5TZ 2218-H
L-LN800/900	R	22M, 23M	15" x 7"	A	C5TZ 2218-J	C5TZ 2218-J
L800/900, LN800	R	22M	16" x 6"	H	C8TZ 2218-F	C8TZ 2218-F
L-LN800/800 (Eaton)	R	17.5M	16 1/2" x 4 1/2"	A	C8TZ 2218-A	C8TZ 2218-A
L-LN800/800-Rockwell (Timken)	R	17.5M	16 1/2" x 4 1/2"	A	C8TZ 2218-D	C6TZ 2218-A
L-LN700/900 (Eaton)	R	18.5M, 22M, 23M	16 1/2" x 7"	A	C1TZ 2218-C	C1TZ 2218-C
L-LN700/900-Rockwell (Timken)	R	18.5M, 22M, 23M	16 1/2" x 7"	A	C1TT 2218-A	C1TT 2218-A

CONTINUED ON NEXT PAGE

F-front R-rear

NOTE 1. - 3001 or 3100 kit contains 3 primary, 3 secondary shoe and lining assys.

6003 0637

PRODUCED BY FORD