

Volume 34, Number 5

Contents for NOVEMBER, 1936

President's Address—Cassius H. Watson, M.D.	11
New Rules for the Game of Life—Hon. Harold G. Hoffman	13
Planning Safety for Tomorrow's Railroads—Ralph Budd	14
New Jersey Salutes Safety—Carman T. Fish	16
Officers of the National Safety Council, 1936-37	20
Occupation Study Is Safety's Partner—William R. Mullee	22
Detroit's Drive for Safer Driving—C. F. Scheer	25
Safe Handling Means Fewer Injuries—P. H. Hunter	27
Hard at the Congress	30
Hunting We Will Go!	32
Never Known Facts About Occupational Diseases— Robert B. Hunt, M.D.	34
Silicon—Industrial Data Sheet D-Chem. 20	38
Do You See It at the Exhibit?—C. H. Miller	52
Why Winners in Sectional Contests	58
National Officers	62

REGULAR DEPARTMENTS

Editorial	9	The Safety Library	64
Managing Director's Page	10	Asked and Answered	66
Safety Exchange	31	Personals	73
Industrial Health	34	Coming Events	77
Bulletin Board	40	The Honor Roll	89
Instruction Cards	48	With the Manufacturer	90

N. T. FISH, Editor
J. P. ERSKAW, Poster Editor

C. F. SCHEER, Associate Editor
C. H. MILLER, Advertising Manager

November, 1936 by National Safety Council,
435 N. W. R. A. Entered as second-class matter
21, at the Post Office at Chicago, Ill., under
March 1, 1919. Additional entry at St. Joseph,

to members for extra subscriptions to the
SAFETY NEWS is \$4.00 per year. Single
copies reduced quantity prices for yearly sub-

scriptions and single copies on request. Subscriptions are
available only to members of the National Safety Council.
Member Audit Bureau of Circulation.

This magazine is indexed in the Industrial Arts Index.
Statements and opinions advanced in signed articles are
individual expressions of their authors, not those of the
National Safety Council.

15,700 copies of this issue were printed.



National Safety Council, Inc.

70 North Wacker Drive, Chicago, Ill. U. S. A.

National Safety Council Officers, 1936-37

CASSIUS H. WATSON, M. D. President
D. D. FENNELL, Vice-President for Pub-
lic Relations
HARRY F. FISHER, M. D., Vice-President
for Health
JOHN B. GIBSON, Vice-President for
Safety Councils
HON. HAROLD G. HOFFMAN, Vice-Presi-
dent for Public Safety
ALBERT S. REGULA, Vice-President for
Engineering
A. V. ROMWEN, Vice-President for In-
dustrial Safety
R. T. SOLENTON, Vice-President for
Membership
ALBERT W. WHITNEY, Vice-President for
Education
WILLIAM E. WORTH, Vice-President for
Finance and Treasurer
W. H. CAMERON, Managing Director

Executive Committee Members at Large

THE ABOVE OFFICERS AND:
HAROLD S. BUTTENHEIM, The American
City
HARRY GUILBERT, The Pullman Co.
and Safety Co.
HARRY GUILBERT, The Pullman Co.
WILLIAM C. KNOX, Milwaukee Safety
Commission
EDWARD J. MERRIN, Portland Cement
Assoc.
I. W. MILLARD, Industrial Gloves Corp.
HAROLD L. MINER, E. I. duPont de Ne-
mours & Co.
GEORGE E. SANFORD, General Electric Co.
C. W. SMITH, Standard Oil Co. (Ind.)

Safety Council Representatives

ROBERT R. WALLACE, Worcester Safety
Council
WALTER DEWITT SMITH, Delaware Safety
Council
CARL L. SMITH, Cleveland Safety Council
E. J. O'BRIEN, Jr., Louisville Safety
Council
R. B. FORTUM, Lehigh Valley Safety
Council
W. J. MELVILLE, Chippewa County Safety
Council

Sectional Representatives

GEORGE J. ADAMS, Paper and Pulp
C. M. ALLEN, Metals
C. W. DEMPSEY, Food
C. W. GIBBS, Mining
E. C. HOLDEN, Jr., Marine
HARRY J. KELLEY, Wood Products
D. L. ROYER, ASSE-Engineering

Past Presidents

ROBERT W. CAMPBELL
LEW R. PALMER
CHARLES P. TOLMAN
ARTHUR H. YOUNG
NABUCCO A. DOW
LEWIS A. DILLON
CARL R. AUEL
CHARLES H. SCOTT
WALTER G. KING
LT.-COL. HENRY A. BENNINGER
C. EUGENE PETTIBONE
CARL W. HERQVIST
JAMES I. HAMASH
JOHN E. LONG

Honorary Members

ROBERT W. CAMPBELL LEW R. PALMER

PLAINTIFF'S
EXHIBIT

G-357

Industrial Health

Poisoning, Infection, etc. A Department for Physicians and Laymen

Lesser Known Facts About Occupational Diseases

By ROBERT B. HUNT, M.D.

American Mutual Liability Insurance Company

PROBABLY the leader in the parade of industrial diseases is an acute or chronic inflammation of the skin which we call dermatitis. This disease may present itself in any type of shop, factory or foundry. Any paste, powder, gas or liquid which comes in contact with the employee's skin, even the water supplied by the town in which he lives or works, may be the potential cause of such a skin disturbance.

The wide diversity of causes, together with the varying susceptibility of different individuals, makes the problem of control difficult.

Much investigation is under way to determine why one person may be susceptible to a certain substance while another is not. It has been proved many times that a poisonous substance formed within the body has been able to prolong the action started by some external influence. A printer developed a marked dermatitis from ink which persisted for two years. Finally food tests were made and showed that he was susceptible to lettuce. Removing this from his diet cleared the skin. He returned to his usual occupation without a return of symptoms.

The poisoning of allergic substances is usually an accumulative process. It takes time to produce a manifestation of disease, but let any other substance cause the disease, and the irritating food may be of sufficient strength to magnify its action.

All cases of dermatitis cannot be cured by eliminating offending foods, but further investigation along these lines may give us a clue with which to

the discomfort now produced by industrial dermatitis.

Metals

LEAD: The distribution of lead poisoning is quite extensive.

The skin of the body is a protective covering, and as long as it remains intact it does a good job except in the case of tetraethyl lead, which is used in blending gasoline and which is readily absorbed through the skin, having a tendency to create changes in the nervous system. The effect of other forms of lead, through that avenue of entrance, is practically nil, which explains the extremely low poisoning rate in typesetters, painters and others who continually come in contact with metallic lead.

Lead in any form, introduced through the mouth, acts rather slowly when compared with the inhalation of lead dust or fumes. However, no matter what the portal of entry may be, lead is acted upon by the body fluids and so converted that it may eventually be deposited within the bones.

Those bony safe deposit vaults may retain their lead contents for days or for years, and if the exposure is removed, may also free the employee of all signs and symptoms of lead poisoning. But imagine the surprise of that supposedly cured person when years later, perhaps following some type of infectious disease or the excessive use of alcoholic beverages, he awakes to find that he suffers the aches and pains and paralyses of an acute lead poisoning. As the body fluids alter lead that it may be deposited, so may those fluids attempt to de-

duce the original disease with all its discomforts.

One can readily see, then, that in some cases investigation of previous occupations is quite necessary to determine the original contact with lead.

Heating of molten lead causes a black scum of lead suboxide to form on its surface, and the heat from the metal disbursts the fine powder into the air. Hence, in the process of smelting ores such as zinc, copper and silver, mixed with lead, we find a rather high lead poisoning rate.

Those engaged in the manufacture of lead wire and cables, batteries, glass, pottery and rubber industries, plumbers and users of dry colors offer their share of lead poisoning cases.

Probably the greatest source of lead poisoning may be found among those who sandpaper, scrape, chip or burn lead paint, for the dust and fumes caused by those activities are rather rapid in their action. Such workers may become incapacitated in a few days because the inhalation of lead dust causes the maximum amount of absorption into the blood stream in the minimum space of time.

CHROMIUM: Chromium is a metal widely used as a foundation for colors, and dusts from its various salts may produce lesions of the skin and mucous membranes of the nose. Chromium plating by electrolysis may cause fumes which are similarly irritating. Although chromium poisoning does not usually cause death, the number of days of absence from work on account of incapacity which it causes is gradually increasing.

OTHER METALS: The most efficient portals of entry of foreign substances into the body are the nose and mouth. The smaller the dust (the size of smoke particles for example, the greater the speed of absorption by the blood. Fumes from hot metals carry not only poison-

electric cutting and welding.

When men are so employed over a prolonged period of time, the constant inhalation of fumes and dust might produce symptoms of the metal upon which they work. In the shipbuilding trade, particularly in the construction of metal ships, we find occasional cases of metal-fume fever. "Brass chills" and "spelter shakes" from zinc are names applied by the lay people to such diseases. The terrific heat applied to some of our common metals and alloys by acetylene torches produces sufficient fumes to cause a temporary incapacity in 24 hours. Permanent disability from such causes is rare, however.

Diseases Due to Dust

Twenty-five per cent of all workers exposed to high concentrations of inorganic dust are expected to develop changes within their lungs due to that agency. We are at a loss to explain why the other 75 per cent are not so affected.

Mining, quarrying, foundry work, grinding, sandblasting, abrasive soap manufacturing, asbestos work, the making of emery and carborundum products and many other occupations offer opportunities for employees to inhale microscopic dust particles and create a foundation for possible future incapacity.

We are interested particularly in those men who work with sandstone, quartz, flint, granite, and sand, because they expose themselves to silica, and the chemical changes between that dust and the body fluids, in the presence of tuberculosis, may and usually do lead to a fatal ending.

It is safe to say, in light of our present knowledge, that the action of other inorganic dusts is much less virulent and incapacitating. That, however, does not allow us to lower the vigilant methods to improve dust control and protect employees, because all dusty occupations are potential trouble makers.

Although the actions of various dusts differ within the body, the exposure to asbestos fibres, present in the weaving and grinding of dry asbestos material, offers another type of dust which may cause fatalities among workers.

The organic dusts from cotton, silk, wool, tobacco, flour and similar substances are practically harmless. Such dusts rarely reach the lungs but may cause irritation of the windpipe and larger air tubes and result at the most in

mind, particularly when dealing with silicosis and asbestosis, relates to the progression of such disease. When changes occur within the lungs as a result of the presence of such dusts, nature forms scar tissue to heal such lesions but may fail to stop when the job is finished. As a result, the continuation of that healing process may lead to such structural changes within the lungs that partial or total incapacity may follow months or years after the employee has been removed from his dusty occupation.

Benzol-Benzene

Benzol is a distillate of coal tar used extensively in industry. It is an essential ingredient in the manufacture of explosives. It is an excellent solvent for grease, oils and cements, and because of that property it is important in many phases of the rubber and cleaning industries. In the manufacture of shoes benzol may be an ingredient of the dressing applied to the leather and of the cement which fastens the heels and soles. Not only in the shoe trade but in other branches of industry where employees work with gummy, sticky material, the workers soon learn of the solvent and cleansing action of this liquid and use it freely for that purpose upon themselves. The subsequent outbreak of skin afflictions may be the first indication of such unauthorized use.

Benzol is extremely poisonous, entering either through the nose or mouth or absorbed through the skin. Its action within the body is varied and may produce a multitude of signs and symptoms. The bone marrow becomes affected which in turn alters the character of the blood; hemorrhages are common; it may cause death.

The fumes from benzol are heavier than air and lie near the floor, which is an important point in the engineering problem of ventilation.

The members of the benzene group are absorbed through the skin, and more cases of poisoning are found when men perspire than when their bodies are cool. Probably the answer to that is that the fumes may solidify as they cool and the powder may settle on the skin. The sweat on the body may dissolve this dust so that it is more readily absorbed through the increased surface blood supply.

Chlorinated Hydrocarbons

This group of petroleum derivatives

the industrial field has been widely distributed and most important. Led by carbon tetrachloride and its chemically associated members, it has furnished industry with refrigerants, excellent solvents for rubber, wax, oil and grease, thinners for lacquers and a very fine household necessity for the removal of spots from clothes. Hospitals have been using it more and more for the removal of adhesive plaster.

Due to the non-flammability of carbon tetrachloride, it is used in fire extinguishers. The rapid evaporation produces fumes which may smother a small blaze, but we must not forget that excessive heat of the actual fire may bring about combustion sufficient to produce such by-products as hydrochloric acid and phosgene gas. Like its associated member, chloroform, it may produce sleep when inhaled by an individual, and only 1/350 of an ounce in a quart of air is necessary to produce such action. That thought must be remembered when a large quantity of those liquid products is spilled on the floor, perhaps accidentally. Action should be started at once before the liquid gasifies, and employees should be notified to keep their heads up to avoid the low ceiling of gas.

Chemists have developed and introduced to industry many new products, the basis of which is the chlorinated hydrocarbons. These derivatives of petroleum distillation are frequently combined with those from coal tar to form valuable chemical combinations. They have been placed on the market so rapidly that medical science has been unable to determine their physiological effect upon the health of man. We have known that some of these chemicals are capable of creating changes in the liver, and only recently in a city in Massachusetts one of these newer products caused the death of two employees and a battle to retain life among two others.

Carbon Monoxide

You remember the adage. "Where there is smoke, there is fire." We might add to that, "Where there is fire there is carbon monoxide."

This odorless but poisonous gas may occur in any industry or in any home, but the poorer the ventilation the better the chance of producing physical incapacity.

Since the advent of the motor car whose exhaust pipe may pour forth as high as six per cent of carbon monoxide we are all exposed to that gas.

Any passenger car liberates about two cubic feet per minute, and one can readily estimate the physical damage that may be done if such a motor is allowed to run within the doors of a poorly ventilated garage or shop. Fortunately, serious cases of such poisoning are not common among those employed in public garages, but many employees are likely to complain of headache and faintness at the end of a day's work, especially in colder weather when doors and windows remain closed.

In the steel industry, where gas is used as the heating agency in the blast furnaces, care must be taken to provide proper ventilation. Within the mines, workers are warned to allow enough time following blasts for the escape of this gas.

Infection

The skin is a protective covering of the body against infection and is extremely efficient as long as it remains intact, but allowing it to be broken or punctured introduces bacteria, and a battle ensues between the offensive agencies of infection and the defensive powers of the body. The winner of such a struggle may determine the presence or absence of incapacity. Infections are common throughout industry, but two types are particularly prominent—infection resulting from anthrax and infection among meat packers and fishermen.

Many of our fur, hair or wool-covered animals may contract anthrax. The germs of that disease defy the ordinary methods of sterilization and may linger on hides, bristles or hairs for long periods of time. Tanners, wool sorters, and hair or bristle workers may introduce the anthrax spore beneath their skin and undergo much physical suffering and sometimes death.

Infections are frequently found among meat and fish packers and those engaged in deep sea fishing. Although death rarely occurs, the loss of fingers, hands and nasty septic wounds are the result.

Summary

I feel that the time has come when an employer must demand of a manufacturer the answers to two questions:

1. How will your product affect my business?
2. How will your product affect the health of my employees?

That employer is entitled to honest answers based upon sufficient chemical and physiological examinations of the questionable product. Too many lives have been lost or jeopardized by too little knowledge of a product's action

Ferrosilicon

Industrial Data Sheet D-Chem. 20

A. Problem

1. What are the hazards of ferrosilicon and what precautions are necessary in its use?

B. Hazards

2. The principal hazard is that of poisoning by inhalation of the gases that may be given off, especially in the presence of moisture.

C. Discussion

3. Ferrosilicon is prepared by melting iron ore or steel shavings with coal or coke and ganister or quartz at a temperature of about 2,000 degrees centigrade (3,632 degrees Fahrenheit) in an electric furnace. In making steel, ferrosilicon is used for removing objectionable gases and oxides and also as an alloying element. When alloyed with cast iron, it affects the carbides and renders the iron soft and gray. More concentrated silicon alloys are sometimes used in certain processes for making hydrogen gas and in the manufacture of explosives.

4. The hazard in connection with ferrosilicon results from very small percentages of phosphorus together with other elements which may be present as impurities originating in the raw materials used. In the presence of moisture the phosphorus compounds react to form phosphoreted hydrogen or phosphine. This is a gas which in sufficient quantities is decidedly poisonous. It has a strong and distinctive odor somewhat resembling garlic so that its presence can be readily recognized. The stability of ferrosilicon depends upon its silicon content, grades below 48 percent and above 65 percent being entirely stable and ferrosilicon in these ranges does not give off any appreciable quantities of phosphine, even in the presence of moisture. It is, therefore, only in the intermediate range between 48 percent and 65 percent that there is any appreciable hazard.

Symptoms of Poisoning

5. When a person has breathed poisonous gases liberated from ferrosilicon, the symptoms of poisoning usually de-

velop by general and abdominal pains, nausea, vomiting, diarrhea, hemorrhages, loss of consciousness, dilated pupils, cold clammy perspiration and coma. Cases of poisoning have been mistaken for cholera, gastro-enteritis, ptomaine poisoning, pneumonia and influenza.

First Aid

6. When a person displays any symptoms of poisoning because of the inhalation of the poisonous gases liberated by ferrosilicon, he should be promptly removed to the fresh air and, if conscious, be given a mild alkali drink. If unconscious, the prone pressure method of artificial respiration should be started immediately after the patient has been removed to the fresh air. In all cases of poisoning the services of a doctor should be promptly obtained.

Precautions

7. Ferrosilicon should be stored away from such places as offices and work rooms or living quarters of any description.

8. All buildings in which ferrosilicon is stored should be well ventilated and dry. (See Note X.) Ordinarily, in an open factory building the natural ventilation through monitors in the roof or through windows is sufficient if the ferrosilicon is kept dry.

9. If men are required to handle wet ferrosilicon in a confined space, artificial ventilation should be provided.

10. In case phosphine has been allowed to accumulate in a closely confined space such as a closed room or box-car, so that a strong odor of the gas is noticeable, no one, unless he is wearing a suitable gas mask or fresh air hose mask, should be allowed to enter the room until it has been thoroughly ventilated. (See Note Y.)

NOTE X. Detailed information on ventilation will be found in National Safety Council Safe Practices Pamphlet No. 37 "Industrial Ventilation."

NOTE Y. Detailed information on fresh air hose masks will be found in National Safety Council Safe Practices Pamphlet No. 64 "Respirators, Gas Masks, Hose Masks and Breathing Apparatus."

National Safety Council, Inc.

20 North Wacker Drive

Chicago, Ill.

Occupational Diseases

PLAINTIFF'S

EXHIBIT

3830

PENGAD-Bryant, N. J.

FRIDAY MORNING SESSION

October 9, 1936

The session was called to order by the chairman, Dr. Hart E. Fisher, Vice-President for Health, National Safety Council,

and Chief Surgeon, Chicago Rapid Transit Co., Chicago, who presided, introducing the speakers.

The Lesser Known Facts About Common Occupational Diseases

By DR. ROBERT B. HUNT

Medical Advisor, American Mutual Liability Insurance Co., Boston

Probably the leader in the parade of industrial diseases is an acute or chronic inflammation of the skin which we call dermatitis. This disease may present itself in any type of shop, factory or foundry. Any paste, powder, gas or liquid which comes in contact with the employee's skin, even the water supplied by the town in which he lives or works, may be the potential cause of such a skin disturbance.

The wide diversity of causes together with the varying susceptibility of different individuals makes the problem of control difficult.

Much investigation is under way to determine why one person may be susceptible to a certain substance while another is not. It has been proved many times that a poisonous substance formed within the body has been able to prolong the action started by some external influence. A printer developed a marked dermatitis from ink which persisted for two years. Finally food tests were made and showed that he was susceptible to lettuce, which, when removed from his diet cleared the skin. He returned to his usual occupation without a return of symptoms.

The poisoning of allergic substances is usually an accumulative process. It takes time to produce a manifestation of disease, but let any other substance cause the disease, and the irritating food may be of sufficient strength to magnify its action.

All cases of dermatitis cannot be cured by eliminating offending foods, but further investigation along these lines may give us a clue with which to lessen the loss of time from work and the discomfort now produced by industrial dermatitis.

Metals

Lead

The distribution of lead poisoning is quite extensive.

The skin of the body is a protective covering, and as long as it remains intact it does a good job except in the case of tetraethyl lead, which is used in blending gasoline and which is readily absorbed through the skin, having a tendency to create changes in the nervous system. The effect of other forms of lead, through that avenue of entrance, is practically nil, which explains the extremely low poisoning rate in typesetters, painters and others who continually come in contact with metallic lead.

Lead in any form, introduced through the mouth, acts rather slowly when compared with the inhalation of lead dust or fumes. However, no matter what the portal of entry may be, lead is acted upon by the body fluids and so converted that it may eventually be deposited within the bones.

Those bony safe deposit vaults may retain their lead contents for days or for years, and if the exposure is removed, may also free the employee of all signs

symptoms of lead poisoning. But the surprise of that supposedly person when years later, perhaps from some type of infectious disease, excessive use of alcoholic beverages awakes to find that he suffers from pains and paralysis of an old poisoning. As the body fluids flow that it may be deposited, so these fluids attempt to de-lead the old too rapid absorption may produce original disease with all its dis-

an readily see, then, that in some investigation of previous occupations necessary to determine the contact with lead.

ing of molten lead causes a black lead suboxide to form on its surface the heat from the metal dis-

he fine powder into the air. in the process of smelting ores zinc, copper and silver, mixed d, we find a rather high lead rate.

engaged in the manufacture of e and cables, batteries, glass, and rubber industries, plumbers and of dry colors offer their share poisoning.

by the greatest source of lead may be found among those paper, scraps, chip or burn lead the dust and fumes caused by activities are rather rapid in their such workers may become in-

d in a few days because the of lead dust causes the maxi- unit of absorption into the blood the minimum space of time.

Although the actions of various dusts differ within the body, the exposure to asbestos fibres, present in the weaving and grinding of dry asbestos material, offers another type of dust which may cause fatalities among workers.

The organic dusts from cotton, silk, wool, tobacco, flour and similar substances are practically harmless. Such dusts rarely reach the lungs but may cause irritation of the windpipe and larger air tubes and result at the most in a mild bronchitis.

The factor which should be borne in mind, particularly when dealing with silicosis and asbestosis, relates to the progression of such disease. When changes occur within the lungs as a result of the presence of such dusts, nature forms scar tissue to heal such lesions but may fail to stop when the job is finished. As a result, the continuation of that healing process may lead to such structural changes within the lungs that partial or total incapacity may follow months or years after the employee has been removed from his dusty occupation.

Diseases Due to Dust

Twenty-five per cent of all workers exposed to high concentrations of inorganic dust are expected to develop changes within their lungs due to that agency. We are at a loss to explain why the other seventy-five per cent are not so affected.

Mining, quarrying, foundry work, grinding, sandblasting, abrasive soap manufacturing, asbestos work, the making of emery and carborundum products and many other occupations offer opportunities for employees to inhale microscopic dust particles and create a foundation for possible future incapacity.

We are interested particularly in those men who work with sandstone, quartz, flint, granite, and sand, because they expose themselves to silica, and the chemical changes between that dust and the body fluids, in the presence of tuberculosis, may and usually do lead to a fatal ending.

It is safe to say, in light of our present knowledge, that the action of other inorganic dusts is much less virulent and incapacitating. That, however, does not allow us to lower the vigilant methods to improve dust control and protect employees, because all dusty occupations are potential trouble makers.

hemorrhages are common; it may cause death.

The fumes from benzol are heavier than air and lie near the floor, which is an important point in the engineering problem of ventilation.

The members of the benzene group are absorbed through the skin, and more cases of poisoning are found when men perspire than when their bodies are cool. Probably the answer to that is that the fumes may solidify as they cool and the powder may settle on the skin. The sweat on the body may dissolve this dust so that it is more readily absorbed through the increased surface blood supply.

Chlorinated Hydrocarbons

This group of petroleum derivatives has been known to science for years but during the past decade its advance into the industrial field has been widely distributed and most important, led by carbon tetrachloride and its chemically associated members, it has furnished industry with refrigerants for ice chests, excellent solvents for rubber, wax, oil and grease, thinners for lacquers and a very fine household necessity for the removal of spots from clothes. Hospitals have been using it more and more for the removal of adhesive plaster.

Due to the non-flammability of carbon tetrachloride, it is used in fire extinguishers. The rapid evaporation produces fumes which may smother a small blaze, but we must not forget that excessive heat of the actual fire may bring about combustion sufficient to produce such biproducts as hydrochloric acid and phosgene gas. Like its associated members, chloroform, it may produce sleep when inhaled by an individual, and only 1/350 of an ounce in a quart of air is necessary to produce such action. That thought must be remembered when a large quantity of those liquid products is spilled on the floor, perhaps accidentally. Action should be started at once before the liquid gasifies, and employees should be notified to keep their heads up to avoid the low ceiling of gas.

Chemists have developed and introduced to industry many new products, the basis of which is the chlorinated hydrocarbons. These derivatives of petro-

is a metal widely used as a for colors, and dusts from its its may produce lesions of the mucous membranes of the nose. plating by electrolysis may es which are similarly irritat- ough chromium poisoning does y cause death, the number of y cause from work on account ity which it causes is gradu- sing.

it efficient portals of entry of 'stances into the body are the

distillation are frequently combined those from coal tar to form valuable chemical combinations. They have placed on the market so rapidly that medical science has been unable to mine their physiological effect upon health of man. We have known that of these chemicals are capable of making changes in the liver, and only in a city in Massachusetts one new product caused the death of employees and a battle to retain among two others.

Carbon Monoxide

I remember the adage, "Where is smoke, there is fire." We might say that, "Where there is fire there is a monoxide."

odorless but poisonous gas may be in any industry or in any home, but under the ventilation the better the of producing physical incapacity. The advent of the motor car, exhaust pipe may pour forth as much as 6% of carbon monoxide, we are exposed to that gas, particularly in cities. The ordinary passenger carries about two cubic feet per minute, and one can readily estimate the damage that may be done if a motor is allowed to run within the of a poorly ventilated garage or. Fortunately, serious cases of such poisoning are not common among those in public garages, but many of employees are likely to complain of lache and faintness at the end of a work, especially in colder weather floors and windows remain closed. In steel industry, where gas is used heating agency in the blast furnace must be used to provide ventilation. Within the mines, workers are warned to allow enough time for blasts for the escape of this

a colorless, odorless and tasteless, quick of action within the human system may be too late to save a man from partial or total incapacity or death.

Since the exposed person suffers from motor paralysis, he may be helped to help himself or even to warn

others of the danger. Even if removed from the poisonous gas at that period, the damage actually done by the gas may result in permanent physical damage.

Infection

The skin is a protective covering of the body against infection and is extremely efficient as long as it remains intact, but allow it to be broken or punctured, introduce bacteria, and a battle ensues between the offensive agencies of infection and the defensive powers of the body. The winning of such a struggle may determine the presence or absence of incapacity. Infections are common throughout industry, but two types are particularly prominent—infection resulting from anthrax and infection among meat packers and fishermen.

Many of our fur, hair or wool-covered animals may contract anthrax. The germs of that disease defy the ordinary methods of sterilization and may linger on hides, bristles or hairs for long periods of time. Tanners, wool sorters, and hair or bristle workers may introduce the anthrax spore beneath their skin and undergo much physical suffering and sometimes death.

Infections are frequently found among meat and fish packers and those engaged in deep sea fishing. Although death rarely occurs, the loss of fingers, hands and nasty septic wounds are the result.

Punctured wounds, cuts, abrasions, burns and scratches are potential avenues of entrance for bacteria which would seem to be waiting everywhere at all times for such a break in the skin. Early medical treatment might often save later surgical interference, not to mention the accompanying discomfort, incapacity and perhaps the loss of an essential body part.

Summary

I feel that the time has come when an employer must demand of a manufacturer the answers to two questions:

1. How will your product affect my business?
2. How will your product affect the health of my employees?

That employer is entitled to honest answers based upon sufficient chemical and physiological examinations of the questionable product. That manufacturer

should be held responsible for the ills produced by the use of his product and unless he can guarantee its safety, it has no place in industry. Too many lives have been lost or jeopardized by too little knowledge of a product's action upon those who handle it.

The incidence of lost time due to illness and injury in industry has been greatly lessened by the many agencies working along lines of safety. When in-

dustry has been made fool-proof by the substitution of non-toxic preparations for those now found to be harmful, and when each employee is imbued with the idea that constant thoughtfulness and care are most necessary for the maintenance of health and happiness, then, and not until that idealistic stage has been reached may vigilance and perseverance to maintain and preserve health, limb and life be lessened.

Pre-Employment Examination as an Aid to the Control of Industrial Diseases

By DR. W. C. TEMPLER

Medical Director, Corning Glass Works, Corning, N. Y.

We may well ask whether or not physical examination is of any value to the world at large, rather than limit the discussion to the control of industrial diseases. In the conservation of life and health much progress has been made in the eradication or control of such diseases as occur in epidemic form, as well as that type of disease which is not truly epidemic, but occurs in such frequency that general health programs are necessary. Much has been done to control such disabling illnesses as heart disease, arterio-sclerosis, kidney disease and diabetes; and something has been accomplished in the control of morbidity, which tends to, at least, make people happier through good health, even though an increased span of life is not gained.

Physical examination has played a large role in accomplishing these things, because it was through physical examination and physical observations that investigators were led to exert themselves to find a remedy for the cause of such conditions. Small-pox is no longer prevalent, due to such observations, which led to its control by vaccination. Malaria and yellow fever have been brought largely under control, and knowledge is now available in the control of venereal diseases, if the proper physical examination and laboratory methods are used to arrive at a diagnosis. We are all familiar with the results obtained in decreasing the

death rate due to tuberculosis. In fact, in the treatment of all epidemic-type diseases that have so far been eradicated, the examination of patients to determine the severity of symptoms and the improvement has been of foremost value.

Knowing that the average span of life has been increased eight years in the last quarter century and assuming that the above mentioned factors have had some bearing on it, could we decree the value of physical examinations for the general population?

If we know that examinations made by insurance companies and their associating examining institutions, the clinics run by the United States Public Health Service, and the great mass of physicians, who all carefully examine their clientele, have been of value in the control of disease, may we not assume that examinations in industry will help control the incidence and extent of industrial disease, particularly when the life expectancy of industrial workers is less than that of the general population?

In fact on April 14, 1936, at the National Conference on Silicosis and Similar Dust Diseases, called by the Secretary of Labor, Dr. R. R. Sayers of the United States Public Health Service said, "Pre-employment and periodic physical and neurological examination should be made of all employees engaged in industrial processes where there is a potential in-

tual exposure to excessive concentration of silica in the atmosphere." usually in the early work of industry, basic materials were used, ingredients arrived at a state of development complexity, when intricate chemical compounds and other toxic materials were known of, much less used. At the time over 500 materials are listed in, under certain conditions, cause disease and the list is by no means complete, inasmuch as experimental work is being done by the personnel of every plant or industry to improve or enlarge its manufactured products and advantage of the great amount of knowledge science has given us.

First, the pre-employment examination, which consists of a very elementary, not only of the family, but of the previous occupations with service in each, previous health history is of no value unless truthfulness and a reasonable amount of must be taken to acquire details, are often vague in a workman's considered by him to be unimportant.

The physical examination, of varies with the type of industry, would be given with the knowledge by a physician familiar with the processes in which he is to be employed. In this way selected employees can be obtained for men who have basic disqualification for one job, which does not impair their ability of employment and the conserving in another.

Physical examination must be h. It should include all methods, including a latent disability or one already present. Many examinations are available from insurance companies or other health services, which are designed entirely for industrial use. It has been the experience of men in this work, that all the special of the body must be tested as well as measurement of motion in all joints. Cardio-vascular system is of great importance as is the respiratory and intestinal tract.

Examination and periodical checks, of particular industrial hazards,

must be correlated as to time spent in the hazard, although a period of one year is, perhaps, proper for persons who feel in good health and have no complaints, or who are not working in toxic substances or with other materials which would under some conditions impair their health and usefulness.

The objectives of pre-employment and post-employment examinations are the same, that is: the establishment of a physical standard in which the employee can pursue his trade or labor, having no discomfort or ill effect due to industrial exposure to harmful products. Such products and materials are, as we have mentioned, of great number and variety. Attempts have been made to classify workmen as to age, sex, color and nationality. Whether or not any of these classifications are of value, it still remains that the primary effort is to have healthy workmen and the benefit is of as great value to the workman as to the industry. The benefits of individual and community good health are numerous and obvious; and the benefits of good health to industry are equally important. The employee will be more productive, receive higher wages and be happier. The labor turn-over rate because of poor health will be lowered as will the costs of insurance. The working personnel will be more efficient and contented, and will dislike to be exposed to the overt acts of people who are epileptic, insane or who disregard communicable disease, and will use their endeavors to work safely among hazards they have been taught to respect.

The harmful exposure to each hazard is, of course, different, ranging from a few days as, for example, an acute poisoning from toxic gases, to that of 15 or 20 years in some of the less toxic dusts; therefore the period before re-examination for each class of employee will be different. However, individuals differ also and it is hard to state a definite period which may be satisfactory for each employee in a single class of hazard. Supervisors can often be of great value in sending employees out for physical examination whenever there is a change in appearance or work ability, or when they have been off on account of some illness, such as those self-diagnosed as common cold, influenza, cough, sore throat or skin irritation. Such observations should be

considered, where there is not a full-time physician, and they are of the greatest value in the early determination of a susceptibility to or the beginning of an industrial disease.

We are fortunate in having had a large amount of research work done on industrial diseases, until at the present time, materials from acetaldehyde to zinc are listed, together with the processes in which they are used and the symptoms which they cause, and an estimate of the amount of exposure in nearly every case necessary to produce symptoms. It is really not too much of a problem for an interested physician to accumulate a supply of such knowledge, particularly when he knows the processes involved during the manufacturing procedure of his industry. It thus becomes relatively a routine matter of observation, together with examination for specific signs or symptoms at the time of the periodical re-examination, to obtain some degree of control of the hazard.

We cannot discuss the benefits of pre-employment examination and periodic re-examination without mentioning some of the objections to it. If a man has a disability, he naturally is anxious to keep it to himself, and in some cases we find that the workman is disinterested to a point that he would rather not know of a disability even though he has it. Certain social groups regard each man as entitled to employment whether he is physically fit or not, on the assumption that industry hires labor, not health, and that rejection because of physical disability causes a class of artisans to become prejudiced against and become charity cases. It is also alleged that the quality of medical service in industry is such that the results of examinations are misleading and of no value. Another objection is voiced by labor unions, it being claimed that pre-employment examinations are used to discriminate against labor union workers or members. Many labor leaders realize, however, that pre-employment examination and periodical check-ups are the only means of preventing disability from certain industrial hazards. Competent and honest medical service renders all these objections quite impotent; for if an endeavor is made to

properly place employees, such a small percentage is finally rejected, and that percentage is so obviously unfit to work, that no fair-minded person can fail to see the justice of it.

These objections, however, are being noticed by legislative bodies, and in one State a law is in force which says: "It is hereby declared to be the policy of the legislature of this State, in enacting this article, to prohibit through every lawful means available, any requirement as a pre-requisite to employment which compels an applicant for employment in any occupation coming within the purview of this article to undergo a medical examination." This statement is in a paragraph labeled, "Prevention of Silicosis and Other Dust Diseases," and the logic of it is entirely non-understandable, even though at the present time there is no lawful means available to enforce the stated policy.

If physical examinations are of benefit to the population at large, they certainly must be to the industrial workers, who may be exposed to special hazards; periodical check-up examinations are necessary in any hazardous work or trade, in order to protect the workers as well as the industry; and the benefits to the workers of proper and fair-minded examinations, in all ordinary cases, outweigh the objections.

I have purposely omitted any reference to the economics of pre-employment and periodic re-examination, which apply either to the individual or the industry. However, one of the great public health problems of today is the question of the cost of medical care. If industry assumes some of this cost by periodical examination in connection with the prevention of industrial disease, it relieves the individual of this responsibility and allows more room in his budget for the care of his family. The benefits to industry, of course, are those of a better personnel and a lower rate of insurance. This rate, due to industrial disease hazards, is in many States very high and the logical conclusion is that the real remedy lies in the prevention of industrial disease by any method, one of which, I believe, is pre-employment and periodical examinations.

What Can the Engineer Do to Eliminate the Hazards of Occupational Diseases?

By REUEL C. STRATTON
Supervising Chemical Engineer, The Travelers Insurance Co., Hartford, Conn.

If I were asked, "Can the engineer prevent the majority of occupational diseases?" my answer would be, "yes." Obviously, with the exception of those cases brought about through a sudden accidental contact with a poisonous material or a virulent disease-producing animal, if the exposure were controlled by engineering technique, then there would be no occupational disease.

The engineer must rely upon the local director to place individuals capable of working in hazardous occupations and to assist him in controlling individuals through periodic physical examinations when the men are exposed to occupational disease hazards; but the engineer alone is responsible for reducing the hazard of harmful substances and for control of employees' contact with processes using harmful materials.

He ascribes of many and new occupational diseases to industrial environment produced a problem for him. The engineer generally works with materials which he can see, but the study of industrial disease control may require the handling of invisible materials. It is a common fault to focus attention upon one aspect to such an extent that others of importance may thereby be relegated to obscurity. Today safety engineers and industrial hygienists are concentrating their attention upon diseases caused by the inhalation of dust, but I do not believe the safety engineer is warranted in confining himself to the prevention of diseases caused by dust alone. His consideration should extend to include all materials produced in any manner that may cause an effect upon a worker. The question of whether a material exists as a gas, a vapor, or a dust is but one of the size and chemical make-up.

must not forget that many such diseases are produced by exposure to gases and vapors as well as to dust, and the control of these industrial diseases must be brought about by the application of fundamental principles common

While the problem confronting industrial safety engineers varies according to the industry, there are certain fundamentals common to all such problems which provide a workable basis upon which an occupational disease prevention program may be developed. Once these fundamentals are set in motion toward a safe working environment, continuance is much the same whether the engineer is engaged with a large organization or with a small one. The fundamentals follow this sequence:

- (1) An occupational disease inventory is required.
- (2) A plan for correction of the exposures shown by the inventory requires development.
- (3) A concentrated attack upon the major exposures first, following through until all are corrected or eliminated.

An inventory of all materials used in a plant will astound the average engineer. He will find many items about which he may have little or no knowledge. He may be confronted with items he had not recognized previously, even though he has been associated with the plant perhaps many years. When this inventory is complete, he should card index it, placing against the name of the material the health hazard associated with it both from a material and a process viewpoint. Such a card index should contain the component parts or constituency of compounds.

Process exposures should be studied in conjunction with hazardous materials. Assistance in compiling such data may be obtained in the bulletin "Occupational Hazards and Diagnostic Signs," prepared by Dublin and Vane of the Metropolitan Life Insurance Company, and in a publication of the United States Public Health Service, Public Health Bulletin No. 216, "The Potential Problems of Industrial Hygiene in a Typical Industrial Area in the United States."

In addition the engineer should obtain all available information upon the materials he is required to study. New

chemicals, solutions, dusts, degreasing agents, condensation products, paints, lacquers, dyes, abrasives, and other products too numerous to mention are being placed upon the market daily, and the average engineer's knowledge of their possible effects upon health is slight. Academic research determining the effect of these new materials upon humans is progressing slowly, and serious injuries may be sustained in industrial application long before the toxicologist is able to determine the properties of the material and the maximum permissible amount to which a worker may be exposed. In seeking this information it is essential to determine in so far as possible the maximum permissible amount of contaminants which may exist in a work place without causing an occupational disease.

Armed with this information, the engineer is in a position to locate properly in his own plant the process and the operation in which the exposure may exist. The engineer should study together with the plant physician the length of employment of exposed individuals and they should jointly determine the normal expectancy or average length of employment for the specific exposure. From such data may be developed a factor of safety, and the maximum allowable period of employment in certain areas may be assigned. Naturally this study should be focused upon the more hazardous locations first, and when these are corrected, attention turned toward minor conditions.

Housing. One of the most important considerations in attempting to control occupational disease is housing. Whenever practical, any hazardous manufacturing process should be separately housed and isolated; every effort should be made to arrest harmful substances—dust, vapors, or gases—at their source of generation. Buildings should be so constructed that accumulations of dust may be avoided.

When physical separation of departments is required, such physical divisions should be dust or vapor tight. Floors should be tight to prevent transfer of materials to floors or departments below. The engineer should give study to the complete enclosure of machinery or process units as individual units and, if so required, vent each one separately. The transfer of hazardous operations into

the open air does not always eliminate the danger; in fact, it may increase the number of workers affected.

Process Revision. To reduce transportation of materials and exposure to harmful substances it is desirable to have all processes mechanically continuous and, if possible, enclosed. When this cannot be accomplished, suitable physical divisions should be provided. The engineer should consider the substitution of wet processes for dry processes, providing at the same time for the disposal of the moist collected material in a safe place. He should consider the substitution of automatic operations for hazardous hand work or machine work. A change of abrasive material will often reduce the quantity of dust produced.

I can cite an example of how a little thought can cure a hazardous machine operation with little or no expense:

A plant producing a finely pulverized material created large amounts of dust in bagging the material, using porous sacks. This high concentration of dust, not necessarily toxic, inconvenienced the workers. The cost of ventilating the department would have been prohibitive. By careful study the engineer determined that the fall of the material into the sacks forced the air out through the interstices of the material, carrying with it a quantity of the pulverized product. His problem, thus, was to provide a means whereby this air could be harmlessly expelled from the sack prior to filling. Study led him to suggest and apply the use of a collapsed paper bag which contained little or no free air. The problem was solved. Dust generation was practically eliminated by this simple change. Many hazardous processes in ordinary manufacturing operations may be cured in like manner if the engineer exercises his ingenuity.

Ventilation. Proper ventilation is of paramount importance in the control of any occupational exposure. Most of the chief occupational diseases other than dermatitis arise through the inhalation or ingestion of foreign material. If ventilating equipment can reduce the concentration of contaminating materials to a safe limit, the problem is solved. The engineer should study each process separately and ventilate each separately. It is seldom wise to rely upon general ven-

tilation. Instead, high velocity ventilating apparatus should be installed, functioning as closely to the point of generation of the harmful substance as is possible.

Individual machines should be so equipped if possible. Baffles may be introduced to prevent air stream disturbances or to increase the intake efficiency at the nozzle. Down-draft systems should be preferred for the collection of dust or gases of high specific gravity.

Even after the installation of exhaust systems, the engineer must study the type of maintenance required to keep them operating at peak efficiency. Nozzles should not be permitted to become covered nor moved out of proper position. Exhaust piping must be kept dust tight. Blower efficiencies must be constantly checked to insure that intake velocities are proper. The best ventilating system is a false protection if it does not function properly or if it is so poorly maintained that it falls below its designed rating. The engineer must exercise extreme care to provide a clean source of replacement air for the work place. He may find it necessary to install filtering and heating devices. The engineer must study the proper disposal of the collected or expelled material to be positive it will not drift back into the work place.

Employee Protection. While the primary engineering means of protection against possible occupational diseases should be mechanical correction, the engineer will find instances where even the best systems must be supplemented by individual protection. He must carefully study such exposures to provide the highest efficiency of protection, yet obtain a device easy for the operator to wear continuously. When the engineer has been successful in obtaining such a device, he must educate workers to use it.

Sanitation. Clean washing facilities and toilets should be provided. Lunch rooms should be not only clean but also well lighted and attractive and should be under the supervision of the plant physician.

Scientific Tests. Up to this point the engineer has deduced that an exposure exists, and from accumulated data has devised his means of prevention. How-

ever, the engineer interested in ascertaining not only exposure but also efficiency of control should realize control cannot be fully effective nor the efficiency of any protective device determined without scientific tests. Assumption, guesswork, unscientific procedure or apparatus have no place in an engineering program. The engineer must test each step unless it has been previously proved, carefully calculating in advance to avoid false protection.

He must be familiar with dust counting, air sampling, and chemical analysis technique, having such determinations made by established and proper methods. If such tests are beyond the scope of his ability or equipment and if the engineer considers such tests absolutely essential, then his executives should permit him to obtain experts qualified to make such surveys as his problem may require. The need for an accurate engineering approach to any control measure cannot be over-emphasized.

Conclusion. Every engineer realizes control of any industrial disease exposure is divided, part of such control falling within the jurisdiction of the industrial physician and part within his own engineering province. Medical knowledge is invaluable in the detection of early symptoms and in the administration of suitable preventive treatment. The engineer should gladly obtain the services of an industrial physician to make a study of the plant, to assist in the classification of the hazardous operations and working locations. By such coordination he will speed control of the exposure.

Each individual occupational disease exposure must be studied, analyzed, and controlled individually. While general data may be available upon common exposures, the solution can be found only in individual treatment. Such exposures cannot be compared to ordinary safety engineering efforts. A circular saw is a circular saw wherever it may be operating, but industrial disease exposure varies within plants and certainly varies between different manufacturing establishments, even though they may produce a like product or article.

ADJOURNMENT

The
Chair

fre
tife
win
acri
cost
man
that
unn
F
and
into
Ma
fou
gen
of
dat
saf
stre
wh
req
acc
1.5
rec
low
me
V
tes
tion
one
bel
has
I
an