Table 5. Properties of Saturated Air[a]

Weights of Air, Vapor of Water, and Saturated Mixture of Air and Vapor at Different Temperatures, Under Standard Atmospheric Pressure of 29.921 in. of Mercury

Temperature, Deg. Fahr.	Vapor Pressure, Inches of Mercury	Weight per Cubic Foot of Mixture			B.t.u. Absorbed by 1 Cu. Ft. Saturated Air per Deg. Fahr.	Cubic Feet Saturated Air Warmed 1 Deg. per B.t.u.
		Weight of Dry Air, Pound	Weight of Vapor, Pound	Total Weight of Mixture, Pound		
0	0.0383	0.08625	0.000069	0.08632	0.02082	48.04
10	0.0631	0.08433	0.000111	0.08444	0.02039	49.05
20	0.1030	0.08247	0.000177	0.08265	0.01998	50.05
30	0.1640	0.08063	0.000276	0.08091	0.01955	51.15
40	0.2477	0.07880	0.000409	0.07921	0.01921	52.06
50	0.3625	0.07694	0.000587	0.07753	0.01883	53.11
60	0.5220	0.07506	0.000829	0.07589	0.01852	54.00
70	0.7390	0.07310	0.001152	0.07425	0.01811	55.22
80	1.0290	0.07095	0.001576	0.07253	0.01788	55.93
90	1.4170	0.06881	0.002132	0.07094	0.01763	56.72
100	1.9260	0.06637	0.002848	0.06922	0.01737	57.57
110	2.5890	0.06367	0.003763	0.06743	0.01716	58.27
120	3.4380	0.06062	0.004914	0.06553	0.01696	58.96
130	4.5200	0.05716	0.006357	0.06352	0.01681	59.50
140	5.8800	0.05319	0.008140	0.06133	0.01669	59.92
150	7.5700	0.04864	0.010310	0.05894	0.01663	60.14
160	9.6500	0.04341	0.012956	0.05637	0.01664	60.10
170	12.2000	0.03735	0.016140	0.05349	0.01671	59.85
180	15.2900	0.03035	0.019940	0.05029	0.01682	59.45
190	19.0200	0.02227	0.024465	0.04674	0.01706	58.80
200	23.4700	0.01297	0.029780	0.04275	0.01750	57.15

[a]From *Fan Engineering*, published by The Buffalo Forge Company.

Table 6. Velocities of Dry Air (At Various Temperatures) Corresponding to Various Velocity Pressures in Inches of Water[a]

Pressure		Temperature, Deg. Fahr.									
Inches	Ounces	50°	60°	70°	80°	100°	150°	200°	300°	500°	550°
0.1	0.0577	1242	1255	1266	1278	1300	1358	1413	1516	1704	1830
0.2	0.1154	1757	1776	1791	1808	1841	1921	2000	2145	2411	2590
0.25	0.1443	1965	1986	2003	2022	2059	2149	2235	2399	2696	2895
0.3	0.1730	2151	2175	2193	2214	2254	2352	2447	2626	2952	3175
0.4	0.2308	2485	2512	2533	2557	2603	2717	2827	3033	3409	3660
0.5	0.2884	2778	2808	2832	2859	2911	3038	3160	3391	3812	4095
0.6	0.3460	3043	3076	3102	3131	3188	3327	3462	3715	4175	4490
0.7	0.4037	3287	3323	3351	3383	3445	3595	3740	4013	4510	4850
0.75	0.4326	3402	3439	3468	3501	3565	3720	3870	4153	4668	5020
0.8	0.4614	3524	3552	3582	3616	3682	3843	3997	4290	4821	5185
0.9	0.5190	3728	3768	3800	3836	3906	4076	4241	4550	5114	5500
1.0	0.5768	3929	3971	4005	4043	4117	4296	4470	4796	5390	5795
1.25	0.7209	4393	4440	4478	4520	4602	4804	4997	5362	6027	6470
1.50	0.8650	4812	4864	4905	4952	5042	5262	5474	5874	6602	7100
1.75	1.0092	5197	5254	5298	5348	5446	5683	5912	6344	7131	7655
2.00	1.1535	5556	5616	5664	5718	5822	6076	6320	6783	7624	8195
2.25	1.2975	5892	5956	6007	6064	6174	6443	6704	7193	8085	8690
2.50	1.4418	6211	6278	6332	6392	6508	6792	7066	7582	8523	9150
2.75	1.5860	6514	6585	6641	6704	6827	7124	7412	7952	8938	9600
3.00	1.7300	6807	6879	6937	7003	7130	7440	7742	8307	9336	10000
4.00	2.3070	7857	7942	8010	8086	8233	8592	8940	9581	10780	11580
5.00	2.8840	8772	8867	8943	9027	9192	9593	9980	10710	12037	12900
6.00	3.4600	9623	9728	9810	9903	10083	10523	10950	11750	13203	14180

[a]From *Fan Engineering*, published by The Buffalo Forge Company.

Table 7. Circumferences and Areas of Circles

Diameter in Inches	Area		Circumference		Diameter in Inches	Area		Circumference	
	Sq. In.	Sq. Ft.	Inches	Feet		Sq. In.	Sq. Ft.	Inches	Feet
¼	0.049	0.0003	0.785	0.0652	28	615.8	4.276	87.97	7.330
½	0.196	0.0014	1.571	0.1309	28½	637.9	4.430	89.54	7.462
¾	0.442	0.0031	2.356	0.1964	29	660.52	4.587	91.11	7.592
1	0.785	0.0054	3.142	0.2618	29½	683.5	4.747	92.63	7.725
1¼	1.227	0.0085	3.927	0.3273	30	706.8	4.909	94.25	7.854
1½	1.767	0.0123	4.712	0.3927	31	754.8	5.241	97.39	8.116
1¾	2.405	0.0167	5.498	0.4582	32	804.3	5.585	100.5	8.378
2	3.142	0.0218	6.283	0.5236	33	855.3	5.940	103.7	8.639
2¼	3.976	0.0276	7.069	0.5891	34	907.9	6.305	106.8	8.901
2½	4.909	0.0341	7.854	0.6546	35	962.1	6.681	109.9	9.163
2¾	5.939	0.0412	8.639	0.7200	36	1018.0	7.069	113.1	9.425
3	7.069	0.0491	9.425	0.7854	37	1075.0	7.467	116.2	9.686
3¼	8.296	0.0576	10.21	0.8510	38	1134.0	7.876	119.4	9.948
3½	9.621	0.0668	10.99	0.9160	39	1195.0	8.296	122.5	10.21
3¾	11.04	0.0767	11.78	0.9818	40	1256.0	8.727	125.6	10.47
4	12.57	0.0873	12.57	1.047	41	1320.0	9.168	128.8	10.73
4¼	14.19	0.0986	13.35	1.113	42	1385.0	9.621	131.9	10.99
4½	15.90	0.1104	14.14	1.178	43	1452.0	10.08	135.1	11.26
4¾	17.72	0.1231	14.92	1.243	44	1521.0	10.56	138.2	11.52
5	19.64	0.1364	15.71	1.309	45	1590.0	11.04	141.4	11.78
5¼	21.65	0.1504	16.49	1.374	46	1662.0	11.54	144.5	12.04
5½	23.76	0.1650	17.28	1.440	47	1735.0	12.05	147.7	12.30
5¾	25.97	0.1840	18.06	1.505	48	1810.0	12.51	150.8	12.57
6	28.27	0.1964	18.85	1.571	49	1886.0	13.09	153.9	12.83
6¼	30.68	0.2131	19.64	1.637	50	1963.0	13.64	157.1	13.09
6½	33.18	0.2304	20.42	1.702	51	2043.0	14.19	160.2	13.35
6¾	35.79	0.2486	21.21	1.768	52	2124.0	14.75	163.4	13.61
7	38.49	0.2673	21.99	1.833	53	2206.0	15.32	166.5	13.88
7¼	41.28	0.2867	22.78	1.899	54	2290.0	15.90	169.6	14.14
7½	44.18	0.3068	23.56	1.964	55	2376.0	16.50	172.8	14.40
7¾	47.17	0.3276	24.35	2.029	56	2463.0	17.10	175.9	14.66
8	50.27	0.3491	25.13	2.094	57	2552.0	17.72	179.1	14.92
8¼	53.46	0.3713	25.92	2.160	58	2642.0	18.35	182.2	15.18
8½	56.75	0.3942	26.70	2.225	59	2734.0	18.99	185.4	15.45
8¾	60.13	0.4175	27.49	2.291	60	2827.0	19.63	188.5	15.71
9	63.62	0.4418	28.27	2.356	61	2922.0	20.29	191.6	15.97
9¼	67.20	0.4668	29.06	2.422	62	3019.0	20.97	194.8	16.23
9½	70.88	0.4923	29.85	2.488	63	3117.0	21.65	197.9	16.49
9¾	74.66	0.5185	30.63	2.553	64	3217.0	22.34	201.1	16.76
10	78.54	0.5454	31.42	2.618	65	3318.0	23.04	204.2	17.02
10½	86.59	0.6010	32.99	2.750	66	3421.0	23.76	207.3	17.28
11	95.03	0.6600	34.56	2.880	67	3526.0	24.48	210.5	17.54
11½	103.9	0.7215	36.13	3.011	68	3632.0	25.22	213.6	17.80
12	113.1	0.7854	37.70	3.142	69	3739.0	25.97	216.8	18.06
12½	122.7	0.8520	39.27	3.273	70	3848.0	26.73	219.9	18.33
13	132.7	0.9218	40.84	3.403	71	3959.0	27.49	223.1	18.59
13½	143.1	0.9937	42.41	3.535	72	4072.0	28.27	226.2	18.85
14	153.9	1.069	43.98	3.665	73	4185.0	29.07	229.3	19.11
14½	165.1	1.146	45.55	3.796	74	4301.0	29.87	232.5	19.37
15	176.7	1.227	47.12	3.927	75	4418.0	30.68	235.6	19.63
15½	188.7	1.310	48.69	4.058	76	4536.0	31.50	238.8	19.90
16	201.1	1.396	50.27	4.189	77	4657.0	32.34	241.9	20.16
16½	213.8	1.485	51.84	4.321	78	4778.0	33.18	245.0	20.42
17	226.9	1.576	53.41	4.451	79	4902.0	34.04	248.2	20.68
17½	240.5	1.670	54.98	4.582	80	5027.0	34.91	251.3	20.94
18	254.5	1.767	56.55	4.712	81	5153.0	35.78	254.5	21.21
18½	268.8	1.867	58.12	4.845	82	5281.0	36.67	257.6	21.47
19	283.5	1.969	59.69	4.974	83	5411.0	37.57	260.8	21.73
19½	298.6	2.074	61.26	5.105	84	5542.0	38.48	263.9	21.99
20	314.2	2.182	62.83	5.236	85	5675.0	39.41	267.0	22.25
20½	330.1	2.293	64.40	5.367	86	5809.0	40.34	270.2	22.51
21	346.4	2.405	65.97	5.498	87	5945.0	41.28	273.3	22.78
21½	361.1	2.508	67.54	5.629	88	6082.0	42.24	276.5	23.04
22	380.1	2.640	69.12	5.760	89	6221.0	43.20	279.6	23.30
22½	397.6	2.761	70.69	5.891	90	6362.0	44.18	282.7	23.56
23	415.5	2.885	72.26	6.021	91	6504.0	45.17	285.9	23.82
23½	433.7	3.012	73.83	6.153	92	6648.0	46.16	289.0	24.09
24	452.4	3.142	75.40	6.283	93	6793.0	47.17	292.2	24.35
24½	471.4	3.274	76.97	6.415	94	6940.0	48.19	295.3	24.61
25	490.9	3.409	78.54	6.545	95	7088.0	49.22	298.4	24.87
25½	510.7	3.547	80.11	6.676	96	7238.0	50.27	301.6	25.13
26	530.9	3.687	81.68	6.807	97	7390.0	51.32	304.7	25.39
26½	551.6	3.832	83.25	6.938	98	7543.0	52.38	307.9	25.66
27	572.6	3.976	84.82	7.069	99	7698.0	53.46	311.0	25.92
27½	593.9	4.125	86.39	7.199	100	7854.0	54.54	314.2	26.18