NOTICE: If the film image below is less clear than this notice, this is due to the quality of the document being filmed.

CONFIDENTIAL

MATERIAL 7789 (C.C.3500) July [illegible], 1946
ASBESTOS FELT, HIGH TEMPERATURE
FOR USE BY - South Philadelphia
FURNISHED BY - Union Asbestos & Rubber Co, 1823 S.54th Ave, Chicago (50), Illinois
ORDER FROM SUPPLIER AS - Insubestos felt, stating size and thickness.
CHARACTERISTICS - A brown or buff colored, stitched or quilted, fibrous, asbestos base, loosely packed, high temperature felt. Available in rolls in many sizes and thicknesses. Usually obtained in strips 12 inches wide by 1 inch thick. Density approximately 15 lbs per cubic foot. Temperature use limit 371 C (700 F).
APPLICATION - Used as a liner for metal jacket turbine covers to prevent the turbine heat from burning the paint from the outside surfaces of the jacket.
SPECIFY AS - FELT 7789

Issued by Mtls & Stds Sec, Eng Labs & Stds Dept, East Pgh, Pa.

Printed in U.S.A.

DOCUMENTS PRODUCED DALLAS COUNTY CASES 3/18/92

DOCUMENTS PRODUCED DALLAS COUNTY CASES 3/18/92

PLAINTIFF'S EXHIBIT WH-61

0 0 0 7 3 0