Effective 11-3-70 (Original)

SANTOVAC 1
SANTOVAC 2

Sold For Use In Vacuum Pumps Only

TERMS Net 30 days

DELIVERY

Domestic F.O.B. Saugat, Ill.

Export F.A.S. Atlantic and Gulf Ports

PRICES U.S. $ per Lb.

DOMESTIC PRICES

	55 GALLON DRUM	5 GALLON CAN
SANTOVAC 1 6776-001-11-03	1.00 lb.	1.30 lb.
SANTOVAC 2 6776-002-11-03	1.05 lb.	1.35 lb.

EXPORT PRICES

	55 GALLON DRUM	5 GALLON CAN
SANTOVAC 1 6776-001-11-03	1.05 lb.	1.35 lb.
SANTOVAC 2 6776-002-11-03	1.10 lb.	1.30 lb.

Minimum order 50 lbs.

STANDARD CONTAINERS

Type	Net Weight	Gross Wt. Approx.	Cubic Feet
SANTOVAC 1			
55 gal. metal drum	600 lbs.	648 lbs.	10 3/4
5 gal. metal can	55 lbs.	60 lbs.	1
SANTOVAC 2			
55 gal. metal drum	600 lbs.	648 lbs.	10 3/4
5 gal. metal can	60 lbs.	65 lbs.	1

SAMPLES 8 ounces. Mailable.

SHIPPING CLASSIFICATION Plastics Synthetic Liquid NOIBN — Rail

Plastic Liquid NOIBN — Truck

HANDLING PRECAUTIONS

CAUTION! Contains chlorinated hydrocarbons. Avoid prolonged breathing of vapors or mists. Avoid contact with eyes or prolonged contact with skin. If skin contact occurs, remove by washing with soap and water. Following eye contact flush with water. If clothing becomes soaked with fluid, launder before wearing again.

MONS 057109

NOTICE: Santovac 1 and 2 are sold for use only in vacuum pumps and potential customers should be informed of the following:

"This product contains polychlorinated biphenyls which some studies have shown may be an environmental contaminant. Extreme care should be taken to prevent any entry into the environment through spills, leakage, use, disposal, vaporization, or otherwise."

The customer may return used Santovac 1 or 2 to Monsanto, WGK Plant, Supervisor, Dept. 246, Sauget, Ill., 62201 for incineration and disposal. The customer will pay the freight and be invoiced .03/lb. on material disposed of.

LABELING REQUIREMENTS Product label required by law.

TYPICAL PROPERTIES

	Santovac 1	Santovac 2
Color	100 APHA	100 APHA
Viscosity	73-80 SUS @ 130°F	44-48 SUS @ 210°F
Acidity mg KOH/gm	0.010	0.010
Specific Gravity 25/15.5°C	1.405/1.415	1.495/1.505

GENERAL INFORMATION

Santovac 1 replaces Arocior 1242 and Arocior 1248 as vacuum pump fluids. Santovac 2 replaces Arocior 1254 as a vacuum pump fluid. Santovac 2 offers the lowest vapor pressure of the two products and in turn the lowest vacuum. Santovac 1 is used for intermediate vacuum performance and where a lower viscosity is desired. Both materials have stability above 600°F.

Literature Data Sheet

COMPETITION None

AUTHORIZED DISTRIBUTORS None

---

519 W 300 O

MONS 057110