

BESTWALL

GYPSUM

PRODUCTS

PLAINTIFF'S EXHIBIT

GP-1039

FEBRUARY 1959

PRODUCT SPECIFICATION DIRECTORY

This list provides a simple up-to-date cross reference of Bestwall products with applicable American Society for Testing Materials Standards (ASTM Standards), Federal Specifications and American Standards Association Specifications (ASA). The last two digits in the ASTM reference number indicates the year of the edition. Where any specifications covers more than one material the type or paragraph is shown. Items for which no standard is written is indicated.

GYPSUM BOARD PRODUCTS

PRODUCT	THICK- NESS	WIDTH	LENGTH	ASTM STANDARDS	FEDERAL SPEC.	APPLIED UNDER			
BESTWALL WALLBOARD									
Tapered Edge	1/4"	4'	6' to 16'	C 36-55	SS-W-51A ⊕	ASA 97.1			
Square or Tapered Edge	3/8"	4'	6' to 16'						
	1/2"	4'	6' to 16'						
	3/4"	4'	6' to 16'						
BESTWALL INSULATING WALLBOARD									
Square or Tapered Edge	3/8"	4'	6' to 16'	C 36-55	SS-W-51A ⊕	ASA 97.1			
	1/2"	4'	6' to 16'						
	3/4"	4'	6' to 16'						
BESTWALL BRAINBOARDS									
Knotty Pine (Square Edge)	1/4"	4'	8' 9' 10'	C 36-55	SS-W-51A ⊕	ASA 97.1			
Figured Aspen (Beveled Edge)									
Ribbon Mahogany (Beveled Edge)	1/2"	4'	8' 9' 10'						
Fawn Mahogany (Beveled Edge)									
Driftwood Mahogany (Beveled Edge)									
Autumn Mahogany (Beveled Edge)									
FIRESTOP BESTWALL WALLBOARD									
Square or Tapered Edge	1/2"	4'	6' to 16'	C 36-55	SS-W-51A ⊕	ASA 97.1			
	3/8"	4'	6' to 16'						
FIRESTOP BESTWALL INSULATING WALLBOARD									
Square or Tapered Edge	1/2"	4'	6' to 16'	C 36-55	SS-W-51A ⊕	ASA 97.1			
	3/8"	4'	6' to 16'						
BESTWALL FIREPROOF GYPSUM SHEATHING									
Long edges core treated	1/2"	2'	8' Std.†	C 79-54	SS-S-276	—			
Tongue and Groove Non core-treated	1/2"	2'	8' Std.†	C 79-50	SS-S-276	—			
BESTWALL BACKER									
Square Edge	3/8"	4'	8' Std.†	—	—	—			
Tongue and Groove Edge	1/2"	2'	8' Std.†						
Firestop Tongue and Groove Edge	3/8"	2'	8' Std.†						
BESTWALL LATH									
Plain or Perforated (Perfolath)	3/8"	16"	4'	C 37-54	SS-P-431A	ASA 42.4			
	1/2"	16"	4'						
Insulating Lath	3/8"	16"	4'						
	1/2"	16"	4'						
Long Length (Plain Only)	1/2"	24"	8' Std.†						
Round Edge or Tongue and Groove Edge									

†Standard Length — Other Lengths on Order.

SGP 0003878

PRODUCT SPECIFICATION DIRECTORY

PLASTER PRODUCTS

BRAND	PRODUCT	ASTM STANDARDS	FEDERAL SPEC.	APPLIED UNDER
BESTWALL	NEAT BASE COAT PLASTER Unfibred, Fibred*, and Extra Fibred*	C-28-57	SS-P-402 (N)	ASA 42.1
BESTWALL	LITE-MIX BASE COAT PLASTER Unfibred, Fibred (Glass Only) and Masonry Mix	C-28-57	—	ASA 42.1
BESTWALL	WOOD FIBERED PLASTER	C-28-57	SS-P-402 (W)	ASA 42.1
BESTWALL	CONCRETE BOND PLASTER	C-28-57	SS-P-402 (W)	ASA 42.1
BESTWALL	PREPARED TROWEL FINISH PLASTER	—	—	ASA 42.1
BESTWALL	PREPARED SAND FLOAT FINISH PLASTER—White	—	—	ASA 42.1
BESTWALL	BUILDERS LIME (Autoclaved Finish Lime)	C 206-49	SS-L-351 (F)	ASA 42.1
BESTWALL	SMOOTH FINISHING LIME (Normal Hydrated Finish Lime)	C 6-49	SS-L-351 (F)	ASA 42.1
BESTWALL	SPEEDY MASON'S LIME (Autoclaved Mason's Lime)	C 207-49 S	SS-L-351 (M)	ASA 42.1
BESTWALL	MASON'S LIME (Normal Hydrated Mason's Lime)	C 207 49 N	SS-L-351 (M)	ASA 42.1
BESTWALL	KEENE'S CEMENT	C 61-50	SS-C-161	ASA 42.1
BESTWALL	KALITE ACOUSTICAL PLASTER Natural, Gray or Buff	—	SS-A-111 (I)	ASA 42.1
BESTWALL	LIGHT ACOUSTICAL PLASTER	—	—	ASA 42.1
BESTWALL	GAUGING PLASTER —White (SATIN SPARK)	C 28-57	SS-P-402 (G)	ASA 42.1
	Local	C 28-57	SS-P-402 (G)	ASA 42.1
BESTWALL	MOULDING PLASTER —White (SUNFLOWER)	C 59-50	—	—

*Glass Fibred unless Specified Sisal

⊕ In some instances the Specification does not reflect all the details of an item as the depth of taper on taper edge board, the different thicknesses and the core composition in Firestop, the finish on wood grain gypsum board, etc.

MISCELLANEOUS PRODUCTS

BRAND	PRODUCT	ASTM STANDARDS	FEDERAL SPEC.	APPLIED UNDER
BESTWALL	JOINT SYSTEM	—	—	ASA 97.1
BESTWALL	GYPSTEEL PLANK	C 377-56T Long Span Slab	SS-S-439 Type I	—
BESTWALL	METRO MIX	C 317-55	—	ASA 59.1
BESTWALL	FORM BOARD	C 318-55	—	ASA 59.1

Any question not answered by the information on this sheet or available in the District Sales Office should be referred to the General Sales Office. Be sure to give all information as to issuing office, date of specification, job description, location, enforcing party, product involved, description of use if other than normal, amount involved, etc. This is particularly important when special limitations under standard specifications are involved.

Each Bestwall Certain-teed Sales Corporation District Sales office has a book of applicable Federal Specifications. Each specification is prepared with a detailed analysis prepared by the Laboratory of which Bestwall products meet the specification and any limitations. The District Sales Manager is authorized to write a letter of certification in accordance with the Laboratory analysis.