

44-
#12

**SHERWIN-WILLIAMS
PRODUCTS**

24313

*Trade Sales
Catalog*



THE SHERWIN-WILLIAMS Co.

ADMINISTRATION OFFICES: CLEVELAND 3, OHIO
SALES OFFICES, FACTORIES AND WAREHOUSES
IN PRINCIPAL CITIES

TS CAT. 4-29 1534

Introduction

WE offer our line of paints, varnishes, enamels and special products to the trade with the knowledge that they will fulfill every claim we make for them, and when used as intended will prove satisfactory.

Since we control the source of so many of the raw materials used in our products and maintain chemical laboratories and testing rooms where these materials are carefully examined for quality, we are able consistently to offer goods of more reliable and uniform quality than merchandise made by less favorably situated manufacturers.

New developments planned and tested for the future are regularly introduced as soon as field tests prove their superiority and raw materials become available—as products of Sherwin-Williams Research.

The Sherwin-Williams Company was founded in 1866. Ever since that time we have held strictly to the highest standard of quality in the products manufactured. We believed that the best goods would sell the best and our splendid success has proved we were right.

THE SHERWIN-WILLIAMS CO.

INDEX

	Page		Page
All Purpose Spar Varnish.....	28	One Coat Enamel No. 39, Painter	19
Aluminaum Paint No. 29.....	6	Craft.....	19
Applicator, Wax.....	32	Paint and Varnish Remover	
Asphaltum "B".....	7	(Taxis).....	23
Auto Polish.....	30	Painter Craft Finishes.....	18
Barn Paint (Commonwealth Red)	8	Painters Paste Paint White No. 66	20
Blue Grass Stock Farm White....	7	Paste Oil Colors (Tubes).....	16
Brick and Stucco Paint.....	7	Paste Wood Filler.....	16
Bronzing Liquid No. 33.....	5	Pestroy 5 and 10% D D T.....	33-34
Brushes (Kam-Glo).....	17	Pestroy 25% D D T.....	34
Brushes (Kam-Tone).....	16	Pigmented Wall Sealer No. 77,	
Bug-Blaster.....	33	Painter Craft.....	19
Colors in Oil, Paste.....	10	Plastic Patch.....	15
Colors, Tinting First Quality....	10	Polish Furniture (Cream).....	30
Commonwealth Red.....	8	Porch and Floor Enamel.....	21
Concrete Floor Paint (Porch and		Preparite.....	21
Floor).....	21	Primer, Galvanize (Galvite).....	13
Concrete Wall Finish (Brick and		Primer, Metal, Red.....	18
Stucco).....	7	Primer, Walls (Wall Primer and	
Cream Polish, Furniture.....	30	Sealer).....	29
D D T Pestroy.....	33	Primer, Wood Interior (Flat-Rite)	11
Deck Paint (Porch and Deck).....	21	Primer, Wood Interior (PG XXX)	20
Decorators Colormix.....	8	Primer, Wood Exterior (SWP).....	5
Drier (Q D).....	28	R and B Utility Paint.....	25
Enameloid.....	9	Respar.....	27
Enamel, Stove and Iron.....	23	Roller-Koater (Kam-Tone).....	15
Enamel, Tractor and Implement..	24	Screen Enamel Black.....	23
Enamel Undercoater (Flat-Rite)...	11	Self Polishing Wax.....	32
Enamel Undercoater (PG XXX)....	20	Semi-Lustre.....	22
Erolvent.....	10	Shingle Stain.....	23
Filler, Wood Paste.....	10	Soap (Paste and Liquid).....	30-31
First Quality Colors.....	10	Sprayer, Wood-No-More.....	35
Flat Black (Enameloid).....	11	Stain, Shingles.....	23
Flat-Rite.....	11	Stain, Varnish (Flo-Lac).....	12
Flat-Tone.....	42	Stain, Woodcraft.....	29
Flaxop.....	30	Stock Farm White, Blue Grass....	7
Flo-Lac.....	12	Stove and Iron Enamel.....	23
Floor Enamel (Porch and Floor)...	21	Stucco Paint (Brick and Stucco)...	7
Floor-Seal.....	27	S W P.....	5
Floor and Iron Varnish, Painter		Taxite (Paint and Varnish	
craft.....	20	Remover).....	23
Fluid Tinting Colors.....	10	Thinner (Erolvent).....	10
Furniture Polish.....	30	Thinners Red.....	24
Galvite.....	13	Tinting Colors (First Quality)...	10
Glass Polish.....	31	Tractor and Implement Enamel..	24
Glazing Liquid.....	13	Traffic Zone Paint.....	24
Graining Preparation (Flo-Lac)...	12	Trim Colors (SWP).....	6
House and Garden Products.....	33	Trims (Kam-Tone).....	16
Household Products.....	30	Turpentine.....	25
House Paint (SWP).....	5	Undercoater, Enamel (Flat-Rite)...	11
Interior Semi-Gloss No. 16, Painter		Undercoater, Enamel (PG XXX)...	20
Craft.....	19	Undercoater, Exterior (SWP).....	5
Japan Drier (Q D).....	28	Utility Paint, R and B.....	25
Kam-Glo.....	17	Varnishes.....	25
Kam-Namel Snow White Gloss....	13	Varnish Stain (Flo-Lac).....	12
Kam-Tone.....	14	V 94 Quick Drying Varnish.....	28
Lipseed Oil Soap Flaxop.....	30	Wall Finish (Brick and Stucco)...	7
Lin-X Clear Gloss Varnish.....	18	Wall Finish (Flat-Tone).....	12
Liquid Oil Soap.....	31	Wall Finish (Painter Craft).....	18
Mar-Not.....	25	Wall Finish (Semi-Lustre).....	22
Metal Primer Red.....	18	Wall Primer and Sealer.....	29
Mildew Resisting (SWP).....	5	Waxer Kit No. 11.....	32
Oil Colors (Paste).....	10	Waxes.....	32
Oil Soap (Fluid).....	31	Wood-No-More 14.....	35
One Coat Flat Wall Paint No. 10,		Woodcraft Stain.....	29
Painter Craft.....	18	Wood Filler, Paste.....	10
		XXX Undercoater, Painter Craft..	20
		Zone Paint, Traffic.....	24

S W P HOUSE PAINT

For Exterior Painting

6003

New copy

SWP House Paint embodies the most up-to-date improvements known to paint science. Today's SWP is the finest house paint ever made by Sherwin-Williams. It is not only one of the best known, but also one of the highest quality paints on the market. In its whiter brighter whites and its cleaner, more beautiful colors, it now gives an extra year of beauty.

SWP White and SWP Colors are made under the most careful supervision with the finest pigments, colors, oils and driers of our own manufacture, in order to insure a performance that is uniform and dependable. Each step of manufacture from mine to mill is under strict control of the world's largest paint research laboratories.

Being a prepared house paint which comes in proper consistency for use under most conditions, it should not be thinned in any way except as directed on the label. SWP is an economical Painters paint because:

1. Its close-knit film has stronger hiding power and requires less brushing to obtain solid covering.
2. Its controlled chalking offers the kind of surface which painters like to repaint.

SWP Gloss White has been carefully formulated to produce a brilliant true white, more permanent and more beautiful than ever before. This highest-quality house paint gives homes smart, long-lasting beauty and, having an even all-over film, does a good job of protecting the surface.

The smart SWP colors are cleaner, more permanent, more beautiful than they have ever been before. SWP jobs stand out conspicuously, giving beauty and protection that last longer than ordinary paints.

Ready-to-use SWP Undercoater No. 450 primes and seals badly weathered painted surfaces or unpainted wood and uniforms painted sheltered surfaces. It dries to a dull coat—makes possible better, longer-lasting paint jobs.

SWP MILDEW RESISTING WHITE

SWP Mildew Resisting White possesses strong mildew resisting properties for homes located in sections where mildew and fungus are prevalent. Surfaces that are protected with SWP Mildew Resisting White resist attack from these conditions, and as a result, stay white longer than areas treated with paint not containing mildew and fungus inhibitors. SWP Mildew Resisting Undercoater is recommended in these Mildew-affected areas followed by a finishing coat of SWP Mildew Resisting Gloss White. These paints should be applied according to the instructions outlined on the label for Mildew Resistant Undercoater #451 and SWP White Paint #472.

SWP FUME RESISTING WHITE

SWP Fume Resisting White is formulated with special oils and pigments which impart a better appearance and added protection against decaying seaweed and fumes from factories, oil refineries and coal furnaces. The "stay white" characteristic of Fume Resisting White is outstanding. This product is a companion product to the regular SWP Gloss White for outside use and should be used only in those localities where sulphur fumes cause objectionable darkening. Directions for applying SWP Fume Resisting White are listed on the label which outlines the procedure to be followed in new work and the repainting of old surfaces.

SHERWIN-WILLIAMS PRODUCTS

S W P TRIM COLORS

SWP Trim Colors are specially formulated with extra-permanent colors and other highest quality ingredients to insure maximum durability and mildew resistance. These Trim Colors are used on shutters, window sash, doorways, grillwork and similar trim surfaces which are subjected to greater punishment than on house siding.

Applied according to directions SWP produces the "required thickness" of the most durable house paint known today. It will stand up year after year. Covering capacity: SWP 450 Undercoater—450 square feet per gallon, one coat. SWP House Paint—550 square feet per gallon, one coat. Color Card CC-465.

	Pints	Quarts	Gallons	5 Gallons
Undercoater, 450.....	XXXX			
Gloss White, 471.....				
Black, 467.....				XXXX
Berkeley Yellow, 459.....				
Chelsea Gray, 474.....				
Colonial Yellow, 465.....				
Geneva Cream, 478.....	XXXX			
Fume Resisting White, 486.....				
Ivory, 496.....				
Plymouth Green, 458.....				
Westchester Gray, 477.....				
Willow Green, 461.....				
Woodland Brown, 498.....	XXXX			XXXX
MILDEW RESISTING				
Undercoater, 451.....	XXXX			
White, 472.....				
TRIM COLORS				
Manor Brown, 495.....	XXXX			XXXX
Royal Maroon, 497.....				
Ardmore Green, 416.....				
Castilian Blue, 412.....				
Hillcrest Green, 482.....	XXXX			XXXX
Trim Super White, 410.....				
Verdun Green, 417.....				
Solfast Red, 418.....	XXXX			XXXX

ALUMINUM PAINT No. 29

BRIGHT SILVER FINISH

Aluminum Paint No. 29 is a general purpose, ready-mixed Aluminum spar enamel for interior and exterior use. It will give good protection on wood and metal surfaces. Because of its excellent hiding qualities, Aluminum Paint No. 29 will completely conceal a clean, black surface. Further, it possesses good heat resisting qualities, and can be easily "brushed out."

This product is formulated with a bright, fine-flake aluminum paste and does not lose its brilliancy when permitted to stand in the package for long periods of time.

One gallon covers approximately 1,000 square feet.

1/2 Pts. Quarts Gallons 5 Gallons

SHERWIN-WILLIAMS PRODUCTS

ASPHALTUM "B"

A quick-drying popularly priced black asphaltum for use on metal and wood. Works easily, covers well and possesses exceptional alkali and acid-resisting qualities. It dries dust-free in 15 to 20 minutes and can be handled in two to three hours.

One gallon covers approximately 600 square feet.

1/4 Pts. Pints Quarts Gallons 5 Gallons

FARM, RANGE AND PLANTATION BLUE GRASS STOCK FARM WHITE

Blue Grass Stock Farm White is made particularly for use on stock farms. It is a quality, low cost paint, economical to use and easy to apply on exterior wood surfaces, fences, barns, outhouses, sheds, etc., either smooth or rough lumber. The creosote odor and taste discourage gnawing of the surface by the stock, and being made of lead-free formula, it is not poisonous to animals. In addition to the above advantages, it offers protection against the elements.

It is furnished in brushing consistency but can be sprayed when reduced according to the directions on the label. For best results on new or weathered surfaces two coats should be applied. One coat on previously painted surfaces in normal condition will give excellent service.

Covering capacity will vary according to the porosity of the surface, but on the average one gallon will cover one coat approximately 400 square feet on new wood or 600 square feet on previously painted surfaces.

Gallons 5 Gallons

BRICK AND STUCCO PAINT WATERPROOFS AND BEAUTIFIES

6626

Sherwin-Williams Brick and Stucco Paint is a high quality, semi-gloss oil paint made especially for exterior use on brick, concrete, cement, stone, stucco and other types of masonry surfaces. It may also be applied to similar interior surfaces. When used according to directions, it will repel moisture, and cover all stains and discoloration. Because it prevents moisture from penetrating stucco, brick and cement, it lengthens the life of exterior walls, and keeps buildings dry.

Old or unpainted surfaces attract and retain dirt and soot. Use of this tight oil paint will beautify these surfaces, keep walls clean and buildings protected, presenting a tough, smooth attractive surface to the weather.

For the first coat on unpainted, porous surfaces, apply a mixture consisting of equal parts Brick and Stucco Paint and Mixing Sealer. Do not substitute linseed oil or turpentine for thinning. Apply the second coat as it comes from the package. On old painted surfaces the first coat should be a mixture of Brick & Stucco Paint and Mixing Sealer, amounts being determined by the porosity of the surface.

One gallon covers 300 to 450 square feet—one coat. Brick and Stucco Cream matches SWP Geneva Cream. Color Card CC-283. *Discontinued*

	Quarts	Gallons	5 Gallons
Cream, 913.....			
White, 910.....			
Mixing Sealer, 024.....			

BRONZING LIQUID No. 33

For interior use with aluminum powder or paste and gold bronze. Because Sherwin-Williams Bronzing Liquid binds the metal flakes together forming an unbroken shield, the resultant surface will impart a metallic effect. Bronzing Liquid No. 33, when used with metal powders or pastes, is suitable for decorative purposes, such as mirror and picture frames, metal work of all kinds, childrens toys, wood trim, etc.

We recommend two pounds of aluminum powder or paste or four pounds of gold bronze be added to a gallon of Bronzing Liquid for best decorative purposes.

One gallon of Bronzing Liquid plus the recommended bronze covers approximately 1000 square feet—one coat.

1/2 Pint Pint Quart Gallon

COMMONWEALTH RED

Sherwin-Williams Commonwealth Red is unquestionably the finest general purpose red paint on the market today. It has excellent color, is rich in oil and dries to a durable gloss.

This quality product is not restricted to use on barns alone, but may be successfully used on other buildings, roofs (except composition), metal, and all types of exterior surfaces subject to ravaging elements.

Commonwealth Red is easy to apply and one coat will cover most surfaces, 500 square feet to the gallon. Color Card CC-331.

Gallons 5 Gallons

DECORATORS COLORMIX

POUR—STIR AND PAINT

Sherwin-Williams Decorators' Colormix is a simplified blending or mixing system of decorative oil base wall paint that produces many hundreds—even thousands of unusual colors, tints and shades in two stylish sheens, a soft non-glare sheen—a flat paint and a rich semi-gloss sheen, both of unexcelled beauty. The Colormix line comes in 7 deep base colors and 2 base whites. All are packaged in convenient sizes for easy, quick and practical intermixing. No difficult measuring of minute parts is required.

The seven base colors are ready for use as Deep Tone Colors Flat Wall Paint for interior walls. When mixed with Flat White they make beautiful clean flat tints and shades. When mixed with Semi-Gloss White, not to exceed one quart of base color with one gallon of white, the resulting paint is a glossy sheen or satin gloss—the finish that is most popular for use on kitchen and bathroom walls. This satin gloss is preferred for woodwork in living rooms, dining rooms and bedrooms where a correlating color is needed to harmonize with flat finished walls.

Colormix is easy to use. It goes on smoothly and covers well on all interior surfaces of plaster, wallboard, wood, brick or metal, water emulsion or casein finishes. For producing a most popular and attractive finish with uniform appearance a stipple coat is recommended either by brushing or by the use of a roller.

One coat of light tints or pastel shades of Decorators' Colormix applied at package consistency will cover most surfaces satisfactorily. However, when deep colors are applied over light tints or pastel shades it is advisable to use two coats. S-W Wall Primer and Sealer tinted with one pint of the finishing color should first be applied to the surface before the finish coat is brushed on.

DECORATORS COLORMIX—Continued

One gallon covers approximately 500 square feet, one coat. Color Card PA131B.

	$\frac{1}{2}$ Pint	$\frac{1}{4}$ Pint	Pint	Quart	Gallon
Flat White, 960.....					
Semi-Gloss White, 970.....					
Black, 966.....					
Blue, 963.....					
Brown, 965.....					
Burgundy, 964.....					
Green, 962.....					
Red, 968.....					
Yellow, 961.....					

ENAMELOID

THE DECORATIVE ALL PURPOSE ENAMEL

(One Coat Covers)

6146

The ease of application, fast drying qualities, and the fact that one coat covers without brush marks, makes Enameloid a very popular enamel for those who want a good finish at a minimum cost. Either inside or out, on small surfaces or large, for furniture, walls or woodwork, use Enameloid wherever you want a surface that is smooth, lustrous, full-gloss—and washable.

In a few hours Enameloid dries with a beautiful, full, porcelain-like finish which is most durable and resistant to wear, and may be washed repeatedly with soap and warm water. This immediately recommends its use for finishing the walls and ceiling of baths, kitchens, pantries, refrigerator rooms, laundries, and similar rooms where steam and vapors are present. A glass-smooth film of Enameloid resists boiling water, hot cooking and hot dishes, also stains from fruit juices and other beverages.

Any homemaker will find it easy to apply Enameloid. Anyone can give lustrous, colorful beauty to interior furniture and woodwork as well as porch and lawn furniture. The resultant smooth hard finish makes it very easy to keep the surfaces clean and bright looking. Enameloid comes in a wide assortment of colors selected for their popularity and decorative value.

Flat Black Enameloid has been formulated to produce a dull black, wrought iron finish on ornamental ironwork, lamps, gas fixtures, picture frames, moulding and similar surfaces. Flat Black should be applied with a camel hair or other soft type brush in smooth, even coats avoiding a heavy film and excessive brushing.

One gallon covers approximately 400 square feet—one coat. Color Card CC-487.

	$\frac{1}{2}$ Pint	$\frac{1}{4}$ Pint	Pint	Quart	Gallon
Black, 729.....					
Blue, 708.....					
Canton Jade, 705.....					
Cream, 704.....					
Fiesta Orange, 708.....					
Flame Red, 721.....					
Flat Black, 780.....					
Ivory, 701.....					
Killarney Green, 723.....					
Maple, 706.....					
Medium Brown, 716.....					
Milan Green, 707.....					
Pastel Blue, 714.....					
Peach, 719.....					
Seaspray Green, 723.....					
Sunny Yellow, 720.....					
White, 710.....					

Even Day 702

EXOLVENT
A UNIVERSAL THINNER

Economically priced Exolvent has no objectionable odor, and produces good flow in products to which it is added. The solvent properties of Exolvent are greater than the best mineral spirits. It is therefore, a preferred thinner for all kinds of paste and liquid paints, varnishes and enamels.

Exolvent is ideal for cleaning brushes as it leaves no gummy residue, as is the case when turpentine is used.

1/2 Pint ^{Pints} Quarts Gallons 5 Gallons

FILLER—PASTE WOOD
FOR FILLING ALL OPEN-GRAIN HARDWOOD

S-W Paste Wood Filler is a dependable product for filling all open-grain wood such as oak, walnut, mahogany, ash, etc. It dries hard and will not shrink or break away from the pores of the wood. Being easy to wipe and sand, its use provides a smooth surface for varnish, shellac or other finishes.

When used on dark colored or stained open grained woods, the filler should be tinted to a similar color with S-W Fluid Tinting Colors. Reduced with S-W Exolvent, Turpentine or Benzine to the consistency of thick cream, one quart will fill approximately 120 square feet.

Natural Oak, 1.....
Transparent

FIRST QUALITY FLUID TINTING COLORS

First Quality Fluid Tinting Colors are ready to use. Painters, decorators, artists, sign-writers and the home painter will find the following outstanding characteristics make them superior to ordinary oil colors.

- A. Pouring consistency permits the user to add Fluid Tinting Colors directly to the product to be tinted, whether it be enamel, wall paint, house paint, varnish or Glazing Liquid. (Not recommended for water emulsion paints or lacquers).
- B. The fluid consistency of these colors gives real economy and convenience.
- C. First Quality Fluid Tinting Colors are ground much finer than average oil colors—a quality of great importance in tinting fine enamels.
- D. These colors mix easily and completely with a minimum of stirring when added to the product to be tinted. There are no particles of pigment to streak the surface.
- E. Fluid Tinting Colors are economical to use since the higher tinting strength permits production of brilliant clear tints with minimum amount of added color.

SHERWIN-WILLIAMS PRODUCTS

FIRST QUALITY FLUID TINTING COLORS—Continued

PASTE OIL COLORS

Paste Oil Colors finely ground are supplied in tubes. They are especially suited for art work or tinting small quantities of paint or enamel.

Color Card CC-470.

	Fluid Tinting Colors Per Package			Paste Oil Colors Per Tube	
	$\frac{1}{2}$ Pint	Quart	Gallon	Small	Large
BLACK					
Lamp (CP).....					
BLUES					
Prussian.....			XXXX		
Ultramarine.....		XXXX	XXXX		
BROWNS					
Raw and Burnt Umber.....					
Raw Sienna.....					
Burnt Sienna.....			XXXX		
Vandyke.....			XXXX		
GREENS					
Chrome, Light.....					
Chrome, Medium and Dark.....			XXXX		
REDS					
Dragon.....			XXXX		
American Vermilion.....		XXXX	XXXX		
Venetian.....					
YELLOW					
Chrome, L, M and D.....			XXXX		
Yellow Ochre.....					
WHITE					
Flake White.....	XXXX	XXXX	XXXX		

FLAT-RITE

6147

INTERIOR ENAMEL UNDERCOATER

Flat-Rite is an interior enamel undercoater of highest quality which embraces latest developments of our Research Laboratories in a scientifically formulated enamel undercoater.

This product which is extremely white, has excellent "hiding" power. It is very finely ground, so that it can be mixed with highest quality gloss enamels to produce eggshell finish.

Flat-Rite flows onto the surface very evenly and has excellent leveling properties. It dries to a tight, flat finish which will hold out succeeding coats of enamel so as to produce a very beautiful effect. Surfaces on which Flat-Rite has been applied can be easily sanded when desired.

One gallon covers approximately 400 square feet, one coat.

$\frac{1}{2}$ Pint Pint Quart Gallon

.....

FLAT-TONE
THE WASHABLE FLAT WALL PAINT

Flat-Tone produces a rich velvety wall finish of the finest quality for interior walls and ceilings. Its beauty is of a very practical nature because the paint is durable and washes very easily.

The 8 beautiful shades are scientifically blended to harmonize with all modern and period home furnishings. These shades may be altered to suit individual taste in decoration by intermixing either with white, another color or through the addition of S-W Fluid Tinting Colors.

Flat-Tone covers in one coat. It may be applied over itself when repainting without first rescaling the surface, provided a similar color is used. Where surfaces are tight and there is a minimum porous condition, Flat-Tone may be applied without a first coat of Wall Primer and Sealer.

Painters will appreciate the many advantages of Flat-Tone which help them turn out better jobs economically such as (1) excellent brushability, (2) freedom from brush marking, (3) good "wet edge", (4) solid hiding power, (5) dependable uniformity and (6) pleasant colors.

Over a suitable foundation color, one gallon of Flat-Tone covers approximately 500 square feet, one coat.

Color Card CC-477.

	Quarts	Gallons	5 Gallons
Cottage Ivory, 805.....			
Dawn Blue, 808.....			
Hollywood Cream, 804.....			
White, 810.....			
Petal Rose, 800.....			
Seaford Green, 803.....			
Shadow Blue, 885.....			XXXX
Spring Green, 823.....			
Sunglow Yellow, 844.....			

FLO-LAC

FOR WOODWORK, FLOORS AND FURNITURE
STAINS AND VARNISHES IN ONE OPERATION

S-W Flo-Lac is a tough, hard-wearing varnish stain for use on woodwork, floors and furniture. It is easily applied with a soft brush and is ready for use after overnight drying. It resists sun, water, heel marks and scratching, and retains its gloss for a long period of time. The transparent nature of Flo-Lac does not tend to obscure the grain of the wood.

There are hundreds of uses for Flo-Lac. It is a splendid finish for floors, old furniture of all descriptions and all suitable interior surfaces. Having a wide variety of shades, it may be used for touching up worn and marred chairs, tables, radios and other furniture and woodwork most satisfactorily. A can of Flo-Lac and a Handcraft brush produce surprisingly good results.

Discolored and painted surfaces can be made attractive by covering them with Flo-Lac Ground after which the desired color of Flo-Lac is applied. It is possible to imitate a wood grain effect by using Flo-Lac Graining Preparation.

One gallon of Ground Color covers approximately 400 square feet while the same quantity of Flo-Lac Colors cover approximately 500 square feet, one coat. Colors shown on the color card are representative of colors of Flo-Lac over Ground Color. Flo-Lac applied to new wood will result in darker shades than that shown by the color card. CC-468.

	1/2 Pint	Pint	Quarts	Gallons
Dark Oak, 109.....				
Light Oak, 108.....		XXXX		
Mahogany, 106.....				
Maple, 111.....				
Walnut, 107.....				
Ground, 110.....		XXXX		
Graining Preparation, 112.....	XXXX			XXXX

SHERWIN-WILLIAMS PRODUCTS

GALVITE GALVANIZED IRON PRIMER GRAY

Galvite is a specially formulated primer designed for use on galvanized iron or other zinc coated metal surfaces, to prevent corrosion of these surfaces while providing an ideal surface for the application of any type of finishing coat. For best results when applying Galvite to new metal, it is important that the galvanized surface first be washed with one of the recommended proprietary chemical preparations. Dilute acetic acid, vinegar, or copper sulfate solutions may also be used for this purpose.

Galvite adheres to the metal, provides tooth for the finishing coats, and has durability. Covers approximately 700 square feet per gallon and dries to touch in 8 hours—to recoat in 48 hours. Descriptive Folder E-671.

Quarts Gallons 5 Gallons
.....

GLAZING LIQUID FOR BLENDING AND ANTIQUING

Glazing Liquid has been specially formulated for blending and antiquing work. When applied to a surface it is colorless unless tinted with Paste Oil Colors or First Quality Fluid Tinting Colors. S-W Glazing Liquid is translucent and permits the color over which it is applied to show through when wiped and blended. It may be applied over most painted surfaces including Flat-Tone, Semi-Lustre, Enameloid or gold and silver bronze or leaf to produce so-called "mottled" or "tiffany" wall effect. It is also recommended for antiquing, polychroming, wiped enamel finishes, parchment lamp shades, etc.

It dries overnight to a dull or egg-shell lustre and, containing no wax, can be repainted without difficulty. Being a specially treated oil preparation of fairly heavy body, this Glazing Liquid may be washed easily with soap and water. Although S-W Glazing Liquid provides a very durable finish, in some instances, woodwork and pieces of furniture are subjected to extremely hard usage and, consequently, require additional protection. All glaze finishes can be coated with Mar-Not Satin Finish Varnish to preserve the finish indefinitely and simplify washing.

One gallon covers approximately 750 square feet—one coat. Descriptive Folder E-688:

751 ½ Pints Quarts Gallons
.....

KEM-NAMEL SNOW WHITE GLOSS FOR INTERIOR AND EXTERIOR USE

Sherwin-Williams Kem-Namel Snow White Gloss is a high quality gloss enamel. Its remarkable hiding and covering plus its unsurpassed toughness puts Kem-Namel in a class by itself. The intense whiteness and rich full gloss, the extremely easy brushing and perfect flow are a combination of outstanding qualities which results in one of the most attractive enamel finishes it is possible to produce.

Not only does Kem-Namel Snow White have a beautiful whiteness immediately after application, but it retains that whiteness for an exceptionally long time. This enamel can also be tinted with S-W Fluid Tinting Colors to any desired pastel shade.

Kem-Namel Snow White Gloss represents a formulation of the highest quality raw materials which assures a smooth enamel finished surface. For best results it should be applied over the undercoater recommended for the particular job, depending upon whether it is an exterior surface or an interior wall, woodwork, plaster, etc. It dries dust free in 2 to 3 hours—hard in 12 to 16 hours, covering approximately 400 square feet per gallon, one coat.

Quarts Gallons 5 Gallons
.....

KEM-TONE

Kem-Tone, the miracle wall finish for interior walls and ceilings, is a synthetic resin and oil paint so treated that it takes water as a thinner instead of turpentine, mineral spirits or other paint thinners. In this way the advantages of oil and water paints are combined at the same time eliminating the disadvantages of both.

Here, then, we have a product with such outstanding characteristics as the following:

A completely flat wall finish of style and beauty, which provides perfect light diffusion without glare and obliterates unsightly appearance of rough and uneven wall surfaces.

Colors with eye appeal—Kem-Tone colors make any room more inviting, more attractive, more livable.

Dries in less than an hour. When the water evaporates the paint is dry. Rooms can be put back in order immediately after painting.

Economical—comes in paste form; 1 gallon reduced with water makes 1½ gallons of ready to use paint.

No disagreeable odor of paint thinners or solvents. Rooms can be occupied immediately after painting.

Covers most surfaces with just one coat—painted or unpainted walls, plaster, cement, wallpaper, wallboard, plywood, brick, building tile, etc. (Unpainted plaster normally requires two coats.)

No sizing or priming—except on surfaces with extreme variations of suction or porosity.

Speed and ease of application—use a large flat wall or Semi-Dutch Brush and flow on generously. No laps or brushmarks will show. Can also be sprayed.

Decorative finish—beautiful stippled effects are easily, speedily obtained using the Kem-Tone Super-Cushion Roller-Koater.

Permanent durable finish—assured by its Kem Thermo-Tempered oil and synthetic resin film.

Washable—Kem-Tone may be easily cleaned with wallpaper cleaner or ordinary wall washing cleaners.

No fire hazard—does not require inflammable solvents or thinners.

Quick convenient clean-up—brushes and equipment easily cleaned with soap and water after using.

Because of these advantages Kem-Tone is the ideal finish, not only for the home but for offices, stores, factories, schools, hospitals, institutions, public buildings, hotels, etc. Color Card KT-1F.

Avalon Blue, 65403.....	Quarts	Gallons	5 Gallons
Beechwood Beige, 65422.....			
Belmont Ivory, 65401.....			
Beldedre Cream, 65404.....			
Cameo Rose, 65417.....			
Cascade Green, 65420.....			
Heather Rose, 65423.....			
Midland Green, 65405.....			
Pale Jonquil, 65406.....			
Peach Tint, 65407.....			
Turquoise, 65419.....			
Wellington Buff, 65402.....			
Willowick Blue, 65421.....			
Yorktown White, 65400.....			

Intense White 65424

Berkeley Green 65435

Sheddie Gray 65434

— 14 —

SHERWIN-WILLIAMS PRODUCTS

KEM-TONE VOGUE DEEP COLORS

Kem-Tone Vogue Deep Colors will add that new look to any room. With these eight Deep Colors it is possible to make an endless variety of wall shades from delicate, soft pastels to the newest, smartest colors in deep, rich tones to harmonize, contrast or match perfectly with other S-W paints and the latest colors in rugs and drapes.

Being made in the same high quality as Kem-Tone, Vogue Deep Colors should not be compared with ordinary casein paints or fresco colors. They are designed to dry to a flat, matte finish and can be used in the following manner:

1. Full strength as deep brilliant Wall Colors.
2. Intermixed with each other to produce other interesting tones.
3. Intermixed with regular Kem-Tone Colors to produce an endless variety of new Kem-Tone Colors.
4. Let-down with white to produce softer tones of the Kem-Tone Vogue Deep Colors.

Vogue Deep Colors and deep intermixes of deep colors should be applied with a Super-Cushion Roller-Koater. This will produce a smooth even stippled effect usually seen in much more expensive finishes. Two coats must be applied. Color Card KT 551.

	1/2 Pint	Quart
Vogue Blue, 65425.....		
Vogue Brown, 65432.....		
Vogue Burgundy, 65430.....		
Vogue Green, 65428.....		
Vogue Red, 65426.....		
Vogue Sienna, 65429.....		
Vogue Umber, 65431.....		
Vogue Yellow, 65427.....		

PLASTIC PATCH

AN ALL-PURPOSE PATCHING, SURFACING AND FILLING COMPOUND

Plastic Patch is a synthetic compound of plastic materials for repairing damaged walls and woodwork to be painted or enameled.

No muzz, no under-cutting or soaking of the edges of old plaster are necessary. Mix with water—stir to a soft paste, apply with a flexible broad knife, putty knife or trowel.


Will adhere to surfaces without shrinking or cracking.

PER PACKAGE

1 lb. 2 1/2 lbs. 5 lbs.

KEM-TONE SUPER-CUSHION ROLLER-KOATER

THE CONVENIENT, EASY WAY TO APPLY KEM-TONE



Rolls Kem-Tone on like magic with fine stipple texture not possible to duplicate with brush application. Designed for use with Kem-Tone and other oil paints.

When used with Kem-Tone wash with soap and hot water. When used with other oil paints wash with mineral spirits then in soap and hot water. (Do not wash in lacquer thinner.)

Each

SHERWIN-WILLIAMS PRODUCTS

KEM-TONE TRIMS

Kem-Tone Trims are distinctive trims or borders that add the final touch of style and charm to Kem-Tone painted walls. They have been especially designed to harmonize with Kem-Tone wall colors. They are prepepsted and easy to apply—color-fast and washable.

Trims No. 208, 210, 212, 214, 216, 218, 220, 222—2 in. wide (1- $\frac{1}{8}$ in.)

Trims No. 302, 304, 306, 310, 312, 314, 316, 318, 320, 322, 324, 326—3 in. wide.

Trims No. 402, 404, 408, 410—4 in. wide.

PER ROLL
2 inch 3 inch 4 inch

KEM-TONE BRUSH

Scientifically designed and constructed to enable consumer customers to obtain top-quality Kem-Tone jobs by brush application.

Width 4 inches, thickness $\frac{1}{4}$ inches, length clear 8 $\frac{1}{4}$ inches.

Made with pure Neoceta Bristles—synthetic bristles that pick up and carry more paint than Chinese hog bristle.

Neoceta Bristles anchored in vulcanized rubber.

Streamlined type of beavertail handle that fits snugly in the hand, and is comfortable to use, which makes painting easy.

Handle enameled in Royal Blue with "Kem-Tone" imprinted in Yellow. Handle block enameled in standard Kem-Tone label Yellow.

Metal ferrule embossed with "Kem-Tone Brush" on one side and "Pure Neoceta Bristles—vulcanized in Rubber" on the reverse side.

Brush wrappers are in standard Kem-Tone label Yellow, imprinted with "Kem-Tone Brush" on the front, with cleaning instructions on the back of the wrapper.

Although especially designed to apply Kem-Tone, the brush is suitable for applying all types of oil paints.

With reasonable care, the Kem-Tone Brush will give long and satisfactory service. It should always be cleaned promptly after use. Clean with soap and water after applying Kem-Tone. Clean with Turpentine or Mineral Spirits after applying oil paints. **DO NOT USE THE BRUSH IN LACQUER, OR CLEAN IN LACQUER THINNER OR PAINT AND VARNISH REMOVER.**

Each

SHERWIN-WILLIAMS PRODUCTS

KEM-GLO THE MIRACLE LUSTRE-FINISH OF MODERN PAINT CHEMISTRY



The most beautiful, easiest to clean lustre wall finish, Kem-Glo—is the miracle achievement of modern paint chemistry; scientifically engineered and manufactured to produce an amazingly tough, durable finish that looks and washes like baked enamel. It is a wonderful, tile-like finish for walls and woodwork in kitchens, bathrooms, nurseries, playrooms, hallways and for all woodwork in every room in the house.

All shades in the Kem-Glo line match or harmonize with Kem-Tone colors enabling the architect to achieve smartly styled home decoration effects to harmonize with the latest colors in home furnishings. S-W Fluid Tinting Colors may be used to produce a large variety of beautiful pastel shades. Kem-Glo is also a superior finish for furniture, either wood or metal, and is equally suitable for interior and exterior use.

Kem-Glo comes ready to use, covers most surfaces (except dark colored surfaces) in one coat and dries in three to four hours under normal conditions. No wall primer for wall surfaces or enamel undercoater for wood surfaces are needed and one gallon is sufficient for an entire average kitchen—walls, woodwork and cabinets. Two quarts will do the average bathroom and one quart for woodwork in the average living room, dining room and bedroom.

Kem-Glo quarts are filled in a patented, attractive, easy-to-open, easy to close Circle Seal container. This is the first step forward in paint packaging in decades and we are proud that Kem-Glo should be given this distinction. Color Card KG-1.

	Quarts	Gallons
Arbor Green, 51408.....		
Canterbury Gray, 51410.....		
Capri Blue, 51405.....		
Georgian Cream, 51402.....		
Lakeland Blue, 51404.....		
Mandalay Ivory, 51401.....		
Maywood Green, 51408.....		
Rose Coral, 51409.....		
Seacrest Green, 51407.....		
Stay-White, 51400.....		
Sunbury Yellow, 51403.....		

KEM-GLO BRUSH

A pure China bristle Kem-Glo Brush is available as a companion item to Kem-Glo.

Width $2\frac{1}{4}$ inches, thickness $\frac{1}{8}$ inches, length clear $2\frac{3}{4}$ inches.

Its size makes it ideal for use in a Kem-Glo quart container.

The two-tone handle finished with blue and maroon enamel match the colors on the Kem-Glo can. In addition "Kem-Glo Trim Brush" imprinted on the handle further identifies it as a companion item.

Although designed primarily as a Kem-Glo brush for trimming it is suitable for applying all types of paint, varnish and enamel.

Each

— 17 —

SHERWIN-WILLIAMS PRODUCTS

LIN-X CLEAR GLOSS VARNISH FOR INTERIOR AND EXTERIOR USE

Lin-X Clear Gloss is a transparent varnish that is tough. By combining these essential requisites of a good varnish it has unlimited uses, giving beauty and protection both inside and out. Resistant to boiling water, sizzling grease, fruit juices, even alcohol, it flows on smoothly and is easy to apply to linoleum, floors, furniture, woodwork, doors, boats, etc. It is also easy to clean. This varnish is recommended as a top quality, all purpose, serviceable gloss finish.

One gallon covers approximately 550 square feet, one coat.

Flat Quart Gallon 5 Gallons

METAL PRIMER RED *No. 49*

An economical, effective primer formulated particularly for use on structural and ornamental iron, steel and other surfaces which require protection from rusting. It should not be used over galvanized iron, galvaneal or other zinc-coated surfaces unless they have been exposed to the weather for at least a year, or have been given special washing treatment to neutralize the chemicals used in the plating process.

Metal Primer Red possesses good weather-resistance and durability. One full coat gives a solid covering and a tough, flexible film that will have intimate adhesion to the metal surface over which it is applied. Its overnight dry, non-bleeding and low gloss characteristics have been designed to provide a foundation for interior or exterior paints and enamels.

Covering capacity: Approximately 600 square feet per gallon, one coat.

Quarts Gallons 5 Gallons

PAINTER CRAFT FINISHES

ONE COAT FLAT WALL PAINT No. 10 (630)

Painter Craft One Coat Flat Wall Paint No. 10 is the outstanding quality one coat flat wall paint on the American market today. Reduced with one to two pints of S-W Evolvent or mineral spirits to the gallon, it has excellent brushing and flowing qualities and dries overnight to a tough, uniform flat film with a pleasing sheen when viewed at an angle.

No. 10 is a full-bodied, intensely white, washable flat wall paint which will do a one-coat job of hiding over many surfaces that would ordinarily require a coat of primer and sealer, plus a flat wall paint. This one coat application is designed primarily for use on nearly all types of interior surfaces and finishes, such as plaster, plaster board, flat paint, water paint and various types of wall board.

When necessary to apply two coats to cover exceptionally dark surfaces, simply apply a second coat of One Coat No. 10 in the same manner as the first coat. On surfaces having extreme variations in porosity, such as tight painted areas broken by porous plaster patches, a surface uniforming coat of Pigmented Sealer No. 77 is recommended.

Covering capacity: One gallon will cover 550-800 square feet, one coat when reduced according to directions.

Gallons 5 Gallons

PAINTER CRAFT FINISHES — Continued

INTERIOR SEMI-GLOSS No. 16 (616)

Interior Semi-Gloss No. 16 is a high-quality semi-gloss finish for walls and woodwork. It has the hiding power characteristics of a wall paint, yet it levels out like an enamel. It spreads easily with a wall brush—does not run or sag.

No. 16 dries hard overnight with a rich, half-gloss that will withstand repeated washings.

When used on unpainted walls or ceilings or over previously painted surfaces which are extremely porous or lack uniformity, a first or prime coat of Pigmented Wall Sealer No. 77 is recommended.

Covering capacity: Approximately 500 square feet per gallon, one coat on average surfaces.

Gallons 5 Gallons

.....

PIGMENTED WALL SEALER No. 77 (647)

Wall Sealer No. 77 is a full bodied, pigmented first coater and sealer for inside surfaces of plaster, brick, concrete, tile and most composition boards.

Ordinarily one coat will prime and seal properly and furnish an excellent tooth for the next coat. If the surface is unusually porous, however, it may be necessary to apply a second coat, or at least, touch up the unsealed spots.

Pigmented Wall Sealer No. 77 is easy brushing, levels well and dries overnight.

Covering capacity: 300 to 500 square feet per gallon, one coat, varying according to the porosity of the surface.

Gallons 5 Gallons

.....

ONE COAT ENAMEL No. 39 (639)

One Coat Enamel No. 39 is a full-bodied enamel built especially for maintenance work where it is important to obtain one-coat hiding over old surfaces on "price" jobs.

No. 39 is easy working and builds uniformly without sags or runs. While it has good leveling qualities, it holds its "build" uniformly in the corners of panels and on the edges of moldings, etc., which is important for one coat work.

One Coat Enamel No. 39 has good whiteness and retains whiteness, excellent hiding, a deep full gloss and dries overnight. Ordinarily it should be applied as it comes in the package but may be thinned with approximately $\frac{1}{2}$ pint of S-W Exsolvent, turpentine or mineral spirits for wall work.

Covering capacity: Approximately 300 square feet per gallon, one coat.

Gallons 5 Gallons

.....

PAINTER CRAFT FINISHES — Continued

XXX ENAMEL UNDERCOATER (643)

Painter Craft XXX Enamel Undercoater is an intensely white and finely ground enamel undercoater of highest quality. It has excellent brushing, levels well and dries overnight to a tight, close-knit film which holds out the enamel beautifully. This popular undercoater is ground so fine that a minimum of sanding is necessary. A slight sanding produces an economical hand rubbed effect.

XXX is outstanding because of its clean, fine grinding. Its fineness of grind makes it possible to mix it with enamels to produce a high grade dull enamel with varying degrees of sheen depending upon the amount of XXX Undercoater added.

Covering capacity: Approximately 400 square feet per gallon, one coat.

Gallons 5 Gallons
.....

FLOOR AND TRIM VARNISH (022)

Sherwin-Williams Painter Craft Floor & Trim Varnish is a product made especially for the painting contractor and decorator for general use on floors, woodwork or finishes where an elastic and durable interior clear coating is desired.

It dries, dust free, in 1 to 2 hours under normal conditions and can be walked on lightly in about 15 hours. Painter Craft Floor & Trim Varnish resists hot and cold water, soaps and detergents.

Covering capacity: Approximately 500 square feet per gallon, one coat.

Gallons 5 Gallons
.....

PAINTERS' PASTE PAINT WHITE No. 66

For Painters who want a Superior Hand-Mixed Paint. A high quality exterior paint, prepared in soft-paste consistency. Requires only the addition of linseed oil and turpentine to make it ready for use. No. 66 is economical to use because it can be reduced approximately gallon for gallon, thus producing two gallons for one.

No. 66 has desirable qualities of both opacity and whiteness because it has greater resistance to atmospheric discoloration than White Lead. It is made on a carefully balanced formula of S-W Oxide lead-zinc pigment, White Lead Carbonate and Titanium Magnesium.

No. 66 has uniform shallow chalking action which helps to shed the dirt thus prolonging the good appearance and useful life of the paint.

Gallons 5 Gallons
.....

SHERWIN-WILLIAMS PRODUCTS

PORCH AND FLOOR ENAMEL FOR ALL INTERIOR AND EXTERIOR FLOORS

6145

Sherwin-Williams Porch and Floor Enamel will give interior and exterior floors a rich, colorful and lasting finish. One easily applied coat covers solidly and restores the good looks of all but the most badly worn floors. This synthetic enamel dries overnight. Dust, dirt and grime wash off easily with such little effort.

Porch and Floor Enamel will resist hard wear and repeated cleaning and scrubbing—will withstand outside exposure to sun, water and gritty sand. It is an extra-tough protection too, an ideal finish for interior and exterior floors and steps, worn linoleum, boat decks, metal stairs, dadoses, and dry concrete floors.

Porch and Floor Enamel is not recommended for concrete floors laid directly on the ground. Paint applied to such surfaces will invariably peel or powder off due to the presence of moisture that would aid saponification by the concrete.

Alkaline cement floors must be neutralized by applying a wash made up of 8 pounds Zinc Sulphate to the gallon of water in order to allow proper drying of the paint film.

Covers approximately 500 square feet—one coat per gallon. Color Card CC-469.

	Quarts	Gallons
Dark Gray, 153.....		
Dark Oak, 155.....		
Light Gray, 151.....		
Mahogany, 157.....		
Medium Gray, 152.....		
Oak, 154.....		
Tile Green, 159.....		
Tile Red, 158.....		
Walnut, 156.....		

PREPARITE

Preparite is a clear, non-abrasive liquid developed specifically to simplify the work of enameling or varnishing over old surfaces.

A rag moistened with Preparite will remove wax, grease, polish, etc., from old surfaces. It deadens the gloss of varnish or enamel and temporarily creates a slight tack to which the new finish can bond and anchor firmly. It does not leave any caustic residue to be neutralized and washed off.

On a glossy surface that is clean, sanding of the old finish may be omitted. Add four ounces of Preparite to the gallon of varnish or enamel to insure a deep, firm bond and avoid the chances of the enamel or varnish "shelling" when applied over an unsanded surface.

NOTE: Preparite should be used on old finishes only—never on a new finish or a between-coat, as it is likely to soften and lift a new film.

Descriptive Folder E-633.

1/2 Pints Pints Quarts

Brush
Cleaner

SCREEN ENAMEL BLACK

Sherwin-Williams Screen Enamel Black is a durable high-gloss enamel formulated especially to withstand outside exposure, and prevent rusting of window and door screens. The use of Screen Enamel Black assures longer life for your screens and prevents unsightly corrosion stains on surfaces painted white or light tints.

For best results when using Screen Enamel Black on these surfaces, be sure the surfaces are dry, clean and free from all loose dirt or paint. The use of a wire brush will clean the surface adequately with a minimum of effort.

In most cases, Screen Enamel Black may be applied as it comes in the package. However, if it is apparently too heavy for certain work, it may be thinned with Exolvent or turpentine without losing its protective qualities.

One quart covers the screens of an average 8 room house.

1/2 Pint Pint Quart Gallon

SEMI-LUSTRE

SATIN-FINISH FOR WALLS AND WOODWORK

Semi-Lustre, an interior finish of high quality, is scientifically formulated to include the hard drying and washable qualities of an enamel, together with the brushing and working qualities of an oil paint. It "levels" beautifully without brush marks, covers well and dries with a soft pleasing gloss. Needing no undercoat on interior new wood, it is quick and easy to apply.

The uses of Semi-Lustre are manifold. It answers every problem as a wall and woodwork finish in hospitals, schools, public buildings, etc. Being a tough, hard-drying oil type finish, Semi-Lustre is well suited to heavy duty walls and woodwork, providing durability, washability and freedom from the harsh reflections of a full gloss wall finish.

Semi-Lustre is a popular wall finish for bathrooms, kitchens and laundries, where these eight colors lend their beauty in modern decoration. It dries with a smooth satin-lustre that does not catch dirt easily, and may be washed readily with soap and water to restore its original finish. The lustrous, durable film resists the steady beating these rooms must take.

The beautiful, mellow, satin glow produced with Semi-Lustre lends itself to the finishing of woodwork or wood trim throughout the home. Semi-Lustre colors match or harmonize with Flat-Tone and Kam-Tone shades for coordinated wall and trim decoration. It can also be tinted, if desired, with S-W Fluid Tinting Colors by which it is possible to secure a variety of shades.

Semi-Lustre dries to re-coat in 24 hours, and has a covering capacity approximately 500 square feet one coat per gallon on average surfaces. Color Card CC-466.

	Pint	Quart	Gallon	5 Gallons
Ivory, 201.....				
White, 210.....				
Cream, 204.....				XXXX
April Yellow, 205.....				
Colony Buff, 206.....				
Pastel Green, 208.....	XXXX			XXXX
Peach Glow, 209.....				
Vista Green, 211.....				
Vogue Blue, 212.....				

Low Price 207

SHINGLE STAIN

6629

Sherwin-Williams Shingle Stain is formulated with treated oils and color-fast pigments. This stain gives excellent protection for shingle roofs, shingle and rough-sawn siding, or any rough outside wood surface. It brings out the natural beauty of the grain of the wood and adds to it a rich and distinctive coloring.

Shingle Stain may be applied to shingles by dipping if the application is to be made to new shingles before they have been laid. Back priming through this method of application adds years to the life of the shingles.

The shades of Shingle Stain will vary according to the various types of wood applied to. It should be pointed out that the samples shown approximate only the shades which may be obtained when used on Red Cedar. S-W Shingle Stains are rich in color, warm and harmonious, and after they have aged they become even more soft and pleasing in tone. Since this Shingle Stain penetrates very deeply, stained surfaces retain their color exceedingly well.

A two coat application of S-W Shingle Stain is recommended for best results. They produce a more uniform finish and give additional protection. The first coat should be applied as it comes from the package. However, the final coat should be reduced with one pint of pure raw linseed oil for greater protection. This applies particularly where the stain is to be used on old weathered shingles.

One gallon covers approximately 150 square feet, one brush coat. Color Card CC-838.

	Gallons	6 Gallons
Indian Red, 765.....		
Nut Brown, 753.....		
Thatch Brown, 757.....		
Dark Green, 761.....		
Medium Green, 763.....		
Silver Gray, 771.....		

STOVE AND IRON ENAMEL

Stove and Iron Enamel is an all-purpose, glossy, heat resisting, utility finish for interior and exterior surfaces and metal surfaces subjected to heat. It may be used as a decorative finish on metal surfaces where a glossy, black finish is desired, such as: stoves, pipes, iron trusses, hand rails, iron fences etc.

One pint covers approximately 100 square feet, one coat.

1/2 Pint 1/2 Pint Pint

TAXITE

1785

PAINT AND VARNISH REMOVER

Quick-acting Taxite penetrates old paints, varnishes and enamels and softens them for easy removal within a short time. After the Taxite has softened the old film, it can easily be removed with a putty knife, scraper or rag. Corners, moldings, carvings, etc. may be cleaned out by using a small wire brush or steel wool.

Taxite does not damage the surface, raise the grain or loosen veneers as do removers made with water.

After the old film has been removed, wash the surface thoroughly with a rag moistened with S-W Solvent or turpentine to eliminate the wax and all remaining residue. Use alcohol as a wash for shellacked surfaces.

Taxite is recommended for cleaning brushes.

1/2 Pint Quarts Gallons

SHERWIN-WILLIAMS PRODUCTS

TINNERS RED

Sherwin-Williams Tinnens Red is a high quality oil paint designed for priming and/or painting galvanized iron gutters, flashings and drainspouts.

Before applying Tinnens Red to new galvanized iron we recommend that the surface be etched by washing with dilute acetic acid or vinegar.

Tinnens Red can also be used on structural steel, iron, brick or wood. It covers approximately 800 sq. ft. on metal surfaces or 600 sq. ft. on wood surfaces per gallon.

Quarts Gallons 5 Gallons

.....

TRACTOR AND IMPLEMENT ENAMEL

Tractor and Implement Enamels will give excellent service on tractors, farm implements, wagons, trucks and jeeps as well as garden tools, water pumps, mowing machine, wheel harrows, metal fences and all exterior wood or metal surfaces.

It is easy to apply and produces a tough, high gloss finish that resists the elements.

Valuable wood or metal equipment can be protected by this quick drying, easily-applied S-W Tractor and Implement Enamel by touching up rust spots or giving it a periodic painting.

The colors match standard colors of leading farm implement manufacturers.

Covers approximately 400 square feet per gallon, one coat. Color Card CC-472.

	Quarts	Gallons
Black, 557.....		
Gray, 558.....		
Green, 552.....		
Yellow, 551.....		
Orange, 554.....		
Red, 553.....		

TRAFFIC ZONE PAINT

These flat finish zone paints can be used on all kinds of pavement. Prepared in ready-to-use consistency, they work easily and have good hiding. Dry to touch in 10 minutes and free from pick-up by traffic in 30 to 40 minutes when applied in favorable painting weather.

One gallon will cover approximately 400 linear feet, 4 inches wide, one brush coat. Color Card CC-243.

	Gallons	5 Gallons
White, 37.....		
Yellow, 38.....		

SHERWIN-WILLIAMS PRODUCTS

PURE SPIRITS OF TURPENTINE

WOOD SULFATE—03914

A product refined and purified in our Chicago Factory, S-W Pure Spirits of Turpentine is in many ways superior to pure gum spirits and more economical. Its solvent strength is at least equal and in some cases slightly better than gum spirits, and nearly twice that of mineral spirits. It has a mild odor and meets government specifications TT-T-801, which supercedes LLL-T-871b.

Turpentine is generally recommended by chemists for thinning outside house paint (when thinning is necessary) because they have learned through experience that its penetrating power gives two definite advantages: (1) Better adhesion over hard surfaces (2) Avoidance of finish coat crawling over a slick priming coat.

Turpentine is also best for thinning varnishes. It prevents curdling, speeds up drying and cleans the brushes when the job is done.

Pints Quarts Gallons Gallons Drums

UTILITY PAINT R AND B

R and B Utility Paint is a general serviceable paint for any exterior surface where a good quality, economical paint is required. Made from salvage paints due to overgrinds, damaged containers, etc., including even our highest quality products, it is most applicable to paint jobs where an excellent Utility paint is needed and color is not a prime requisite. Summer cottages, garages, buildings, structural iron work, bridges, roofs, (except composition) are among many suggested places where R and B Utility Paint may be used at a saving to the customer.

Reduce R and B Utility Paint with raw linseed oil, proportions depending upon type and porosity of the surface to be painted. One gallon covers approximately 500 square feet, one coat. Color Card CC-140.

Black, 292.....	} Gallons 5 Gallons
Bronze Green, 293.....	
Brown, 294.....	
Gray Slate, 295.....	
Red, 296.....	

MAR-NOT

TOP QUALITY INTERIOR VARNISH

For Floors, Furniture and Woodwork

Mar-Not Varnish is a highly water-resisting, serviceable and wear-resistant clear varnish formulated primarily for use on interior floors, woodwork and furniture. This top quality varnish is produced under close supervision and control throughout every step in its manufacture to assure its meeting many rigid tests, some of the most outstanding performance tests of which are listed below.

1. Dry to touch in not less than $\frac{1}{2}$ hour in order to assure good wet edge, brushability, and not over $2\frac{1}{4}$ hours to minimize dust catching.
2. Dry firm overnight for recoating (14 hours).

MAR-NOT — Continued

3. Dry tack free in 16 hours to test of paper pressed upon varnish or to withstand foot traffic.
4. Dry hard enough in 48 hours to permit rubbing with F.F. pumice and mineral oil.
5. Resists liquids such as fruit juices, tea, coffee and beverages, tests being performed on films which are 96 hours old.
6. Immersion in boiling water for one hour produces no visible effect. Likewise, immersion in cold water for 72 hours shows no apparent effect.
7. Wet neutral soap blocks, such as Ivory, placed on film for one hour, then rinsed off leave no permanent mark on the film.
8. Immersion in 50 per cent grain alcohol (188 proof cut to 94) for 16 hours shows only moderate softening, and recovery is complete in less than 1 hour. This compares with the effect of straight whiskey or gin left on the film overnight.

Because of its fine, full film and sharp lustre, Mar-Not is popular as a trim varnish, as well as a finish for floors and furniture. One quick coat gives new beauty to any previously finished wood surface. Mar-Not dries to a clear, smooth, hard finish that keeps dirt and grime from rubbing in. A sparkling clean surface is easily maintained by an occasional wiping with a damp cloth or mop.

To assure a beautiful, high quality and long wearing finish with Mar-Not Varnish, it is of utmost importance that individual effort be made to adequately prepare the surface for careful application of the varnish. The suggestions on the label of the can prepared for guidance should be followed closely to wind up with a varnish job of which any one will be proud.

One gallon covers approximately 550 square feet, one coat. Color Card CC-473.

1/2 Pint Pint Quart Gallon

MAR-NOT SATIN FINISH

FOR FLOORS, FURNITURE AND WOODWORK

Mar-Not Satin Finish gives floors, trim and furniture the beautiful, mellow smoothness of a fine hand-rubbed finish quickly and easily without the effort of rubbing. It stubbornly resists marring, scratching and scuffing and will stand up as ruggedly, as lastingly as the toughest gloss varnish. Mar-Not Satin Finish is recommended wherever a clear varnish with a dull finishing sheen is needed for all types of woodwork, every type of wood floor.

Always apply over a prime coat of Mar-Not Gloss varnish.

It dries dust-free in 8 hours and hard enough in 16 hours to withstand light foot traffic. Covers approximately 550 square feet per gallon, one coat. Color Card CC-473.

1/2 Pint Pint Quart Gallon

SHERWIN-WILLIAMS PRODUCTS

REXPAR KING OF ALL SPAR VARNISHES

Rexpar, a colorless spar varnish, produces a tough elastic film that is very durable, able to withstand the wear and tear of varying weather conditions without water spotting or discoloring. It has extreme elasticity, absolute resistance to fresh and salt water, to wind and parching sun. These outstanding characteristics make Rexpar an ideal spar varnish for motor boats, station wagons, delivery trucks, and for all nautical and aeronautical varnish requirements. The use of Rexpar is highly recommended for kitchens, bathrooms, laundries and for window sills, outside doors, porch ceilings and other places in or around the home where surfaces are subjected to much abuse from the elements.

We put into Rexpar the maximum amount of oils which give it elastic qualities and weather resisting properties. It will not turn white and dries elastic to be able to expand and contract without cracking under extreme variations of temperature.

This King of All Spar Varnishes is easily applied and can be had in many sized packages. It dries dust free in 2 to 3 hours, can be recoated in 15 to 18 hours. Covers approximately 650 square feet per gallon, one coat.

½ Pint Pint Quart Gallon

Gym Floor Finish

FLOOR SEAL THE WOOD FLOOR HARDENER

Floor-Seal, a wood floor surface sealer and hardener is not intended to produce a varnish film. It penetrates into the wood and hardens it from within by filling the pores and actually toughening the fibres of the wood itself. Dust does not adhere, dirt is quickly and easily removed, and heavy duty floors are kept looking their best.

Water and other liquids soon deteriorate wood flooring when it is left unprotected, resulting in discoloration and uncleanness. The fibrous condition of this surface holds dirt like a carpet. Ordinary floor oils also are unsatisfactory. They are dust catchers as they do not dry properly, and they darken and discolor wood. Floors sealed with S-W Floor-Seal are sealed tight, are unaffected by water, do not discolor, and absorb no water.

Floor-Seal possesses the following outstanding advantages for use on wood floors in schoolrooms, stores, factories and mills where the service is too heavy for either a floor varnish, floor enamel or any surface finish.

1. Does not darken the wood as does hot linseed oil.
2. It dries completely and is not a dust-catcher as are linseed oil and other floor oils.
3. Floor-Seal does not make the floor slippery as do floor oils. Accident insurance companies recognize this fact.
4. A floor finished with Floor-Seal may be waxed for dancing with perfect satisfaction after drying six to eight days.
5. For regular maintenance after the floor is sealed, periodic applications of S-W Self-Polishing Wax is recommended.

One coat of Floor-Seal is our standard recommendation for hard wood floors as it is not intended to produce a varnish film over the surface. This one coat will enter completely into the wood, leaving little or no surface film. It remains in the wood, maintaining a hardened wood surface even as the wood surface wears down. For soft wood floors two coats are usually required. Where Floor-Seal is to be applied to open grain woods, it is recommended that S-W Paste Wood Filler be used first.

Floor-Seal is economical and easy to apply. Brush or mop it on the wood, making certain favorable penetration has been made into the wood. One gallon will seal approximately 500 square feet, one coat.

Quart Gallon 5 Gallons

SHERWIN-WILLIAMS PRODUCTS

ALL PURPOSE SPAR VARNISH

Sherwin-Williams All Purpose Spar Varnish is a pale colored, hard drying varnish planned particularly for those interested in a general purpose varnish that possesses good coverage on floors, woodwork and exterior surfaces such as doors, porch ceilings, etc. for a minimum cost. This finish will resist chipping or cracking, scratching, scuffing, staining and water spotting. It will provide a good gloss surface and excellent protection.

This medium priced varnish is easy to apply, covers evenly and produces a smooth lustrous finish that resists hot and cold water, soaps and detergents. It dries dust free in 1 to 2 hours under normal conditions and can be walked upon lightly in 12 to 14 hours. It can be recoated after 18 hours.

All Purpose Spar Varnish (V98) covers approximately 550 square feet per gallon, one coat.

1/2 Pint Pint Quart Gallon

V 94 QUICK DRYING VARNISH FOR FLOORS AND WOODWORK

This quick drying varnish represents remarkable value and can be recommended to all who require moderately priced varnish. The gloss and elasticity, which are good, keep floors and woodwork protected and beautiful. Being a pale, light color, V 94 will not darken or discolor woods over which it is applied.

While of a fairly heavy body, this varnish does not require reduction, except on the first coat of new work where it is advisable to thin it with approximately one pint of S-W Solvent or turpentine to the gallon. It dries dust free in about 2 hours and hard in 18 hours. It can be sanded in 17 to 24 hours and rubbed in approximately 72 hours. It covers approximately 500 square feet per gallon, one coat.

1/2 Pint Pint Quart Gallon

Q. D. DRIER

A quality drier for general use. Made from the best materials. It will dry linseed oil perfectly when mixed in the proportion of about one part of drier to twenty parts of oil. This drier will mix with oil without any indications of curdling or separations and will not affect the most delicate shades or tints when used in the proportions indicated above.

1/2 Pint Pint Quart Gallon 5 Gallons

WALL PRIMER AND SEALER

This is the most effective primer and sealer for brick and concrete interior walls, all types of plaster such as smooth, sand finish and textured, standard wall board and unglazed tile. It is not recommended over wood. It primes and seals walls against suction, enabling succeeding coats to cover properly, evenly and with greater ease. It is equally efficient in sealing any porous surface and will not crack or peel. Possessing considerable opacity, it causes the second coat to stand out so that one coat of S-W Flat-Tone or S-W Semi-Lustre over Wall Primer and Sealer is usually sufficient to produce a good job.

The success of finished jobs invariably depends on the character of the foundation coat. Therefore, proper use of Wall Primer and Sealer will be instrumental in assuring best results whether on new work or old work.

Coming in White only, Wall Primer and Sealer may be tinted to a suitable ground color with S-W Fluid Tinting Colors. It dries overnight. *11/24 HRS.* Covering capacity: 300 to 550 square feet per gallon, one coat, varying according to the porosity of the wall.

Quarts Gallons 5 Gallons

WOODCRAFT STAIN

Woodcraft penetrating oil type stains are formulated to produce clean, sharp colors for new wood. They bring out the full beauty and intensity of the grain. These stains produce uniform full tones without streaks or laps, and are designed for the finishing of finest interior woodwork, floors and furniture.

The colors are rich and pleasing. Lighter effects can be secured by the addition of S-W Woodcraft Stain Reducer. Darker shades than those produced by the full strength stain will require double coating. Painters will find S-W Woodcraft Stains perfectly suited to their work on both hard and soft woods.

Wiping is not necessary (except Moss Green and Maple), however wiping does bring out the highlights and accentuates the grain of the wood.

Woodcraft Stain will not raise the grain. Varnish can be applied directly over all the colors excepting Adam Brown and Dark Mahogany. A sealing coat of thin white shellac is recommended over these two colors.

Coverage:—Approximately 500 square feet per gallon. Color Card CC-355.

	1/2 Pint	Quarts	Gallons
Adam Brown, 251.....			
Dark Mahogany, 252.....			
Golden Oak, 253.....			
Walnut, 255.....			
Maple, 254.....			
Moss Green, 256.....			XXXX
Woodcraft Stain Reducer, 029.....			XXXX

SHERWIN-WILLIAMS HOUSEHOLD PRODUCTS

Here is a Quality line of Household Products with bright new labels designed to give excellent shelf-display and "tops" in sale appeal. The product uses are illustrated clearly for consumers, and salespeople alike.

AUTO POLISH

In one easy operation this Auto Polish cleans, waxes and polishes—restores original beauty of old and new car finishes—makes chromium gleam. This high quality polish resists dirt, wear and weather and does the job more quickly and easily. Just apply it—let it dry—then wipe it off.



Plata Quarta

CREAM POLISH

A high-quality product of the world's largest manufacturer of fine furniture finishes, Sherwin-Williams Cream Polish quickly restores the rich natural beauty of all furniture. One of the finest polishes on the market, it cleans as it polishes, yet leaves no oily film. It dries hard, polishes bone dry, won't show finger prints, no rubbing necessary, hides scratches and protects.



1/4 Plate Plate

vegetable

FLAXOAP (Paste)

A well-known household product, paste Flaxoap is a pure Linseed Oil Soap of excellent quality. It is wonderful for any cleaning task where an efficient and safe cleaner is needed. Readily soluble in hot or cold, hard or soft water, Flaxoap cleans woodwork, floors, furniture, automobiles, carpets and rugs, glassware, dishes, laundry and all painted, lacquered, enameled, varnished or plastic-coated surfaces.



1 Lb. Can 5 Lb. Pail 40 Lb. Pail Drum

SHERWIN-WILLIAMS PRODUCTS

HOUSEHOLD PRODUCTS—Continued

GLASS POLISH

The S-W formula, quick-lustre Glass Polish with faster cleaning action has remarkable ability as a glass cleaner, and is used in many other ways to beautify silver, chromium and copper. It will not streak and will not harm or scratch the finest, most delicate surfaces. This new Glass "Wax Polish" with protective cleanability keeps surfaces cleaner longer, windows and mirrors brighter longer and resists water spotting and dirt collecting. One application does an excellent job on most surfaces, leaving a clean sparkling polish. Just wipe on—let dry—wipe off.



Pints Quarts

**OIL SOAP
(Fluid)**



This excellent Fluid Oil Soap is ideal for general purpose household cleaning. It is made with purest vegetable oils, which means a soft pure soap that goes into solution immediately in any kind of water. Mild enough for any toilet use, yet strong enough in concentrated form for effective household cleaning even with stubborn dirt, it gives suds, cleans perfectly and is easy on the hands. This marvelous soap will not scratch or remove the gloss from painted surfaces and gives amazing results on dishes, glassware, tile, porcelain, rugs and carpeting, even on automobiles. Rinsing is not necessary when cleaning most hard surfaces when used as a housecleaning soap and it cuts down scum and grease rings in dish pan or bath tub.

Pts. Quarts 5 Gal. Pails Drums

Gals

PASTE WAX

Especially prepared for use on floors, Paste Wax is also ideal for woodwork, furniture, venetian blinds and leather goods. It offers the finest wear and water-resistant deep-lustre wax finishes. A thin coat applied, allowed to dry, then polished, gives a hard finish and high gloss, oil free surface, bringing out the natural beauty of many home surfaces. Smudges, fingerprints wipe right off.



~~1/2 Lb. Cans 1 Lb. Cans 4 Lb. Cans~~

— 31 —

HOUSE AND GARDEN PRODUCTS

BUG BLASTER

A product that controls all three major types of garden pests, bugs, blight and mildew. Bug Blaster is a multi-purpose insect and fungus dust for flowers and vegetables. It is a scientific blend of proven insecticides and fungicides, DDT, rotenone, copper and sulphur used by commercial growers, into one amazing garden dust.

This effective, ready-to-use garden dust is now available in the giant 36 inch Bug Blaster Dust Gun that contains two pounds of this astounding dust and can be operated from a standing position. Having a small diameter, it is easy to grasp and, without stooping or kneeling, gets the job done in one simple economical operation. It also comes in the Junior 12 in. Gun, ideal for house plants and window box use. The new carburetor cap gives a constant mist-like flow of dust at all times. It prevents clogging and helps insure satisfactory operation under all conditions. The louvered openings eject dust up and under leaves where bugs hide. Hands or clothes do not get soiled.

Bug Blaster Refills contain 2 pounds of multi-purpose garden dust. A specially designed package with pour-type top makes refilling the Bug Blaster Gun simple and non-messy.

Descriptive Folder AC-10.



Senior
36" gun and 2 lbs. dust

Junior
12" gun and 8 oz. dust

Refill
2 lbs. dust

PESTROY 6% DDT LIQUID COATING



Pestroy 6% DDT Liquid Coating is a surface treatment—economical, sure way of controlling insects, flies, ants, mosquitoes, etc. This residual coating compounded with a synthetic resin may be applied by brush or applicator and clings to any surface, will not brush off or blow away. Since DDT is a relatively stable substance, one application properly applied, may be effective in killing insects—months after it has been applied.

Quick-drying Pestroy DDT Liquid Coating is clear in the package and gives screens, plumbing, other hard to protect surfaces an almost transparent, odorless coating that is sure death to insects. It is safe to use, long lasting and knits the crystals to the surface where they can not be easily wiped off. It leaves no oily or greasy film.

One gallon covers approximately 500 to 600 square feet. Descriptive Folders AC-10, DDT-22.

Pints Quarts

HOUSE AND GARDEN PRODUCTS—Continued

PESTROY 10% ACTIVATED INSECT POWDER



Pestroy 10% Activated Insect Powder is designed for application to all horizontal surfaces, thresholds, baseboards, under rugs, etc. It contains stabilized pyrethrum, an activator which "stampedes the insects" from their hiding places so that they are "exposed" to the full effects of DDT. An excellent all-around household insect powder that kills flies, ants, mosquitoes, fleas, crickets, bedbugs, moths, lice, wasps, silverfish, gnats, beetles, ticks, etc. It may even be used on dogs to get rid of fleas.



With the press-cap applicator, which is quick and handy, it is easy to whisk this sensational powder into cracks and corners where the bugs hide out. One application lasts for months. Descriptive Folders AC-10, DDT-22.

3 oz. 8 oz.

PESTROY 25% DDT CONCENTRATE

An economical, water mixable solution, Pestroy 25% DDT Concentrate is formulated for use on farm, industrial and commercial buildings for control of many kinds of insects such as:—Flies, Moths, Mosquitoes, Gnats, Fleas, Wasps, Roaches, Crickets, Silverfish, Ants, Bedbugs and Horn Flies. It is also ideal for mosquito and fly control outdoors around buildings, camps, picnic grounds, etc. Having a resin base, emulsifiable xylene solution of DDT, each gallon contains two pounds of technical DDT. The resin base increases the adherence of the crystalline DDT deposit and in addition increases the stability of the diluted Pestroy spray. Once thoroughly mixed, the spray stays uniform for a period of hours.

Furnished in concentrated form Pestroy 25% DDT is designed to be diluted with water on a 4 to 1 ratio. One gallon of Pestroy plus 4 gallons of water gives 5 gallons of a full 5% strength DDT for building application. This will give satisfactory control of insects for 3 months or longer on interior surfaces. When applied on exterior surfaces, the control properties are retained 2 to 3 weeks or even longer depending on the amount of exposure to the elements.

For most lasting results Pestroy 25% DDT Concentrate diluted according to directions should be brushed or sprayed at a rate not exceeding 1,000 square feet to the gallon. Do not use it as an air spray.

Descriptive Folder AC-10.

Quarts Gallons 5 Gallons

HOUSE AND GARDEN PRODUCTS—Continued



WEED-NO-MORE

2,4-D MAGK WEED KILLER

14

Truly Sensational in the Results
It Achieves

Selective killing of ugly broad-leaf weeds that mar lawns is accomplished by this miracle "weed exterminator."

Unlike ordinary weed killers—Weed-No-More is based on an entirely new principle and contains 14% butyl ester of 2, 4D, which has been found to be more uniformly effective and active in weed killing than any other 2, 4D formulation on the market today. Because it has great penetrating and killing power it strikes at the growth system of the plant—killing it completely. Caution must be exercised when applying Weed-No-More in the proximity of vegetables, fruit or ornamentals since spray drift may injure or kill such susceptible plants, also clover or bent grass. Crab grass and other similar grasses are not killed by Weed-No-More.

Check these Weed-No-More advantages:

- *Kills most big leafy weeds that mar the lawn!
- *Harmless to animals and humans when used as directed!
- *Has no unpleasant odor!
- *Will not injure the soil!
- *More active than other similar products!
- *Will not stain hands or clothing!
- *Under normal conditions, one treatment is highly effective!
- *Not affected by rain after lawn treatment!
- *Dilutes immediately. Economical to use!
- *Does not create a fire hazard!

Weed-No-More should be considered as one essential part of a lawn improvement program, since best results are obtained when the weed-killing is accompanied by fertilization and by reseeding or resodding the bare areas. Reseeding or resodding is needed for large areas left bare by weeds and fertilization stimulates the lawn grass to fill in the thin or smaller bare areas.

The eight ounce package, lawn size, will make 8 gallons of solution and is sufficient to treat an area of 1600 square feet.

The quart, economy size, will make 32 gallons of solution which will treat 6,400 square feet. Descriptive Folder AC-10.

8 ounce Quarts

WEED-NO-MORE SPRAYER

JUST TILT AND SPRAY THE WEEDS AWAY



The new 7 inch long Weed-No-More Sprayer fits any screw top ½ gallon or gallon jug. It is made of durable plastic and has a convenient, time-saving measuring device built into the top which holds ½ ounce of Weed-No-More, sufficient for ½ gallon of water.

Each sprayer is fastened to a display card, with complete instructions.

Sprayer



PRINTED IN U. S. A.

TS CAT. 4-49 834

0007-SWP-000191239