


Bell and Gossett Company

Morton Grove, Illinois


HYDRO-FLO HOT WATER SYSTEMS AND SPECIALTIES

B & G Booster Pumps



The B & G Booster is the basic unit of a B & G *Hydro-Flo* Forced Hot Water Heating System. It is built as a horizontally driven unit for sound engineering reasons which have demonstrated their practical value in thousands of installations. This construction makes possible many desirable, exclusive features. For example, the patented water-tight Seal eliminates need for a stuffing box.

This Seal positively prevents entry of water into bearings. Shaft is of highly polished, hardened machine steel. The close-fitted Impeller makes every revolution count by holding water slippage to a minimum.




Oil Lubricated Bearings

B & G Boosters have a genuine oil-circulating lubrication system—one of the greatest reasons for quiet, dependable, economical operation. Oil is drawn up from the oil well by wool fibre wicking and dropped on the horizontal bearing surfaces. Medium grade motor oil is used and only a few drops at infrequent intervals are required.

SEE THE B & G HANDBOOK FOR COMPLETE DESIGNING DATA

1598



B & G Flo-Control Valves


This valve, installed in the main, shuts off circulation to radiators when heat is not needed, permitting summer operation of a B & G Indirect Water Heater. It also helps maintain a uniform room temperature during the heating season.

B & G Monoflo Fittings

B & G Monoflo Fittings permit the use of a single pipe main instead of the conventional flow and return lines. They are installed at the junction of the radiator risers to the single main and assure the diversion of the proper amount of heated water into each radiator. Savings in space, labor and materials are obviously effected. Available in cast-iron and copper.

B & G Motorized Valves

Thermostatically operated valves used to control boiler water flow through individual circuits of zoned heating systems.



B & G Universal Pumps


Designed for forced hot water heating systems in apartment and office buildings, factories, schools, etc. The Universal is not an ordinary centrifugal pump, but is specially designed to assure quiet operation, so essential in heating system applications.

HOT WATER SYSTEMS AND SPECIALTIES

B & G Relief Valves

Designed and built to ASME requirements. Tested by National Board—labelled with ASME symbol.


For relieving excess boiler pressures in hot water heating systems, and in the lines of service water systems. B & G Relief Valves have the design features which assure dependable service.




B & G Reducing Valves

All working parts brass, with built-in strainer. Easily adjusted to meet varying building heights. Also high pressure reducing valves for protection of plumbing fixtures.


B & G Comfort Control System



Outdoor type, wind-compensating temperature control. The Regulator projects through the building wall, with the indoor end warmed by water in the radiation circuit. A small amount of this heat is conducted to the outside end, where it is dissipated at a rate dependent upon temperature and wind velocity. This heat dissipation governs the Control Valve, which permits hot boiler water to enter the system in required amounts.




B & G Type "WU" Heat Exchangers



A shell and tube heat exchanger with hot boiler water pumped through the shell by a B & G Booster, making possible big capacity in a small unit.


Pumping boiler water through the heater also affords excellent temperature control and permits use of much smaller pipe and fittings.

B & G Type "SU" Heat Exchangers



For heating water with steam. Ideal for industrial plants or wherever large volumes of hot water are required continuously for service water supply or process work. No storage tank required—the large heat transfer surface in these units heats water instantly as needed. Available in a wide range of capacities.

B & G Centrifugal Pumps



Design and construction based on years of experience in the industrial field. Rugged, compact units—built to withstand strain of continuous operation. Semi-open or enclosed impellers—motors flexible coupled or integral with pump. Series 1522 illustrated.

B & G Refrigeration Components

A very complete line of direct expansion evaporators, condensers, liquid receivers, combination liquid receivers and subcoolers for refrigeration and air conditioning. Special alloys may be incorporated in the units for those critical heat transfer applications.

1599