

110 • BRIGHT WHITE



1 GALLON

Dutch Boy

HOUSE PAINT

Dutch Boy® BRIGHT WHITE

For a Finish that's Sparkling White . . . Long Lasting

This durable exterior paint is engineered to give exceptional hiding and to produce a dazzling white finish.

Follow Directions—STIR WELL—Do Not Add Color

Do not tint this paint. If color is desired, use Dutch Boy 111 White or House Paint in Color.

Make sure the surface to be painted is clean and dry. Scrape or burn off all loose or scaling paint. Before painting, be certain the paint is well mixed.

New, Unpainted Wood and Previously Painted Surfaces Badly Weathered or in Poor Condition:

Apply one coat of Dutch Boy 010 Primer. Allow at least three days of good drying weather; then apply one coat of the paint in this package without thinning.

Previously Painted Surfaces in Good Condition:

First apply one coat of this paint with turpentine per gallon. Allow five days drying; then apply one coat of this paint without turpentine. In porous areas, raw linseed oil may be used as a primer coat, in amounts not exceeding one ounce per gallon.

On surfaces in better condition, it gives good results with only one coat. For best results, it should be applied as received in the original container.

PAINTING HINTS

Moisture getting behind the paint film may cause any paint to blister and peel. Seal cracks and other openings, repair leaky flashings, downspouts and roofs to prevent entrance of water. Ventilate areas where moisture condenses within the walls.

Paint in good weather—not when it is damp, stormy or there is likelihood of a temperature drop to near freezing. Avoid painting in the late evening or in an intense sun.

Apply a good full coat of paint, brush on smoothly and evenly. Allow about one day drying.

After first coat is dry, coat sappy lumps with putty nailholes and similar defects.

Stains from exposed copper, bronze, iron, etc., which are not the fault of the paint, are minimized by coating such surfaces with Marine Spar Varnish or Screen Enamel.

COMPOSITION OF PAINT BY WEIGHT

PIGMENT 61.3%

Basic Carbonate	
White Lead . . . 63.5%	} 29.8%
Basic Silicate	
White Lead	} 36.5%
(48% PbO type)	
Titanium Dioxide	20.9%
Zinc Oxide	25.0%
Magnesium Silicate	24.3%

VEHICLE 38.7%

Linseed Oil	79.1%
Liquid Drier	5.0%
Mineral Spirits	15.9%

CAUTION—COMBUSTIBLE: CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from fire. Do not apply on window sills, toys, furniture or interior surfaces of rooms which may be used for prolonged contact with skin and breathing of vapor or spray mist. Close container after use. Provide adequate ventilation. **KEEP OUT OF THE REACH OF CHILDREN.**



NATIONAL LEAD COMPANY

PAINT DIVISION: NEW YORK, NEW YORK