



Enamel

CODE 3400
YELLOW

Enamel
BRUSHING AND SPRAYING

ONE GALLON U. S. MEASURE
3.785 LITRES

FLAMMABLE!
See cautions elsewhere on label.

CAUTION: FLAMMABLE! CONTAINS LEAD. HARMFUL IF SWALLOWED.
Keep away from heat, sparks and open flame. Do not apply on toys, furniture, window sills, or other interior surfaces of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use With Adequate Ventilation. **KEEP OUT OF THE REACH OF CHILDREN.**

3400 YELLOW ENAMEL

Directions for Use — Read Carefully

C-3400 can be used for either brush or spray application over a primer or old paint in sound condition. It is specified for pumps, and other station equipment to be painted yellow. Be sure all is sanded thoroughly smooth and that the surface to be painted from grease, grime and foreign matter.

For Brush Application the material should be applied full by comes in the package. If it has thickened somewhat with age cold weather, thin with a small amount of Turpentine, not to exceed 10%—and apply sufficient material around and the job to give a solid hiding coat. Bare metal first should be with C-3304 Spraying Pump Primer-Surfacer. Then either spray coat of C-3400 within 30 minutes or allow the Primer-Surface 5-6 hours before applying the finish coat of enamel.