THE DISCOVERY COMPANY

16 of 4
Union Carbide

Calidria ASBESTOS

"CALIDRIA" ASBESTOS SG-130 AND SG-210
For Tape Joint Compounds

Lowers Costs Two Ways

CALIDRIA Asbestos acts as a bodying and secondary thickening agent permitting formulation of lower density, more economical tape joint compounds without the sacrifice of performance. CALIDRIA Asbestos is produced by a proprietary manufacturing process that yields unusually high fiber content and more complete fiber liberation from the natural bundles. As a result, CALIDRIA Asbestos goes up to twice as far, pound for pound, as commercial grades of asbestos containing large amounts of other filler materials that have no specific desirable effects on tape joint compound properties.

Reduces Cracking

The fibers of CALIDRIA Asbestos behave as an active lyophobic colloid in aqueous dispersion; by this mechanism CALIDRIA Asbestos increases tape joint compound liquid cohesive strength during drying. Increased liquid cohesive strength greatly reduces the tendency for cracks over nail holes, in thick sections at the center of the joint, and along the feathered edges.

Enhances Sandability

CALIDRIA Asbestos contains mainly chrysotile fiber and is essentially free from abrasive contaminants, such as magnetite and serpentine rock dust. This composition results in a low density product, free from contaminants that interfere with sanding.

Improves Uniformity

Narrow and well-controlled particle size distribution, low alkalinity and high brightness are characteristic of CALIDRIA Asbestos. These properties are consistent from batch to batch and improve the uniformity of tape joint compounds using CALIDRIA Asbestos.

Suggestions for Use of CALIDRIA Asbestos

CALIDRIA Asbestos can be readily used in your present tape joint compound formulation. Add approximately one-half the proportion of asbestos you now use. Increase the proportion of calcium carbonate or other inert filler to make up for the lower quantity of asbestos. You may also be able to use slightly more water in your ready-mix and maintain your present viscosity level. No other changes in your

A23621

October, 1968
F-42258

CALIDRIA, CELLOSIZE, UCAR, and UNION CARBIDE are trade marks of Union Carbide Corporation.

UNION CARBIDE CORPORATION • CHEMICALS AND PLASTICS • 270 PARK AVENUE, N.Y., N.Y. 10017

Suggestions for Use of CALIDRIA Asbestos (Continued)

formulation or manufacturing procedure are required.

CALIDRIA Asbestos SG-130 has the coarser particle size; it finds use for bedding compounds or perhaps spackling compound. The SG-210 has the finer particle size and is favored for topping compounds, all-purpose compositions, texture paints, and similar formulas.

A Suggested Ready-Mix Tape Joint Compound For Use With CALIDRIA Asbestos

	Parts by Weight Dry Basis
Fillers:	
Calcium Carbonate, No. 1 White (Thompson Weinman)	61.42
Mica, P80F (Western Mica)	21.00
Clay, ASP-400 (Minerals and Chemicals Philipp Corp.)	4.00
CALIDRIA Asbestos, SG-210 (Union Carbide)	4.58
Binder:	
UCAR Latex 131 (Union Carbide)	6.60*
Workability Control Agent:	
CELLOSIZE Thickener, TJC Grade (Union Carbide)	0.50
Drying Control:	
Ethylene Glycol (Union Carbide)	1.00
Defoamer:	
"Nopco" PD-1 (Nopco Chemical Company)	0.10
Dispersant:	
"Daxad" 30 (Dewey & Almy Chemical Div.)	0.60*
Bacteriastat:	
"Dowicide" A (Dow Chemical Co.)	0.20
	100.00

Total Water: about 56 parts by weight per 100 parts dry solids

*Contained solids basis

A23622

Typical Product Characteristics

	CALIDRIA Asbestos	
	SG-130	SG-210
Reflectance (G.E. Photovolt)	68%	
Contained magnetite	2% max.	
Alkalinity (as % of Na_2O)	0.05 to 0.06	
pH (5% aqueous slurry)	8.5 to 9.5	
Surface area (BET)	50 to 60 $m^2/g.$	
Oil Adsorption (DOP #/100# asbestos)	90 to 100	110 to 120
Wet Bulk, settled vol. (ml.) 10g/250 ml./1 hr.	200	220
Dry Bulk (#/ft.^{3})	7 to 8	5 to 6
Water absorption (wt. % in filter cake)	55 to 60	62 to 65
Size distribution (cumulative % retained)		
Wet Screen mesh size		
100	5	Trace
200	17	3
325	28 to 32	10 to 15

Packaging and Shipping Information

Product Form – Opened (finely ground) chrysotile asbestos fiber.

Packaging –

	CALIDRIA Asbestos	
	SG-130	SG-210
One Package	40 lb.	30 lb.
Pallet Weight		
Carload	1,600 lb.	1,050 lb.
Truckload	2,000 lb.	1,500 lb.

Shipping –
Classification – asbestos shorts
Rail point of origin – Welby, California (King City, California)

TOXICOLOGICAL PROPERTIES

It has been known for many years that some persons working in asbestos production were prone to develop a disabling lung disease. In time, this condition became known as asbestosis and was related to exposure to high concentrations of asbestos dust. With further experience, it was found that men could work with asbestos without development of lung disease if dust concentrations were kept below a certain level. It is now generally accepted that a man can work a 40-hour week for a lifetime without developing asbestosis if the asbestos dust particle count is kept at or below 5 million particles per cubic foot of air. This dust concentration of 5 million particles per cubic foot of air is the Threshold Limit Value for asbestos, and no cases

A23623

UCC 025522

TOXICOLOGICAL PROPERTIES (Continued)

of asbestosis are believed to have occurred when exposures have been maintained at or below this level, despite large-scale utilization (now approaching one million tons per year in the U.S.A.). This concentration of dust is generally not visible in the average work area unless a beam of light causing a Tyndall effect is present. Usually the dust concentration must be from 8-10 million particles per cubic foot before its presence is visible in average lighting conditions.

Several years ago, it was reported that there was an increase in the incidence of cancerous tumors, especially of the lung, associated with asbestosis. Recently there have been reports of some cancers occurring in individuals exposed to asbestos dust, but who have not developed clinical asbestosis. It is believed by most authorities that these cases have been associated with exposures significantly exceeding the Threshold Limit Value. A major manufacturer of asbestos products who also mines asbestos has not been able to show an increase in cancerous growths in men working where dust concentrations were maintained at the Threshold Limit Value.

Control of asbestos dust exposure is therefore necessary. The control methods are the standard ones applicable to a variety of dusty operations. They include closed flow systems, wet processes where possible, and adequate exhaust ventilation where openings in the system are necessary. Pelletizing is sometimes used to improve the handling characteristics of otherwise dusty materials. Where satisfactory containment to stay within the Threshold Limit Value is impractical or impossible, efficient and reliable respirators are available for the protection of the employee. A program of environmental monitoring in manufacturing operations is highly desirable to determine that Threshold Limit Values are not being exceeded. Employees should wear respirators where dusting occurs in finishing products such as sanding taped joints.

Pre-employment and periodic physical examinations of workers are desirable. These should include chest X-rays to insure that the worker has no chest condition prior to work with asbestos and to determine that no lung changes are resulting from work with asbestos.


In conclusion, while asbestos dust in excess of the Threshold Limit Value is potentially harmful, as are many other dusts encountered in industry, it is as readily controlled as other such dusts and it can be used safely with appropriate precautions.

A23624

UCC 025523

"CALIDRIA" ASBESTOS SG-130 AND SG-210

For Tape Joint Compounds



RELATIONSHIP BETWEEN WATER & OIL ADSORPTION CAPACITY OF SOME ASBESTOS PRODUCTS FOR TAPE JOINT ADHESIVE FORMULATIONS

A23625

UCC 025524

THE DISCOVERY COMPANY

UNION CARBIDE CORPORATION
CHEMICALS AND PLASTICS
270 PARK AVENUE, NEW YORK, N.Y. 10017

Sales Offices

United States

ATLANTA, GEORGIA 30309	1371 Peachtree St., N. E.	404-892-7500
BALTIMORE, MARYLAND 21207	Beltway Bldg., 6707 Whitestone Rd.	301-944-8211
BOSTON, MASSACHUSETTS 02194	300 First Ave., Needham Hgts.	617-444-5400
BUFFALO, NEW YORK 14225	3343 Harlem Rd.	716-837-6450
CHARLOTTE, NORTH CAROLINA 28210	6230 Fairview Rd.	704-364-1400
CHICAGO, ILLINOIS 60606	120 South Riverside Plaza	312-822-7000
CINCINNATI, OHIO 45227	West Street and Madisonville Rd.	513-272-0206
CLEVELAND, OHIO 44114	1300 Lakeside Ave., N.E.	216-621-4202
CLIFTON, NEW JERSEY 07012	935 Allwood Rd.	201-778-2900
DALLAS, TEXAS 75207	2710 Stemmons Freeway	214-631-0010
DETROIT, MICHIGAN 48221	10421 West Seven Mile Rd.	313-341-3131
HARTFORD, CONNECTICUT 06103	410 Asylum St.	203-525-9345
HOUSTON, TEXAS 77027	3839 West Alabama Ave.	713-621-1000
INDIANAPOLIS, INDIANA 46220	720 Broad Ripple Ave.	317-255-3181
KANSAS CITY, MISSOURI 64141	910 Baltimore Ave.	816-221-2400
LOS ANGELES, CALIFORNIA 90058	2770 Leonis Blvd.	213-583-3061
MEMPHIS, TENNESSEE 38116	3385 Airways Blvd.	901-396-5375
MINNEAPOLIS, MINNESOTA 55416	3033 Excelsior Blvd.	612-927-4221
MOORESTOWN, NEW JERSEY 08057	Route 38 and Pleasant Valley Rd.	609-235-6200
NEW YORK, NEW YORK 10017	270 Park Ave.	212-551-4641
PHILADELPHIA (MOORESTOWN, NEW JERSEY SALES OFFICE)		215-923-3200
PITTSBURGH, PENNSYLVANIA 15220	P'kway Center, 875 Greentree Rd.	412-922-5700
ST. LOUIS, MISSOURI 63105	10 South Brentwood Blvd.	314-726-0324
SAN FRANCISCO, CALIFORNIA 94106	22 Battery St.	415-982-1360
SEATTLE, WASHINGTON 98118	4726 Rainier Ave., South	206-723-8660
TULSA, OKLAHOMA 74114	2901 South Harvard	918-742-5524

Affiliates

Pan America

ARGENTINA	Union Carbide Inter-America, Inc., Buenos Aires
BRAZIL	Union Carbide do Brasil S. A., Sao Paulo, Rio de Janeiro
CANADA	Union Carbide Canada Ltd., Calgary, Lachine (P.Q.), Toronto, Vancouver, Winnipeg
CARIBBEAN	Union Carbide Inter-America, Inc., San Juan, Puerto Rico
CENTRAL AMERICA	Union Carbide Inter-America, Inc., Panama City, Panama
CHILE	Union Carbide Comercial Chile Ltd., Santiago
COLOMBIA	Union Carbide Colombia, S. A., Bogota
MEXICO	Unicarb Comercial, S. A. de C. V., Mexico, D. F., Guadalajara, Monterrey
PERU	Union Carbide Inter-America, Inc., Lima
VENEZUELA	Union Carbide de Venezuela, C. A., Caracas
WESTERN HEMISPHERE	Union Carbide Inter-America, Inc., New York, N. Y.

Eastern

AUSTRALIA	Union Carbide Australia Ltd., Sydney, N. S. W.
HONG KONG	Union Carbide Asia Ltd., Hong Kong
INDIA	Union Carbide India Ltd., Calcutta, Bombay, Madras, New Delhi
NEW ZEALAND	Union Carbide New Zealand (Pty) Ltd., Auckland
PAKISTAN	National Carbon Co. (Pakistan) Ltd., Karachi
PHILIPPINES	Union Carbide Philippines Inc., Manila
SINGAPORE	Union Carbide Singapore Ltd., Singapore

Europe
Middle East, and North Africa

AUSTRIA	Union Carbide Austria Ges. mbH., Vienna
BELGIUM	Union Carbide Belgium N. V., Brussels
FRANCE	Union Carbide Europe s.a., Succursale Francaise, Puteaux-Paris
GERMANY	Union Carbide Deutschland, GmbH, Dusseldorf
ITALY	Union Carbide Italia S.p.A., Milan
MIDDLE EAST	Union Carbide Middle East Ltd., Athens, Greece
NETHERLANDS	Union Carbide Belgium N. V., Amsterdam
SCANDINAVIA	Union Carbide Norden A.B., Stockholm, Sweden
SPAIN	Union Carbide Iberica S. A., Madrid
SWITZERLAND	Union Carbide Europe s.a., Geneva
UNITED KINGDOM	Union Carbide U. K. Limited, London, Manchester, Rickmansworth; England

A23620

Africa

AFRICA (EAST)	Union Carbide Africa Ltd., Nairobi, Kenya
AFRICA (SOUTH)	Union Carbide South Africa (Pty) Ltd., Johannesburg, Capetown, Durban; Republic of South Africa

F-42258
10/68 – 2M

UCC 025525

Lithographed in U.S.A.