

GLIDDEN-DURKEE

FROM: Mr. W. M. Tomc November 24, 1975 FOR: Mr. J. Grabowsky, #1

CITY: Strongsville, DPJRC cc: Mr. J. D. Russell, UCB
Mr. S. T. Bowell
SUBJECT: GLID GUARD CHEMICAL RESISTANT EPOXY Mr. T. W. Batt
SAFETY ORANGE 512-L-01105 Mr. E. D. Hood
Mr. J. G. Kingston
Mr. J. W. Rode
Mr. C. W. Wright, UCB
Mr. J. Sainsbury, UCB
Mr. M. W. Malaga, #1

The question of standard color for this product has been reviewed with Sales. It has been agreed that the last production of 512-L-01105CX - 144550 is acceptable as the standard.

Under separate cover T. Batt will send you 1 gallon of 5580 Deep Tint Base and a pint each of a black, red oxide and phthalo green tints as prepared in the Lab following the method attached. The tint level was established to match the Silicone Alkyd Deep Tint Base 523-W-01101A.

By a copy of this letter J. Rode is requested to assign and issue a Glidden Test number to the procedure and add to the 5580 card.

Production is making a batch of 5582. If this meets the standard tint it will be established as the standard.

WMT:n1

W. M. Tomc
W. M. Tomc

N 4061

GLD012128