

O'BRIEN

REGISTERED	
REGN. No.	37410
Code No.	0160
Date	8-21-13

WEATHER KING[®]

Latex

HOUSE PAINT

WARNING!
CONTAINS LEAD
DRIED FILM OF THIS
PAINT MAY BE HARMFUL
IF EATEN OR CHEWED
See other cautions on back panel.

A20-08 WOOD PRIMER (LATEX)
FOR REDWOOD & CEDAR
NET 128 FL. OZ (1 GAL.)

N21608

WEATHER KING LATEX EXTERIOR PRIMER (For Unpainted Wood Surfaces)

Weather King Latex Exterior Primer is for UNPAINTED wood siding, wood trim and wood shingles. Provides excellent holdout for uniform finish coats of Weather King Latex House Paint and Trim Enamel, Ultra Coating Latex House Paints, or for finish coats of solvent-thinned house paints. Resists grain checking, provides blister-resistant properties, eliminates fire hazard. Dust free, bug free in just 20 minutes. Clean up with soap and water. For unpainted surface only; do not use as a primer over previous paint.

PREPARATION---Surface must be clean. Sand smooth any rough grain areas. Repair and caulk flashings. Provide adequate ventilation for release of moisture.

TINTING---Tint toward the finish color with Tone-All Universal Tinting Colors, with the exception of Interior Yellow which is not a light-fast pigment. DO NOT TINT WITH OIL COLORS or intermix with other paints.

APPLICATION---Apply by nylon brush when temperature is 50°F. or above. Flow on liberally, spreading at a rate not more than 300 square feet per gallon. Dries in 1 hour. Recoat the same day after 4 hours. If the humidity is high, allow additional drying time. On new redwood or red cedar allow 48-hour drying and examine for yellow or brown stains. If stain is present, sand lightly and reprime. Thinning is not necessary. Clean tools with water.-(PWT)

KEEP FROM FREEZING

"WARNING" CONTAINS LEAD

Do not apply on toys and other children's articles, furniture, or interior surfaces of any dwelling or facility which may be occupied or used by children.

Do not apply on those exterior surfaces of dwelling units, such as window sills, porches, stairs, or railings, to which children may be commonly exposed. Close container after each use.

KEEP OUT OF THE REACH OF CHILDREN. (94A)

WEATHER KING LATEX EXTERIOR PRIMER--Titanium Dioxide 12.39%, Basic Silicate White Lead 10.33%, Calcium Carbonate 12.39%, Acrylic Latex Resin 19.46%, Methyl Cellulose .25%, Water 45.18%, 100.00%-(PRWT)

THE O'BRIEN CORPORATION • SOUTH BEND, IND. 46627

SAN FRANCISCO, CAL. • BALTIMORE, MD. • BRUNSWICK, GA. • OKLAHOMA CITY, OKLA.