



Mills Water Tube Steam and Water Boilers

Sectional cast iron boilers which are moderate in first cost, low maintenance and extremely economical in fuel. Sectional view shows large combustion chamber and vertical waterways of small area. The latter absorb the heat quickly, circulate the water rapidly and make dry steam. May be fired with anthracite coal, wood, coke or fuel gas.



No. 44 Mills Steam Boiler




No. 44 Mills Boiler—Interior

Size of Boiler	Nominal Width Fire Pot Inches	Commercial Rating—Capacity in Sq. Ft.		Max. Allowable Working Pressure		
		Steam	Water	Steam	Water (Open Tank)	Water (Closed Tank)
No. 24	24	900 to 2025	1500 to 3350	15 lb.	30 lb.	15 lb.
No. 34	34	2000 to 5200	3300 to 8575	15 lb.	30 lb.	15 lb.
No. 44	44	3600 to 9000	5950 to 14,850	15 lb.	30 lb.	15 lb.
No. 48	48	4800 to 12,000	7925 to 19,800	15 lb.	60 lb.	30 lb.

H-B Steam and Water Boilers

H-B Boilers have three waterways between sections. They are the only boilers in which ascending and descending currents of water are circulated through separate connections, giving a steady water line and rapid circulation without back pressure.




Commercial Ratings

Diam. of Fire Pot Inches	Steam	Water
	Rating Feet	Rating Feet
15 to 27	250 to 1000	425 to 1650

17 Hy-Test Boiler

For Hot Water Supply
A. S. M. E. Standard

Maximum allowable working pressure, 120 lb. Open Tank; 80 lb. Closed Tank.




Princess Direct Radiators

For sanitary reasons, radiators with wide spacing should be demanded.

If ordinary radiators are not sanitary enough for hospitals, they are not sanitary for the home. To meet hospital specifications some manufacturers make special radiators with wide spacing and charge an increased price.


Princess Radiators are the standard radiators of The H. B. Smith Co. and are sold at regular list prices.




"Princess" Water Radiator

Princess Wall Radiators

Suited for all places where direct radiators or pipe coils cannot be used. Especially desirable in locations where floor space is valuable and where wall, column or ceiling space is more available. They possess extreme flexibility of size and arrangement. Made in two heights, 15 and 22 in. Can be furnished with heating surfaces from 5 sq. ft. up, in multiples of 2½ sq. ft. Corresponding lengths in 22 in. radiator are from 9 in. up, in multiples of 4 in. (1 in. allowed in over all length for plugs and bushings). In the 15 in. radiator, corresponding lengths are from 13 in. up, in multiples of 6 in. By combinations of the two heights, these radiators can be arranged in tiers, either for horizontal runs or for column work. Hung horizontally, they make excellent ceiling radiators.



"Princess" Wall Radiator



"Princess" Steam Radiator