

DRY-GRADED FIBRE PACKING IS PACKAGED BY USING OIL-PROOF BINDER, GRAPHITE AND SPECIAL LONG FIBRE ASBESTOS. RINGS ARE DIE-FORMED AND PACKAGED IN SETS AS NOTED. EACH SET IS INDIVIDUALLY WRAPPED. TEMPERATURES TO 750°F.

PAGE 8-85.626
SUPPDS. REV. 6
DATE 7-22-85

PLAINTIFF'S EXHIBIT

GOU-11

J. CRANE SUPER SEAL NO. 2

SUFF NO.	I.D.	O.D.	CROSS SECTION	RINGS PER SET	WHERE USED
1	2	2-3/4	3/8 SQUARE	6	3735-36M
2	2-1/2	3-3/8	7/16 SQUARE	6	3735-36L, 3196XL
3	2-1/4	3-1/8	7/16 SQUARE	6	API "S" GROUP
4	2-3/4	3-3/4	1/2 SQUARE	6	API "M" GROUP
5	3-3/8	4-3/8	1/2 SQUARE	6	API "L" GROUP
6	4-1/8	5-1/8	1/2 SQUARE	7	API "XL" GROUP
7					
8					
9					
10					

OBSOLETE
REPLACED BY
DWG. A01074A.

APPROVED VENDORS:

CRANE SUPER SEAL NO. 2

3	N2 3 ADDED 6/13/79 GKH	5	ADDED #5 4/3/81 GKH	7	OBSOLETE - REMOVED				
4	N2 4 ADDED 4/25/79 GKH	6	ADDED #6 11/9/81 GKH						

 GOULDS PUMPS Seneca Falls, N. Y.	PART	PACKING - S.B.	DR. BY 	CR. BY 	DATE 2-2-79	85626	REV. 7

CAT. ES-2
 PAGE 0-85.626
 DATE 02-17-75

DRY-GRAPHITIZED PLASTIC PACKING IS MANUFACTURED BY
 USING OIL-PROOF BINDER, GRAPHITE AND SPECIAL LONG
 FIBRE ASBESTOS. RINGS ARE DIE-FORMED AND PACKAGED
 IN SETS AS NOTED.
 EACH SET IS INDIVIDUALLY WRAPPED. TEMPERATURES TO 750°F

U. CRANE SUPER SEAL NO. 2

No.	OD	OD	CROSS SECTION	RINGS PER SET	WHERE USED
1	2	2 3/4	3/8 SQ	6	3755-36
2	2 1/2	3 3/8	7/16 SQ	4	3755-36
3	2 1/2	3 3/8	7/16 SQ	6	8196
4	2 1/2	3 3/8	7/16 SQ	6	85626

APPROVED VENDORS:

SPECIFICATION EQUIVALENTS:

CRANE SUPER SEAL NO. 2

1	2	3	4	5	6	7	8	9	10
1	2	3	4	5	6	7	8	9	10
1	2	3	4	5	6	7	8	9	10
1	2	3	4	5	6	7	8	9	10

GOULDS PUMPS INC

PACKING 9.8

85626

2

REDRAWN

1-1

22959