

FILE NAME: Johns-Manville (JMA)

DATE: 1939 Oct

DOC#: JMA325

DOCUMENT DESCRIPTION: Raybestos-Manhattan; Stratford Plant Survey
by Metropolitan Life Insurance

9826

X

THE ASBESTOS DIVISION
of
RAYMOND-SMITH, INC.
Stratford, Conn.

A third survey of this plant was conducted on October 12, 13 and 16, 1939 by the Industrial Health Section of the Metropolitan Life Insurance Company. The two previous surveys had been made during March, 1930 and June, 1935.

This plant is engaged in the manufacture of packing, gaskets, and brake linings. Since the previous surveys the woven brake lining processes have been eliminated and new processes have been installed. ✓

* * *

02490

5-12-77

H6 Jek

R-M 2592 Rd

PLANT CONSTRUCTION

The plant is housed in a number of one and two story brick buildings of modern construction. Ample natural illumination and ventilation are supplied by numerous side wall windows and skylights. Offices are located in separate buildings apart from the manufacturing departments.

PLANT PROCESSES

Bldg. 6, Dept. 12. Sheet Packing

In this building sheet packing is made, from which brake lining, gaskets, and packing are stamped or cut.

Asbestos Room

Asbestos used in sheet packing is prepared for use in a crusher and opener. The asbestos is graded on screens. The asbestos passing through the opener is dumped on the floor and then hand shoveled into the opener. The opened asbestos is then conveyed by air to a hopper on the roof and dropped through pipes into the grading screens or directly into a hand truck. Scrap material is ground in a pulverizer, then conveyed by air to hoppers on the roof and dropped through pipes directly into bags. The lone operator in this room is supplied with an approved dust respirator. This room opens directly into the dry mold mix room and the main mixing and roll room. Since the previous survey, the equipment in this room has been improved. Sample 6 of 1935 survey and sample 3 of the present survey show that good results have been attained.

Dry Mold Mix Room

Material for the dry mold mix is hand scooped from original containers and dumped into a barrel on a scale. Most of the materials used are

kept in loosely covered or uncovered containers. After the batch is weighed out, the operator carries the barrel up a flight of stairs to a platform and dumps the batch into the mixer. The mixed batch is then dropped from the bottom of the mixer into a truck. The materials used in these batches contain asbestos, carbonite, resin, anticiser (plasticiser) and scrap. Two rubber mills are located in this room. At the time of sampling one of these mills was operating. The rubber is thrown around the floor scattering some soapstone dust. Respirators are available to the operator but it was noted that the respirator was not worn. X No exhaust equipment is used in this department.

Rubber Compounding Room

This room is located at one end of the building and opens into the mixing and roll room. The operations in this room are intermittent. Batches containing large quantities of litharge (81% free lead) and mica are weighed out from original containers into a pan on a scale. The mica is received in bags. These bags are ripped open down the middle and allowed to lie on the floor. It was noticed that during the weighing considerable quantities of the litharge and mica were spilled upon the scale and floor where they were allowed to remain until close to the end of the shift. The floors and scale were then cleaned by dry sweeping. The complete batch contains liquid bakelite, sulphur, mica, asbestos, litharge, croclor, scrap and rubber. The percent of litharge in the batch varies from 30 to 35%. The weighed batch is then trucked to the mixers into which it is dumped and mixed with gasoline and asbestos. The operator working in this department had been at one time supplied with a dust respirator but preferred to work without it, complaining that it interfered with his glasses. He also said it was too hot for comfort. This man stated that he has been engaged at this work for about seven years.

02492

Mixing and Rolling

In this department the batches are mixed with gasoline in closed mixers. The mixed material is then hand shoveled from the mixer into the rolls. One roll is hot, the other cold. The material adheres to the cold roll. The material is rolled to the desired thickness. From the rolls the material is then run onto cutting tables where the sheets are cut to length. The gasoline used is recovered in a condenser located in the same room. From the sheets, rings, gaskets and packing are stamped out on power machines.

One end of the building is used for storage of raw material.

Main Building, Dept. 20 - Asbestos Board

Asbestos board used in making clutch facing and a special material called L8 is made in this department.

Scrap material and new asbestos are hand dumped into paper beaters; mixed with water and starch and worked to the proper consistency. The pulp is then passed through the rolls to the required thickness. The L8 material which is composed of asbestos, atomized metallic lead, alum, gilsonite, graphite, and scrap are mixed in a beater and the pulp pumped to storage tanks. The atomized lead is about 200 mesh. The lead is dumped on a piece of cardboard on the floor in front of the beater and is sieved into the pulp by hand shoveling into a sieve resting on the top of the beater. The wet pulp is run from the beaters to storage tanks. From the storage tank the wet pulp is run into troughs (coffins) where the water is drained out, leaving the solid material in the trough. The solid material is then transferred to a heated press where it is pressed to required thickness, removed and cut into strips by hand. It was noted that the operator handling the atomized lead as well as others in close

proximity did not wear respirators.

Cutting Dept. #21.

Asbestos board is cut to size for the punching machines. Facings are stamped out on machines by men and wiped and stacked on skips by girls. The composition of this board is practically 95% or more asbestos.

Finishing Dept. #22

Facings are cured and then finished. The finishing operations include grinding surfaces and edges on Blanchard, Cincinnati and cylinder grinders; drilling and shot blasting. All machines in this department are equipped with exhaust systems. On the Blanchard grinders and drilling operations these exhaust systems are augmented by the use of compressed air. At the time of this survey, the compressed air line on the grinder, machine #758, sample #19, had been moved out of position, causing puffs of dust to be dispersed into the atmosphere with each revolution of the grinder. This condition was readily remedied after attention had been called to the condition. Considerable dust adhering to the clutch facings is dispersed into the atmosphere when loading the machines and restacking the facings on the skips. No provision is made to entrap the dust at these points.

Dry Mold

This is a new operation. The mixture for this operation is made in building #6. At the time of this survey machines were being installed or renovated, so that tests taken at this operation would not have been representative. Therefore, no tests were made.

Wirmold

The materials used in the wirmold batch are mixed in small mixers

in a partitioned area on the main floor. These materials include asbestos, hardwood pitch, sulphur, lampblack, graphite, asbestos, powdered white lead and index oil. The hardwood pitch is run through a grinder four times to the required mesh. The pitch is hand scooped from the container into the grinder. This grinder is enclosed and exhausted. The powdered white lead, as well as the pitch and index oils, are kept in open barrels just outside the partition on the main floor. The compounded batch is used on the wire-mold machine which is also located in this partition. The men engaged at batch mixing wear dust respirators, but the men at the machine a few feet from the mixer are not so protected. The mixed material is pressed around a wire backing and is used to make brake lining. Information was advanced that plans and appropriations have been made to provide dust control at these operations.

Dept. #22 and 24 - Molded and Rubber Brake

Molded and rubber brake linings are finished in these departments. The operations consist of grinding and drilling. All machines, with the exception of a few small drill presses (machines #360, 277 and 93) are exhausted.

Dept. #23 - LF Pressing

In this department LF brake lining is shaped and pressed in molds. Soapstone is hand dusted to prevent the linings from sticking. The operator on this job wears an approved dust respirator.

Solvent Room

The dopes used on the brake linings and clutch facings are prepared and stored in a separate brick building. All solvents are kept and prepared in closed tanks. The main solvents used are xylol, formaldehyde, cresylic acid and acetone. The acetone is stored in tanks outside the building. The

prepared esturant is pumped to the saturation room as required. The asphalt used in the saturation is not a cold tar product.

Other operations and departments include inspection, assembly of parts and packing of finished product, also a machine shop and stock section. These operations are located in the newest section of the main building. There are no dusts produced by these operations.

PERSONAL FACILITIES AND PLANT HOUSEKEEPING

Ample washing and toilet facilities are provided. Drinking water is supplied from mechanically cooled bubbler fountains. A restaurant is available to all employees. A first aid room under the direction of a full time nurse is maintained.

Housekeeping in general is good. Aisles are well defined and are always kept free from obstructions. Vacuum cleaning is employed on the rafters, walls and floors in the main building. It is planned to extend this to other buildings.

Safety meetings are held once a week, at which time the employees' representatives, as well as the foreman, are present and take an active part in the proceedings.

METHOD OF SAMPLING AND ANALYSIS

Atmospheric dust samples were taken with the impinger⁽¹⁾ and the solvent fumes with the interferometer at the breathing level of the workmen at representative operations. The interferometer is an instrument designed for use in detecting gases and vapors. The impinger, developed by the United States Public Health Service, is the standard method used in this country. Air is drawn in through a glass tube at the rate of one cubic foot per minute.

(1)U.S. Public Health Service, Public Health Bulletin #217, Determination and Control of Industrial Dust, J.J. Bloomfield and J.W. Dallavalle, 1935.

The tube ends in a constricted orifice under the surface of distilled water contained in a flask. The air passes through the orifice and impinges upon a glass plate which breaks up the air stream, allowing the dust particles to be wet and entrapped in the water in the flask.

Alcohol is added to the sample as a preservative to inhibit the solution of the fine particles and also to prevent the formation of aggregates of the fine particles by clumping.

Suction is supplied for drawing the air sample through the impinger by means of an ejector, or else an electrically driven pump where compressed air is not available to actuate the impinger.

The dust counts were made by the methods and technique developed and used by the United States Public Health Service.

The following table offers comparison of the results of analysis of samples taken at identical locations for the 1935 and 1939 surveys. As asbestos is involved at practically all operations, dust counts are given as total count in millions of particles per cubic foot of air.

CONCLUSIONS AND RECOMMENDATIONS

In the asbestos room the count at the crusher is high (sample #1). Apparently the operator was overloading the pans. Crushed asbestos was falling upon the floor, necessitating frequent sweeping and hand shoveling. It is recommended that the amount of material that can be handled without spilling on the floor be ascertained and controlled. Enclosing this crusher would also be of value. Since the other operations in this room are now well controlled, as evidenced by samples #2 and 3, it is not necessary to install an elaborate system for this one machine. The operator is supplied with and wears the proper type of respirator. *Look
Hillman*

The dry mold batch weighing is a dust dispersing operation (sample #4). The operator is exposed to the heavy concentrations because of the close proximity of his face to the containers while scooping out the ingredients and carrying the weighed batch up the stairs to the mixer platform.

It is recommended that all batch weighing operations - dry mold, wire-mold and rubber compounding - be done at one point where effective control by exhaust systems should be installed.

Hand handling of materials should be eliminated as much as possible. The resin (bakelite) used in this batch may produce a dermatitis. Therefore, it will be necessary to provide some protection for the skin if the resin is to be handled by hand. Weighed batches should then be kept in closed containers when transporting to the department where they are to be used. Vacuum system should be used for all cleaning purposes. *Yaman
Clean*

The mixing and rolling operations do not present any dusty conditions, with the exception of mixers #332 and 313 (sample #6). At this point consider-

*Can mixers be installed
in room -
Small Collection
Hillman*

02498

mer only
able cardolite dust is dispersed when dumping and mixing, until the material becomes thoroughly wet. This is for a short time only. The floor around these mixers is slippery due to the spilled material and moisture. These operators could be adequately protected if they were supplied with and wore approved dust respirators while handling and dumping the cardolite. The floor should be kept free of the dust to eliminate the hazardous slippery condition that exists. *H. H. H.*

Concentrations of 128 to 160 parts per million of gasoline vapors were detected in department 19, mixing and milling room. This concentration is far below approximately 1,000 parts per million, which is the maximum concentration allowable for prolonged exposure.

The batch weighing operations in the rubber compounding room are definitely hazardous under the present methods of operation. Samples 7 and 11 show concentrations of lead far in excess of the toxic limits, which have been determined to be 1.5 milligrams in a ten-hour day. The dust respirators supplied to the operator are not approved for lead dust. As this operator has not worn the respirator supplied him and has been exposed for a period of seven years, on and off, it is recommended that he be physically examined. Symptoms of lead poisoning are given in the rear of the report for the information of your physician. *man
man
man
approved
respirator*

Sample #15 does not indicate the need for any further protection for the operators working in the vicinity of #4 beater, other than the proper type of respirator. As this is an intermittent and comparatively short operation, the insistence by the foreman that the respirators be worn should not be a serious hardship for the man. *1-1-1*

Sample #19 (in the finishing department between Blanchard grinders 371 and 763) shows a definite hazardous condition. Although this result was

obtained under an abnormal condition due to improper setting of the exhaust system, it serves to demonstrate the need for periodic check up of these systems by the engineering staff. The lead concentration found at this point is three times greater than the toxic limit. Sample #21, between machines #457 and 455, indicates the more normal condition at the Blanchard grinders.

Sample #24, department #13, shows a lead concentration approaching closely to the toxic limit. This condition could be eliminated by means of one central batch weighing and mixing department, as has already been suggested for other batch weighing operations.

The saturant room did not show any dangerous concentrations of solvents. Sixty-four parts per million of xylol were found. The maximum concentration for prolonged exposure of xylol has been estimated to be less than 100 parts per million.

It is recommended that when new processes are to be installed a study be made of the various ingredients in the material, as to their toxicity, and the proper protection applied at the beginning of the operation and while it is in the experimental stage.

Taking into consideration the amount of grinding and drilling done, the counts found were low, indicating the efficiency of the exhaust systems. The hazards in the plant are confined solely to the batch weighing and mixing operations. Proper control of these operations will eliminate the health hazards in this plant.

The report of the survey made in June 1935 contains a discussion of health hazards of the toxic substances used. Reference should be made to this report in connection with the findings of the present report.

**THE ASBESTOS DIVISION
of
RAYMOND MANHATTAN, INC.
Stratford, Ct.**

1935

Ft. Lead	Millions Dust Particles per cu. ft. air sampled	Milligrams Lead per cu. ft.	Milligrams Lead per 10-hr. day	Sample No.	Date of Sampling	Cu.Ft. Air Sampled	Millions Dust Particles per cu.ft.air sampled	Milligrams Lead per cu.ft.	Milligrams Lead per 10-hr. day	Type of Dust	Remarks	1939 Survey
0.0	19.3	116								Asbestos	1 man; approved dust respirator worn. No dust control applied at this crusher.	
3.0	3.9	73		1	6/25/35	49.0	4.7			"	Scrap hand shoveled from floor into pulverizer.	
17.0	6.2	38		6	"	8.5	20.0			"	Asbestos scooped from floor by hand into opener.	
21.0	24.0	X 144								Asbestos scrap cardolite resin plasticizer	All materials hand shoveled from original containers into barrel on the scale. No respirator worn. No dust control applied.	
22.0	3.3	9	0.001	2	"	49.3	2.3	0.00038	0.136	Litharge asbestos rubber whiting mica sulphur arcilor	Machines closed while running	
30.0	49.0	X 294								Cardolite	Considerable dust given off when dumping and until material becomes wet.	
9.0	53.6	X 352	0.3895							Litharge asbestos rubber whiting mica sulphur arcilor	1 man; intermittent opera- tion; respirator had been supplied but not worn; no dust control applied.	
12.0	45.0	270	0.3039							"	No dust control applied.	
35.0	6.0	36	0							"	2 men	
42.0	2.5	15	0							"	Miners and rolls closed while operating.	
39.0	1.1	7	0	7	"	42.7	1.2	0	0	"		
54.0	3.5	21		13	6/26/35	105.0	1.4			Asbestos	Scrap material fed into belters by hand.	
70.0	6.4	39	0.0002							Metallic lead asbestos gre-hite silicite alum	Metallic lead dumped on a cardboard on the floor and hand shoveled into a sieve over the belter. Respira- tors not worn. No dust control applied.	
39.0	2.3	14	0							"	Pulp run into troughs (coffins) and dehydrated. Material then pressed and cut into strips.	
76.0	1.2	7		11	6/25/35	56.7	2.4			Asbestos		
76.0	5.0	20		12	"	46.0	4.4			"	1 man looks. 1 man removes excess board from machine 1 girl wiring edges of clutch fatings; no dust control applied.	
26.0	6.4	38		17	6/26/35	42.4	1.6			"	Cutting board to size. Floor cleaned by dry sweep- ing and shoveling during sampling period. No dust control applied.	
77.0	3.1	19		14	"	42.9	1.8			"	No dust control applied.	
76.0	14.8	20	0.0136	18	"	25.4	6.5	0	0	"	The compressed air line used to suggest the ex- haustion of the	

