

WEA 711-1111

WESCO

BUYER'S GUIDE

Westinghouse Electric Supply Co.

ST. LOUIS 2, MO.

1011 SPRUCE ST.

Tel.: Central 1-4838

Free Parking

PLAINTIFF'S
EXHIBIT
WH-158.

ASBESTOS, MAGNET AND RUBBER COVERED WIRES

"ROCKBESTOS" ASBESTOS- VARNISHED CAMBRIC WIRE (Type "A. V. A.")

Max. Operating Temp. 110° C., 230° F.
For open wiring or general conduit work in boiler rooms, or where the wiring may be subjected to heat, oil, grease or fire hazard.
Construction: Solid plain copper conductor. Two layers of Varnished Cambric. Felted Asbestos. Saturated asbestos braid.
Colors: Black or White.

No.	1000 Ft.	250 Ft.	500 Ft.
12	41	\$14.52 C	\$11.12 C
14	60	18.36 C	14.74 C
16	85	28.52 C	22.82 C
18	108	36.00 C	28.00 C
20	132	44.00 C	35.00 C
22	156	52.00 C	42.00 C
24	180	60.00 C	49.00 C
26	204	68.00 C	56.00 C
28	228	76.00 C	63.00 C
30	252	84.00 C	70.00 C
32	276	92.00 C	77.00 C
34	300	100.00 C	84.00 C
36	324	108.00 C	91.00 C
38	348	116.00 C	98.00 C
40	372	124.00 C	105.00 C
42	396	132.00 C	112.00 C
44	420	140.00 C	119.00 C
46	444	148.00 C	126.00 C
48	468	156.00 C	133.00 C
50	492	164.00 C	140.00 C
52	516	172.00 C	147.00 C
54	540	180.00 C	154.00 C
56	564	188.00 C	161.00 C
58	588	196.00 C	168.00 C
60	612	204.00 C	175.00 C
62	636	212.00 C	182.00 C
64	660	220.00 C	189.00 C
66	684	228.00 C	196.00 C
68	708	236.00 C	203.00 C
70	732	244.00 C	210.00 C
72	756	252.00 C	217.00 C
74	780	260.00 C	224.00 C
76	804	268.00 C	231.00 C
78	828	276.00 C	238.00 C
80	852	284.00 C	245.00 C
82	876	292.00 C	252.00 C
84	900	300.00 C	259.00 C
86	924	308.00 C	266.00 C
88	948	316.00 C	273.00 C
90	972	324.00 C	280.00 C
92	996	332.00 C	287.00 C
94	1020	340.00 C	294.00 C
96	1044	348.00 C	301.00 C
98	1068	356.00 C	308.00 C
100	1092	364.00 C	315.00 C

"ROCKBESTOS" ASBESTOS COVERED STOVE WIRE (Underwriters' Approved)

Max. Operating Temp. 200° C., 392° F.

Not for general use. For leads to and within apparatus.
Construction: Copper conductor. Heavy, woven white asbestos outer braid, smoothly finished. Colors: White, Black, Red, Green, and Yellow.

No.	1000 Ft.	250 Ft.	500 Ft.
12	30	\$10.64 C	\$8.54 C
14	36	11.38 C	9.06 C
16	42	12.30 C	9.80 C
18	48	13.02 C	10.54 C
20	54	13.94 C	11.28 C
22	60	14.86 C	12.02 C
24	66	15.78 C	12.76 C
26	72	16.70 C	13.50 C
28	78	17.62 C	14.24 C
30	84	18.54 C	14.98 C
32	90	19.46 C	15.72 C
34	96	20.38 C	16.46 C
36	102	21.30 C	17.20 C
38	108	22.22 C	17.94 C
40	114	23.14 C	18.68 C
42	120	24.06 C	19.42 C
44	126	24.98 C	20.16 C
46	132	25.90 C	20.90 C
48	138	26.82 C	21.64 C
50	144	27.74 C	22.38 C
52	150	28.66 C	23.12 C
54	156	29.58 C	23.86 C
56	162	30.50 C	24.60 C
58	168	31.42 C	25.34 C
60	174	32.34 C	26.08 C
62	180	33.26 C	26.82 C
64	186	34.18 C	27.56 C
66	192	35.10 C	28.30 C
68	198	36.02 C	29.04 C
70	204	36.94 C	29.78 C
72	210	37.86 C	30.52 C
74	216	38.78 C	31.26 C
76	222	39.70 C	32.00 C
78	228	40.62 C	32.74 C
80	234	41.54 C	33.48 C
82	240	42.46 C	34.22 C
84	246	43.38 C	34.96 C
86	252	44.30 C	35.70 C
88	258	45.22 C	36.44 C
90	264	46.14 C	37.18 C
92	270	47.06 C	37.92 C
94	276	47.98 C	38.66 C
96	282	48.90 C	39.40 C
98	288	49.82 C	40.14 C
100	294	50.74 C	40.88 C

"ROCKBESTOS" ASBESTOS A. V. C. SWITCHBOARD WIRE

Solid tinned copper conductor, insulated with varnish cambric, separator, felted asbestos, flameproof cotton braid overall.

Max. Operating Temp. 90° C., 194° F.

No.	1000 Ft.	250 Ft.	500 Ft.
12	37	\$11.48 C	\$9.08 C
14	47	12.76 C	10.00 C
16	62	15.28 C	11.76 C
18	87	19.48 C	15.12 C
20	112	23.68 C	18.48 C
22	137	27.88 C	21.84 C
24	162	32.08 C	25.20 C
26	187	36.28 C	28.56 C
28	212	40.48 C	31.92 C
30	237	44.68 C	35.28 C
32	262	48.88 C	38.64 C
34	287	53.08 C	42.00 C
36	312	57.28 C	45.36 C
38	337	61.48 C	48.72 C
40	362	65.68 C	52.08 C
42	387	69.88 C	55.44 C
44	412	74.08 C	58.80 C
46	437	78.28 C	62.16 C
48	462	82.48 C	65.52 C
50	487	86.68 C	68.88 C
52	512	90.88 C	72.24 C
54	537	95.08 C	75.60 C
56	562	99.28 C	78.96 C
58	587	103.48 C	82.32 C
60	612	107.68 C	85.68 C
62	637	111.88 C	89.04 C
64	662	116.08 C	92.40 C
66	687	120.28 C	95.76 C
68	712	124.48 C	99.12 C
70	737	128.68 C	102.48 C
72	762	132.88 C	105.84 C
74	787	137.08 C	109.20 C
76	812	141.28 C	112.56 C
78	837	145.48 C	115.92 C
80	862	149.68 C	119.28 C
82	887	153.88 C	122.64 C
84	912	158.08 C	126.00 C
86	937	162.28 C	129.36 C
88	962	166.48 C	132.72 C
90	987	170.68 C	136.08 C
92	1012	174.88 C	139.44 C
94	1037	179.08 C	142.80 C
96	1062	183.28 C	146.16 C
98	1087	187.48 C	149.52 C
100	1112	191.68 C	152.88 C

THERMOSTAT CABLE

Extensively used for automatic fuel burner control, signal and intercommunicating systems. Armored Thermostat Cable Table "TC"

No. 18 solid copper conductor with asbestos insulation and cadmium plated steel armor over all.

No.	100 Ft.	500 Ft.
12	3	\$8.30 C
14	4	12.30 C
16	5	16.30 C
18	6	20.30 C
20	7	24.30 C
22	8	28.30 C
24	9	32.30 C
26	10	36.30 C
28	11	40.30 C
30	12	44.30 C
32	13	48.30 C
34	14	52.30 C
36	15	56.30 C
38	16	60.30 C
40	17	64.30 C
42	18	68.30 C
44	19	72.30 C
46	20	76.30 C
48	21	80.30 C
50	22	84.30 C
52	23	88.30 C
54	24	92.30 C
56	25	96.30 C
58	26	100.30 C
60	27	104.30 C
62	28	108.30 C
64	29	112.30 C
66	30	116.30 C
68	31	120.30 C
70	32	124.30 C
72	33	128.30 C
74	34	132.30 C
76	35	136.30 C
78	36	140.30 C
80	37	144.30 C
82	38	148.30 C
84	39	152.30 C
86	40	156.30 C
88	41	160.30 C
90	42	164.30 C
92	43	168.30 C
94	44	172.30 C
96	45	176.30 C
98	46	180.30 C
100	47	184.30 C

PLASTIC THERMOSTAT CABLE

No Over-All Covering
Thermoplastic Insulated
Solid copper conductors, insulated with thermoplastic, color coded for identification.

No.	100 Ft.	500 Ft.
12	2	\$2.46 C
14	3	3.69 C
16	4	4.92 C
18	5	6.15 C
20	6	7.38 C
22	7	8.61 C
24	8	9.84 C
26	9	11.07 C
28	10	12.30 C
30	11	13.53 C
32	12	14.76 C
34	13	15.99 C
36	14	17.22 C
38	15	18.45 C
40	16	19.68 C
42	17	20.91 C
44	18	22.14 C
46	19	23.37 C
48	20	24.60 C
50	21	25.83 C
52	22	27.06 C
54	23	28.29 C
56	24	29.52 C
58	25	30.75 C
60	26	31.98 C
62	27	33.21 C
64	28	34.44 C
66	29	35.67 C
68	30	36.90 C
70	31	38.13 C
72	32	39.36 C
74	33	40.59 C
76	34	41.82 C
78	35	43.05 C
80	36	44.28 C
82	37	45.51 C
84	38	46.74 C
86	39	47.97 C
88	40	49.20 C
90	41	50.43 C
92	42	51.66 C
94	43	52.89 C
96	44	54.12 C
98	45	55.35 C
100	46	56.58 C

THERMOPLASTIC INSULATED ANNUNCIATOR AND BELL WIRE

No.	100 Ft.	500 Ft.
12	2	\$2.46 C
14	3	3.69 C
16	4	4.92 C
18	5	6.15 C
20	6	7.38 C
22	7	8.61 C
24	8	9.84 C
26	9	11.07 C
28	10	12.30 C
30	11	13.53 C
32	12	14.76 C
34	13	15.99 C
36	14	17.22 C
38	15	18.45 C
40	16	19.68 C
42	17	20.91 C
44	18	22.14 C
46	19	23.37 C
48	20	24.60 C
50	21	25.83 C
52	22	27.06 C
54	23	28.29 C
56	24	29.52 C
58	25	30.75 C
60	26	31.98 C
62	27	33.21 C
64	28	34.44 C
66	29	35.67 C
68	30	36.90 C
70	31	38.13 C
72	32	39.36 C
74	33	40.59 C
76	34	41.82 C
78	35	43.05 C
80	36	44.28 C
82	37	45.51 C
84	38	46.74 C
86	39	47.97 C
88	40	49.20 C
90	41	50.43 C
92	42	51.66 C
94	43	52.89 C
96	44	54.12 C
98	45	55.35 C
100	46	56.58 C

ANNUNCIATOR WIRE

Single supplied on 1/2 lb. coil and 7 lb. spool, 140 ft. to lb. Twisted supplied on 5 lb. spool.

No.		Per Lb.	25-lb. Per Ctn.
12	Single, 1 1/2 lb. Coil.....	1.52	\$37.00
14	Single, 1-lb. Coil.....	1.76	42.00
16	Single, 7-lb. Spool.....	1.74	43.50
18	Twisted, 5-lb. Spool.....	1.98	49.50

RUBBER JACKETED, THERMO-PLASTIC PORTABLE LAMP AND HEATER CORDS

RUBBER CORD—TYPE SJ For Stationary Service For the Shop or Commercial Use

Similar in size and appearance to Type SJO Cord. This is a competitive grade of All Rubber Covered Cord.

No.	Wires	O.D.	Strands	Less than 250 Ft. Coil @	250 Ft. Coil @
18-2	2	.31"	16/30	\$74.74 M	\$88.00 M
16-2	2	.33"	26/30	\$9.20 M	\$8.30 M
18-3	3	.34"	16/30	\$12.60 M	\$7.90 M
16-3	3	.36"	26/30	\$13.10 M	\$12.50 M

TYPE "S" 600 VOLTS. ALL RUBBER CORD

GENERAL CABLE

Flexible copper conductors. Cotton separator. 30% rubber insulation over each conductor, color coded. Conductors covered with cotton filler and cotton braid. 40% rubber outer jacket.

No.	Strands	Less than 250 Ft. Coil @	250 Ft. Coil @
18-2	41/30	\$120.76	\$105.00
18-3	41/30	\$151.80	\$132.00
16-2	65/30	\$149.50	\$130.00
16-3	65/30	\$173.10	\$152.00
14-2	41/30	\$97.30	\$87.00
14-3	41/30	\$122.10	\$105.00
12-2	41/30	\$94.40	\$82.00
12-3	41/30	\$117.50	\$102.00
10-2	103/30	\$48.90	\$42.00
10-3	103/30	\$53.42	\$46.24

HOUSEHOLD ALL-RUBBER CORD TYPE T SPEC. 745-S

GENERAL CABLE

No.	Wires	Dis.	Strands	Less than 250 Ft. Coil @	250 Ft. Coil @
18-2	2	.250	41/30	\$71.90 M	\$62.50 M

TYPE SPT-1 THERMOPLASTIC CORD

GENERAL CABLE

2 conductor parallel flexible Type T. Colors: Black, Brown and Ivory.

No.	Strands	Less than 250 Ft. Coil @	500 Ft. Coil @
18-2	41/30	\$33.20 M	\$28.85 M
16-2	65/30	\$70.38 M	\$61.20 M

TYPE SP-1 TWIN PARALLEL ALL RUBBER CORD (POSJ)

GENERAL CABLE

This all rubber parallel cord is "extra special flexible" conductors constructed of 41 strands of No. 34 wire, both embedded in a single strip of soft flexible para rubber.

No.	Less than 250 Ft. Spool @	500 Ft. Spool @
18-2	\$35.90 M	\$31.26 M
16-2	\$2.50 M	\$4.60 M
16-1	\$73.30 M	\$63.76 M

GLAZED COTTON COVERED SINGLE CONDUCTOR CORD—TYPE "FF"

GENERAL CABLE

No.	Less than 1000 Ft. Spool @	1000 Ft. Spool @
18-1	\$25.80 M	\$22.50 M

TYPE SJO-1 INDUSTRIAL CORD

With 60% Neoprene Jacket. Oil Resisting 300 Volts for Constant Service

No.	Strands	O.D.	Less than 250 Ft. Per M Ft.	250 Ft. Per M Ft.	M Ft.
18-2	41/30	.325	\$136.00	\$ 88.40	\$ 81.60
18-3	41/30	.355	\$181.40	\$117.90	\$108.84
16-2	65/30	.350	\$160.40	\$104.26	\$ 96.24
16-3	65/30	.380	\$221.20	\$143.78	\$132.72

TYPE SO-1 INDUSTRIAL CORD

With 60% Neoprene Jacket. Oil Resisting. 600 V.

GENERAL CABLE

Same construction as Security Flex, Super Service, etc., except the neoprene sheath is cured by the continuous vulcanizing (CV) method.

No.	Stranding	O.D.	Less than 250 Ft. Per M Ft.	250 Ft. Per M Ft.	1000 Ft.
18-2	41/30	.400	\$226.00	\$146.90	\$135.60
18-3	41/30	.425	\$268.00	\$187.20	\$172.80
16-2	65/30	.425	\$255.00	\$165.74	\$152.00
16-3	65/30	.450	\$340.00	\$221.00	\$204.00
14-2	41/30	.455	\$477.00	\$310.94	\$284.20
14-3	41/30	.550	\$415.20	\$268.88	\$248.12
12-2	41/30	.550	\$340.00	\$221.00	\$204.00
12-3	41/30	.625	\$741.00	\$481.64	\$444.00
10-2	65/30	.625	\$630.00	\$384.94	\$357.80
10-3	103/30	.675	\$764.00	\$494.60	\$458.40
8-3	105/30	.710	\$822.00	\$521.30	\$480.20

TYPE COTTON TWISTED LAMP CORD

GENERAL CABLE

Type C—Green and Yellow and Olive Green

On 250 Ft. Metal Spools

No.	Less than 250 Ft. Coil @	250 Ft. Coil @
18	\$57.50 M	\$50.00 M
16	\$50.50 M	\$42.00 M
14	\$45.10 M	\$37.50 M

BREWERY CORD TWISTED

GENERAL CABLE

Type C—Twisted Flexible

Less than 250 Ft. Coil @

No.	Less than 250 Ft. Coil @	250 Ft. Coil @
18	\$75.50 M	\$68.20 M
16	\$67.00 M	\$60.00 M
14	\$58.50 M	\$52.00 M

TYPE "TF" THERMO-PLASTIC INSULATED WIRES

GENERAL CABLE

600 Volts—60° C.

No braid or wrap. Single conductor

Less than 1000 Ft. Spool @

Per M Ft.

18/4

16/2

18/4

16/2

Colors: Black, White, Red, Green, or Blue.

TYPE TFF FIXTURE WIRE

GENERAL CABLE

Thermoplastic Insulated

600 Volts, No Braid, Stranded Extra Flexible.

Less than 1000 Ft. Spool @

No. Stranding Ins. Coil

18 16/30 1/4 \$22.48 \$19.54

16 26/30 1/4 26.36 23.36

HEATER CORD—Type HPD—3000 Cycle

GENERAL CABLE

Extra flexible. All sizes have strands constructed of No. 34 wire, insulated, with pure asbestos yarn, covered with black and gray braid.

No.	Less than 250 Ft. Spool @	250 Ft. Spool @
18	\$81.90 M	\$71.26 M
16	\$60.70 M	\$57.50 M
14	\$35.10 M	\$31.75 M

THREE WIRE HEATER CORD

GENERAL CABLE

Type HPD—3000 Cycle

Less than 250 Ft. Spool @

18-3 \$12.48 C 250 Ft. Coil @ \$108.46 M

HEATER CORD—Type HPD—10,000 Cycle

GENERAL CABLE

"Special extra flexible" with conductors constructed of strands of No. 36 wire. Insulated with pure asbestos yarn. Glazed black and gray cotton braid with rayon marker.

Less than 250 Ft. Spool @

18 \$66.24 M \$57.00 M

16 \$52.92 M \$45.50 M

"AMERICAN BEAUTY" HEATER CORD

GENERAL CABLE

Each conductor is wound with rayon marker and insulated with rubber and pure asbestos yarn. Conductors are twisted together with black and gold outer braid.

Each conductor constructed of strands of No. 36 wire. (With Braid Overall)

Less than 250 Ft. Spool @

No. Gauge Per M Ft.

100GB 17 \$92.70

ASBESTOS INSULATED HEAT RESISTING FIXTURE CORD—Type AF

GENERAL CABLE

Flexible, plain copper conductor, rated asbestos insulation.

Less than 250 Ft. Spool @

No. Stranding Spool

WITH RAYON BRAID—TABLE 1

18 16/30 \$37.98 M \$33.00 M

16 26/30 \$41.60 M \$36.00 M

14 41/30 \$4.96 M \$4.00 M

WITHOUT BRAID—TABLE 2

18 16/30 \$26.10 M \$22.00 M

16 26/30 \$31.10 M \$26.00 M

14 41/30 \$9.10 M \$7.00 M

12 65/30 \$1.08 M \$0.80 M

TYPE CF SINGLE CONDUCTOR FIXTURE CORD

GENERAL CABLE

Flame resisting insulation, constructed of strands of No. 30 wire.

Black, White, Brown, Soft Cotton

Less than 1000 Ft. Spool @

No. Strands Spool @

18 16/30 \$ 2.92 C \$2.00 M

28 30/30 3.82 C 2.80 M

TWO AND THREE CONDUCTOR OSCILLATING FAN CORD

GENERAL CABLE

Extremely flexible and well suited for operating service.

Less than 1000 Ft. Spool @

No. Cond. Stranding Spool @

20-2 2 105 #40 \$10.50

20-3 3 105 #40 16.34