



R.T. Vanderbilt Company, Inc.

INDUSTRIAL MINERALS AND CHEMICALS

10 Winfield Street, Norwalk, CT 06855 • (203) 853-1400 • TWX 710-368-2940
West Coast: 6279 East Stauson Avenue, Los Angeles, CA 90040 • (213) 723-5208

MATERIAL SAFETY DATA SHEET

DATE: APR 4 1985

SECTION I

CHEMICAL NAME AND SYNONYMS
sym. Di- β -naphthyl-p-phenylenediamine

EMERGENCY TELEPHONE NO.
(203) 853-1400

CHEMICAL FAMILY
Organic secondary amine

FORMULA
(C₁₀H₇)₂NC₆H₄NH₂

TRADE NAME AND SYNONYMS
AGERITE[®] WHITE

SECTION II INGREDIENTS

MATERIAL	%	TOXICITY DATA
sym. Di- β -naphthyl-p-phenylenediamine	95 min.	
Product		Acute oral LD ₅₀ 4.5 g/kg rats; acute oral LD ₅₀ 1.8 g/kg mice

SECTION III PHYSICAL DATA

BOILING POINT (°F.)	600	DENSITY Mg/m ³	1.25
VAPOR PRESSURE (mm Hg.)	None	PERCENT VOLATILE BY VOLUME (%)	1.0% max.
VAPOR DENSITY (AIR=1)	-	EVAPORATION RATE (_____ =1)	None
SOLUBILITY IN WATER	Negligible		
APPEARANCE AND ODOR	Light grey powder with slight amine odor		

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED) Ignition temp: 640 °C (1140 °F)	FLAMMABLE LIMITS	LeI	UeI
EXTINGUISHING MEDIA Foam, dry chemical			
SPECIAL FIRE FIGHTING PROCEDURES CO ₂ may be ineffective on larger fires due to lack of cooling capacity which may result in reignition.			
UNUSUAL FIRE AND EXPLOSION HAZARDS Positive pressure self-contained breathing apparatus should be used in fighting fire. Ignition sensitivity: 0.41 (low); Explosion severity: 3.67 (severe); Explosibility Index: 1.50 (strong). Min. explosion concentration: 0.023 oz./cu. ft.			

DO 085845
CONFIDENTIAL

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be construed as recommending any practice or any product in violation of any patent or in violation of any law or regulation. It is the user's responsibility to determine for himself the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. We make no warranty as to the results to be obtained in using any material and, since conditions of use are not under our control, we must necessarily disclaim all liability with respect to the use of any material supplied by us.

SECTION V HEALTH HAZARD DATA	
THRESHOLD LIMIT VALUE	N.A.
EFFECTS OF OVEREXPOSURE	
EMERGENCY AND FIRST AID PROCEDURES	
Skin: wash with soap and water	
Eyes: irrigate with water - call physician	
Inhalation: expose to fresh air	

SECTION VI REACTIVITY DATA			
STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	
INCOMPATIBILITY (MATERIALS TO AVOID) Strong oxidizing agents			
HAZARDOUS DECOMPOSITION PRODUCTS Oxides of carbon and nitrogen, aromatic and aliphatic hydrocarbon decomposition			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	temperature.

SECTION VII SPILL OR LEAK PROCEDURES	
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED	Spillings should be cleaned up immediately. Sweep or vacuum into containers using care to avoid dust generation.
WASTE DISPOSAL METHOD	As per organic compounds

SECTION VIII SPECIAL PROTECTION INFORMATION			
RESPIRATORY PROTECTION (SPECIFY TYPE) NIOSH dust respirator in dusty conditions			
VENTILATION	LOCAL EXHAUST	Exhaust ventilation	SPECIAL
	MECHANICAL (GENERAL)		OTHER
PROTECTIVE GLOVES	Rubber	EYE PROTECTION	Goggles
OTHER PROTECTIVE EQUIPMENT			

SECTION IX SPECIAL PRECAUTIONS	
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING AGERITE WHITE - as manufactured does not involve β -naphthylamine as a raw material. Some new techniques of analysis indicate trace quantities of β -naphthylamine present. Although we believe no abnormal hazard is involved in normal use of the antioxidant, normal safety handling techniques should be observed. Do not breathe processing fumes and dust. Wash hands after handling and before smoking and eating. Wash contaminated clothing before reuse. Prevent an accumulation of potentially explosive dust concentrations. Use explosion proof electrical equipment and ground processing equipment.	

DO 085846
CONFIDENTIAL



R. T. Vanderbilt Company, Inc.

INDUSTRIAL MINERALS AND CHEMICALS

30 Winfield Street, Norwalk, CT 06855 (203) 853-1400

West Coast: 6279 East Slauson Avenue, Los Angeles, CA 90040 (213) 723-5208

SPECIFICATION

AGERITE® WHITE

Antioxidant

Rubber Department

September 15, 1977

<u>Composition:</u>	Sym. di-beta-naphthyl-p-phenylenediamine
<u>Physical state:</u>	Powder
<u>Color:</u>	Gray to light tan
<u>Density:</u>	$1.25 \pm 0.03 \text{ Mg/m}^3$
<u>Melting range:</u>	224 - 230 C
<u>Heating loss:</u>	1.0% maximum
<u>Ash:</u>	0.25% maximum
<u>Beta naphthol:</u>	1.5% maximum
<u>Fineness (100 mesh):</u>	99.5% minimum
<u>Standard container:</u>	200 lb. drum
<u>Use data:</u>	Antioxidant and copper inhibitor in all elastomers. 1-2 phr provides good resistance to heat and oxidation. Used alone or in combination with other antioxidants to provide maximum service life for all rubber products. Products are non-staining, with reference to lacquers, enamels, but discolor on light exposure. Maximum non-blooming dosage 2.0%.

RV-77-1-1

DO 085847
CONFIDENTIAL

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be construed as recommending any practice or any product in violation of any patent or in violation of any law or regulation. It is the user's responsibility to determine for himself the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. We make no warranty as to the results to be obtained in using any material and, since conditions of use are not under our control, we must necessarily disclaim all liability with respect to the use of any material supplied by us.



MATERIAL SAFETY DATA SHEET

(Approved by U.S. Department of Labor as "essentially similar" to Form LSB-00S-4)

SECTION I IDENTIFICATION OF PRODUCT	
MANUFACTURER AKRON CHEMICAL COMPANY	EMERGENCY TELEPHONE NO. 216-535-2108
ADDRESS 255 Fountain St., Akron, Ohio 44304	
TRADE NAME AND SYNONYMS AKROCHEM® E-8851 DARK BROWN IRON OXIDE	
CHEMICAL NAME AND SYNONYMS IRON OXIDE CAS# 1309-38-2	
CHEMICAL FAMILY METAL OXIDE	MOLECULAR FORMULA COLOR INDEX NO. 77491

SECTION II HAZARDOUS COMPONENTS OF MIXTURES					
COMPONENT	%	THRESHOLD LIMIT VALUE (UNITS)	COMPONENT	%	THRESHOLD LIMIT VALUE (UNITS)
OUR INTERPRETATION OF THE OCCUPATIONAL SAFETY AND HEALTH ACT OF 1970 INDICATES THIS PRODUCT SHOULD NOT BE CONSIDERED HAZARDOUS.					

SECTION III PHYSICAL DATA			
APPEARANCE AND ODOR BROWN, ODORLESS POWDER			
BOILING POINT (DEGREES FAHRENHEIT)	NA	SPECIFIC GRAVITY (WATER = 1)	4.4
VAPOR PRESSURE (MM. OF MERCURY)	NA	PERCENT VOLATILE (BY VOLUME)	NA
VAPOR DENSITY (AIR = 1)	NA	EVAPORATION RATE (BUTYL ACETATE = 1)	NA
SOLUBILITY IN WATER	INSOLUBLE	EVAPORATION RATE (ETHYL ETHER = 1)	NA

SECTION IV FIRE AND EXPLOSION HAZARD DATA			
FLASH POINT (SPECIFY METHOD) (DEGREES FAHRENHEIT)	NA	FLAMMABLE LIMITS (PERCENT BY VOLUME)	LOWER NA UPPER
FIRE-EXTINGUISHING MEDIA NONE (DOES NOT BURN)			
SPECIAL FIRE-FIGHTING PROCEDURES NONE			
UNUSUAL FIRE AND EXPLOSION HAZARDS NONE			

DO 085848
CONFIDENTIAL

THIS INFORMATION IS GIVEN WITHOUT A WARRANTY OR REPRESENTATION. WE DO NOT ASSUME ANY LEGAL RESPONSIBILITY FOR SAME, NOR DO WE GIVE PERMISSION, INDUCEMENT, OR RECOMMENDATION TO PRACTICE ANY PATENTED INVENTION WITHOUT A LICENSE. IT IS OFFERED SOLELY FOR YOUR CONSIDERATION, INVESTIGATION AND VERIFICATION. BEFORE USING ANY PRODUCT, READ ITS LABEL.

SECTION V HEALTH HAZARD DATA	
THRESHOLD LIMIT VALUE	N/E TREAT AS INERT OR NUISANCE DUST
EFFECTS OF OVEREXPOSURE	N/A
EMERGENCY AND FIRST AID PROCEDURES	
EYE CONTACT: FLUSH WITH PLENTY OF WATER. CONSULT PHYSICIAN SKIN CONTACT: WASH WITH SOAP AND WATER.	

SECTION VI REACTIVITY DATA			
STABILITY	UNSTABLE		CONDITIONS TO AVOID N/A
	STABLE	XX	
INCOMPATIBILITY (Materials to avoid) N/A			
HAZARDOUS DECOMPOSITION PRODUCTS N/A			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID N/A
	WILL NOT OCCUR	XX	

SECTION VII SPILL OR LEAK PROCEDURES	
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED SWEEP OR VACUUM UP.	
WASTE DISPOSAL METHOD LANDFILL, IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.	

SECTION VIII SPECIAL PROTECTION INFORMATION			
RESPIRATORY PROTECTION (Specify type) NIOSH APPROVED DUST RESPIRATOR			
VENTILATION	LOCAL EXHAUST	XX	SPECIAL
	MECHANICAL (General)		OTHER
PROTECTIVE GLOVES RECOMMENDED		EYE PROTECTION SAFETY GOGGLES	
OTHER PROTECTIVE EQUIPMENT N/A			

SECTION IX SPECIAL PRECAUTIONS	
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING N/A	
OTHER PRECAUTIONS N/A	

DO 085849
CONFIDENTIAL

SECTION X DATE AND SOURCE OF INFORMATION		
DATE 10-8-85	NAME AND TITLE	SHEET NUMBER

J.E. MYERS MANAGER-TECHNICAL SERVICES



MATERIAL SAFETY DATA SHEET

E-5365

(Approved by U.S. Department of Labor as "essentially similar" to Form LSB-00S-4)

SECTION I IDENTIFICATION OF PRODUCT

MANUFACTURER	AKRON CHEMICAL COMPANY	EMERGENCY TELEPHONE NO.	216-535-2108
ADDRESS	255 Fountain St., Akron, Ohio 44304		
TRADE NAME AND SYNONYMS	AKROCHEM® 5172 MED. LT. CADMIUM RED LITHOPONE		
CHEMICAL NAME AND SYNONYMS	C.I. PIGMENT RED 108, C.I. NO. 77196		
CHEMICAL FAMILY	MOLECULAR FORMULA		

SECTION II HAZARDOUS COMPONENTS OF MIXTURES

COMPONENT	%	THRESHOLD LIMIT VALUE (UNITS)	COMPONENT	%	THRESHOLD LIMIT VALUE (UNITS)
CADMIUM COMPOUNDS (AS CD)	27%				
PEL=0.2 MG CD/CU.M AIR TWA (OSHA)					
SELENIUM COMPOUND (AS SE)	6%				
PEL=0.2 MG SE/CU.M AIR TWA (OSHA)					

SECTION III PHYSICAL DATA

APPEARANCE AND ODOR			
RED POWDER, ODORLESS			
BOILING POINT (DEGREES FAHRENHEIT)	NOT APPLICABLE	SPECIFIC GRAVITY (WATER = 1)	APPROX. 5
VAPOR PRESSURE (MM. OF MERCURY)	NOT APPLICABLE	PERCENT VOLATILE (BY VOLUME)	NOT APPLICABLE
VAPOR DENSITY (AIR = 1)	NOT APPLICABLE	EVAPORATION RATE (BUTYL ACETATE = 1)	NOT APPLICABLE
SOLUBILITY IN WATER	NEGLIGIBLE	EVAPORATION RATE (ETHYL ETHER = 1)	NOT APPLICABLE

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (SPECIFY METHOD) (DEGREES FAHRENHEIT)	NOT APPLICABLE	FLAMMABLE LIMITS (PERCENT BY VOLUME)	LOWER	UPPER
FIRE-EXTINGUISHING MEDIA	WATER			
SPECIAL FIRE-FIGHTING PROCEDURES	NONE REQUIRED.			
UNUSUAL FIRE AND EXPLOSION HAZARDS				

THIS INFORMATION IS GIVEN WITHOUT A WARRANTY OR REPRESENTATION. WE DO NOT ASSUME LIABILITY FOR SAME, NOR DO WE GIVE PERMISSION, INDUCEMENT, OR RECOMMENDATION TO PRACTICE ANY PATENTED INVENTION WITHOUT A LICENSE. IT IS OFFERED SOLELY FOR YOUR CONSIDERATION, INVESTIGATION AND VERIFICATION. BEFORE USING ANY PRODUCT, READ ITS LABEL.

DO 085850
CONFIDENTIAL

SECTION V HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE

SEE HAZARDOUS INGREDIENTS

EFFECTS OF OVEREXPOSURE

CAUTION: REPEATED AND PROLONGED INHALATION MAY CAUSE DELAYED INJURY.

EMERGENCY AND FIRST AID PROCEDURES

FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES.
SKIN: WASH WITH SOAP AND WATER.

SECTION VI REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	
INCOMPATIBILITY (Materials to avoid)			
NONE KNOWN			
HAZARDOUS DECOMPOSITION PRODUCTS			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

SWEEP OR VACUUM AND PLACE INTO CLOSABLE CONTAINER FOR DISPOSAL.
WEAR PROTECTIVE EQUIPMENT SPECIFIED BELOW.

WASTE DISPOSAL METHOD

DISPOSE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type)

USE NIOSH APPROVED DUST MASK.

VENTILATION	LOCAL EXHAUST	USE LOCAL EXHAUST	SPECIAL
	MECHANICAL (General)		OTHER
PROTECTIVE GLOVES		EYE PROTECTION	
RECOMMENDED		PROTECT FROM DUST PARTICLES	
OTHER PROTECTIVE EQUIPMENT			

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

AVOID BREATHING DUST OR MIST. USE WITH ADEQUATE VENTILATION.

OTHER PRECAUTIONS

AVOID CONTACT WITH SKIN, EYES AND CLOTHING. WASH THOROUGHLY AFTER HANDLING, BEFORE EATING, DRINKING OR SMOKING. KEEP AWAY FROM FEED AND FOOD PRODUCTS. FOR MANUFACTURING USE ONLY.

SECTION X DATE AND SOURCE OF INFORMATION


DATE	4/1/83	NAME AND TITLE	W. H. Silver	SHEET NUMBER	E-5365
------	--------	----------------	--------------	--------------	--------

DO 085851
CONFIDENTIAL

Material Safety Data Sheet

HAZARD/ INDEX	0 Minimal 1 Slight 2 Moderate 3 Serious 4 Severe
HEALTH	2 *
FLAMMABILITY	0
REACTIVITY	1
PERSONAL PROTECTION	

H	2 *
F	0
R	1
PP	



ASTM: D-4257

HMIS System: NPCA

Date Prepared

11/19/85

*Also chronic effects - See Section VII

Section I - Product Identification	
MANUFACTURER AKRON CHEMICAL COMPANY	EMERGENCY TELEPHONE NO. 216-535-2108
ADDRESS 255 Fountain St., Akron, Ohio 44304	
TRADE NAME AND SYNONYMS AKROCIEM® RED LEAD 97 571150	
CHEMICAL NAME AND SYNONYMS LEAD TETRAOXIDE, LEAD ORTHOPLUMBATE C.A.S. #1314-41-6	
CHEMICAL FAMILY LEAD OXIDES	MOLECULAR FORMULA Pb₃O₄

Section II - Hazardous Ingredients						
Material or Component	Weight %	TLV-TWA mg/m ³ -8hrs.	TLV-STEL mg/m ³	TLV-C	BLV	LEL
Lead Tetraoxide	100	.03	0.45	NA	50 mg/100 R whole blood	NA
Material is a lead compound. Refer to Federal Register Vol. 43 #220, pp 53007-53014, Nov. 14, 1978. Standard (OSHA) - Occupational Exposure to Lead. Also Code of Federal Regulation CFR Title 29 1910.1025.						

Section III - Physical Data	
Boiling Point @ 760 mm Hg - Decomposes 1022°F	Specific Gravity (H ₂ O=1) - 9.1
Melting Point - 1642°F (Approx.)	Solubility in H ₂ O(g/l) - 6.85 x 10 ⁻⁷
Vapor Pressure (mm Hg) - 10 at 1985°F	Evaporation Rate - Not Applicable
Vapor Density - Not Applicable	Molecular Wt. - 685.6
% Volatiles by Volume - Not Applicable	
Appearance and Odor - Bright Red Powder; Odorless	

DO 085852
CONFIDENTIAL

Section IV - Fire and Explosion Hazard Data**Flammability:** NFPA FLAMMABILITY RATING = 0**Flash Point:** Not Applicable**Autoignition Temperature:** Not Applicable**Flammable Limits:** Not Applicable**Extinguishing Media:** Water Fog or Flood, CO₂ and Dry Chemical**Special Fire Fighting Procedures:** Wear full body protective clothing and full facepiece, self-contained breathing apparatus operated in positive-pressure mode.**Unusual Fire and Explosion Hazard:** Fume, vapor, and/or dust may occur and are considered toxic and respiratory irritants. The product or dust can react vigorously with strong oxidizing agents. Refer to FIRE PROTECTION GUIDE ON HAZARDOUS MATERIALS by N.F.P.A. for specific individual problem combination.**Section V - Reactivity Data****Reactivity:** NPCA HMIS RATING = 1**Stability:** Stable to 930°F**Conditions to Avoid:** Do not heat in presence of Al, Na, Ti, Zn.**Incompatibility (Materials to Avoid):** Reacts violently with Hydrogen Peroxide.**Hazardous Decomposition Products:** High temperatures or fire may produce lead oxide fume, vapor, or dust.**Hazardous Polymerization:** Not Applicable**Section VI - Spill or Leak Procedures****Steps To Be Taken In Case Material Is Released Or Spilled:** Clean the area of spill, returning all material possible to container. Wear gloves, goggles, respirator. Do not breathe or ingest dust. For a SMALL spill, use a vacuum. Do not broom sweep. Recovered material should be stored in dry containers for later disposition. Do not use compressed air for cleaning. Exclude all individuals not wearing protective equipment from the spill area until clean up is completed.**Waste Disposal Method:** Disposal of waste and hazardous material should be handled in a manner which complies with local, state and federal Environmental Protection Agency regulations. It is preferable to send waste material to a recycling facility which is approved by the state and federal EPA. City, state and federal regulations must be followed at all times.**Neutralizing Chemicals:** Not Applicable

Section VII - Health Hazard Information**Routes of Exposure When Handling or Processing**Health Hazard;
NPCA HMIS RATING = 2**Mode of entry into body:**

1. by INHALATION of dusts or fumes, the respiratory system may be irritated and both acute and chronic overexposure can result.
2. By INGESTION of lead compounds coming from dust trapped in the upper respiratory tract or introduced into the mouth on food, tobacco, fingers or other objects, both acute and chronic overexposure can result.
3. SKIN CONTACT of dusts may cause irritation.
4. SKIN ABSORPTION does not apply, as dusts are not absorbed.
5. EYE CONTACT of dusts or fume may cause irritation.

Effects of Overexposure

ACUTE OVEREXPOSURE: Lead intoxication will occur with accompanying symptoms of constipation, sleep disturbance, fatigue, headache, loss of appetite. Where inhalation is severe from heavy dusting or a large quantity is ingested and left untreated, colic, anemia, vomiting and neuritis will follow as evidenced by intense periodic cramps, aching bones and muscles, uncoordinated body movements. Worst case situations could result in convulsions, stupor, coma, and encephalopathy.

CHRONIC OVEREXPOSURE: Normal ingestion of lead from the ambient air, foods and beverages is about 0.25 to 0.35 mg. per day. The normal adult metabolism can eliminate almost one mg. of lead per day. When lead ingested exceeds the body's ability to eliminate it, accumulation can reach the point where symptoms and disability occur. In this context, lead has a cumulative toxic effect.

Early effects of chronic overexposure to lead are difficult to detect, but symptoms include persistent fatigue, sleep disturbance, headache, aching bones and muscles, constipation, abdominal pains and loss of appetite. Prolonged ingestion may be indicated by intense periodic cramps and constipation, nausea and vomiting. Excessive exposure may affect blood, nervous, digestive systems. Synthesis of hemoglobin is inhibited and will result in anemia. Apathy and depression may be symptoms. If left untreated, neuromuscular dysfunction, possible paralysis and encephalopathy can result. Unusual occurrence of symptoms should prompt immediate contact of a physician.

For industrial exposure, a worker's lead accumulation can be detected by an increase in blood lead above the base level established upon the employee's entry to the workplace. Blood lead above the biological limit value requires job removal.

Emergency and First Aid Procedures

INHALATION - Remove from exposure. Get medical attention if experiencing effects of acute overexposure.

INGESTION - Induce vomiting in a conscious individual. Get immediate medical attention. Call a physician.

SKIN - Wash thoroughly with soap and water.

EYES - Flush with copious quantities of water. Get immediate medical attention.

Notes to Physician: Lead and its inorganic compounds are neurotoxins which may produce peripheral neuropathy. For an overview of the effects of lead exposure, consult Occupational Safety and Health Adm. App.A of Occupational Exposure to Lead (29CFR1910.1025). "A Guide for Physicians, Health Maintenance of Workers Exposed to Inorganic Lead" is available from Lead Industries Association, Inc., 292 Madison Ave., New York, NY 10017.

Section VIII - Special Protection**SPECIFIC PERSONAL PROTECTION EQUIPMENT**

RESPIRATORY: As specified by 29CFR1910.1025(f) of the Federal Occupational Safety and Health Administration Standard for Occupational Exposure to Lead -- When handling, use a dust/fume respirator with NIOSH/MSHA approval. Respirator must be worn if TLV is exceeded.

Refer to Table II as specified in 29CFR1910.1025(f)(2)(i) for various exposure levels.

Other local, state, and federal regulations may also apply.

PROTECTIVE GLOVES: Not required, but recommended.

EYE PROTECTION: Not required, but recommended.

OTHER CLOTHING AND EQUIPMENT: Protective clothing is required if lead exposures exceed PEL or TLV; otherwise, full body clothing should be worn during product use and handling, be left at the work site and be properly laundered after use, with the wash water disposed of in accordance with local, state and federal regulations. Hard hat, safety boots, and other safety equipment should be worn as appropriate for the industrial environment. Personal clothing, including shoes, should be protected from contamination.

VENTILATION REQUIREMENTS

Ventilation as described in the Industrial ventilation Manual, by ACGIH shall be provided where exposures exceed PEL or TLV specified in and in accord with OSHA Standard 29CFR1910.94. Currently 0.050 mg/m³ maximum and 0.030 mg/m³ set as trigger and action levels.

Other local and state regulations may apply.

Section IX - Definitions

TLV-TWA	-	Threshold Limit Value-Time Weighted Average
TLV-STEL	-	Threshold Limit Value-Short Term Exposure Limit
TLV-C	-	Threshold Limit Value-Ceiling
BLV	-	Biological Limit Value
LEL	-	Lethal Exposure Limit
PEL	-	Permissible Exposure Limit

Section X - Special Precautions

PRECAUTIONS: There are two major means of lead absorption; namely inhalation and ingestion. Most inhalation problems can be prevented with attention to ventilation and respirator use. Ingestion can be prevented with good hygiene practices.

Do not inhale or swallow dust. Wash thoroughly after handling. Use gloves and avoid spilling on hands, face, or body, to prevent secondary contamination by ingestion or inhalation. Do not smoke, eat, or apply cosmetics in work area. Wash thoroughly before entering into eating areas. Do not wear any part of work clothing home. This includes shoes.

Keep lead materials away from feed and food products. Keep away from children. Do not reuse containers. This product is intended for industrial use only.

Section XI - Other Handling and Storage Requirements

Store in dry area where accidental contact with acids or bases is not possible.

When a spill releases material into the environment, it may be necessary to file a report of the discharge. Contact your local environmental authorities to determine what rules apply.

Avoid Skin contact.

Adhere to all personal protection procedures and ventilation requirements when exposure limits exceed PEL or TLV.

Before using this product, be familiar with information contained in:

The Federal Standard For Occupational Exposure To Lead (29CFR1910.1025), first published in the Federal Register on Tuesday, November 14, 1978, by the Occupational Safety and Health Administration, and as also later modified.

PREPARED BY:**AKRON CHEMICAL COMPANY**

JAMES E. MYERS
MANAGER TECHNICAL SERVICES

VENDEE AND THIRD PERSONS ASSUME THE RISK OF INJURY PROXIMATELY CAUSED BY THE MATERIAL IF REASONABLE SAFETY PROCEDURES ARE NOT FOLLOWED AS PROVIDED FOR IN THE DATA SHEET, AND VENDOR SHALL NOT BE LIABLE FOR INJURY TO VENDEE OR THIRD PERSONS PROXIMATELY CAUSED BY ABNORMAL USE OF THE MATERIAL EVEN IF REASONABLE SAFETY PROCEDURES ARE FOLLOWED.

ALL PERSONS USING THIS PRODUCT, ALL PERSONS WORKING IN AN AREA WHERE THIS PRODUCT IS USED, AND ALL PERSONS HANDLING THIS PRODUCT SHOULD BE FAMILIAR WITH THE CONTENTS OF THIS DATA SHEET. THIS INFORMATION SHOULD BE EFFECTIVELY COMMUNICATED TO EMPLOYEES AND OTHERS WHO MIGHT COME IN CONTACT WITH THE PRODUCT.

WHILE THE INFORMATION ACCUMULATED AND SET FORTH HEREIN IS BELIEVED TO BE ACCURATE AS OF THE DATE HEREOF, HAMMOND LEAD PRODUCTS, INC. MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE FOR THEIR PARTICULAR CIRCUMSTANCES.

DO 085856
CONFIDENTIAL