

SIERRA SLATE

HOUSE PAINT

Low Lustre

“SEVENTY-FIVE”

O'BRIEN



REGISTERED
REGD. No. 95134
DATE 8/22/69
9/2/69

"SEVENTY-FIVE" LOW LUSTRE HOUSE PAINT (FORMERLY "75" EXTERIOR EGGSHELL)

"Seventy-Five" Low Lustre house paint is highly pigmented, for exterior wood siding and wood shingles. May be used also over properly primed masonry and metal. Available in standard colors and three types of white: self-cleaning White; CC White for Controlled Chalking—trim work, etc.; and White Bases No. 1, 2, and 3 (for tinting only) for body or trim work.

DIRECTIONS

Preparation — Remove dirt, chalk, and loose paint. Repair flashings, caulk, and provide adequate ventilation for release of moisture. Sand under eaves and protected areas, wash with detergent and thoroughly rinse.

Priming — Prime new wood, new wood shingles, and prime or spot prime previous paint in poor condition with "75" House Paint Priming White. Prime new masonry with alkali-resistant "A-R" Primer. Prime bare metal with Flexico Metal Primer. Etch galvanized metal before priming. Tint primers toward topcoat color.

Tinting — Tint White Bases No. 1, 2, and 3 with Tone-All Universal Tinting Colors according to O'Brien Symphonic Color System formulas. Do not use alkali-sensitive colorants Orange, Medium Yellow, and Medium Green on masonry surfaces unless sealed with alkali-resistant primer.

Application — Stir well. Apply over a dry surface at temperature not less than 60° F. (Note: Apply only one coat—reduced with one pint of linseed oil per gallon—over previously painted wood shingles.) If required, thin sparingly with "75" Low Lustre Thinner, working limited areas to maintain a wet edge. Avoid brushing back into semi-dried film which creates lap marks. Allow 48 hours good drying weather between coats. —(PYOW)

CAUTION! COMBUSTIBLE!
CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat and open flame. Do not apply on window sills, toys, furniture or interior surfaces of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. KEEP OUT OF THE REACH OF CHILDREN.

"75" LOW LUSTRE HOUSE PAINT	
Pigment	43.89%
Sierra Slate	15.31%
Iron Oxide	1.00%
Lead Oxide	34.08%
Silicates	100.00%
Vehicle	56.11%
Raw Linseed Oil	11.37%
Heat Treated Linseed Oil	22.46%
Alkyd Resin	15.00%
Aromatic Hydrocarbons	10.70%
Mineral Spirits and Driers	50.11%
	100.00%
(W/TYOE)	
Less than 5% Tinting Colors added	



SINCE

1875

THE O'BRIEN CORPORATION • SOUTH BEND, IND.

BALTIMORE, MD. • OKLAHOMA CITY, OKLA. • LOS ANGELES, CAL. • SAN FRANCISCO, CAL. • BRUNSWICK, GA.