

MATERIAL SAFETY DATA SHEET

FOR COATINGS, RESINS AND RELATED MATERIALS

HEALTH
FLAMMABILITY
REACTIVITY
PERSONAL PROTECT

1706

Section I

MANUFACTURER'S NAME **Gilsonite, Inc.** DATE OF PREP **November, 1985**

STREET ADDRESS **2946 N.E. Columbia Blvd.** CITY, STATE AND ZIP CODE **Portland, Oregon 97211**
P.O. Box 11242

EMERGENCY TELEPHONE NO. **503/288-5454** PRODUCT CLASS **Asphalt Roofing Compound**

INFORMATION TELEPHONE NO. **503/288-5454**

MANUFACTURER'S CODE IDENTIFICATION **105** TRADE NAME **CD-
(Fibermastic Plastic Cement)**

Section II—HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	OCCUPATIONAL EXPOSURE LIMITS	VAPOR PRESSURE	TOXICITY DATA
Mineral Spirits	28%	TLV 100 PPM	3.4 mm Hg @ 20°C.	
Asbestos*	15%			

*Asbestos is a health hazard when inhaled. In this product asbestos is encapsulated in liquid asphalt and is not considered hazardous.

Section III—PHYSICAL DATA

BOILING RANGE **300 - 405°F** VAPOR DENSITY **XX HEAVIER** **LIGHTER THAN AIR**

EVAPORATION RATE ☐ FASTER ☒ SLOWER THAN ETHER PERCENT VOLATILE BY VOLUME **37.5** WEIGHT PER GALLON **8.7 pounds**

Section IV—FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION **Combustible, Class II** OSHA **XXX** FLASH POINT **105°F Min.** LEL

EXTINGUISHING MEDIA: ☒ FOAM ☐ ALCOHOL ☒ CO2 ☒ DRY CHEMICAL ☐ WATER FOG ☐ OTHER

UNUSUAL FIRE AND EXPLOSION HAZARDS

Characteristics similar to combustible petroleum products.

SPECIAL FIREFIGHTING PROCEDURES

Do not enter any enclosed or confined fire spaces without proper protective equipment; this may include self contained breathing apparatus to protect against the hazardous effect of normal products of combustion or oxygen deficiency.

EFFECTS OF OVEREXPOSURE In confined areas, prolonged exposure to high vapor concentrations may cause signs and symptoms of central nervous system depression such as: headaches, dizziness, loss of appetite, weakness and loss of coordination. Affected persons normally experience complete recovery when removed from exposure area. Aspiration can lead to chemical pneumonitis. Minor irritation to eyes may be noted following contact. Prolonged or frequent skin contact may cause the skin to become dry or cracked from the defatting action of the material.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:

Not established.

PRIMARY ROUTES OF ENTRY:

☒ DERMAL

☒ INHALATION

☐ INGESTION

EMERGENCY AND FIRST AID PROCEDURES

Eyes: Flush with fresh water for 15 minutes; if irritation persists, see physician.
Overexposure to vapors: Move person to uncontaminated area and get medical attention.
If breathing stops, apply artificial respiration.
If ingested: DO NOT induce vomiting -- see physician immediately.

Section VI—REACTIVITY DATA

STABILITY ☐ UNSTABLE ☒ STABLE

CONDITIONS TO AVOID

COMPATIBILITY (Materials to avoid)

May react with strong oxidizing materials.

HAZARDOUS DECOMPOSITION PRODUCTS

Normal combustion forms carbon dioxide and water vapor, incomplete combustion can produce carbon monoxide.

HAZARDOUS POLYMERIZATION ☐ MAY OCCUR ☒ WILL NOT OCCUR

Section VII—SPILL OR LEAK PROCEDURES

ACTIONS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Eliminate all sources of ignition in vicinity of spill or released vapors. Clean up spills as soon as possible, observing precautions in Section IX: Special Precautions.

DISPOSAL METHOD Absorb large spills with absorbent clay or dry earth and dispose of the contaminated material in an approved dumping area. A fire or vapor hazard may exist since these clean materials will absorb liquids and not vapors.

Section VIII—SPECIAL PROTECTION INFORMATION

HAZARD PROTECTION The vapor or mist concentration should be kept below the threshold limit values. For concentrations above the TLV, use NIOSH approved organic vapor respirator.
VENTILATION Use adequate ventilation to keep the vapor or mist concentrations below the TLV.

PROTECTIVE GLOVES Impervious neoprene or rubber gloves if frequently exposed.

OTHER PROTECTIVE EQUIPMENT If eye or skin contact can occur, a washing facility should be available.

PROTECTION Wear safety goggles if frequently exposed.

Section IX—SPECIAL PRECAUTIONS

ACTIONS TO BE TAKEN IN HANDLING AND STORAGE Keep away from open flames, heat and spark sources. Avoid splash-filling.

PRECAUTIONS Avoid breathing vapor. Keep container closed. Use with adequate ventilation. Keep out of reach of children.

Material Safety Data Sheet is furnished without charge to responsible persons who use it at their discretion and risk. Although the information and suggestions contained have been compiled from sources believed to be reliable, there is no warranty of any kind express or implied, as to the completeness or accuracy thereof.

TX GARRETT

RMC0000494