

S.V. 240, 241, 242, 245, 246

CG 01 CODE YC-016-B PQ 93

DATE: _____ LOT: E1338

ESTIMATED WEIGHT: 3130#

PROCESSES

APPROVED BY

(A) YC-017-B () FWP 05/08/81

() ()

() ()

COMTYP JOB NAME: 01YC017BMA

EQUIP MENT	NAME: MOLYBDATE ORANGE	USE LBS	N-DE (RMCON)	ACCT LBS
PREP				
1	1 WEIGH FOR S-36	90	3-A	90
	2 WEIGH FOR S-44	80	3-A	80
	3 WEIGH IN DRUM FOR S-40	145	32-D	145
	4 WEIGH FOR S-30	250	4-A	250
	5 WEIGH IN PAILS FOR S-31 <u>32.00</u> %	<u>69</u>	28-D	22
	6 WEIGH FOR S-42	225	15-A	225
	7 DISSOLVE IN 20 GAL WATER AT 100-110°F IN	13	978-A	13
	DRUM FOR S-48	2	979-A	2
356	8 RUN 25" (451 G) WATER INTO V-356			
2	9 TURN ON AGITATOR AND STEAM			
	10 WEIGH AND SIFT IN	270	131-B	270
	11 HEAT TO AND MAINTAIN 60-66° C FOR S 38			
359	12 WEIGH IN OPTR _____, MK <u>48</u> , <u>38.15</u> %	<u>490</u>	423-D	<u>214</u>
3	V-360 OPTR _____, MK _____, _____ %			<u>187</u>
351	13 WEIGH IN OPTR _____, MK <u>241</u> , <u>38.18</u> %	<u>3038</u>	10-D	<u>1144</u>
4	OPTR _____, MK _____, _____ %			<u>1160</u>
4	14 RUN IN V-359			
358	15 RUN 10" (473 G) WATER INTO V-358			
5	16 PUMP V-351 INTO V-358			
	17 ADJ TO 68" (3216 G) AT 67-69°F. RECORD: <u>68</u>			
	18 STIR 3 MIN. RECORD: <u>67</u> °F & PH <u>9.2</u>			
	19 IF NECESSARY, ADJ TO PH 9.8-9.9 ASSUME 50%	<u>2</u>	7-D	<u>1</u>
	RECORD: PH <u>9.8</u> ASSUME 66%	<u>2</u>	33-D	<u>1</u>
	20 RECORD: G/ML <u>1.077</u> (1.044-1.047)			
SV	21 RUN 40" (1908 G) WATER INTO V- <u>242</u>			
6	22 RUN IN FROM V-354			
	OPTR _____, MK <u>475</u> , <u>27.41</u> %	<u>11116</u>	41-D	3047
	OPTR _____, MK _____, _____ %			
	23 ADJ TO 3148 G AT 67-69°F (64" IN V-240 &			
	V-246; 66" IN V-241, V-242, & V-245)			
	24 STIR 3 MIN RECORD: <u>68</u> °F	<u>5x330</u>	57-A	<u>1650</u>
	25 RECORD: PH <u>3.0</u> (2.8-3.6)			
	26 ADJ TO PH 4.0-4.1 ASSUME 66%	<u>2</u>	33-D	<u>1</u>
	RECORD: PH <u>4.0</u> & VOL <u>66</u> ASSUME 50%	<u>2</u>	7-D	<u>1</u>
	NOTE: DILUTE N-7-D 10:1 WITH WATER			
	27 RECORD: G/ML <u>1.100</u> (1.097-1.100)			
	28 OBTAIN 1 QT SAMPLES OF S-20 & S-27			
	SOLUTIONS & TITRATE TWICE			
	RECORD: LOWEST PH <u>3.0</u> & ML N-10-D <u>2.34</u>			
	LOWEST PH <u>3.99</u> & ML N-10-D <u>2.33</u>			
	NOTIFY SUPV IF ML N-10-D IS NOT IN RANGE			
	8.0-8.6 OR IF THE TWO TITRATIONS DIFFER			
	BY MORE THAN 0.10 ML N-10-D (IF YES,			
	FLUSH ALL EQUIPMENT & REPEAT TITRATIONS)			
	DO NOT PROCEED IF N-10-D TITRATION IS OUT			
	OF RANGE			

EQUIP	MENT	PAGE 02 OF 2	CG 01	CODE YC-016-B	USE	N-CODE	ACCT
29		RUN V-358 AT 67-69°F THRU BOTH UNDERSURFACE					
		DISTRIBUTORS INTO SV AT 67-69°F IN 17-19 MIN					
		RECORD: START 4:40 AM & TOTAL MIN 20					
		NOTE: V-358 STRIKE TIME UP WHEN 1/2 VAT BOTTOM SHOWS MT					
30	SV	WHEN S 29 COMPLETED AND BEFORE WASHING IN					
31	(CONT)	V-358, DUMP IN N-4-A FROM S-4					
32		IMMEDIATELY POUR IN N-28-D FROM S 5					
33		DURING S'S 30 AND 31 (IF ALONE, AFTER S'S 30 & 31) WASH IN V-358					
34		STIR 2 MIN					
35		RECORD: PH 2.4 (2.2-2.5) & PB XS 7 (+)					
36		STIR TOTAL OF 15 MIN FROM COMPLETION OF					
37		S 29 RECORD: START 5:44 TOTAL MIN 15					
38		DUMP IN N-3-A FROM S 1					
39		STIR 3 MIN					
40		RUN IN N-131-B FROM S 3 IN 7 MIN					
41		STIR 3 MIN					
42		POUR IN N-983-D FROM S-3					
43		STIR 2 MIN					
44		DUMP IN N-15-A FROM S 6					
45		STIR 3 MIN					
46		DUMP IN N-3-A FROM S 2					
47		STIR 3 MIN					
48		RECORD: PH 6.0 (5.8-6.0)					
49		IF NECESSARY, ADJ TO PH 5.8-6.0. ASSUME 50%					
50		RECORD: PH 6.0					
51		POUR IN N-978/979-A FROM S-7					
52		STIR 10 MIN					
53		FLOOD TO 153° (7298 G)					
54		STOP AGITATOR					
		START 4:00 AM					
		FINISH 6:00 AM					
		OPTR 237-58					
		33-D					
		7-D					