

VCM TRAINING CLASS

Test, 1978

J. R. McCRIMON
NamePROCESS ENGR
Department4-21-78
Date

1. The VCM Standard sets limits for VCM exposure of 1 ppm time-weighted-average and 5 ppm for any 15 minute period.
2. Respiratory protection devices (gas mask, airline respirators, Scott Air Paks, etc.) are required above:

☒ A. 1 ppm

B. 10 ppm

C. 32 ppm

3. Our Honeywell continuous monitors sound an alarm when 1 ppm is reached in an area.

☒ A. 1 ppm

B. 10 ppm

C. 32 ppm

4. All respirators are cleaned:

A. Weekly

B. Monthly

☒ C. Daily

5. We monitor your VCM exposure to:

A. Minimize your exposure to VCM

B. Monitor our progress in reducing VCM concentrations in our plant

☒ C. Both A & B

D. Neither A or B

6. The VCM regulation does not apply to products made from PVC.

☒ True☐ False

7. The three VCM-regulated areas in our plant are:

A. Dry blend basement and Q.C. Lab.

B. P-1 Building and Boiler House

☒ C. VCM Tank Farm, the two Large Reactor areas.

8. Our Plant Emergency Procedures are outlined in the:

A. Collective Bargaining Agreement

B. "Make Safety a Habit" Booklet

☒ C. PVC Plant Safety and Health Manual

9. Do non-Conoco personnel have to sign Regulated Area Logs before entering regulated areas?

☒ Yes☐ No

10. Our plant is continuously monitored for VCM at 40 different points 24 hours/day, year-round.

☒ True☐ False