

Section I — Product Information

Trade Name and Product Code Number Airflex		Chemical Name and Synonyms Friction Material	
DOT Hazardous Material Proper Shipping Name N/A		DOT Hazard Shipping Class N/A	
Manufacturer's Name Eaton Corporation, Airflex Division		Manufacturer's Emergency Telephone No./Person to Contact 216-281-2211 Paul Elphinstone	
Manufacturer's Address (Number, Street, City, State, Zip Code) 9919 Clinton Rd., Cleveland, Ohio 44144			

Section II — (For Eaton Use Only)

Stocked At: Plant Location and Department N/A		Annual Consumption N/A	
Used In — Department(s) N/A		Per Drawing No. or Formula No. N/A	
Material Code or Part No. N/A		Common (Shop) Name N/A	

Section III — Chemical Substance (Liquids, Solids, Gases)

Ingredients (Approximate percentage by weight)	C.A.S. Number	%	TLV Specify Units
1. Chrysotile Asbestos	12001-29-5	10 - 70	**
2. * Fillers		1 - 65	
3. * Binders		15 - 35	
4. Lead and Lead Compounds	7439-92-1	0 - 20	
5.			
6.			
7. * Not Hazardous Per 29CFR1910-1200			
8. ** See Section VI			
9.			
10.			

Section IV — Physical Data

Boiling Point (°F) or Range N/A	Vapor Density (air = 1) (60-90°F) N/A	Evaporation Rate (ETHER = 1) N/A
Vapor Pressure (mm Hg.) @ 20°C N/A	Specific Gravity (H ₂ O=1) 1.60 - 1.91	pH N/A
Solubility In Water N/A	Percent Volatile by Volume (70°F) N/A	
Appearance and Odor Gray or Tan		Material Is: Liquid ☐ Solid ☒ Gas ☐ Paste ☐ Powder ☐

Section V — Fire and Explosion Hazard Data

Flash Point (Method Used) N/A	Upper Explosive Limit N/A %	Lower Explosive Limit N/A %
Extinguishing Agents N/A		
Special Fire Fighting Procedures N/A		
Unusual Fire or Explosion Hazards N/A		