

NEG. NO. K-12A

TRADEMARK FILE INFORMATION

Trademark: Johns Manville JM
Trademark Owner: Johns-Manville Corporation
Last Assignee: None
Date of First Use
in Commerce: April 10, 1929
Registration No.: 566,486
Date Trademark
Registered: November 11, 1952
Size of Label in
Trademark File: N/A

Receipt of Pictured Label by Patent Office: N/A

Johns-Manville

ZEROSEAL

Plastic Bituminous Coating

PRODUCTS  OF QUALITY

CAUTION—COMBUSTIBLE MIXTURE

N. Y. F. D.—C. of A. No. 2224

- Keep away from heat, sparks and open flame.
- Keep container closed and away from heat.
- Use with adequate ventilation.

DIRECTIONS FOR APPLYING

Apply Zeroseal with a trowel to a minimum of 1/16". Press joints of pipe insulation firmly together. For sealing tape used on fittings, be sure the tape is well coated where valve stems or handles project through the insulation.

Contents: 5 GALLONS

A special heavy-bodied plastic cement composed of asbestos fibre, asphalt and other mineral ingredients to seal joints and close sealing-membrane pores for installations of Rock Cork* and Zerolite* Pipe Insulation and Fittings.
*Reg. U. S. Pat. Off.

HANDLING INSTRUCTIONS

- Nothing should be added to this product without consulting the manufacturer.
- As temperature falls this material tends to thicken.
- Restore proper consistency by placing in a warm room.

REPLACE COVER TIGHTLY

JOHNS-MANVILLE
SALES CORPORATION
NEW YORK, N. Y.

L-870-8

Printed in U.S.A.