

Report to Building Code Officials on SHEETROCK* FIRECODE 60

*New Gypsum Wallboard, released after
exhaustive tests, has 1-HOUR RATING*

What it is: SHEETROCK Firecode 60 gypsum wallboard is $\frac{5}{8}$ -inch SHEETROCK with a specially formulated core of gypsum and other incombustible materials. It was developed by U.S.G. to meet rigid code requirements in single layer application for new construction or remodeling, commercial or residential.

What it does: SHEETROCK Firecode 60 has received the One-Hour Fire Retardant Classification Label of Underwriters' Laboratories. Partitions and/or floor and ceiling areas faced with SHEETROCK Firecode 60, qualify the construction for the one-hour fire retardant rating.

In addition: SHEETROCK Firecode 60 offers all these recognized advantages of SHEETROCK: tapered edges for easier joint finishing and smooth ends for smoother butt end joints; new pre-creased triple-spark perforated PERF-A-TAPE* that eliminates perforation pattern; new PERF-A-BEAD Corner Reinforcement for true, enduring outside corners.

You can recommend, specify, and approve SHEETROCK Firecode 60 with full assurance that this product is made to the high quality standards for which U.S.G. products are famous.

See Pacific Coast Building Officials Conference Research Recommendation Report No. 338, dated July 11, 1952

*T.M.Reg.U.S.Pat.Off.

TECHNICAL DATA: Underwriters' Laboratories rated for partitions and floor and ceiling construction, single layer application, requiring a 60-minute fire retardant classification.

$\frac{5}{8}$ -in. thick, available in panels 4 ft. wide and up to 12 ft. long, with tapered edges and smooth ends.

For complete data and specifications for erection, consult your local U.S.G. Architects' Service Representative.



UNITED STATES GYPSUM

CHICAGO 6, ILLINOIS

the greatest name in building