

Form Approved OMB
No. 44-R1387
Approval Expires:
July 30, 1972

U.S. DEPARTMENT OF LABOR

R. Mc Cutchan
Form No. OSHA-20
May, 1971

82610-RM
(Same as 81106)

MATERIAL SAFETY DATA SHEET

SECTION I					
MANUFACTURER'S NAME MONSANTO COMPANY				EMERGENCY TELEPHONE NO. (314) 604-1000	
ADDRESS (Number, Street, City, State, and ZIP Code) 800 North Lindbergh Boulevard, St. Louis, Missouri 63166					
CHEMICAL NAME AND SYNONYMS Chlorinated Aromatic				TRADE NAME AND SYNONYMS Capacitor 21	
CHEMICAL FAMILY Chlorinated Aromatic				FORMULA Mixture	
SECTION II HAZARDOUS INFORMATION					
PAINTS, PRESERVATIVES, & SOLVENTS		%	TLV (Units)	ALLOYS AND METALLIC COATINGS	
PIGMENTS				BASE METAL	
CATALYST				ALLOYS	
VEHICLE				METALLIC COATINGS	
SOLVENTS				FILLER METAL PLUS COATING OR CORE FILL	
ADDITIVES				OTHERS	
OTHERS					
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)
SECTION III PHYSICAL DATA					
BOILING POINT (°F.)		760 mm	215-320	SPECIFIC GRAVITY (H ₂ O = 1) (25/15.5°C)	
VAPOR PRESSURE (mm Hg.)		at 100°F	> 0.005	PERCENT VOLATILE BY VOLUME (%)	
VAPOR DENSITY (AIR = 1)		Not Avail.		EVAPORATION RATE (H ₂ O = 1)	
SOLUBILITY IN WATER		at 25°C negligible		< 0.01%	
APPEARANCE AND ODOR		colorless oil		aromatic odor	
SECTION IV FIRE AND EXPLOSION HAZARD DATA					
FLASH POINT (ASTM D 568)		Not Avail		FLAMMABLE LIMITS	
				LOI	UOI
EXTINGUISHING MEDIA Water, foam, CO ₂ , or dry chemical.					
SPECIAL FIRE FIGHTING PROCEDURES Respiratory protection when fighting fires where exposure to vapors or gases is possible.					
UNUSUAL FIRE AND EXPLOSION HAZARDS Highly toxic gases (chlorides and chlorine) can be evolved in fires of this product.					

EXHIBIT

K-100

GBRN 001564

Capacitor 21

SECTION V HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE	Not Available
EFFECTS OF OVEREXPOSURE Skin irritation in the form of chloracne, systematic intoxication leads to nausea, vomiting, loss of weight, edema and abdominal pain.	
EMERGENCY AND FIRST AID PROCEDURES Remove from exposure. Remove contaminated clothing. Wash contacted area with large amounts of water and soap. Refer to physician.	

SECTION VI REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	
INCOMPATIBILITY (Materials in contact)			
HAZARDOUS DECOMPOSITION PRODUCTS CO, CO ₂ , smoke, soot, chlorides and chlorine			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Absorb on clay, sawdust or other absorbant material. Place in drums. Bury in approved chemical landfill in accordance with local and state regulations.	
WASTE DISPOSAL METHOD Burn in an approved incinerator in accordance with local and state regulations.	

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type) Bureau of Mines approved respirator for organic vapors.			
VENTILATION	LOCAL EXHAUST	Yes - for vapors	SPECIAL Vapors.
	MECHANICAL (General)		OTHER
PROTECTIVE GLOVES rubber		EYE PROTECTION chemical goggles	
OTHER PROTECTIVE EQUIPMENT			

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING Avoid skin and eye contact. Avoid inhalation of vapors.	
OTHER PRECAUTIONS	

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, MONSANTO COMPANY MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

JAG:HOH:JTG:WBP

4/14/72

GBRN 001565

Form Approved OMB
No. 44-R1387
Approval Expires:
July 30, 1972

U.S. DEPARTMENT OF LABOR

Form No. OSHA-20
May, 1971
81092

MATERIAL SAFETY DATA SHEET

SECTION I					
MANUFACTURER'S NAME MONSANTO COMPANY			EMERGENCY TELEPHONE NO. (314) 694-1000		
ADDRESS (Number, Street, City, State, and ZIP Code) 800 North Lindbergh Boulevard, St. Louis, Missouri 63166					
CHEMICAL NAME AND SYNONYMS			TRADE NAME AND SYNONYMS		
Chlorinated aromatics			Inerteen PPO		
CHEMICAL FAMILY			FORMULA		
Chlorinated aromatics			Mixture		
SECTION II HAZARDOUS INGREDIENTS					
PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FILLER		
ADDITIVES			OTHERS		
OTHERS					
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)
SECTION III PHYSICAL DATA					
BOILING POINT (°F.)	760 mm	200-415°C	SPECIFIC GRAVITY (H ₂ O = 1)	(15.5/15.5°C)	1.564
VAPOR PRESSURE (mm Hg.)	Not Avail.		PERCENT VOLATILE BY VOLUME (%)	N.A.	
VAPOR DENSITY (AIR = 1)	Not Avail.		EVAPORATION RATE (Btu/lb. °F.)	C	
SOLUBILITY IN WATER	20°C negligible		Not Avail.		
APPEARANCE AND ODOR	colorless to yellow oil		aromatic odor		
SECTION IV FIRE AND EXPLOSION HAZARD DATA					
FLASH POINT (METHOD USED)	None 245°F		FLAMMABLE LIMITS	LOI	UOI
EXTINGUISHING MEDIA	N.A.			N.A.	N.A.
SPECIAL FIRE FIGHTING PROCEDURES					
Respiratory protection when fighting fires where exposure to vapors or gases is possible.					
HAZARDOUS FIRE AND EXPLOSION HAZARDS					
Highly toxic gases (chlorides and chlorine) can be evolved in fires of this product.					

EXHIBIT

K-101

GBRN 001566

Inerteen PPO SECTION V HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE		Not available.	
EFFECTS OF OVEREXPOSURE			
Skin irritation in the form of chloracne, systematic intoxication leads to nausea, vomiting, loss of weight, edema and abdominal pain.			
EMERGENCY AND FIRST AID PROCEDURES			
Remove from exposure. Remove contaminated clothing. Wash contacted area with large amounts of water and soap. Refer to physician.			
SECTION VI REACTIVITY DATA			
STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	
INCOMPATIBILITY (Materials to avoid)			
HAZARDOUS DECOMPOSITION PRODUCTS			
CO, CO ₂ , smoke, soot, chlorides and chlorine			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	
SECTION VII SPILL OR LEAK PROCEDURES			
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED			
Absorb on clay, sawdust or other absorbant material. Place in drums. Bury in approved chemical landfill in accordance with local and state regulations.			
WASTE DISPOSAL METHOD			
Burn in an approved incinerator in accordance with local and state regulations.			
SECTION VIII SPECIAL PROTECTION INFORMATION			
RESPIRATORY PROTECTION (Specify type)			
Bureau of Mines approved respirator for organic vapors			
VENTILATION	LOCAL EXHAUST	Yes - for vapors	SPECIAL
	MECHANICAL (General)		OTHER
PROTECTIVE GLOVES		rubber	EYE PROTECTION
			chemical goggles
OTHER PROTECTIVE EQUIPMENT			
SECTION IX SPECIAL PRECAUTIONS			
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING			
Avoid skin and eye contact.			
Avoid inhalation of vapors.			
OTHER PRECAUTIONS			

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, MONSANTO COMPANY MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

JAG:HOH:JTG:WBP

1/26/72

GBRN 001567

Form Approved OMB
No. 44-11387
Approval Expires:
July 30, 1972

U.S. DEPARTMENT OF LABOR

Form No. OSHA-20
May, 1971

81094

MATERIAL SAFETY DATA SHEET

SECTION I					
MANUFACTURER'S NAME MONSANTO COMPANY		EMERGENCY TELEPHONE NO. (314) 694-1000			
ADDRESS (Name, Street, City, State, and ZIP Code) 800 North Lindbergh Boulevard, St. Louis, Missouri 63166					
CHEMICAL NAME AND SYNONYMS Mixture		TRADE NAME AND SYNONYMS Inerteen 54201 KJ			
CHEMICAL FAMILY Chlorinated Aromatic		FORMULA mixture			
SECTION II HAZARDOUS INGREDIENTS					
PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FILL		
ADDITIVES			OTHERS		
OTHERS					
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)
SECTION III PHYSICAL DATA					
BOILING POINT (°F.)	760 mm	200-350°C	SPECIFIC GRAVITY (H ₂ O = 1) (25/15.5°C)	1.333	
VAPOR PRESSURE (mm Hg.)	Not Avail		PERCENT VOLATILE BY VOLUME (%)	N.A.	
VAPOR DENSITY (AIR = 1)	Not Avail		EVAPORATION RATE (1-Pint @ 25°C)	<1	
SOLUBILITY IN WATER	29°C negligible				
APPEARANCE AND ODOR	colorless oil		aromatic odor		
SECTION IV FIRE AND EXPLOSION HAZARD DATA					
FLASH POINT (Method used)	None		FLAMMABLE LIMITS	LOI	UOI
				N.A.	N.A.
EXTINGUISHING MEDIA					
SPECIAL FIRE FIGHTING PROCEDURES					
Respiratory protection when fighting fires where exposure to vapors or gases is possible.					
UNUSUAL FIRE AND EXPLOSION HAZARDS					
Highly toxic gases (chlorides and chlorine) can be evolved in fires of this product.					



GBRN 001568

Inerteen 54201 KJ

SECTION V HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE	Not available.
EFFECTS OF OVEREXPOSURE	Skin irritation in the form of chlorachne, systematic intoxication, leads to nausea, vomiting, loss of weight, edema and abdominal pain.
EMERGENCY AND FIRST AID PROCEDURES	Remove contaminated clothing. Wash contacted area. Remove from exposure. Wash with large amounts of water and soap. Refer to physician.

SECTION VI REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	
INCOMPATIBILITY (Materials to avoid)			
HAZARDOUS DECOMPOSITION PRODUCTS CO, CO ₂ , smoke, soot, chlorides and chlorine.			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED	Absorb on clay, sawdust or other absorbant material. Place in drums. Bury in approved chemical landfill in accordance with local and state regulations.
WASTE DISPOSAL METHOD	Burn in an approved incinerator in accordance with local and state regulations.

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type)		
Bureau of Mines approved respirator for organic vapors		
VENTILATION	LOCAL EXHAUST	SPECIAL
	MECHANICAL (General)	OTHER
PROTECTIVE GLOVES	Rubber	EYE PROTECTION
		Chemical goggles
OTHER PROTECTIVE EQUIPMENT		

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING	Avoid skin and eye contact, avoid inhalation of vapors.
OTHER PRECAUTIONS	

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, MONSANTO COMPANY MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

JAG:HOH:JTG:WBP

1/26/72

GBRN 001569

Form Approved OMB
No. 44-R1387
Approval Expires:
July 30, 1972

U.S. DEPARTMENT OF LABOR

Form No. OSHA-20
May, 1971

MATERIAL SAFETY DATA SHEET

SECTION I				
MANUFACTURER'S NAME MONSANTO COMPANY			EMERGENCY TELEPHONE NO. (314) 604-1000	
ADDRESS, Number, Street, City, State, and ZIP Code 800 North Lindbergh Boulevard, St. Louis, Missouri 63166				
CHEMICAL NAME AND SYNONYMS Chlorinated Aromatic			TRADE NAME AND SYNONYMS Aroclor 1232	
FORMULA Mixtures				
SECTION II HAZARDOUS INGREDIENTS				
PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%
TLV (Units)			TLV (Units)	
PIGMENTS			BASE METAL	
CATALYST			ALLOYS	
VEHICLE			METALLIC COATINGS	
SOLVENTS			FILLER METAL	
ADDITIVES			PLUS COATING OR CORE FLUX	
OTHERS			OTHERS	
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%
				TLV (Units)
SECTION III PHYSICAL DATA				
BOILING POINT (°F)	760 mm	290-325°C	SPECIFIC GRAVITY IN G/CC (25/15.5°C)	1.272
VAPOR PRESSURE (mm Hg)		.005	PERCENT VOLATILE BY VOLUME (%)	N.A.
VAPOR DENSITY (AIR = 1)		Not Avail	EVAPORATION RATE (PUAC)	<1
SOLUBILITY IN WATER	At 25°C negligible <0.01%			
APPEARANCE AND ODOR	colorless oil aromatic odor			
SECTION IV FIRE AND EXPLOSION HAZARD DATA				
FLASH POINT (METHOD)	C.O.C., 310°F		FLAMMABLE LIMITS	LOI
			NOT Avail.	LOI
EXTINGUISHING MEDIA Water, foam, CO2 or dry chemical.				
SPECIAL FIRE FIGHTING PROCEDURES Respiratory protection when fighting fires where exposure to vapors or gases is possible.				
UNUSUAL FIRE AND EXPLOSION HAZARDS Highly toxic fumes (chlorides and chlorine) can be evolved in fires of this product.				

EXHIBIT
K-103

GBRN 001570

-Aroclor 1232

SECTION V HEALTH HAZARD DATA

HEALTH HAZARD DATA	Not available.
SKIN IRRITATION in the form of chloracne, systematic intoxication leads to nausea, vomiting, loss of weight, edema and abdominal pain.	
Remove from exposure. Remove contaminated clothing. Wash contacted area with large amounts of water and soap. Refer to physician.	

SECTION VI REACTIVITY DATA

STABILITY	UNSTABLE	CONDITIONS TO AVOID
	STABLE	X
INCOMPATIBILITY (Materials to avoid)		
HAZARDOUS DECOMPOSITION PRODUCTS CO, CO2, smoke, soot, chlorides and chlorine		
HAZARDOUS POLYMERIZATION	MAY OCCUR	CONDITIONS TO AVOID
	WILL NOT OCCUR	X

SECTION VII SPILL OR LEAK PROCEDURES

Absorb on clay, sawdust or other absorbant material. Place in drums. Bury in approved chemical landfill in accordance with local and state regulations.
Burn in an approved incinerator in accordance with local and state regulations.

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type)		
Bureau of Mines approved respirator for organic vapors.		
VENTILATION	LOCAL EXHAUST	SPECIAL
	Yes - for vapors	
	MECHANICAL (Control)	OTHER
PROTECTIVE GLOVES	rubber	EYE PROTECTION
		chemical goggles
OTHER PROTECTIVE EQUIPMENT		

SECTION IX SPECIAL PRECAUTIONS

Avoid skin and eye contact. Avoid inhalation of vapors.
OTHER PRECAUTIONS

GBRN 001571

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, MONSANTO COMPANY MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

JAG:HOH:JTG:WBP

4/14/72

Form Approved OMB
No. 44-R1387
Approval Expires:
July 30, 1972


U.S. DEPARTMENT OF LABOR

Form No. OSHA-
May, 1971

MATERIAL SAFETY DATA SHEET

SECTION I			
MANUFACTURER'S NAME MONSANTO COMPANY		EMERGENCY TELEPHONE NO. (314) 664-1000	
ADDRESS, including street, city, state, and ZIP Code 800 North Lindbergh Boulevard, St. Louis, Missouri 63166			
COMMON NAME AND SYNONYMS Mixture		TRADE NAME AND SYNONYMS Arcochlor 1015, MCS 1015	
FORMULA Chlorinated aromatic		FORMULA Mixture	
SECTION II HAZARDOUS INGREDIENTS			
PAINTS, PRESERVATIVES, & SOLVENTS	TLV (Parts)	ALLOYS AND METALLIC COATINGS	TLV (Parts)
PIGMENTS		BASE METAL	
CATALYST		ALLOYS	
VEHICLE		METALLIC COATINGS	
SOLVENTS		FILLED METAL PLUS COATING OR OTHER FILLS	
ADDITIVES		OTHERS	
OTHERS			
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES			TLV (Parts)
SECTION III PHYSICAL DATA			
BOILING POINT (P.S.) 760 mm	325°C	SPECIFIC GRAVITY IN, G/CC (25/25.5°C)	1.367
VAPOR PRESSURE (mm Hg) (155-195°C)	7 mm	PERCENT VOLATILE BY VOLUME (%)	N.A.
VAPOR DENSITY (AIR = 1)	Not Avail	EVAPORATION RATE (P.S.)	<1
SOLUBILITY IN WATER 20°C negligible	<0.01%		
APPEARANCE AND ODOR colorless oil		slight aromatic odor	
SECTION IV FIRE AND EXPLOSION HAZARD DATA			
FLASH POINT (CLOUPE METHOD) C.O.C. 160°C	FLAMMABLE LIMITS		
EXTINGUISHING MEDIA Water, foam, CO₂ or dry chemical			
SPECIAL FIRE FIGHTING PROCEDURES Respiratory protection when fighting fires where exposure to vapors or gases is possible.			
UNUSUAL FIRE AND EXPLOSION HAZARDS Highly toxic gases (chlorides and chlorine) can be evolved in fires of this product.			

GBRN 001572



SECTION V HEALTH HAZARD DATA

STABILITY (UNIT VALUE)
 EFFECTS OF OVEREXPOSURE
 Skin irritation in the form of chloracne, systematic intoxication leads to nausea, vomiting, loss of weight, edema and abdominal pain.

EMERGENCY AND FIRST AID PROCEDURES

SECTION VI REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	
INCOMPATIBILITY (Reactivity to water)			
HAZARDOUS DECOMPOSITION PRODUCTS CO, CO ₂ , smoke, soot, chlorides and chlorine			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	

SECTION VII SPILL OR LEAK PROCEDURES

Absorb on clay, sawdust or other absorbent material. Place in drums. Bury in approved chemical landfill in accordance with local and state regulations.

WASTE DISPOSAL METHOD Burn in an approved incinerator in accordance with local and state regulations.

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION Bureau of Mines approved respirator for organic vapors.		
VENTILATION	LOCAL EXHAUST	Yes - for vapors
	MECHANICAL (General)	
PROTECTIVE GLOVES rubber		EYE PROTECTION chemical goggles
OTHER PROTECTIVE EQUIPMENT		

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE
 Avoid skin and eye contact. Avoid inhalation of vapors.
 OTHER PRECAUTIONS

GBRN 001573

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, MONSANTO COMPANY MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

JAO:HOH:JTG:WBP

1/25/72

Monsanto

PRODUCT SPECIFICATION

MONSANTO INDUSTRIAL CHEMICALS CO.

PRODUCT Aroclor 1016
GRADE

CODE NO 1040-016-16-03
DATE EFFECTIVE June 10, 1975

CHARACTERISTICS	LIMITS
Color (APHA)	40 Max.
Condition	Clear
Sp. Gr. 25/15.5°C	1.362-1.372
Acidity (mg KOH/g)	0.010 Max.
Moisture	35 ppm Max.
Refractive Index, 25°C	1.6215-1.6235
Inorganic (Free) Chlorides	0.05 ppm Max.
Pour Point	-14°C Max.
Dielectric Constant (60 Hz, 100°C)	4.80-4.95
Hydrolysis Stability Test (as Chlorides)	0.5 ppm Max.
Monsanto Stability Test (as Chlorides)	0.4 ppm Max.
Distillation Range (ASTM D-20 Corrected)	
10% (by weight)	323°C Min.
90% (by weight)	356°C Max.
Higher Boiling Homologs	0.4% Max.
Sulfates	None
Dielectric Strength 25°C, KV	35 Min.
Flash Point, °F	338 Min.
Fire Point	None to B.P.
Visc. 100°F (SUS)	71-81
Power Factor, 100°C, 60 Hz Max.	
Bulk	1.0%
Drums	4.0%

GBRN 001574

a unit of Monsanto Company

MS-68 (REV. 1-72)

TOXICITY INFORMATION ON: AROCLOR® 1016 Capacitor Dielectric**TOXICITY**

The rat acute oral LD₅₀ of AROCLOR 1016 is 2.3 grams/kilogram. When held in continuous 24-hour contact with rabbit skin, the dermal LD₅₀ was estimated to be between 1.58 grams/kilogram and 2.0 grams/kilogram. Thus, AROCLOR 1016 is considered to be slightly toxic by ingestion in single doses and by single dermal applications.

When undiluted AROCLOR 1016 was placed into the conjunctival sac of the rabbit eye, a slight degree of irritation resulted. The average score of the 24-, 48- and 72-hour readings was 5.1 on a scale of 110.0. The irritation in 4 of 6 treated eyes had subsided by 72 hours after dosing. The other two treated eyes had regained a normal appearance by 168 hours after dosing.

A severe degree of irritation resulted when undiluted AROCLOR 1016 was held in continuous 24-hour contact with intact and abraded rabbit skin. The Primary Irritation Index was 5.3 on a scale of 8.0.

HANDLING PRECAUTIONS

Care should be taken to avoid AROCLOR 1016 contact with the skin. In case of skin contact, immediately wash exposed surfaces thoroughly with soap and water. If irritation persists, consult a physician.

In case of eye contact, flush immediately with large volumes of water. If irritation persists, consult a physician.

AROCLOR 1016 has a negligible vapor pressure at room temperature and it is not expected to present a significant vapor inhalation hazard under ambient conditions. However, precautions should be observed to avoid inhalation of increased vapor concentrations which may occur if AROCLOR 1016 is used at elevated temperatures.

ENVIRONMENTAL HAZARDS

During the past several years, evidence has accumulated to indicate that polychlorinated biphenyls are widely dispersed throughout the environment and that they can have adverse ecological and toxicological effects. Extreme care should, therefore, be taken by all users of AROCLOR 1016 to prevent any entry into the environment through spills, leakage, use or disposal.

11A/75,Y-75-282

GBRN 001575

The above information is based upon studies conducted for Monsanto Company. It is believed to be correct, and it is supplied to others upon the condition that the persons receiving it shall make their own determination of its suitability for their purpose. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use.

Inquiries regarding this information are to be referred to the Corporate Medical Department, 800 N. Lindbergh, St. Louis, Mo. 63166, (314) 694-1000.

Monsanto Industrial Chemicals Company Sales Offices

AKRON, OHIO 44313
380 Springside Drive
Montross Development Park
Tel. (216) 666-4111

**ATLANTA, GEORGIA
30339**
320 Interstate North
Parkway
Tel. (404) 432-7111

**BOSTON,
MASSACHUSETTS
02149**
Everett Station
Tel. (617) 387-6010

CHICAGO, ILLINOIS
3158 Des Plaines Ave.
Des Plaines, Illinois 60018
Tel. (312) 296-6688

**CINCINNATI, OHIO
45206**
1601 Madison Road
Tel. (513) 751-6707

DETROIT, MICHIGAN
800 Northland Towers West
Southfield, Mich. 48075
Tel. (313) 357-0910

**HOUSTON, TEXAS
77027**
1300 Post Oak Tower
8061 Westheimer Road
Tel. (713) 621-8660

**LOS ANGELES,
CALIFORNIA 90040**
6670 E. Flotilla St.
Tel. (213) 723-2492

**NEW YORK,
NEW YORK 10036**
1114 Avenue of the
Americas
Tel. (212) 764-6000

**ST. LOUIS, MISSOURI
63166**
800 N. Lindbergh Blvd.
Tel. (314) 694-1000

**SAN FRANCISCO
BAY AREA**
2710 Lafayette
San Jose, Calif. 95052
Tel. (408) 243-0414

**WILMINGTON,
DELAWARE 19810**
3411 Silverside Road
Tel. (302) 478-4600

MONSANTO, 800 N. LINDBERGH BLVD., ST. LOUIS

GBRN 001576

REV. 5/79