FILE NAME: Reddaway Manufacturing (REDD)

DATE: 0000

DOC#: REDD008

DOCUMENT DESCRIPTION: Material Safety Data Sheets

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Form Approved
OMB No. 44-R3383

MATERIAL SAFETY DATA SHEET

DEPOSITION EXHIBIT #2 11-8-93 WALKER

Required under USDL Safety and Health Regulations for Ship Repairing, Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I

MANUFACTURER'S NAME	EMERGENCY TELEPHONE NO.
Reddaway Mfg. Co., Inc.	589-1410
ADDRESS (Number, Street, City, State, and ZIP Code) 32 EUCLID AVENUE, NEWARK, NEW JERSEY 07105	
CHEMICAL NAME AND SYNONYMS	TRADE NAME AND SYNONYMS REDCO RBW
CHEMICAL FAMILY	FORMULA

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES	%	TLV (Units)
50% Asbestos - 50% Aromatic Hydrocarbons		

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)		SPECIFIC GRAVITY (H_2O=1)	
VAPOR PRESSURE (mm Hg.)		PERCENT, VOLATILE BY VOLUME (%)	
VAPOR DENSITY (AIR=1)		EVAPORATION RATE (_____ =1)	
SOLUBILITY IN WATER			
APPEARANCE AND ODOR			

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	FLAMMABLE LIMITS	Lel	Uel
EXTINGUISHING MEDIA			
SPECIAL FIRE FIGHTING PROCEDURES			
UNUSUAL FIRE AND EXPLOSION HAZARDS			

(Continued on reverse side)

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE
2 Fibers per C.C. (of Air) Greater than 5 microns in l[illegible] over a time weighted averag[illegible] of 8 hours.

EFFECTS OF OVEREXPOSURE
Suspected carcinogen.

EMERGENCY AND FIRST AID PROCEDURES
Avoid breathing dust. Use approved respirator mask.

SECTION VI - REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE		

INCOMPATABILITY *(Materials To Avoid)*

HAZARDOUS DECOMPOSITION PRODUCTS

HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR		

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

WASTE DISPOSAL METHOD
Place in sealed container and dispose of in approved landfill.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION *(Specify type)* Avoid creating dust. Use adequate ventilation

VENTILATION	LOCAL EXHAUST not directed toward worker.	SPECIAL
	MECHANICAL *(General)*	OTHER

PROTECTIVE GLOVES | **EYE PROTECTION**

OTHER PROTECTIVE EQUIPMENT

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
Store in area posted with approved warning signs indicating a hazardous substance. The resins used lock in the asbestos fibers.

OTHER PRECAUTIONS
Hazards normally only occur when cutting or machining the material

Material Safety Data Sheet

Required under USDL Safety and Health Regulations for Shipyard Employment (29 CFR 1915)

U.S. Department of Labor
Occupational Safety and Health Administration

OMB No 1218-0072
Expiration Date 05/31/88

EXHIBIT
10
4-13-17

Section I

Manufacturer's Name: REDDAWAY MFG. CO., INC.

Emergency Telephone Number: 201-589-1410

Address (Number Street City State and ZIP Code): 32 EUCLID AVENUE, NEWARK, NEW JERSEY 07105

Chemical Name and Synonyms:

Trade Name and Synonyms: REDCO RFM (FLEX MOLDED)

Chemical Family:

Formula:

Section II - Hazardous Ingredients

Paints, Preservatives, and Solvents	%	TLV (Units)	Alloys and Metallic Coatings	%	TLV (Units)
Pigments			Base Metal		
Catalyst			Alloys		
Vehicle			Metallic Coatings		
Solvents			Filler Metal Plus Coating or Core Flux		
Additives			Others		
Others					

Hazardous Mixtures of Other Liquids, Solids or Gases

	%	TLV (Units)
52% BY WEIGHT OF CHRYSOTILE ASBESTOS		
16% BY WEIGHT OF RUBBER		
32% BY WEIGHT OF FILLER		

Section III - Physical Data

Boiling Point (°F)	N/A	Specific Gravity (H_2O=1)	
Vapor Pressure (mm Hg)	N/A	Percent Volatile by Volume (%)	
Vapor Density (AIR=1)	N/A	Evaporation Rate (_____=1)	

Solubility in Water: INSOLUBLE

Appearance and Odor: GREY NO ODOR

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)	N/A	Flammable Limits	Lel	Uel

Extinguishing Media: N/A

Special Fire Fighting Procedures: N/A

Unusual Fire and Explosion Hazards: N/A

ELECTRO LIFT 11