

R. E. Byrne
File ✓

THE DISCOVERY COMPANY

UNION CARBIDE CORPORATION • MINING & METALS DIVISION • 17 EXECUTIVE PARK DRIVE • ATLANTA, GEORGIA • TEL: 404-633-6161

November 23, 1976

PLAINTIFF'S EXHIBIT

UC-4965

Mr. Bob Favero, Plant Manager
Georgia Pacific
Gypsum Division
1466 White Circle, N.W.
Marietta, Georgia

Dear Bob:

During my recent call at your plant you mentioned instances where your sales people had run into a problem of selling asbestos-containing joint cement to contractors who advised them that they had been told that the use of asbestos had been banned in joint cements. To combat this incorrect information and hopefully assist both Georgia Pacific and your sales people in the sale of asbestos-containing joint cements, I would like to offer the following information on the current status of the Federal OSHA asbestos regulations, particularly as they effect the continued use of asbestos in tape joint compounds.

The Asbestos Standard promulgated on June 7, 1972, states:

(b) Permissible exposure to airborne concentrations of asbestos fibers -- (1) Standard effective July 7, 1972. The 8-hour time-weighted average airborne concentrations of asbestos fibers to which any employee may be exposed shall not exceed five fibers, longer than 5 micrometers, per cubic centimeter of air, as determined by the method prescribed in paragraph (e) of this section. (Emphasis added.)

(2) Standard effective July 1, 1976 weighted average airborne concentration to which any employee may be exposed, fibers, longer than 5 micrometers air, as determined by the method (e) of this section. (Emphasis added.)


The reduction in the allowable 8-hour time-weighted average airborne concentration from 5 fibers/cc to 2 fibers/cc that took place on in the asbestos regulations that has been promulgated, prohibition on the use of asbestos in tape joint compounds.

G.P.
3/5

On October 9, 1975, OSHA proposed a new asbestos rulemaking that has received considerable publicity. The construction industry where tape-joint compounds are used is specifically excluded from the new proposal and will be considered later. Until such time as an asbestos standard for the construction industry is promulgated the existing June 7, 1972, standard with the 5 fiber/cc and 2 fiber/cc (July 1976) allowable limits noted above will continue to apply. It is important to point out that even the considerably more restrictive proposed rulemaking has no suggestion whatsoever that the use of asbestos in tape joint compounds will be prohibited by OSHA.

If you have any further questions, please do not hesitate to call.

Very truly yours,

A handwritten signature in cursive script that reads "Jack Walsh".

J. E. Walsh
Sales Manager - Southern Region

JEW:ct