

SECTION V HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE	1 ppm 8-hr TWA; 5 ppm Ceiling over 15 min.
EFFECTS OF OVEREXPOSURE	See Section II Also, exposure to very high concentrations may cause asphyxiation, persistent irregular heartbeat, unconsciousness, nausea, or dizziness. Liquid on body or clothing may cause freezing or lead to above symptoms via overexposure from inhalation or systemic absorption.
EMERGENCY AND FIRST AID PROCEDURES	Remove victim to area free of vinyl chloride vapors. Give artificial respiration if necessary. Remove contaminated clothing. Notify supervisor immediately of spills. Remove from eyes with large amounts of water. or leaks.

SECTION VI REACTIVITY DATA

STABILITY	UNSTABLE	X	CONDITIONS TO AVOID
	STABLE		Avoid sunlight and/or heat and exclude all oxygen
INCOMPATIBILITY (Materials to avoid)	air, oxygen		
HAZARDOUS DECOMPOSITION PRODUCTS	HCl, CO and phosgene on combustion		
HAZARDOUS POLYMERIZATION	MAY OCCUR	X	CONDITIONS TO AVOID
	WILL NOT OCCUR		air, sunlight and/or heat

SECTION VII SPILL OR LEAK PROCEDURES

FLAMMABLE.	Remove all sources of ignition. Remove all personnel not wearing protection equipment shown in Sect. VIII. Use forced ventilation from explosion-proof equipment. Allow to evaporate slowly.
WASTE DISPOSAL METHOD	Do not permit material to enter sewers. Use controlled evaporation. Guard against fire and explosion hazards.

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type)	Air pack or supplied air respirator as required.		
VENTILATION	LOCAL EXHAUST	Highly recommended (Use explosion proof equipment)	
	MECHANICAL (General)	OTHER	
PROTECTIVE GLOVES	Rubber	EYE PROTECTION	
OTHER PROTECTIVE EQUIPMENT	Chemical goggles and/or face shields		
To prevent all contact with body as required.			

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING	Prevent any leakage. Provide sufficient ventilation to prevent high concentrations. Keep away from all sources of ignition. Handle as an extremely flammable material which is stored under pressure.
AVOID BREATHING VAPOR	

NAME D. M. Sheets, Supervisor
 TITLE Regulatory Affairs - Chemical Products
 COMPANY Shell Chemical
 SIGNATURE *D. M. Sheets*
 DATE June, 1975

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE HOWEVER NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.
 VENDOR ASSUMES NO RESPONSIBILITY FOR INJURY TO VENDOR OR THIRD PERSONS PROXIMATELY CAUSED BY THE MATERIAL IF REASONABLE SAFETY PROCEDURES ARE NOT ADHERED TO AS STIPULATED IN THE DATA SHEET. ADDITIONALLY, VENDOR ASSUMES NO RESPONSIBILITY FOR INJURY TO VENDOR OR THIRD PERSONS PROXIMATELY CAUSED BY ABNORMAL USE OF THE MATERIAL EVEN IF REASONABLE SAFETY PROCEDURES ARE FOLLOWED. FURTHERMORE VENDOR ASSUMES THE RISK IN HIS USE OF THE MATERIAL.