

Form Approved OMB
No. 44-R1387
Approval Expires:
July 30, 1972

U.S. DEPARTMENT OF LABOR

Form No. OSHA-20
May, 1971

MATERIAL SAFETY DATA SHEET

81104-246
1- S.D. Fale
1- R. McCutchan

SECTION I					
MANUFACTURER'S NAME MONSANTO COMPANY				EMERGENCY TELEPHONE NO. (314) 694-1000	
ADDRESS (Number, Street, City, State, and ZIP Code) 800 North Lindbergh Boulevard, St. Louis, Missouri 63166					
CHEMICAL NAME AND SYNONYMS Mixture			TRADE NAME AND SYNONYMS Aroclor 1016, MCS 1016		
CHEMICAL FAMILY Chlorinated aromatic			FORMULA Mixture		
SECTION II HAZARDOUS INGREDIENTS					
PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)
SECTION III PHYSICAL DATA					
BOILING POINT (P.F.)	760 mm	325°C	SPECIFIC GRAVITY (H ₂ O=1) (25/15.5°C)	1.367	
VAPOR PRESSURE (mm Hg.)	(155-195°C)	3 mm	PERCENT VOLATILE BY VOLUME (%)	N.A.	
VAPOR DENSITY (AIR=1)	Not Avail		EVAPORATION RATE (BuAc = 1)	<1	
SOLUBILITY IN WATER	20°C negligible	<0.01%			
APPEARANCE AND ODOR	colorless oil		slight aromatic odor		
SECTION IV FIRE AND EXPLOSION HAZARD DATA					
FLASH POINT (Method used) C.O.C. 180°C			FLAMMABLE LIMITS	Lel	Uel
				N.A.	N.A.
EXTINGUISHING MEDIA Water, foam, CO ₂ or dry chemical					
SPECIAL FIRE FIGHTING PROCEDURES Respiratory protection when fighting fires where exposure to vapors or gases is possible.					
UNUSUAL FIRE AND EXPLOSION HAZARDS Highly toxic gases (chlorides and chlorine) can be evolved in fires of this product.					

DSW 267536

TOWOLDMON0011779

Aroclor MCS 1016 SECTION V HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE			
EFFECTS OF OVEREXPOSURE Skin irritation in the form of chloracne, systematic intoxication leads to nausea, vomiting, loss of weight, edema and abdominal pain			
EMERGENCY AND FIRST AID PROCEDURES			
SECTION VI REACTIVITY DATA			
STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	
INCOMPATIBILITY (Materials to avoid)			
HAZARDOUS DECOMPOSITION PRODUCTS CO, CO ₂ , smoke, soot, chlorides and chlorine			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	
SECTION VII SPILL OR LEAK PROCEDURES			
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Absorb on clay, sawdust or other absorbant material. Place in drums. Bury in approved chemical landfill in accordance with local and state regulations.			
WASTE DISPOSAL METHOD Burn in an approved incinerator in accordance with local and state regulations.			
SECTION VIII SPECIAL PROTECTION INFORMATION			
RESPIRATORY PROTECTION (Specify type) Bureau of Mines approved respirator for organic vapors.			
VENTILATION	LOCAL EXHAUST	Yes - for vapors	SPECIAL
	MECHANICAL (General)		OTHER
PROTECTIVE GLOVES rubber		EYE PROTECTION chemical goggles	
OTHER PROTECTIVE EQUIPMENT			
SECTION IX SPECIAL PRECAUTIONS			
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING			
Avoid skin and eye contact. Avoid inhalation of vapors.			
OTHER PRECAUTIONS			

DSW 267537

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, MONSANTO COMPANY MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

JAG:HOH:JTG:WBP

1/25/72