

CC: L. S. Dymitro
H. Gosselink

DANA CORPORATION

Victor Divisions

INTRA-COMPANY COMMUNICATION

SUBJECT Victopac 100 Thickness Control

DATE December 2, 1969

to Steve Lillis

Your letter of November 18, requests information regarding our ability to make Victopac 100 to a tolerance of +/- .0025, .0020, .0015. I must state that we cannot at this time hold gage in these ranges. The best that we can do on a production basis is +/- .004. It is true that we are supplying some material to Chicago at present which is held better than +/- .004 but this is done on a selected basis, material out of gage is diverted to Robinson use. Victopac 100 would not be a material that could be used at Robinson due to cost even if deviation authority would be allowed. Your letter points out that the Viton Elastomer in Victopac 100 costs 20 times as much as the Neoprenes used in the more standard Victopac material.

Steve Cerve sent a memo to G. Brown in early October quoting a sheet cost of \$18.26 per 62½ x 56½ sheet. This was in response to a memo from George which gave no indication of gage restriction other than the standard +/- .005. The cost of this was based on results experienced in project 84407, formula number 839. Again, no gage restrictions. I must point out that if a tighter tolerance is required, out of gage sheets must be paid for by the customer one way or another. Robinson cannot absorb the costs of rejected sheets, nor can we absorb the cost of centers or ends trim. This is true for .031/.037 which your letter states you are presently specifying (?)

In affect I submit that the customer will have to pay for the full sheet, full batch, regardless of yield as there is no other outlet for the material. I presume salvage through refiberizing would also be question mark. I know of no experiments or formulas which establish that refiberized material may be used. I would also comment that maintaining refiberized Viton Victopac in our present equipment would introduce the probability of contamination with other refiberized material.

The results of a discussion at Robinson regarding a method to hold gage as required suggests at least two major needs:

1. Rebuild mills and run in and back out devices, new bearings, ratcheting devices, etc.
2. Automatic feeding equipment to feed mix into the mills.

(continued)

VPD-91-0001070