

294.3 K (70°F) established in a standard reference text or as determined by ASTM method D-2879; or which has 0.1 Reid Vapor Pressure as determined by ASTM method D-323; or which when distilled requires a temperature of 421.95K (300°F) or greater to recover 10% of the liquid as determined by ASTM method D-86.

**"In Vacuum Service"**: For the purposes of Subpart Q, Sections 215.430 through 215.438 equipment which is operating at an internal pressure that is at least 5 kPa (0.73 psia) below ambient pressure.

**"Light Liquid"**: Volatile organic material in the liquid state which is not defined as heavy liquid.

**"Light Oil"**: A liquid condensed or absorbed from coke oven gas composed of benzene, toluene, and xylene.

**"Material Recovery Section"**: Any equipment designed to transport and recover styrene monomer and other impurities from other products and by-products in a polystyrene plant, including but not limited to the styrene devolatilizer unit and styrene recovery unit.

**"Offset"**: Use of a blanket cylinder to transfer ink from the plate cylinder to the surface to be printed.

**"Opaque Stains"**: All stains containing pigments not classified as semi-transparent stains including stains, glazes and other opaque material to give character to wood.

**"Open-Ended/Valve"**: Any valve, except pressure relief devices, having one side of the valve in contact with process fluid and one side open to the atmosphere, either directly or through open piping.

**"Pigments Coatings"**: Opaque coatings containing binders and colored pigments which are formulated to conceal the wood surface either as an undercoat or topcoat.

**"Polystyrene Plant"**: Any plant using styrene to manufacture polystyrene resin.

**"Polystyrene Resin"**: A substance consisting of styrene polymer and additives which is manufactured at a polystyrene plant.

**"Repair Coatings"**: Coatings to correct imperfections or damage to furniture surface.

**"Repaired"**: For the purposes of Subpart Q, Sections 215.430 through 215.438 equipment component which is adjusted, or otherwise altered, to eliminate a leak.

**"Sealer"**: Coating containing binders which seals the wood prior to application to subsequent coatings.

**"Semi-transparent Stains"**: Stains containing dyes or semi-transparent pigments which are formulated to enhance wood grain and change the color of the surface but not to conceal the

surface, including, but not limited to, sap stain, toner, non-grain-raising stains, pad stain, spatter stain.

**"Specialty Soybean Crushing Source"**: Any hexane extraction soybean crushing equipment using indirect steam heat in flash or vapor desolventizers as the primary method of desolventizing and producing specialty solvent extracted soy flakes, grits or flour.

**"Styrene Devolatilizer Unit"**: Equipment performing the function of separating unreacted styrene monomer and other volatile components from polystyrene in a vacuum devolatilizer.

**"Styrene Recovery Unit"**: Equipment performing the function of separating styrene monomer from other less volatile components of the styrene devolatilizer unit's output. The separated styrene monomer may be reused as raw material in the polystyrene plant.

**"Wash Coat"**: Coating containing binders which seals wood surfaces, prevents undesired staining and controls penetration.

**"Web"**: A substrate which is printed in continuous roll-fed presses.

**"Wood Furniture"**: Room furnishings including cabinets (kitchen, bath and vanity), tables, chairs, beds, sofas, shutters, art objects, wood paneling, wood flooring, and any other coated furnishings made of wood, wood composition or fabricated wood materials.

(Source: Amended at 12 III. Reg. 815, effective December 24, 1987)

#### Section 215.185 Incorporations by Reference

The following materials are incorporated by reference:

a) American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA. 19103:

- 1) ASTM D 1644-59 Method A
- 2) ASTM D 1475-60
- 3) ASTM D 2369-73
- 4) ASTM D 2879-83 (Approved 1983)
- 5) ASTM D 323-82 (Approved 1982)
- 6) ASTM D 86-82 (Approved 1982)
- 7) ASTM E 260-73 (Approved 1973), E 168-67 (Reapproved 1977), E 169-63 (Reapproved 1981), E 20 (Approved 1985)
- 8) ASTM D 97-66
- 9) ASTM D-1946-67
- 10) ASTM D-2382-76

b) Federal Standard 141a, Method 4082.1