

NEG. NO. AI-4

TRADEMARK FILE INFORMATION

Trademark:	Perfectseal
Trademark Owner:	M. J. Merkin Paint Co., Inc.
Last Assignee:	Karnak Chemical Corporation
Date of First Use in Commerce:	June 1, 1922
Registration No.:	541,014
Date Trademark Registered:	April 17, 1951
Size of Label in Trademark File:	21.3750 x 7 inches



Receipt of Pictured Label by Patent Office:



CAUTION—INFLAMMABLE MIXTURE DO NOT USE NEAR FIRE
OR FLAME. C. O. A. NO. 1523
APPROVED BY THE BOARD OF STANDARDS & APPEALS
CITY OF NEW YORK, CAL. No. 987-38-54

PERFECTSEAL

Compare with the One Gallon or More

LIQUID STIR THOROUGHLY PLASTIC

Apply With Roof Brush Apply With Trowel

Any surface where Perfectseal is applied must be thoroughly cleaned
or washed to remove all loose material.

Repair all large holes with roofing paper or felt. If holes are large paper
or felt must be done all round hole.

Remove a coat of Perfectseal Plastic from all exposed areas. Repurpose
the surface and remove with Power 118 sand block.

After the above preparation Perfectseal Liquid is generally ground in
the flat roof or garden and should not be a good heavy coating the
amount depending upon the surface.

For waterproofing and damp proofing walls with coat the inside if
possible.

Any further information liberally given upon request.

TIN AND METAL SURFACES: Remove about 1 gallon. Apply and Coat
with about 1 1/2 to 2 gallons per 100 square feet.

GRAVEL ROOFS: Remove 2 to 4 gallons of liquid for 100 square feet. No
gravel and dirt must be cleaned off before coating.

CONCRETE ROOFS: Remove a coat of old Asphalt Roof Put on a primer
and about 1/2 gallon a coat of liquid. This gives a new 100 square feet.

BRICK ROOFS: Must be carefully washed and remove approximately 1
gallon of liquid per 100 square feet.

SEAMS: Apply a heavy coat of Perfectseal Plastic over the seams two inches
on each side.

FLASHINGS: Coat the top with 4 inches high and 3 inches wide on the
surface with Perfectseal Plastic.

ONE GALLON — U. S. STANDARD