


SHERWIN-WILLIAMS

ONE GALLON

U.S. STANDARD MEASURE



ONE COAT

FLAT-TONE

A Truly Superior, Washable One-Coat
Flat Wall Paint

810 WHITE

7-SWP-0051407
N15080

WILLIAMS

SHERWIN-WILLIAMS

U. S. STANDARD MEASURE

COAT

ONE

able One-Coat
fini

ITE



1. Clean Wall. — Remove all grease and dirt.



2. Crack. — Scrape off loose paint and fill cracks.



3. Uncoated Floor. — Be sure the surface is thoroughly dry.



4. Mix thoroughly.



5. Brush or Roller.



6. Cover. — Working uniformly.



7. One coat covers most wall surfaces.

A truly superior, ventilable, one coat flat wall paint that dries with a subdued sheen. One-Coat Flat-Tone is used for all interior wall surfaces including smooth, textured and sand finish plaster, wall board, smooth masonry and other types wall. It may be applied by brush, roller, sprayer or stippled.

DIRECTIONS FOR USE — IMPORTANT!

For thorough, easy mixing, pour off a liberal portion into a clean container, thoroughly stir the remaining paint to a smooth, soft consistency, then pour the balance back gradually while continuing to stir. Normally, apply at moderate consistency. Reduce if necessary with Evolvent or turpentine. Apply generously with wall brush or roller-koater.

New Work. — Surface must be perfectly dry. Damp or uncured plaster may cause paint to peel, discolour or peel. Priming the surface with Sherwin-Williams Wolf Primer and Sealer is recommended for the best paint job on plaster or where extensive repairs have been made.

Old Work. — Be sure surface is smooth, clean and free from dirt, grease and loose paint. Loose wallpaper should be removed or pasted tightly to the wall before painting over it. Do not use over Glue Size, Kalsomine or Wallpaper with bleeding colors. Remove these with warm water.

Finishing. — Additional attractive tints and tones may be obtained through the use of Sherwin-Williams Fluid Tinting Colors.

CAUTION! — Keep away from fire. Use in a well ventilated place. Clean lines and sanitary precautions should be observed.

THE SHERWIN-WILLIAMS CO.

ADMINISTRATION OFFICES AND FACTORY, CLEVELAND, OHIO
OFFICES, FACTORIES AND WAREHOUSES IN PRINCIPAL CITIES
OF THE UNITED STATES



8. Drier to touch in four hours.